

# **NetIQ® CloudAccess**

## **Installation and Configuration Guide**

January 2013



## Legal Notice

THIS DOCUMENT AND THE SOFTWARE DESCRIBED IN THIS DOCUMENT ARE FURNISHED UNDER AND ARE SUBJECT TO THE TERMS OF A LICENSE AGREEMENT OR A NON-DISCLOSURE AGREEMENT. EXCEPT AS EXPRESSLY SET FORTH IN SUCH LICENSE AGREEMENT OR NON-DISCLOSURE AGREEMENT, NETIQ CORPORATION PROVIDES THIS DOCUMENT AND THE SOFTWARE DESCRIBED IN THIS DOCUMENT "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SOME STATES DO NOT ALLOW DISCLAIMERS OF EXPRESS OR IMPLIED WARRANTIES IN CERTAIN TRANSACTIONS; THEREFORE, THIS STATEMENT MAY NOT APPLY TO YOU.

For purposes of clarity, any module, adapter or other similar material ("Module") is licensed under the terms and conditions of the End User License Agreement for the applicable version of the NetIQ product or software to which it relates or interoperates with, and by accessing, copying or using a Module you agree to be bound by such terms. If you do not agree to the terms of the End User License Agreement you are not authorized to use, access or copy a Module and you must destroy all copies of the Module and contact NetIQ for further instructions.

This document and the software described in this document may not be lent, sold, or given away without the prior written permission of NetIQ Corporation, except as otherwise permitted by law. Except as expressly set forth in such license agreement or non-disclosure agreement, no part of this document or the software described in this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, or otherwise, without the prior written consent of NetIQ Corporation. Some companies, names, and data in this document are used for illustration purposes and may not represent real companies, individuals, or data.

This document could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein. These changes may be incorporated in new editions of this document. NetIQ Corporation may make improvements in or changes to the software described in this document at any time.

U.S. Government Restricted Rights: If the software and documentation are being acquired by or on behalf of the U.S. Government or by a U.S. Government prime contractor or subcontractor (at any tier), in accordance with 48 C.F.R. 227.7202-4 (for Department of Defense (DOD) acquisitions) and 48 C.F.R. 2.101 and 12.212 (for non-DOD acquisitions), the government's rights in the software and documentation, including its rights to use, modify, reproduce, release, perform, display or disclose the software or documentation, will be subject in all respects to the commercial license rights and restrictions provided in the license agreement.

**© 2013 NetIQ Corporation and its affiliates. All Rights Reserved.**

For information about NetIQ trademarks, see <https://www.netiq.com/company/legal/>.

---

# Contents

<b>About this Book and the Library</b>	<b>7</b>
<b>About NetIQ Corporation</b>	<b>9</b>
<b>1 Overview of NetIQ CloudAccess</b>	<b>11</b>
1.1 Inherent Problems Using SaaS Applications	11
1.2 The Solution CloudAccess Provides	12
1.3 How CloudAccess Works	13
1.4 How to Manage CloudAccess	13
1.5 How CloudAccess Fits into Your Network	13
1.6 How CloudAccess Merges Existing Accounts	14
1.6.1 CloudAccess Matching Criteria	15
1.6.2 CloudAccess Naming Convention	16
1.6.3 Samples of Account Creations	16
<b>2 Installing CloudAccess</b>	<b>19</b>
2.1 CloudAccess Installation Worksheet	19
2.2 Requirements	19
2.3 Deploying the Appliance	22
2.4 Configuring the Appliance Without a DHCP Server	23
2.5 Initializing the Appliance	24
<b>3 Configuring the Appliance</b>	<b>25</b>
3.1 Accessing the Administration Pages	25
3.2 Registering CloudAccess	26
3.3 Configuring Additional Identity Sources	26
3.4 Verifying the Identity Source User Attributes	27
3.4.1 Active Directory Mandatory Attributes	27
3.4.2 eDirectory Mandatory Attributes	28
3.5 Configuring Roles Management	28
3.5.1 Defining the Role Types	28
3.5.2 Assigning Roles to Users	28
3.6 Configuring Clustering	29
3.6.1 Advantages of Clustering	29
3.6.2 Managing Nodes in the Cluster	29
3.6.3 Configuring an L4 Switch for Clustering	31
3.6.4 Configuring an L4 Switch for Email Proxy	31
3.7 Configuring Integrated Windows Authentication with Kerberos	33
3.7.1 Configuring the Kerberos User in Active Directory	34
3.7.2 Configuring the Appliance to Use Integrated Windows Authentication with Kerberos	34
3.7.3 Configuring the End User Browsers	35
<b>4 Configuring Connectors</b>	<b>37</b>
4.1 Connector for Google Apps for Business	37
4.1.1 Meeting the Requirements	37
4.1.2 Configuring the Connector for Google Apps for Business	37
4.1.3 Configuring Multiple Connectors for Google Apps for Business	39

4.2	Connector for Office 365	39
4.2.1	Meeting Requirements	39
4.2.2	Installing the Connector for Office 365	40
4.2.3	Validating the Connector for Office 365	41
4.2.4	Changing Configuration of the Connector for Office 365	41
4.2.5	Uninstalling the Connector for Office 365	41
4.2.6	Installing Multiple Connectors for Office 365	41
4.3	Connector for Salesforce	41
4.3.1	Meeting the Requirements	42
4.3.2	Configuring Salesforce to Trust CloudAccess	42
4.3.3	Configuring the Connector for Salesforce	42
4.3.4	Configuring Multiple Connectors for Salesforce	43
4.3.5	Configuring Delegated Authentication	44
4.4	Single Sign-On Connectors	44
4.5	Importing and Configuring Custom Connectors	45
<b>5</b>	<b>Providing Access to the SaaS Applications for Users</b>	<b>47</b>
<b>6</b>	<b>Mapping Authorizations</b>	<b>49</b>
6.1	Supported Roles and Authorizations	49
6.2	Prerequisites	50
6.3	Loading Authorizations	50
6.4	Reloading Authorizations	50
6.5	Mapping Authorizations	51
6.6	A Mapping Example	51
<b>7</b>	<b>Approving Requests</b>	<b>53</b>
<b>8</b>	<b>Reporting</b>	<b>55</b>
8.1	Running a Report	55
8.2	Integrating with Sentinel Log Manager	55
<b>9</b>	<b>End User Configuration</b>	<b>57</b>
9.1	Configuring Email Clients	57
9.2	Configuring Mobile Devices	57
9.3	Configuring End User Browsers for Kerberos Authentication	58
<b>10</b>	<b>Maintenance Tasks</b>	<b>59</b>
10.1	Changing the IP Address	59
10.2	Changing Public DNS Name or NTP Server Settings, or Uploading New Certificates	59
10.3	Updating the Appliance	60
10.4	Recovering from a Disaster	61
<b>11</b>	<b>Troubleshooting CloudAccess</b>	<b>63</b>
11.1	Displaying Health	63
11.2	Troubleshooting Tools	63
11.3	Troubleshooting Different States	65
11.3.1	Master Node Health	65
11.3.2	Front Panel of the Node	65
11.3.3	Top of the Node	66

11.3.4	Identity Source	66
11.3.5	SaaS Applications	67
11.4	Provisioning Behavior	68
11.5	Troubleshooting Authentications or Single Sign-On Issues	69
11.6	Valid Salesforce Credentials Fail	69
11.7	Troubleshooting the Connector for Office 365	69
11.7.1	Obtaining the Installation Logs	69
11.7.2	Obtaining the Provisioning Logs	70
11.8	Troubleshooting Custom Connectors	70

## A Open Source Licenses Release Notes 71

A.1	Documentation	71
A.2	Open Source Components	71
A.2.1	Apache 2.2.17	72
A.2.2	Apache Commons Logging 1.1.1	72
A.2.3	Apache Portable Runtime 1.4.2	72
A.2.4	Argo 2.21	72
A.2.5	Bouncy Castle 1.5.140	73
A.2.6	dom4j 1.6.1	73
A.2.7	dovecot20-backend-pgsql-2.0.20-31.1	73
A.2.8	dovecot20-backend-mysql-2.0.20-31.1	74
A.2.9	dovecot20-backend-sqlite-2.0.20-31.1	74
A.2.10	dovecot20-2.0.20-31.1	74
A.2.11	dovecot20-devel-2.0.20-31.1	74
A.2.12	GWT 2.4.0	74
A.2.13	GWT Mosaic 0.4.0-rc4	74
A.2.14	gwtupload 0.6	75
A.2.15	Hibernate 3	75
A.2.16	httpclient 4.1.2	75
A.2.17	JavaMail 1.4.3	75
A.2.18	JavaService 2.0.10	75
A.2.19	Jaxb 2.2	75
A.2.20	jersey 1.0.3	76
A.2.21	jgroups 2.10.0 GA	76
A.2.22	log4cxx 0.10.0	76
A.2.23	log4j 1.2.15	76
A.2.24	NTLM Library (TCP implementation) 1	76
A.2.25	OpenSSL 0.98j	76
A.2.26	Open-vm-tools 9.0.0-9.1	77
A.2.27	libvmttools 9.0.0-9.1	77
A.2.28	Recaptcha4j 0.0.8	77
A.2.29	Tomcat 5.5.27	77
A.2.30	Tomcat 7.7.0.27-10	78
A.2.31	Xalan 2.7.1	78
A.2.32	Xerces 2.9.1	78
A.2.33	XMLSec 1.3.0	79
A.3	Open Source Licenses	79
A.3.1	Apache 2.0 License	79
A.3.2	BouncyCastle - Adaptation of the MIT X11 License	82
A.3.3	BSD Style License	83
A.3.4	MIT	83
A.3.5	GPL V2.1	84
A.3.6	Javamail	91
A.3.7	JavaService	95
A.3.8	COMMON DEVELOPMENT AND DISTRIBUTION LICENSE (CDDL) Version 1.0	96
A.3.9	GPL V2 + classpath exception dual license	101
A.3.10	Microsoft Public License MS-PL	106
A.3.11	OpenSSL License and SSLeay License	107

A.3.12	GNU LESSER GENERAL PUBLIC LICENSE Version 2.1, February 1999. . . . .	109
A.3.13	GNU GENERAL PUBLIC LICENSE Version 2 . . . . .	116
A.4	Obtaining a Copy of the Media. . . . .	121

---

# About this Book and the Library

The *Installation and Configuration Guide* provides conceptual information about the NetIQ CloudAccess product (CloudAccess). This book contains configuration information for the appliance and for the SaaS applications.

## Intended Audience

This book provides information for individuals responsible for deploying and configuring the CloudAccess appliance and configuring the SaaS applications.

## Other Information in the Library

The library provides the following information resources:

### Help

Provides context-sensitive information and step-by-step guidance for common tasks, as well as definitions for each field on each window.

## Conventions

The library uses consistent conventions to help you identify items throughout the documentation. The following table summarizes these conventions.

Convention	Use
<b>Bold</b>	<ul style="list-style-type: none"><li>♦ Window and menu items</li><li>♦ Technical terms, when introduced</li></ul>
<i>Italics</i>	<ul style="list-style-type: none"><li>♦ Book and CD-ROM titles</li><li>♦ Variable names and values</li><li>♦ Emphasized words</li></ul>
Fixed Font	<ul style="list-style-type: none"><li>♦ File and folder names</li><li>♦ Commands and code examples</li><li>♦ Text you must type</li><li>♦ Text (output) displayed in the command-line interface</li></ul>
Brackets, such as <i>[value]</i>	<ul style="list-style-type: none"><li>♦ Optional parameters of a command</li></ul>
Braces, such as <i>{value}</i>	<ul style="list-style-type: none"><li>♦ Required parameters of a command</li></ul>
Logical OR, such as <i>value1 value2</i>	<ul style="list-style-type: none"><li>♦ Exclusive parameters. Choose one parameter.</li></ul>





---

# About NetIQ Corporation

NetIQ, an Attachmate business, is a global leader in systems and security management. With more than 12,000 customers in over 60 countries, NetIQ solutions maximize technology investments and enable IT process improvements to achieve measurable cost savings. The company's portfolio includes award-winning management products for IT Process Automation, Systems Management, Security Management, Configuration Audit and Control, Enterprise Administration, and Unified Communications Management. For more information, please visit [www.netiq.com](http://www.netiq.com).

## Contacting Sales Support

For questions about products, pricing, and capabilities, please contact your local partner. If you cannot contact your partner, please contact our Sales Support team.

<b>Worldwide:</b>	<a href="http://www.netiq.com/about_netiq/officelocations.asp">www.netiq.com/about_netiq/officelocations.asp</a>
<b>United States and Canada:</b>	888-323-6768
<b>Email:</b>	<a href="mailto:info@netiq.com">info@netiq.com</a>
<b>Web Site:</b>	<a href="http://www.netiq.com">www.netiq.com</a>

## Contacting Technical Support

For specific product issues, please contact our Technical Support team.

<b>Worldwide:</b>	<a href="http://www.netiq.com/Support/contactinfo.asp">www.netiq.com/Support/contactinfo.asp</a>
<b>North and South America:</b>	1-713-418-5555
<b>Europe, Middle East, and Africa:</b>	+353 (0) 91-782 677
<b>Email:</b>	<a href="mailto:support@netiq.com">support@netiq.com</a>
<b>Web Site:</b>	<a href="http://www.netiq.com/support">www.netiq.com/support</a>

## Contacting Documentation Support

Our goal is to provide documentation that meets your needs. If you have suggestions for improvements, click **Add Comment** at the bottom of any page in the HTML versions of the documentation posted at [www.netiq.com/documentation](http://www.netiq.com/documentation). You can also email [Documentation-Feedback@netiq.com](mailto:Documentation-Feedback@netiq.com). We value your input and look forward to hearing from you.

## Contacting the Online User Community

Qmunity, the NetIQ online community, is a collaborative network connecting you to your peers and NetIQ experts. By providing more immediate information, useful links to helpful resources, and access to NetIQ experts, Qmunity helps ensure you are mastering the knowledge you need to realize the full potential of IT investments upon which you rely. For more information, please visit <http://community.netiq.com>.

---

# 1 Overview of NetIQ CloudAccess


CloudAccess is a virtual appliance that enables you to provide secure access to Software-as-a-Service (SaaS) applications for your corporate users.

- ♦ [Section 1.1, “Inherent Problems Using SaaS Applications,” on page 11](#)
- ♦ [Section 1.2, “The Solution CloudAccess Provides,” on page 12](#)
- ♦ [Section 1.3, “How CloudAccess Works,” on page 13](#)
- ♦ [Section 1.4, “How to Manage CloudAccess,” on page 13](#)
- ♦ [Section 1.5, “How CloudAccess Fits into Your Network,” on page 13](#)
- ♦ [Section 1.6, “How CloudAccess Merges Existing Accounts,” on page 14](#)

## 1.1 Inherent Problems Using SaaS Applications

Many corporate users want to use SaaS applications to increase business agility. If the corporation does not provide an easy way for users to obtain accounts for the SaaS applications, several problems can occur. [Figure 1-1](#) depicts some of these problems.

**Figure 1-1** Problems with Using SaaS Applications in the Corporation




Common problems include the following:

- ♦ Users bypass the IT department and create their own accounts in the SaaS application.
- ♦ Users must wait for the IT department to create accounts in the SaaS application. It is a manual process, whether the IT department creates the account or the user creates the account.
- ♦ Users must remember separate passwords for each SaaS application, and often use their corporate credentials.
- ♦ Administrators receive no compliance reports of user activity in the SaaS application.

## 1.2 The Solution CloudAccess Provides

CloudAccess provides a simple, secure solution to the problems presented with using SaaS applications.

**Figure 1-2** CloudAccess Solution



CloudAccess provides the following benefits:

- ♦ An automated process to provision user accounts to the SaaS applications
- ♦ Secure single sign-on to the SaaS applications without corporate credentials leaving the security realm
- ♦ The ability for users to securely access SaaS applications inside or outside of the corporation
- ♦ Compliance reporting of users' activities in the SaaS applications

## 1.3 How CloudAccess Works

CloudAccess is a virtual appliance that provides a Web service for users to access the SaaS applications securely. The appliance performs the following functions:

- ♦ **Provisioning:** CloudAccess allows you to map roles (groups) in an identity source, such as Active Directory or eDirectory, to account authorizations in the SaaS applications. After mapping the authorizations, by leveraging group management in the identity source, CloudAccess automatically creates and manages the associated user accounts in the SaaS application.
- ♦ **Secure Single Sign-on:** CloudAccess provides single sign-on to the SaaS applications and supports Integrated Windows Authentication for background authentication to the certificate authority (CA). Provisioned users automatically have access to the SaaS applications, if they are logged in to the identity source. The corporate credentials never leave the firewall.
- ♦ **Reporting:** CloudAccess provides reports of the usage of the SaaS applications to help enforce corporate policies and prove compliance.
- ♦ **Enabling Mobile Devices:** CloudAccess enables mobile devices to securely access the SaaS applications.

## 1.4 How to Manage CloudAccess

Before you can manage CloudAccess, you must deploy and initialize the appliance. For more information about deploying the appliance, see [Section 2.3, “Deploying the Appliance,” on page 22](#). For more information about initializing the appliance, see [Section 2.5, “Initializing the Appliance,” on page 24](#).

After you have initialized the appliance, the browser automatically redirects to the Admin page. You can also manually access the Admin page as needed. For more information, see [Section 3.1, “Accessing the Administration Pages,” on page 25](#). The Admin page allows you to configure and maintain the appliance. The Admin page also provides navigation icons to access other functions as follows:


- ♦ **Policy:** Maps roles (groups) from the identity source to authorizations from the SaaS applications. For more information, see [Chapter 6, “Mapping Authorizations,” on page 49](#).
- ♦ **Approval:** Approves or denies authorizations for the SaaS applications. This icon appears only if you have mapped roles to authorizations and selected the option to require approval for accounts, and there are accounts waiting for approval. For more information, see [Chapter 7, “Approving Requests,” on page 53](#).
- ♦ **Reports:** Reports on the user activities to the SaaS applications. For more information, see [Chapter 8, “Reporting,” on page 55](#).
- ♦ **Roles:** Configures roles for different users within CloudAccess. For more information, see [Section 3.5.2, “Assigning Roles to Users,” on page 28](#).

Proceed to [Chapter 2.1, “CloudAccess Installation Worksheet,” on page 19](#) to gather the information required to install and configure the appliance.

## 1.5 How CloudAccess Fits into Your Network

The following sample network diagram illustrates how CloudAccess fits into your network.

**Figure 1-3** Sample Network Diagram



CloudAccess resides behind the corporate firewall in your IT network. The diagram depicts a three-node cluster for the appliance communicating through an L4 switch. For more information about clustering, see [Section 3.6, “Configuring Clustering,”](#) on page 29.

The user accounts reside in the identity source. CloudAccess provisions those users to the SaaS application. Users can then access the SaaS application resources by logging in with their identity source accounts, whether they are inside or outside the firewall.

Administration occurs through a browser on a workstation inside or outside of the firewall. The graphic depicts the workstation inside of the firewall.

## 1.6 How CloudAccess Merges Existing Accounts

CloudAccess creates a new account or merges an existing account in the SaaS applications for users that are members of mapped groups in the identity sources. This is called *provisioning*.

Provisioning occurs in two ways:

- ♦ Automatic provisioning occurs when you map authorizations for the SaaS applications to the identity source roles.
- ♦ You can configure the SaaS connectors to allow users control of when their accounts are provisioned. A configuration option is available on the Connector for Google Apps and the Connector for Salesforce to **Prompt users for an existing account before provisioning**.

When you select this option, users have two choices: create a new account or specify an existing SaaS application account during their initial attempt to access the SaaS application using single sign-on through CloudAccess.

When provisioning a new account, CloudAccess determines if a matching user account already exists in the SaaS application. If a match is found, CloudAccess merges the user with the existing SaaS application account. If no match is found, CloudAccess creates a new account. For more information, see the following sections:

- ♦ [Section 1.6.1, “CloudAccess Matching Criteria,” on page 15](#)
- ♦ [Section 1.6.2, “CloudAccess Naming Convention,” on page 16](#)
- ♦ [Section 1.6.3, “Samples of Account Creations,” on page 16](#)

## 1.6.1 CloudAccess Matching Criteria

The following sections define the matching criteria of the connectors that provision users:

- ♦ [“Matching Criteria for the Connector for Google Apps” on page 15](#)
- ♦ [“Matching Criteria for the Connector for Office 365” on page 15](#)
- ♦ [“Matching Criteria for the Connector for Salesforce” on page 16](#)

### Matching Criteria for the Connector for Google Apps

[Table 1-1](#) contains the matching criteria for the Connector for Google Apps. CloudAccess compares the Google Apps email attribute value to the listed identity source attribute value. If there is a match, CloudAccess merges the accounts. If there is no match, CloudAccess creates a new account in Google Apps.

**Table 1-1** Google Apps Matching Criteria

	Google Apps Attribute	Identity Source: Active Directory Attribute	Identity Source: eDirectory Attribute
Attribute Name	UserName	sAMAccountName	CN
Display Name	Email	User logon name	Common Name

### Matching Criteria for the Connector for Office 365

[Table 1-2](#) contains the matching criteria for the Connector for Office 365. CloudAccess compares the Office 365 userPrincipalName attribute value with the value in the identity source attribute plus the @ sign plus the Office 365 federated domain name. If the values match, CloudAccess merges the accounts. If there is no match, CloudAccess creates a new account in Office 365.

**Table 1-2** Office 365 Matching Criteria

	Office 365 Attribute	Identity Source: Active Directory Attribute	Identity Source: eDirectory Attribute
Attribute Name	userPrincipalName (upn)	sAMAccountName@Federated Domain Name	CN@Federated Domain Name
Display Name	User name	User logon name@Federated Domain Name	Common Name@Federated Domain Name

## Matching Criteria for the Connector for Salesforce

Table 1-3 contains the matching criteria for the Connector for Salesforce. CloudAccess matches on three different attributes in a priority order. If CloudAccess does not find a match for the value in the first attribute, it performs a search in the value of the second attribute, and if it does not find a match, it performs the search for the value in the third attribute.

**Table 1-3** *Salesforce Matching Criteria*

	Salesforce Attribute	Identity Source: Active Directory Attribute	Identity Source: eDirectory Attribute
<b>First Priority</b>			
Attribute Name	Federation Identifier	objectGUID	GUID
<b>Second Priority</b>			
Attribute Name	Username	sAMAccountName@Salesforce Domain Name	CN@Salesforce Domain Name
Display Name	Username	User logon name@Salesforce Domain Name	Common Name@Salesforce Domain Name
<b>Third Priority</b>			
Attribute Name	Username	mail	Internet EMail Address
Display Name	Username	E-mail	E-Mail Address

### 1.6.2 CloudAccess Naming Convention

CloudAccess contains a defined naming convention for creating the user accounts in the SaaS applications.

**Table 1-4** *CloudAccess Naming Convention*

Identity Source	Connector for Google Apps	Connector for Salesforce
Active Directory	sAMAccountName	sAMAccountName@Salesforce Domain Name
eDirectory	CN	CN@Salesforce Domain Name

As shown in Table 1-4, the user name attribute in Salesforce is in the form of an email address. CloudAccess creates a unique user name based on the sAMAccountName or CN of the user object in the identity source prepended to the domain name configured in the Company Profile at the Salesforce account.

### 1.6.3 Samples of Account Creations

Sample experience with the **Prompt users for an existing account before provisioning** option enabled:

1. The administrator selects the **Prompt users for an existing account before provisioning** option when configuring the connector for the SaaS application.



2. The administrator maps one or more SaaS authorizations to the identity source role and grants approval, if required.
3. Users log in to CloudAccess with their identity source credentials.
4. CloudAccess presents users with icons of the SaaS applications they are entitled to access.
5. Users click the icon for the entitled SaaS application.
6. CloudAccess presents two options to users:
  - ♦ **I do not have an existing account. Create one for me.**
  - ♦ **I already have an existing account. These are my credentials:**
7. Users select **I do not have an existing account. Create one for me.**

or

Users select **I already have an existing account. These are my credentials**, then specify their credentials for the existing SaaS account.
8. Regardless of the option the user selects, CloudAccess searches for an existing, matching account.
9. (Conditional) If CloudAccess finds an existing account (for example, the user's mail attribute in the identity source matches a user name in the Salesforce domain), CloudAccess merges the existing account with the new account it creates for the user.
10. (Conditional) If CloudAccess does not find an existing account, CloudAccess creates a new account for the user in the SaaS application following the naming conventions in [Table 1-4 on page 16](#).

Whether CloudAccess merges the user account or creates a new account, the user's SaaS application password is set to a random value that CloudAccess generates. The user's authentication to the SaaS application now uses SAML single sign-on. For information about using SAML single sign-on, see [Chapter 5, "Providing Access to the SaaS Applications for Users," on page 47](#).

Sample experience with the automatic account creation:

1. The administrator maps one or more SaaS authorizations to the identity source role and grants approval, if required.
2. (Conditional) The person with the Approval role approves or denies the account creation.
3. CloudAccess searches for an existing, matching account.
4. (Conditional) If CloudAccess finds an existing account (for example, the user's mail attribute in the identity source matches a user name in the Salesforce domain), CloudAccess merges the existing account with the new account it creates for the user.
5. (Conditional) If CloudAccess does not find an existing account, CloudAccess creates a new account for the user in the SaaS application following the naming conventions in [Table 1-4 on page 16](#).
6. Users log in to CloudAccess with their identity source credentials.
7. CloudAccess presents users with icons of the SaaS applications they are entitled to access.
8. Users click the icon for the entitled SaaS application, then CloudAccess uses the SAML single sign-on to authenticate the users to the SaaS application.



---

# 2 Installing CloudAccess

CloudAccess is a VMware appliance that you download and deploy into your IT environment.

- ♦ [Section 2.1, “CloudAccess Installation Worksheet,” on page 19](#)
- ♦ [Section 2.2, “Requirements,” on page 19](#)
- ♦ [Section 2.3, “Deploying the Appliance,” on page 22](#)
- ♦ [Section 2.4, “Configuring the Appliance Without a DHCP Server,” on page 23](#)
- ♦ [Section 2.5, “Initializing the Appliance,” on page 24](#)

## 2.1 CloudAccess Installation Worksheet

Use the following worksheet to gather the required information to install and configure CloudAccess.

- ☐ **Networking Information:** Gather the following networking information:
  - ☐ Publicly resolvable DNS name for the appliance
  - ☐ NTP server
  - ☐ DNS server, subnet mask, and gateway
  - ☐ An SSL certificate signed by a well known certificate authority (CA)
- ☐ **Identity Sources:** Gather the following information to configure the identity sources, such as Active Directory or eDirectory, for CloudAccess:
  - ☐ IP address or DNS name of the server that contains the users
  - ☐ Context of the users
  - ☐ Name and password of a user with the proper rights to the users
- ☐ **Connector Information:** Gather the information needed to configure the Connector for Google Apps for Business, the Connector for Office 365, or the Connector for Salesforce, as applicable to your environment. For more information, see [Section 4.1, “Connector for Google Apps for Business,” on page 37](#), [Section 4.2, “Connector for Office 365,” on page 39](#), or [Section 4.3, “Connector for Salesforce,” on page 41](#).

## 2.2 Requirements

Use the information in the following table to verify that you meet the requirements for CloudAccess before deploying the appliance.

**Table 2-1** *CloudAccess Requirements*

Components	Requirements
VMware	One of the following versions of VMware: <ul style="list-style-type: none"><li>◆ vSphere Hypervisor 5.0</li><li>◆ vSphere 5.0</li><li>◆ ESXi 4.1</li><li>◆ ESX 4.1</li></ul>
Node	Minimum hardware requirements for each appliance node in the cluster: <ul style="list-style-type: none"><li>◆ 60 GB disk space</li><li>◆ 2 Cores</li><li>◆ 8 GB RAM</li></ul>
Cluster	Supported cluster configuration: <ul style="list-style-type: none"><li>◆ Up to a five-node cluster</li><li>◆ Each node must reside in the same IP subnet</li></ul>
Browsers	<b>Administration:</b> Supported browsers for administration tasks: <ul style="list-style-type: none"><li>◆ Firefox 17 and 18 on Windows 7</li><li>◆ Google Chrome on Windows 7</li><li>◆ Internet Explorer 9 on Windows 7</li></ul> <b>Users:</b> Supported browsers for users: <ul style="list-style-type: none"><li>◆ Firefox 17 and 18 on Windows 7</li><li>◆ Internet Explorer 9 on Windows 7</li><li>◆ Safari 5 on Windows 7</li></ul>
Mobile Devices	<b>Administration:</b> Not supported on mobile devices. <b>Users:</b> Supported mobile devices for users: <ul style="list-style-type: none"><li>◆ iPhone with iOS 6.x</li><li>◆ iPad with iOS 6.x</li></ul>
Email Clients	Supported email clients for the email proxy: <ul style="list-style-type: none"><li>◆ Windows Live Mail 2011</li><li>◆ Latest version of Apple Mail Client on iPad or iPhone with iOS 6.x</li></ul>
DNS	CloudAccess requires that all appliance nodes, administration workstations, end-user workstations, and identity sources be able to resolve the public DNS name of the appliance.
SaaS Application Requirements	Each SaaS application has different requirements. To see the requirements for each SaaS application, see the <a href="#">Chapter 4, "Configuring Connectors," on page 37</a> .

Components	Requirements
Active Directory	<p>Verify that your Active Directory environment meets the following requirements:</p> <ul style="list-style-type: none"> <li>♦ Only Windows Server 2008 R2.</li> <li>♦ A unique identity for each user account, whether you have one or more domains. CloudAccess uses the sAMAccountName as the unique identifier for the users.</li> <li>♦ All of the following required Active Directory attributes populated on the Active Directory users: <ul style="list-style-type: none"> <li>♦ First name</li> <li>♦ Last name</li> <li>♦ Full name (<b>Display name</b> is the field that populates this attribute.)</li> <li>♦ sAMAccountName or Logon Name (Pre-Windows 2000)</li> <li>♦ User Principal Name (UPN)</li> <li>♦ Email address</li> </ul> </li> </ul> <p>For more information, see <a href="#">Section 3.4.1, “Active Directory Mandatory Attributes,” on page 27</a>.</p> <p>Obtain the following required items:</p> <ul style="list-style-type: none"> <li>♦ The password and the fully distinguished LDAP-formatted name of a user in Active Directory that has read access to the user objects. This user makes LDAP binds to Active Directory.</li> <li>♦ The name and password of a user in Active Directory that becomes the administrator of the appliance. The user must reside in the search context of the domains.</li> <li>♦ The IP address of one or more Active Directory servers that contain the users.</li> <li>♦ The context of the users in Active Directory.</li> </ul>

Components	Requirements
eDirectory	<p>Verify that your eDirectory environment meets the following requirements:</p> <ul style="list-style-type: none"> <li>♦ eDirectory 8.8.7 or eDirectory 8.8.6.</li> <li>♦ All of the following required eDirectory attributes populated on the eDirectory users: <ul style="list-style-type: none"> <li>♦ CN (<b>Username</b> is the field that populates this attribute.)</li> <li>♦ Given Name (<b>First name</b> is the field that populates this attribute.)</li> <li>♦ Internet EMail Address</li> <li>♦ Surname (<b>Last name</b> is the field that populates this attribute.)</li> </ul> </li> </ul> <p>For more information, see <a href="#">Section 3.4.2, “eDirectory Mandatory Attributes,” on page 28</a>.</p> <p>Obtain the following required items:</p> <ul style="list-style-type: none"> <li>♦ The password and fully distinguished LDAP-formatted name of a user in eDirectory that has the following rights: <ul style="list-style-type: none"> <li>♦ <b>Property Rights</b> <ul style="list-style-type: none"> <li>♦ <b>CN:</b> compare, read, inherit</li> <li>♦ <b>Description:</b> compare, read, inherit</li> <li>♦ <b>Given Name:</b> compare, read, inherit</li> <li>♦ <b>GUID:</b> compare, read, inherit</li> <li>♦ <b>Internet EMail Address:</b> compare, read, inherit</li> <li>♦ <b>Login Disabled:</b> compare, read, inherit</li> <li>♦ <b>Member:</b> compare, read, inherit</li> <li>♦ <b>Group Membership:</b> compare, read, inherit</li> <li>♦ <b>Surname:</b> compare, read, inherit</li> </ul> </li> <li>♦ <b>Entry Rights:</b> browse, inherit</li> </ul> </li> <li>♦ The name and password of a user in eDirectory that becomes the administrator of the appliance. The user must reside in the subtree of the search context for the identity source specified during the initialization of the appliance.</li> <li>♦ The IP address of one or more eDirectory servers that contain a replica of the partition holding the user objects and that run NLDAP.</li> <li>♦ The context of the users in eDirectory.</li> </ul>

## 2.3 Deploying the Appliance

CloudAccess is an OVF virtual appliance. For more information about virtual appliances, see [What is OVF? \(http://www.vmware.com/appliances/getting-started/learn/ovf.html\)](http://www.vmware.com/appliances/getting-started/learn/ovf.html).

You must deploy the appliance to your VMware server.

- 1 If you are using Windows, extract the VMware image.

or

If you are using Linux, use the following command to extract the image:

```
tar -zxvf vmware_image.tar.gz
```

- 2 Deploy the CloudAccess virtual appliance.

For more information, see [Deploy Virtual Appliances \(http://www.vmware.com/it/appliances/getting-started/deploy/get\\_started.html\)](http://www.vmware.com/it/appliances/getting-started/deploy/get_started.html).

- 3 If you do not have a DHCP server in your environment, skip to [Section 2.4, “Configuring the Appliance Without a DHCP Server,”](#) on page 23.

or

Power on the appliance, then proceed to [Section 2.5, “Initializing the Appliance,”](#) on page 24.

The initial boot configures CloudAccess. The initial boot could take between five and twenty minutes for the configuration to complete. When the appliance is ready, it displays a welcome message with the initialization URL `https://ip_address/appliance/Init.html`.

You can deploy the OVF file or convert the OVF file to a VMX file. If you use the VMX file, disable the default option of **Synchronize guest time with host** option for the image. Right-click the appliance in the VMware client, then deselect **Edit Settings > Options > VMware Tools > Synchronize guest time with host**.

## 2.4 Configuring the Appliance Without a DHCP Server

To configure the appliance, the appliance must obtain an IP address through DHCP or have a static IP address assigned through the VMware settings. Perform these steps *only* if there is no DHCP server in your environment. If a DHCP server exists in your environment, you can assign a static IP address after the initial boot without editing the VMware settings.

Edit the VMX file and add the following lines with the appropriate values for your environment:

```
#These settings are related to date/time/timezone and NTP server
#Configures /etc/sysconfig/clock and /etc/ntp.conf
guestinfo.prop1="CLONE_DATE="
guestinfo.prop2="CLONE_timezone="
guestinfo.prop3="CLONE_NTP_SERVER="
guestinfo.prop4="CLONE_HWCLOCK="
guestinfo.prop5="CLONE_SYSTOHC="

#
#Network related settings
#CLONE_DO_DHCP=false, only configure static settings
#CLONE_DO_DHCP=true, tries DHCP and if it fails configure with static settings
guestinfo.prop6="CLONE_DHCP=true"
guestinfo.prop7="CLONE_DNS_NAME_SERVER1="
guestinfo.prop8="CLONE_DNS_NAME_SERVER2="
guestinfo.prop9="CLONE_DNS_NAME_SERVER3="
guestinfo.prop10="CLONE_DNS_SEARCH1="
guestinfo.prop11="CLONE_DNS_SEARCH2="
guestinfo.prop12="CLONE_DNS_SEARCH3="
guestinfo.prop13="CLONE_NETMASK="
guestinfo.prop14="CLONE_DEFAULT_GATEWAY="
guestinfo.prop15="CLONE_IP="
guestinfo.prop16="CLONE_DNS_NAME="
```

If you do not need a setting, either leave the value blank, or leave the setting out of the VMX file altogether. Power on the appliance, then proceed to [Section 2.5, “Initializing the Appliance,”](#) on page 24.

## 2.5 Initializing the Appliance

You must now initialize the appliance.

- 1 Verify that you meet the requirements listed in [Section 2.2, “Requirements,”](#) on page 19.
- 2 From a supported browser, access the initialization Web interface at the URL displayed on the appliance screen after it is deployed.

For example: `https://ip_address/appliance/Init.html`

- 3 Fill in the fields displayed to initialize the appliance.
- 4 Click **Finish**.

A successfully initialized appliance automatically redirects the browser to the CloudAccess administration login page (`https://dns_of_appliance/appliance/index.html`).

- 5 Specify the admin user name of the appliance and password, then proceed with [Chapter 3, “Configuring the Appliance,”](#) on page 25.



---

# 3 Configuring the Appliance

After you have initialized the appliance, configure the appliance to communicate with the SaaS applications.

- ♦ [Section 3.1, “Accessing the Administration Pages,” on page 25](#)
- ♦ [Section 3.2, “Registering CloudAccess,” on page 26](#)
- ♦ [Section 3.3, “Configuring Additional Identity Sources,” on page 26](#)
- ♦ [Section 3.4, “Verifying the Identity Source User Attributes,” on page 27](#)
- ♦ [Section 3.5, “Configuring Roles Management,” on page 28](#)
- ♦ [Section 3.6, “Configuring Clustering,” on page 29](#)
- ♦ [Section 3.7, “Configuring Integrated Windows Authentication with Kerberos,” on page 33](#)

## 3.1 Accessing the Administration Pages

After you properly initialize the appliance using the information in [Section 2.5, “Initializing the Appliance,” on page 24](#), the browser automatically redirects to the administration pages at `https://dns_of_appliance/appliance/index.html`.

If the initialization does not automatically redirect or you need access to the administration pages, use the following steps:

- 1 In a supported browser, enter `https://dns_of_appliance/appliance/index.html`.
- 2 Log in as the administrator of the appliance as specified during the initialization process.

This user name is the identity source user name specified during the initialization process.

The first time you log in, the appliance displays the Admin page and activates users in the search contexts from the identity source. Ensure that this process completes before configuring any SaaS applications.

Icons at the top of the Admin page allow you to access the other administration pages. If your session times out or you log out, the next time you log in to the appliance, CloudAccess displays the page that you last accessed.

For a list of the different administration pages, see [Section 1.4, “How to Manage CloudAccess,” on page 13](#).

## 3.2 Registering CloudAccess

CloudAccess provides a 30-day trial period. If you do not register the appliance within 30 days after installation, the appliance stops working. The bomb icon on the Admin page displays how many days are left in the trial period.

For the purpose of meeting licensing requirements, when you register a single appliance, the cluster as a whole is considered to be registered. However, in order to use the Novell Customer Center (NCC) update channel to download and install software updates, you must register each node in the cluster separately. The bomb icon remains on the Admin page if there are nodes in the cluster that have not yet been registered for channel updates. For more information about the update channel, see [Section 10.3, “Updating the Appliance,” on page 60](#).

To register your appliance:

- 1 Log in to your Customer Center at <http://www.novell.com/center> (<http://www.novell.com/center>).  
The Customer Center is for NetIQ, Novell, and SUSE customers.
- 2 Under **My Products**, select **CloudAccess**.
- 3 Select **License Key**, then save the license key to a location where you can access it from your CloudAccess appliance.
- 4 Log in to your CloudAccess appliance and access the Admin page.  
For more information, see [Section 3.1, “Accessing the Administration Pages,” on page 25](#).
- 5 Click the appliance, then click **Register Appliance**.
- 6 Enter the email address you used when you registered with the Customer Center.
- 7 Enter the license key you downloaded from the Customer Center.
- 8 Click **Register**.
- 9 Repeat [Step 5](#) through [Step 8](#) for each appliance in the cluster.

When you have successfully registered all nodes in the cluster, the bomb icon disappears.

## 3.3 Configuring Additional Identity Sources

CloudAccess supports the use of one or more identity sources to authenticate users and as a source for provisioning accounts to the SaaS applications. The initialization process configures the first identity source and adds the identity source to the Admin page.

CloudAccess currently supports two different types of identity sources: Active Directory and eDirectory. You can have one or more of each type of identity source configured in your appliance.

To change the initial identity source configuration information, on the Admin page, click the identity source, then click **Configure**.

---

**NOTE:**

- ♦ Although CloudAccess allows you to modify an existing eDirectory or Active Directory connector to point to a different tree, NetIQ does not recommend this approach because it can result in inconsistent display of user and group data. If you want to point a connector to a different tree, delete the existing connector and create a new connector that points to the correct tree.
  - ♦ CloudAccess does not prevent you from configuring multiple eDirectory or Active Directory connectors that point to the same identity source. However, in order for the appliance to behave as expected and present accurate data, each identity source connector must point to a unique identity source.
- 

To add another identity source:

- 1 Navigate to the CloudAccess Admin page.  
For more information, see [Section 3.1, “Accessing the Administration Pages,” on page 25](#).
- 2 Click the **Admin** icon on the toolbar.
- 3 Drag and drop an identity source icon from the Identity Palette to the bar in the middle of the page.
- 4 Click the identity source icon, then click **Configure**.
- 5 Fill in the fields to configure the new identity source, then click **OK** to save the configuration information.
- 6 Click **Apply** to commit the changes to the appliance.

## 3.4 Verifying the Identity Source User Attributes

To successfully provision users to the SaaS applications, each user must contain certain attributes. CloudAccess uses these mandatory attributes to provision the user accounts to the SaaS applications. The attributes for each identity source are different.

For security reasons you cannot add a user to CloudAccess with a user name that is the same as a previously added user. If you attempt to do so, CloudAccess displays the user as not activated. For more information, see [Section 11.4, “Provisioning Behavior,” on page 68](#).

- ♦ [Section 3.4.1, “Active Directory Mandatory Attributes,” on page 27](#)
- ♦ [Section 3.4.2, “eDirectory Mandatory Attributes,” on page 28](#)

### 3.4.1 Active Directory Mandatory Attributes

Each Active Directory user account must contain the following attributes for CloudAccess to provision the user accounts to the SaaS applications:

- ♦ First Name
- ♦ Last Name
- ♦ Full Name
- ♦ sAMAccountName or Logon Name (Pre-Windows 2000)
- ♦ User Principal Name (UPN)
- ♦ Email address

## 3.4.2 eDirectory Mandatory Attributes

Each eDirectory user account must contain the following attributes for CloudAccess to provision the user accounts to the SaaS applications:

- ♦ CN
- ♦ Given Name
- ♦ Internet EMail Address
- ♦ Surname

## 3.5 Configuring Roles Management

CloudAccess provides the ability to assign different roles to administrative users in your identity sources. The roles allow administrators to perform certain tasks and deny them access to other tasks.

- ♦ [Section 3.5.1, “Defining the Role Types,” on page 28](#)
- ♦ [Section 3.5.2, “Assigning Roles to Users,” on page 28](#)

### 3.5.1 Defining the Role Types

CloudAccess includes the following types of roles:

- ♦ **Appliance Administrator:** The appliance administrator has full rights to all appliance administration pages and role assignments. You assign the first appliance administrator during the initialization of the appliance.
- ♦ **Application Owner:** The application owner controls access to the SaaS applications. CloudAccess automatically assigns this role to the user that creates the SaaS application on the Admin page. The application owner can access the following Web pages:
  - ♦ **Approvals:** The application owner can allow or deny approvals for the users to obtain a SaaS application account.
  - ♦ **Policy:** The application owner can map authorizations between the identity source and the SaaS application and optionally require approval for authorizations.
  - ♦ **Roles:** The application owner can add or remove users from the application approver role.
- ♦ **Application Approver:** The application approver can access the Approvals page and allow or deny approvals for the users to obtain a SaaS application account. CloudAccess automatically assigns this role to the user that creates the SaaS application on the Admin page.
- ♦ **Compliance Auditor:** The compliance auditor can access the Reports page and generate, view, and download the reports for the appliance. Users assigned to the appliance administrator role have access to the Reports page automatically.

In addition to the default role assignments, you can assign each role to additional users. However, the Roles page never allows you to remove the last appliance administrator role.

### 3.5.2 Assigning Roles to Users

To assign roles to users:

- 1 Access the CloudAccess Admin page as the appliance administrator or application owner.  
For more information, see [Section 3.1, “Accessing the Administration Pages,” on page 25](#).

- 2 Click **Roles** on the toolbar.
- 3 Drag and drop the user to the role you want to assign to that user, then click **OK** to confirm the assignment.

The Roles page displays only the application owner and application approver roles of configured SaaS connectors.

## 3.6 Configuring Clustering

You can cluster the CloudAccess appliance. By default, it is a single node cluster, but CloudAccess supports up to a five-node cluster. You add a node to the cluster by selecting **Join Cluster** during the initialization process.

- ♦ [Section 3.6.1, “Advantages of Clustering,” on page 29](#)
- ♦ [Section 3.6.2, “Managing Nodes in the Cluster,” on page 29](#)
- ♦ [Section 3.6.3, “Configuring an L4 Switch for Clustering,” on page 31](#)
- ♦ [Section 3.6.4, “Configuring an L4 Switch for Email Proxy,” on page 31](#)

### 3.6.1 Advantages of Clustering

Clustering in CloudAccess offers several advantages. Most of these advantages are available only if you configure an L4 switch or Round-robin DNS. The L4 switch is the best solution.

**Disaster Recovery:** Adding additional nodes to the cluster provides disaster recovery for your appliance. If one node stops running or becomes corrupt, you can promote another node to master.

**High Availability for Authentications:** CloudAccess provides high availability for authentications and the single sign-on service, when using an L4 switch in conjunction with clustering. This solution allows users to authenticate in case of problems with the nodes within the cluster. The L4 switch sends authentication requests to the nodes with which it can communicate.

**Load Balancing:** You can configure the L4 switch to distribute authentications to nodes so one node does not receive all authentication requests while other nodes sit idle.

**Scalability:** Configuring an L4 switch with clustering increases the scalability of CloudAccess. Each node in the cluster increases the number of possible simultaneous logins.

### 3.6.2 Managing Nodes in the Cluster

CloudAccess supports up to five nodes in a cluster. You add nodes to the cluster through the initialization process, and perform all other initialization tasks on the Admin page.

- ♦ [“Adding a Node to the Cluster” on page 29](#)
- ♦ [“Promoting a Node to Master” on page 30](#)
- ♦ [“Removing a Node from the Cluster” on page 31](#)

#### Adding a Node to the Cluster

Complete the following steps to add a node to the cluster:

- 1 Verify the cluster is healthy.
  - ♦ All nodes must be running and communicating.

- ♦ All components must be in a green state.
- ♦ All failed nodes must be removed from the cluster.

For more information about verifying that your cluster is healthy, see [Section 11.3, “Troubleshooting Different States,” on page 65](#).

- 2 Download and deploy a new VM machine for the new node.

For more information, see [Section 2.3, “Deploying the Appliance,” on page 22](#).

- 3 Select **Join Cluster** as the first step to initialize the new node, then follow the on-screen prompts.

For more information, see [Section 2.5, “Initializing the Appliance,” on page 24](#).

- 4 Wait for the login screen for the Admin page to be displayed. A progress bar indicates how much time this will take.

- 5 Log in to the Admin page, and wait until all spinner icons stop processing and all components are green before performing any other tasks.

The cluster is adding the node and there are several background processes running. This final step could take up to an hour to complete.

## Promoting a Node to Master

The first node that you install is the master node of the cluster by default. The master node runs provisioning, reporting, approvals, and policy mapping services. You can promote any node to become the master node.

To promote a node to master:

- 1 Verify that the cluster is healthy.  
For more information, see [Section 11.3, “Troubleshooting Different States,” on page 65](#).
- 2 Verify that all nodes in the cluster are running the same version of CloudAccess. If any nodes need to be updated, ensure that you update the nodes *before* you switch the master node. For more information, see [Section 10.3, “Updating the Appliance,” on page 60](#).
- 3 Take a snapshot of the cluster.
- 4 Click the node to become the master node on the Admin page, then click **Promote to Master**.

An M appears on the front of the node icon indicating it is now the master node.

The services move from the old master to the new master. The old master is now just a node in the cluster.

When you switch the master node, the logs start again on the new master and reports start again on the new master. The historical logs are lost. The reporting data is also lost, unless you are using Sentinel Log Manager. For more information, see [Section 8.2, “Integrating with Sentinel Log Manager,” on page 55](#).

---

**WARNING:** If the old master node is down when you promote another node to master, remove the old master from the cluster, then delete it from the VMware server. Otherwise, the appliance sees two master nodes and becomes corrupted.

---

## Removing a Node from the Cluster

You can remove a node from the cluster if something is wrong with the node. However, after you remove a node, you cannot add the same VM instance back into the cluster. You must delete this instance of the appliance from your VMware server, then deploy another instance to the VMware server to add a node back into the cluster.

To remove a node from the cluster:

- 1 (Conditional) If the node you are removing is the master node, promote another node to be master. For more information, see [“Promoting a Node to Master” on page 30](#).
- 2 (Conditional) If you are using an L4 switch, delete the node from the L4 switch. For more information, see the L4 switch documentation.
- 3 On the Admin page, click the node you want to remove from the cluster.
- 4 Click **Remove from Cluster**.  
The Admin page immediately shows that the node is gone, but it takes some time for the background processes to finish.
- 5 Delete the instance of the node from the VMware server.

### 3.6.3 Configuring an L4 Switch for Clustering

If you want high availability or load balancing, you must configure an L4 switch for the CloudAccess appliance. An L4 switch can be configured in many different ways. Use the following recommendations to configure the L4 switch to work with the appliance.

- ♦ **Heartbeat:** Use the following URL to define the heartbeat for the L4 switch:

```
https://ip_address_of_appliance/osp/h/heartbeat
```

The L4 switch uses the heartbeat to determine if the nodes in the cluster are running and working properly. The heartbeat URL returns a text message of Success and a 200 response code.

- ♦ **Persistence:** Also known as **sticky sessions**, allows all subsequent requests from a client to be sent to the same computer. To make this happen, select SSL session ID persistence when configuring the L4 switch.

Persistence increases the performance of the appliance for the end users, by removing the delay that might occur if the client sends a request to a new node instead of using the existing session to the same node.

### 3.6.4 Configuring an L4 Switch for Email Proxy

CloudAccess contains an email proxy for users with Google Apps that supports three protocols: SMTP, POP3S, and IMAPS. You must configure your L4 switch to handle these protocols. Use the following high level steps to configure the protocols for your L4 switch. For more information, see your specific L4 documentation.

- ♦ [“Configuring the SMTP Protocol Handler” on page 32](#)
- ♦ [“Configuring the POP Protocol Handler” on page 32](#)
- ♦ [“Configuring the IMAP Protocol Handler” on page 33](#)

## Configuring the SMTP Protocol Handler

Use the following steps to configure an SMTP protocol handler for your L4 switch:

- 1 On your L4 switch, configure a new IP group (traffic group) or use an existing group for the virtual servers in the L4 switch.  
You can use this group for all of the protocols.
- 2 (Optional) Create a health monitor.
  - 2a Set the health checking for the pool to **TCP transaction monitor**.
  - 2b Set the timeout to 30 seconds.
  - 2c Set the health monitor to separately monitor each node.
- 3 Create a traffic pool for the SMTP virtual server to use.
  - 3a Add each appliance node to the pool using the IP address with the port.  
For example: 192.168.1.14:25. The SMTP port is 25.
  - 3b (Optional) Add the health monitor created in [Step 2](#).
  - 3c Select your load balancing settings.  
For example: round robin or random
  - 3d Set the session persistence to **SSL Session ID**.
- 4 Create a new virtual server.
  - 4a Specify the protocol as SMTP and the port as 25.
  - 4b Use the traffic group defined in [Step 1](#) and the pool defined in [Step 3](#) for the virtual server.
- 5 Start the virtual server.

## Configuring the POP Protocol Handler

Use the following steps to configure a POP protocol handler for your L4 switch:

- 1 On your L4 switch, configure a new IP group (traffic group) or use an existing group for the virtual servers in the L4 switch.  
You can use this group for all of the protocols.
- 2 (Optional) Create a health monitor.
  - 2a Set the health checking for the pool to **TCP transaction monitor**.
  - 2b Set the timeout to 30 seconds.
  - 2c Set the health monitor to separately monitor each node.
- 3 Create a traffic pool for the POP virtual server to use.
  - 3a Add each appliance node to the pool using the IP address with the port.  
For example: 192.168.1.14:995. The POP port is 995.
  - 3b (Optional) Add the health monitor created in [Step 2](#).
  - 3c Select your load balancing settings.  
For example: round robin or random
  - 3d Set the session persistence to **SSL Session ID**.



- 4 Create a new virtual server.
  - 4a Specify the protocol as SSL (POP3S) and the port as 995.
  - 4b Use the traffic group defined in [Step 1](#) and the pool defined in [Step 3](#) for the virtual server.
- 5 Start the virtual server.

## Configuring the IMAP Protocol Handler

Use the following steps to configure an IMAP protocol handler for your L4 switch:

- 1 On your L4 switch, configure a new IP group (traffic group) or use an existing group for the virtual servers in the L4 switch.

You can use this group for all of the protocols.
- 2 (Optional) Create a health monitor.
  - 2a Set the health checking for the pool to **Connect**.
  - 2b Set the health monitor to separately monitor each node.
- 3 Create a traffic pool for the IMAP virtual server to use.
  - 3a Add each appliance node to the pool using the IP address with the port.

For example: 192.168.1.14:993. The IMAP port is 993.
  - 3b (Optional) Add the health monitor created in [Step 2](#).
  - 3c Select your load balancing settings.

For example: round robin or random
  - 3d Set the session persistence to **SSL Session ID**.
- 4 Create a new virtual server.
  - 4a Specify the protocol as SSL (IMAPS) and the port as 993.
  - 4b Use the traffic group defined in [Step 1](#) and the pool defined in [Step 3](#) for the virtual server.
- 5 Start the virtual server.

## 3.7 Configuring Integrated Windows Authentication with Kerberos

CloudAccess allows user authentication with either name and password or Integrated Windows Authentication with Kerberos if your identity source is Active Directory. If you choose to use Integrated Windows Authentication, you must configure Kerberos.

CloudAccess supports the use of only one Kerberos realm. If there are multiple Active Directory domains used as the identity source, all of the domains must use the same realm.

Use the information in the following sections to enable Kerberos authentication between Active Directory and CloudAccess.

- ♦ [Section 3.7.1, “Configuring the Kerberos User in Active Directory,” on page 34](#)
- ♦ [Section 3.7.2, “Configuring the Appliance to Use Integrated Windows Authentication with Kerberos,” on page 34](#)
- ♦ [Section 3.7.3, “Configuring the End User Browsers,” on page 35](#)

### 3.7.1 Configuring the Kerberos User in Active Directory

Use the following steps to configure Kerberos on your Active Directory domain:

- 1 As an Administrator in Active Directory, use MMC to create a new user within the search context specified during the initialization of the appliance.

Name the new user according to the Host and DNS name of the appliance. For example, if the public DNS of the appliance is `serv1.cloudaccess.com` and the context that has been enabled for cloud is `ou=acme corporation,dc=cloudaccess,dc=com`, use the following information to create the user:

**First name:** `serv1`

**User login name:** `HTTP/serv1.cloudaccess.com`

**Pre-windows logon name:** `serv1`

**Set password:** Specify the desired password.

For example: `Passw0rd`

**Password never expires:** Select this option.

- 2 Associate the new user with the service principal name.

Any domain or realm references must be uppercase.

**2a** On the Active Directory server, open a cmd shell.

**2b** At the command prompt, enter the following:

```
setspn -A HTTP/appliancepublicdns@UPN.SUFFIX newusershortname
```

For example: `setspn -A HTTP/serv1.cloudaccess.com@cloudaccess.COM serv1`

**2c** Verify setspn by entering `setspn -L shortusername`

For example: `setspn -L serv1`

- 3 Generate the keytab file using the `ktpass` utility.

Any domain or realm references must be uppercase.

**3a** At the command prompt, enter the following:

```
ktpass /out filename /princ servicePrincipalName /mapuser userPrincipalName /pass userPassword
```

For example: `ktpass /out nidp.keytab /princ HTTP/`

`serv1.cloudaccess.com@cloudaccess.COM /mapuser serv1@cloudaccess.COM /pass Passw0rd`

**3b** Ignore the message Warning: `pType` and `account type` do not match.

- 4 Copy the `nidp.keytab` file created in [Step 3](#) to the browser of the client computer that you are using for administration.

### 3.7.2 Configuring the Appliance to Use Integrated Windows Authentication with Kerberos

The following steps enable the appliance to use Integrated Windows Authentication (IWA) with Kerberos, if your identity source is Active Directory.

- 1 Log in to the Admin page.

For more information, see [Section 3.1, “Accessing the Administration Pages,” on page 25](#).

- 2 Click the Active Directory icon in the Identity Sources palette, then click **Configure**. (Do not drag the icon to the bar as you would when configuring the Connector for Active Directory itself. These IWA configuration options are global for all Connectors for Active Directory.)
- 3 Select **Integrated Windows Authentication**.
- 4 In the **Keytab** field click **Browse**, then browse to and select the `nidp.keytab` file generated in [“Configuring the Kerberos User in Active Directory” on page 34](#).
- 5 Click **OK** to save the changes.
- 6 Click **Apply** to apply the changes to the appliance.

### 3.7.3 Configuring the End User Browsers

To complete the Kerberos configuration for Active Directory, configure the end user browser. For more information, see [Section 9.3, “Configuring End User Browsers for Kerberos Authentication,” on page 58](#).



---

# 4 Configuring Connectors

CloudAccess provides multiple connectors to SaaS applications. The Connector for Google Apps for Business, the Connector for Salesforce, and the Connector for Office 365 enable account provisioning and single sign-on. The other available connectors provide only single sign-on.

- ♦ [Section 4.1, “Connector for Google Apps for Business,” on page 37](#)
- ♦ [Section 4.2, “Connector for Office 365,” on page 39](#)
- ♦ [Section 4.3, “Connector for Salesforce,” on page 41](#)
- ♦ [Section 4.4, “Single Sign-On Connectors,” on page 44](#)
- ♦ [Section 4.5, “Importing and Configuring Custom Connectors,” on page 45](#)

## 4.1 Connector for Google Apps for Business

Use the information in the following sections to configure a Connector for Google Apps for Business:

- ♦ [Section 4.1.1, “Meeting the Requirements,” on page 37](#)
- ♦ [Section 4.1.2, “Configuring the Connector for Google Apps for Business,” on page 37](#)
- ♦ [Section 4.1.3, “Configuring Multiple Connectors for Google Apps for Business,” on page 39](#)

### 4.1.1 Meeting the Requirements

Verify that you meet the following requirements before configuring the Connector for Google Apps for Business:

- ☐ A valid Google Apps for Business account
- ☐ Provisioning APIs enabled on the account
- ☐ An administrative account and password

### 4.1.2 Configuring the Connector for Google Apps for Business

Each cluster can support multiple instances of the Connector for Google Apps for Business. Once configured, the Connector for Google Apps for Business provides user account provisioning and single sign-on access to Google Apps for Business domains. After users log in to CloudAccess, SAML authentication is used to automatically authenticate (single sign-on) users to Google Apps for Business. Providing single sign-on to users increases the security of your company’s information stored in Google Apps for Business.

To configure the connector:

- 1 Access the CloudAccess Admin page.  
For more information, see [Section 3.1, “Accessing the Administration Pages,” on page 25](#).

- 2 Drag and drop the Connector for Google Apps for Business from the SaaS Palette to the bar.
- 3 Click the Connector for Google Apps for Business, then click **Configure**.
- 4 Provide a unique display name for the connector to appear on the Admin and OSP Welcome pages, and also provide the administrator logon credentials and domain for the Google Apps for Business account.
- 5 (Conditional) Select the **Automatically configure SSO settings** option if you want CloudAccess to configure the single sign-on parameters at Google Apps for Business. Otherwise, you must manually configure the parameters at Google Apps for Business.
- 6 (Conditional) Select **Prompt users for an existing Google Apps account before provisioning** if you want to give users control of when their accounts are provisioned. For more information about account provisioning, see [Section 1.6, "How CloudAccess Merges Existing Accounts," on page 14](#).
- 7 (Conditional) If you did not select the **Automatically configure SSO settings** option, click **Federation Instructions**. Read the instructions provided to configure the Connector for Google Apps for Business to allow single sign-on for users, then complete the following steps:
  - 7a Copy and paste the text of the signing certificate provided in the **Federation Instructions** into a file, then save the file.

---

**NOTE:** Ensure that you use a text editor that does not introduce hard returns or additional white space. Otherwise, the certificate file may be improperly formatted and unusable. For example, use Notepad instead of Wordpad.

---

- 7b Log in to the Google Apps Dashboard with your administrator account.
- 7c Navigate to **Advanced Tools > Set up single sign-on (SSO)**.
- 7d Provide the following information:
  - Enable Single Sign-on:** Select this option.
  - Sign-in page URL:** Specify the value provided for the **Single Sign-on URL** in the **Federation Instructions**.
  - Sign-out page URL:** Specify the value provided for the **Single Logout URL** in the **Federation Instructions**.
  - Change password URL:** This is the page that the URL will redirect to when a user clicks **Change Password**. (This is not part of the federation per se, but Google requires a value for this field.)
  - Verification certificate:** Upload the file into which you copied the signing certificate text above.
  - Use a domain specific issuer:** Select this option. This changes the value sent in the SAML request to be `google.com/a/google_apps_domain` instead of `google.com`. For more information, see [SSO \(Single Sign-On\) \(http://support.google.com/a/bin/answer.py?hl=en&answer=60224\)](http://support.google.com/a/bin/answer.py?hl=en&answer=60224) in the documentation for Google Apps for Business.
  - Network masks:** Leave blank. This option is not applicable to SAML configuration.
- 7e Click **Save Changes**.
- 8 Click **OK**, then click **Apply** to commit the changes to the appliance.
- 9 (Optional) To provide users with access to Google Apps Mail from supported mobile devices, click the Connector for Google Apps for Business, then click **Enable mobile access**.

User accounts that have been provisioned to Google Apps for Business using CloudAccess must authenticate through CloudAccess. Direct logins to Google Apps for Business are not allowed. For more information, see the SAML SSO section of the Google Apps for Business Web site.

### 4.1.3 Configuring Multiple Connectors for Google Apps for Business

CloudAccess can support Google Apps domains by using multiple instances of the Connector for Google Apps for Business. Each connector instance must be configured with the unique credentials and domain information of the Google Apps domain that it serves.

---

**NOTE:** The **Enable mobile access** option is global across all instances of the Google Apps connector. (The option is either enabled or disabled for all instances.)

---

## 4.2 Connector for Office 365

The Connector for Office 365 provides automated provisioning of accounts from the identity sources to Office 365. The Connector for Office 365 also provides single sign-on for users from their identity source account to Office 365.

The Connector for Office 365 is included with the CloudAccess appliance. However, the Admin page displays the Connector for Office 365 only after you install the Connector for Office 365 on the Windows server.

- ♦ [Section 4.2.1, “Meeting Requirements,” on page 39](#)
- ♦ [Section 4.2.2, “Installing the Connector for Office 365,” on page 40](#)
- ♦ [Section 4.2.3, “Validating the Connector for Office 365,” on page 41](#)
- ♦ [Section 4.2.4, “Changing Configuration of the Connector for Office 365,” on page 41](#)
- ♦ [Section 4.2.5, “Uninstalling the Connector for Office 365,” on page 41](#)
- ♦ [Section 4.2.6, “Installing Multiple Connectors for Office 365,” on page 41](#)

### 4.2.1 Meeting Requirements

Complete the following steps before installing the Connector for Office 365:

- ☐ Select an existing Office 365 account to use or create a new account.
- ☐ Select a federated domain name for single sign-on with CloudAccess and Office 365.
- ☐ Ensure that the CloudAccess appliance will be able to resolve the DNS of the federated domain to the ADFS server address.
- ☐ Obtain the Windows Server 2008 R2 software.
- ☐ Download the AD FS 2.0 software from the following location: [Active Directory Federation Services 2.0 RTW \(http://www.microsoft.com/en-us/download/details.aspx?id=10909\)](http://www.microsoft.com/en-us/download/details.aspx?id=10909). Select the RTW\W2K8R2\amd64\AdfsSetup.exe file.
- ☐ Download the Microsoft Online Services Sign-In Assistant software from the following location: [Microsoft Online Services Sign-In Assistant for IT Professionals RTW \(http://www.microsoft.com/en-us/download/details.aspx?id=28177\)](http://www.microsoft.com/en-us/download/details.aspx?id=28177). Select the msoidcli\_64bit.msi file.
- ☐ Download the Microsoft Online Services Module for Windows PowerShell software from the following location: [Install Windows PowerShell for single sign-on \(http://onlinehelp.microsoft.com/en-us/office365-enterprises/ff652560.aspx\)](http://onlinehelp.microsoft.com/en-us/office365-enterprises/ff652560.aspx).
- ☐ Download the .NET Framework 4.x from the [.NET downloads \(http://www.microsoft.com/net/download\)](http://www.microsoft.com/net/download) Web page.

## 4.2.2 Installing the Connector for Office 365

You must install the Connector for Office 365 on a Windows server.

To configure the Windows server and install the connector:

- 1 Obtain the credentials for an Office 365 account.  
[Office 365 Web site \(https://www.office365.com\)](https://www.office365.com)
- 2 Add the federated domain name for single sign-on with CloudAccess and Office 365 to Office 365 and validate the ownership. Use the instructions at the following Web page: [Add your domain to Office 365 \(http://onlinehelp.microsoft.com/en-us/office365-enterprises/ff637620.aspx\)](http://onlinehelp.microsoft.com/en-us/office365-enterprises/ff637620.aspx).
- 3 Install Windows Server 2008 R2, then install and apply all available updates.
- 4 As an administrator, install Active Directory on the Windows server.

If you already have an Active Directory domain that matches the domain selected in [Step 2](#), join that domain. Otherwise, make this Active Directory server a domain controller for the domain in [Step 2](#).

---

**IMPORTANT:** The Active Directory domain name must match the federated domain name in Office 365 or the Connector for Office 365 will not work.

---

- 5 As an administrator, complete the following additional steps on the Windows server:
  - 5a Install a server certificate (PKCS #12 key pair). The subject of the certificate must match the DNS name of the domain in [Step 2](#).  
For more information, see [Importing a Server Certificate \(http://technet.microsoft.com/en-us/library/cc732785%28v=ws.10%29.aspx\)](http://technet.microsoft.com/en-us/library/cc732785%28v=ws.10%29.aspx).
  - 5b Install ADFS 2.0.
  - 5c Configure ADFS using the configuration wizard. When you specify the certificate to use for ADFS, ensure that the certificate (self-signed or otherwise) you specify matches the DNS name of your Office 365 domain.
  - 5d Install Microsoft Online Services Sign-In Assistant.
  - 5e Install the Microsoft Online Services Module for Windows PowerShell.
  - 5f Install the .NET Framework 4.0.
- 6 Verify that the subject name of the SSL certificate on the CloudAccess appliance matches the public DNS name of the CloudAccess appliance.
- 7 As an administrator, install the Connector for Office 365 on the Windows server using the following information:
  - ♦ DNS name of the CloudAccess appliance
  - ♦ Administrator name and password of the CloudAccess appliance
  - ♦ Administrator name and password of the Office 365 account
  - ♦ The federated domain name specified in [Step 2](#)

---

**IMPORTANT:** The Connector for Office 365 installation location is `c:\NetIQ\Office365Connector`. You cannot change this location.

---



## 4.2.3 Validating the Connector for Office 365

Once you have installed the Connector for Office 365, perform the following steps to validate the installation:

- 1 Verify that the Admin page displays Connector for Office 365.
- 2 Verify that the Policy Mapping page displays the Office 365 groups on the left side and the Connector for Office 365 on the right side.
- 3 Map one of your groups to the User Authorizations, then verify CloudAccess provisioned your users.
- 4 Log in to Office 365 at <http://www.office365.com> (<http://www.office365.com>) as a provisioned user.
- 5 Specify the user name of `user@domain` where the domain is the federated domain name specified in [Step 2 on page 40](#).

## 4.2.4 Changing Configuration of the Connector for Office 365

If you change the federated domain name, you must reinstall the Connector for Office 365. The installation changes the configuration information in the Connector for Office 365. Delete the existing connector, then run through the installation again using the new federated domain name.

## 4.2.5 Uninstalling the Connector for Office 365

The Connector for Office 365 consists of multiple components. Use the following steps to correctly uninstall the Connector for Office 365:

- 1 Log in to the Windows server as an administrator.
- 2 In Control Panel, uninstall the Connector for Office 365.

Using the Control Panel to uninstall the Connector for Office 365 deletes the Connector for Office 365 from the CloudAccess Admin page. If you delete the Connector for Office 365 icon from the Admin page, all of the components on the Windows server still exist and run. This causes issues in CloudAccess if you need to reinstall the Connector for Office 365.

## 4.2.6 Installing Multiple Connectors for Office 365

CloudAccess supports multiple Connectors for Office 365. However, each connector must connect to a unique Office 365 domain, and you must install each connector on a separate Windows server.

## 4.3 Connector for Salesforce

Use the information in the following sections to configure a Connector for Salesforce:

- ♦ [Section 4.3.1, "Meeting the Requirements," on page 42](#)
- ♦ [Section 4.3.2, "Configuring Salesforce to Trust CloudAccess," on page 42](#)
- ♦ [Section 4.3.3, "Configuring the Connector for Salesforce," on page 42](#)
- ♦ [Section 4.3.4, "Configuring Multiple Connectors for Salesforce," on page 43](#)
- ♦ [Section 4.3.5, "Configuring Delegated Authentication," on page 44](#)

## 4.3.1 Meeting the Requirements

Verify that you meet the following requirements before configuring the Connector for Salesforce:

- ☐ A full or developer account with provisioning APIs enabled
- ☐ An administrative account with password
- ☐ The metadata file from Salesforce
- ☐ (Conditional) A security token from Salesforce

## 4.3.2 Configuring Salesforce to Trust CloudAccess

NetIQ recommends that you configure Salesforce to trust the IP address of the CloudAccess appliance.

To add the CloudAccess IP address as a trusted source to Salesforce:

- 1 Log in to the Salesforce Admin tools Web page.
- 2 Click **Administration Setup > Security Controls > Network Access**.
- 3 Specify the IP address of the CloudAccess appliance.

or

If you are in a clustered environment, specify the IP address of the L4 switch.

If you do not configure Salesforce to trust the IP address of the CloudAccess appliance, you must obtain a security token from Salesforce and append the security token to the administrator password specified when you configure the Connector for Salesforce.

For example, if your Salesforce administrator account password is `Test1234` and the Salesforce security token is `XyZ`, the **Password** field must contain `Test1234XyZ`.

## 4.3.3 Configuring the Connector for Salesforce

Each cluster supports multiple Connectors for Salesforce. You must configure the Connector for Salesforce to provision accounts into Salesforce.

You can configure the connector to allow users single sign-on access into Salesforce. When users log in to the identity source, CloudAccess automatically authenticates the users to Salesforce. Providing single sign-on to users increases the security of your company's information stored in Salesforce. The phone icon that CloudAccess displays on all the Salesforce connectors indicates that Delegated Authentication can be used with Salesforce. All of the configuration required for using Delegated Authentication with CloudAccess is done at Salesforce.

You must go back and forth between the CloudAccess Admin page and the Salesforce administration page to configure the connector.

- 1 In CloudAccess, access the Admin page.  
For more information, see [Section 3.1, "Accessing the Administration Pages," on page 25](#).
- 2 Drag and drop the Connector for Salesforce from the SaaS Palette to the bar.
- 3 Click the Connector for Salesforce, then click **Configure**.
- 4 Provide a unique display name for the connector to appear on the Admin page, and administrator logon credentials for Salesforce.

- 5 Select **Prompt users for an existing Salesforce account before provisioning** if you want to give users control of when their accounts are provisioned. For more information about account provisioning, see [Section 1.6, “How CloudAccess Merges Existing Accounts,”](#) on page 14.
- 6 Click **Federation Instructions** and read the instructions provided to configure the Connector for Salesforce to allow single sign-on for users.
- 7 Copy and paste the text of the signing certificate provided in the **Federation Instructions** into a file, then save the file.

---

**NOTE:** Ensure that you use a text editor that does not introduce hard returns or additional white space. Otherwise, the certificate file may be improperly formatted and unusable. For example, use Notepad instead of Wordpad.

---

- 8 Log in to Salesforce as an administrator and complete the following steps:
  - 8a Select **Administration Setup** from the drop-down menu.
  - 8b Click **Security Controls** under **Administration Setup** in the left pane.
  - 8c Click **Single Sign On Settings**.
  - 8d Click **Edit**, then use the following information to configure single sign-on:
    - SAML Enabled:** Check this option.
    - SAML Version:** Specify 2.0.
    - Issuer:** Copy and paste the value of the **Entity ID** provided in the **Federation Instructions**.
    - Identity Provider Certificate:** Click **Browse**, then browse to and select the file to which you copied and pasted the signing certificate in [Step 7](#).
    - Identity Provider Login URL:** Copy and paste the value of the **Single Sign-on URL** provided in the **Federation Instructions**.
    - Custom Error URL:** Leave this blank.
    - SAML User ID Type:** Select Assertion Contains the Federation ID from the User Object. This option is not selected by default.
    - SAML User ID Location:** Select User ID is in the NameIdentifier element of the Subject statement.
    - Identity Provider Logout URL:** Copy and paste the value of the **Single Logout URL** in the **Federation Instructions**.
- 9 Download the Salesforce metadata file after the configuration is complete.
- 10 On the CloudAccess Admin page, edit the Connector for Salesforce.
- 11 Upload the metadata file generated in [Step 9](#) into the Connector for Salesforce.
- 12 Click **OK**, then click **Apply** to commit the changes to the appliance.

### 4.3.4 Configuring Multiple Connectors for Salesforce

If you want to configure more than one Connector for Salesforce, each Salesforce account must be configured with a unique URL. Configuring the URL requires Salesforce assistance and it often takes at least a day to complete.

To configure the Salesforce URL, perform the following steps:

- 1 Log in to the Salesforce administration Web page.
- 2 Click **Administration Setup > Company Profile > My Domain**.
- 3 Provide a unique subdomain name for your organization and click **Check Availability**.

- 4 If the subdomain you specified is available, select the check box to indicate that you agree to the terms and conditions, then click **Register Domain**.
- 5 Wait for Salesforce to register your domains. This process takes time.

After the registration is complete, Salesforce provides you with a URL that supports SP-initiated logins and is similar to the following:

`https://<custom name>.mysalesforce.com`

### 4.3.5 Configuring Delegated Authentication

Salesforce allows two different types of authentication methods: SAML and delegated authentication. By default, Salesforce activates only the SAML authentication. SAML is available only for browser-based authentication and does not work for applications that use the Salesforce Web Service API. For example, smart phones use the Salesforce Web Service API.

Delegated authentication must be activated on a per-Salesforce organization basis. This allows CloudAccess to support users authenticating with smart phones as well as users authenticating with browsers.

For delegated authentication to work properly with CloudAccess, the DNS name of the CloudAccess cluster must be publicly resolvable and the SSL certificate must be signed by a well known certificate authority (CA).

To configure Salesforce for delegated authentication:

- 1 Follow the instructions in the Salesforce documentation to enable delegated authentication single sign-on for your organization.  
For more information, see [Configuring Salesforce for Delegated Authentication \(https://login.salesforce.com/help/doc/en/sso\\_delauthentication\\_configuring.htm\)](https://login.salesforce.com/help/doc/en/sso_delauthentication_configuring.htm).
- 2 Configure a Connector for Salesforce in CloudAccess.
- 3 Log in to the Salesforce administration page.
- 4 Click **Your Name > Setup > Security Controls > Single Sign-On Settings > Edit**.
- 5 In the **Delegated Gateway URL** field, specify a value similar to the following: `https://cloudaccess_public_dns/osp/a/t1/auth/external/sfda`.
- 6 Do not select **Force Delegated Authentication Callout**.  
This option affects the performance of user logins.
- 7 Enable the **Is Single Sign-On Enabled** permission.

Now when end users authenticate to Salesforce through their smart phones, they use their identity source user name and password to authenticate just as they do from a browser.

## 4.4 Single Sign-On Connectors

NetIQ provides additional connectors that you can use for single sign-on to other applications or Web services. These connectors are available for download from your Customer Center. For more information, see the [Access Connector HQ Web site \(https://www.netiq.com/documentation/access\\_gateway\\_connectors\)](https://www.netiq.com/documentation/access_gateway_connectors).

## 4.5 Importing and Configuring Custom Connectors

CloudAccess allows you to import and configure custom connectors that NetIQ partners create.

To import and configure a custom connector:

- 1 Copy the custom connector .zip file to the computer where you administer CloudAccess.
- 2 Log in to CloudAccess as an administrator.
- 3 On the Admin page, click the **Tools** icon in the toolbar.
- 4 Click **Import Connector Definition**.
- 5 Browse to and select the custom connector .zip file, then click **Import**.
- 6 Drag and drop the new custom connector from the Custom palette into the middle of the page.
- 7 Click the connector, then click **Configure**.
- 8 Fill in the fields and follow the **Federation Instructions** to configure your Web server or application.
- 9 Click **OK**, then click **Apply** to save the changes.



---

# 5 Providing Access to the SaaS Applications for Users

After CloudAccess and the SaaS applications are configured, you must provide a way for users to access the SaaS applications.

CloudAccess includes a sample landing page that contains the links for accessing the SaaS applications. You can use this page or create your own page. Access the sample landing page through the following URL:

`https://dns\_or\_ip\_of\_appliance/osp/a/t1/auth/app`

After you enter valid credentials, the sample landing page appears. The sample landing page displays the links for the SaaS applications only after they are configured properly and if you have an entitlement for that SaaS application.

On the sample landing page, the links for SaaS applications are as follows:

- ♦ **Google Apps for Business:** `https://dns\_of\_appliance/osp/a/t1/auth/app/its/connectors\_GOOGLEAPPS\_IDXXX?target=https://mail.google.com/a/your\_google\_domain`
- ♦ **Salesforce:** `https://dns\_or\_ip\_of\_appliance/osp/a/t1/auth/app/its/connectors\_SFORCE\_IDXXX`
- ♦ **Office 365:** `https://office365\_federated\_domain/adfs/ls/?WHR=https%3A%2F%2Fdns\_of\_appliance%2Fosp%2Fa%2Ft1%2Fauth%2Fsaml2%2Fmetadata&wa=wsignin1.0&wtrealm=urn:federation:MicrosoftOnline`

If you create your own page, copy the links for the SaaS applications from the sample landing page to your landing page.

If you are creating your own landing page, there are two methods to connect to the SaaS applications. You can use either method for your own landing page.

## Method 1: Service Provider (SP) Initiated Logins

1. The user clicks the link `https://mail.google.com/a/your\_google\_domain` for a service provider-initiated login.
2. The browser sends a request to Google Apps for Business.
3. Google Apps for Business redirects the browser session to the appliance for authentication.
4. The user enters login credentials.
5. After a successful authentication against the identity source, the appliance redirects the browser session back to Google Apps for Business with a SAML assertion for authentication.
6. Google Apps for Business receives the assertion, then allows or denies user access based on the content of the assertion.

## Method 2: Identity Provider (IDP) Initiated Logins

1. The user clicks the link `https://dns_of_appliance/osp/a/t1/auth/app/its/connectors_GOOGLEAPPS_IDXXX?target=https://mail.google.com/a/your_google_domain` for an identity provider-initiated login.
2. The browser sends a request to the appliance login URL.
3. The browser displays the CloudAccess login form.
4. The user enters the identity source login credentials, then successfully authenticates to the appliance.
5. The appliance redirects the browser session back to Google Apps for Business with a SAML assertion for authentication.
6. Google Apps for Business accepts the assertion, then allows or denies access based on the content of the assertion.

## Examples

The following are examples of the different logins:

**IDP-Initiated Login for Google Apps for Business:** `https://dns_of_appliance/osp/a/t1/auth/app/its/connectors_GOOGLEAPPS_a20hy?target=https://mail.google.com/a/google domain`

**IDP-Initiated Login for Salesforce:** `https://dns_of_appliance/osp/a/t1/auth/app/its/connectors_SFORCE_a18gs`

**SP-Initiated Login for Google Apps for Business:** There are two options:

`https://mail.google.com/a/google domain`

`https://docs.google.com/a/google domain`

**SP-Initiated Login for Salesforce:** The setup page for this feature at Salesforce is under **Setup > Company Profile > My Domain**. After Salesforce registers the domain, your URL is similar to the following that allows an SP-initiated login:

`https://custom_name.my.salesforce.com`

**IDP-Initiated Login for Office 365:** `https://office365_federated_domain/adfs/ls/?WHR=https%3A%2F%2Fdns_of_appliance%2Fosp%2Fa%2Ft1%2Fauth%2Fsaml2%2Fmetadata&wa=wsignin1.0&wtrealm=urn:federation:MicrosoftOnline`



---

# 6 Mapping Authorizations

Most companies define their business policies through authorization assignments. Examples of authorizations are groups, roles, and profiles. These authorizations are different depending on each SaaS application. For more information, see [Section 6.1, “Supported Roles and Authorizations,” on page 49](#).

Authorizations give users access to resources. CloudAccess provides a simple solution that allows you to map your identity source roles (groups) to the SaaS application authorizations and approve or deny access to those authorizations.

Authorizations are available only to connectors that provision users. If you use connectors only for authentication, there are no authorizations. For example, the Connector for WebEx and the Connector for Accellion do not have authorizations.

The Policy Mapping page maps the authorizations from the SaaS applications to the roles (groups) in the identity sources and allows you to select whether the authorization requires an approval. The Approval page allows you to accept or deny the authorization request.

- ♦ [Section 6.1, “Supported Roles and Authorizations,” on page 49](#)
- ♦ [Section 6.2, “Prerequisites,” on page 50](#)
- ♦ [Section 6.3, “Loading Authorizations,” on page 50](#)
- ♦ [Section 6.4, “Reloading Authorizations,” on page 50](#)
- ♦ [Section 6.5, “Mapping Authorizations,” on page 51](#)
- ♦ [Section 6.6, “A Mapping Example,” on page 51](#)

## 6.1 Supported Roles and Authorizations

Each identity source contains different roles that the Policy Mapping page uses.

- ♦ **Active Directory:** groups, local groups, and global groups
- ♦ **eDirectory:** group

Each SaaS application contains different authorizations that the Policy Mapping page uses.

- ♦ **Google Apps:** user and groups
- ♦ **Office 365:** account, groups, and license
- ♦ **Salesforce:** groups, roles, and profiles (account types)

## 6.2 Prerequisites

Verify that you meet the following prerequisites before mapping SaaS application authorizations to the identity source groups:

- ☐ Configure SaaS connectors. For more information, see [Chapter 4, “Configuring Connectors,” on page 37](#).
- ☐ Ensure that roles (groups) in the identity source exist.
- ☐ Populate the required attributes on the users in the identity source. For more information, see [Section 3.4, “Verifying the Identity Source User Attributes,” on page 27](#).

## 6.3 Loading Authorizations

In order to map an authorization, you must load the authorization into the Policy Mapping page.



- 1 Verify that you have configured the SaaS application connectors that provision users.  
For more information, see [Chapter 4, “Configuring Connectors,” on page 37](#).
- 2 Log in to the Admin page using the application administrator credentials you specified when you created the SaaS application connector.
- 3 Click **Policy** to open the Policy Mapping page.
- 4 In the right pane, click the down arrow next to the connector, then select your SaaS application connector.

If the Policy Mapping page does not display the SaaS application connector, you did not configure the connector properly. For more information, see [Chapter 4, “Configuring Connectors,” on page 37](#).

Successfully completing these steps populates the Policy Mapping page with the SaaS application’s authorizations.


## 6.4 Reloading Authorizations

When you perform a switch master with the cluster nodes, or if authorizations change in the SaaS applications, or you add new roles in the identity sources, you must reload the authorizations on the Policy Mapping page.

- 1 To reload roles (groups) from the identity sources, click the **Reload table** icon  at the end of the Identity Source table.
- 2 To reload authorizations from the SaaS applications, click the **Reload table** icon  at the end of the Authorizations table.

## 6.5 Mapping Authorizations

After the authorizations load, map the SaaS application authorizations to the identity source roles (groups).

- 1 In the right pane of the Policy Mapping page, click the down arrow, then select the desired SaaS connector.
- 2 In the **Role Name** column on the left, select the role (group) from the identity source you want to map to an authorization from the selected SaaS connector.
- 3 In the right pane, drag and drop the desired authorization from the SaaS connector to the left mapping pane.  
or  
In the left pane, drag and drop the desired group from the identity source to the right mapping pane.
- 4 (Optional) Click the **Require Approvals** icon  if an approval is required to grant access.  
NetIQ recommends a maximum of 2,000 simultaneous approvals. For more information about approvals, see [Chapter 7, “Approving Requests,” on page 53](#).
- 5 Click **OK** to map the SaaS authorization to the identity source group.

The mapping grants any users of the existing identity source roles to the SaaS application authorization. When you add new users to the mapped role (group), the users in the role (group) automatically receive the authorization for the SaaS application as long as they have a user account authorization. Or the user is prompted to verify their account information the first time they log in.

## 6.6 A Mapping Example

Use the following example steps to understand how mapping works.

- 1 In Active Directory:
  - 1a Create a group named GoogleAppsUsers in Active Directory.
  - 1b Add users to the GoogleAppsUsers group.
- 2 In Google Apps for Business, create a Google Apps Account group.
- 3 On the Policy Mapping page:
  - 3a Load the authorizations for the Connector for Google Apps for Business.
  - 3b In the **Role Name** column, select the Connector for Active Directory.
  - 3c In the right pane, select the Connector for Google Apps.
  - 3d Drag and drop the Google Apps Account into the left pane, over the Google AppsUsers group.
  - 3e Click **OK**.  
The appliance automatically provisions all users in the GoogleAppsUsers group to the Google Apps Account group. Or the user is prompted to verify their account information the first time they log in.
- 4 In Active Directory, create a new user, then add the user to the GoogleAppsUsers group.  
The user is automatically added to the Google Apps Account group and has access to Google Apps for Business.



---

# 7 Approving Requests

CloudAccess provides the ability to approve or deny requests to the SaaS applications. During the configuration of the connector, you specified an application owner. The application owner approves or denies requests for access to the SaaS applications. The application owner knows who should have access to the SaaS applications, whereas the appliance administrator might not have this knowledge.

The **Approval** icon appears only if you have mapped roles and selected the option to require approval for the account. When there are accounts waiting for approval, CloudAccess adds the **Approval** icon.

By default, CloudAccess automatically provisions users according to mapped authorizations. To enable approvals:

- 1 Select **Approval** when you map the roles (groups) from the identity source to the SaaS applications authorizations on the Policy Mapping page.
- 2 Select the desired authorization, then click **Approve** or **Deny**.

---

**NOTE:** Users that have been deleted from the identity source may still appear on the Approval page. If you know that certain users have been deleted, you can simply deny approval for those users. However, approving requests for users that have been deleted does *not* result in account provisioning for those users in the SaaS applications.

---

NetIQ recommends a maximum of 2,000 simultaneous approvals.



---

# 8 Reporting

CloudAccess provides reports of users' activity through the appliance.

- ♦ [Section 8.1, "Running a Report," on page 55](#)
- ♦ [Section 8.2, "Integrating with Sentinel Log Manager," on page 55](#)

## 8.1 Running a Report

CloudAccess contains predefined reports that you can run to gather information about users' activity.

To run a report:

- 1 In a supported browser, access the Admin page at  
`https://dns_of_appliance/appliance/index.html`
- 2 Log in as the administrator of CloudAccess.
- 3 Click **Reports**.
- 4 (Optional) If you want to see the description of the report before you run it, select the **Show Descriptions** option.
- 5 Click the desired report, then click **Run**.
- 6 Click the report name to download and save the report.

After the report finishes, the report name becomes a hyperlink to view or download the report.

## 8.2 Integrating with Sentinel Log Manager

The CloudAccess appliance can forward events to Sentinel Log Manager 1.2.x if you want more detailed reports. To integrate the appliance with Sentinel Log Manager:

- 1 Configure Sentinel Link in Sentinel Log Manager.  
For more information, see [Sentinel Link Overview Guide \(http://www.novell.com/documentation/sentinel70/sentinel\\_link\\_overview/data/bookinfo.html\)](http://www.novell.com/documentation/sentinel70/sentinel_link_overview/data/bookinfo.html).
- 2 Open TCP port 1290 on the Sentinel Log Manager server.
  - 2a To change the port, ssh in to the Sentinel Log Manager server as root.
  - 2b At the command prompt, enter `yast firewall`.
  - 2c Select **Advanced** > **Allowed Services**, then manually add port 1290 to the list of TCP ports.
- 3 On the Admin page in CloudAccess, drag and drop the Sentinel icon from the Tools Palette to the bar.
- 4 Click the Sentinel icon, then click **Configure**.
- 5 Specify the IP address and port of the Sentinel Link server, then click **OK** and **Apply** to save the changes.

The CloudAccess appliance appears as another event source in Sentinel Log Manager.



---

# 9 End User Configuration

CloudAccess allows you to configure the end user's email client or mobile devices to use the single sign-on authentication to access the SaaS applications. This increases the security of your company's information stored in the SaaS applications because users authenticate with their corporate credentials, but these credentials are never stored in the SaaS applications.

Configure each user's email client or mobile device to point to the appliance. The appliance acts as a proxy, so when users access the SaaS applications, the appliance automatically logs the users in to the SaaS application.

- ♦ [Section 9.1, "Configuring Email Clients," on page 57](#)
- ♦ [Section 9.2, "Configuring Mobile Devices," on page 57](#)
- ♦ [Section 9.3, "Configuring End User Browsers for Kerberos Authentication," on page 58](#)

## 9.1 Configuring Email Clients

You can configure any supported email client to point to CloudAccess. The email clients allow you to receive email from multiple sources in one location. For a list of supported clients, see ["Email Clients" on page 20](#).

- 1 Access your email client.
- 2 Create a new email account using the following information to configure CloudAccess as your email source:

**Incoming email server (IMAP/POP):** Specify the IP address or hostname of your appliance.

**Incoming email server username:** Specify your identity source enterprise logon name for the account name.

**Incoming email server password:** Specify your identity source password.

If your password changes, you must change the password in the email account.

**Outgoing email server (SMTP):** Specify the IP address or hostname of your appliance.

**SSL:** You must select SSL for IMAP (port 993), POP (port 995), and SMTP (port 25).

The SMTP server requires authentication.

For more information, see the appropriate documentation for the email client you are using.

## 9.2 Configuring Mobile Devices

You can also configure your mobile device to receive email from the SaaS applications through CloudAccess. For a list of supported mobile devices, see [Table 2-1 on page 20](#).

On your mobile device:

- 1 Set up a new email account using the following information:

**Incoming Mail Server (IMAP/POP):** Specify the IP address or hostname of your appliance.

**Incoming Mail User Name:** Specify your identity source enterprise logon name for the account name.

**Incoming Mail Password:** Specify your identity source password.

**Incoming Mail > Advanced Options:** Select **Use SSL**, then specify 993 as the IMAP port or 995 as the POP port.

**Outgoing Mail Server (SMTP):** Specify the IP address or hostname of your appliance.

**Outgoing Mail User Name:** Specify your identity source enterprise logon name for the account name.

**Outgoing Mail Password:** Specify your identity source password.

**Outgoing Mail > Advanced Options:** Select **Use SSL**, then specify 25 as the SMTP port.

For more information, see the following Apple knowledge base article: [iOS: Setting up an email account \(http://support.apple.com/kb/HT4810\)](http://support.apple.com/kb/HT4810).

## 9.3 Configuring End User Browsers for Kerberos Authentication

If you are using Windows Integrated Authentication for Kerberos authentication to CloudAccess, each end user browser must be configured to use Kerberos authentication.

- 1 Add the computers of the users to the Active Directory domain.  
For instructions, see your Active Directory documentation.
- 2 Log in to the Active Directory domain, rather than the computer.
- 3 (Conditional) If you are using Internet Explorer, configure the Web browser to trust the appliance:
  - 3a Click **Tools > Internet Options > Security > Local intranet > Sites > Advanced**.
  - 3b In the **Add this website to the zone** field, enter the Base URL for the appliance, then click **Add**.  
In the configuration example, this URL is `serv1.cloudaccess.com`.
  - 3c Click **Close**, then click **OK**.
  - 3d Click **Tools > Internet Options > Advanced**.
  - 3e Verify in the Security section that **Enable Integrated Windows Authentication** is selected, then click **OK**.
  - 3f Restart the browser.
- 4 (Conditional) If you are using Firefox, configure the Web browser to trust the appliance:
  - 4a In the URL field, specify `about:config`.
  - 4b In the **Filter** field, specify **network.n**.
  - 4c Double click `network.negotiate-auth.trusted-uris`.  
This preference lists the sites that are permitted to engage in SPNEGO Authentication with the browser. Specify a comma-delimited list of trusted domains or URLs.  
For this example configuration, add `serv1.cloudaccess.com` to the list.
  - 4d Click **OK**, then restart your Firefox browser.

---

# 10 Maintenance Tasks

CloudAccess allows you to change various appliance configuration settings as needed. For example, moving your appliance from a staging configuration to a production environment requires changes to the networking components.

- ♦ [Section 10.1, “Changing the IP Address,” on page 59](#)
- ♦ [Section 10.2, “Changing Public DNS Name or NTP Server Settings, or Uploading New Certificates,” on page 59](#)
- ♦ [Section 10.3, “Updating the Appliance,” on page 60](#)
- ♦ [Section 10.4, “Recovering from a Disaster,” on page 61](#)

## 10.1 Changing the IP Address

You can change whether a node uses DHCP or a static IP address on the Admin page.

- 1 Log in to the Admin page.  
For more information, see [Section 3.1, “Accessing the Administration Pages,” on page 25](#).
- 2 Click the node icon, then click **Configure**.
- 3 Select whether the appliance uses DHCP or a static IP address.  
If you select to use a static IP address, you can change the required values for the subnet mask, default gateway, and the DNS server.
- 4 Click **OK** to save the changes, then click **Apply** to apply the changes to the appliance.

## 10.2 Changing Public DNS Name or NTP Server Settings, or Uploading New Certificates

The appliance contains self-generated certificates. You can upload custom certificates through this interface.

- 1 Log in to the Admin page.  
For more information, see [Section 3.1, “Accessing the Administration Pages,” on page 25](#).
- 2 Click the cluster icon, then click **Configure**.
- 3 Change the key pairs, NTP server, or public DNS name, then click **OK**.
- 4 Click **Apply** to apply the changes to the appliance.

Expired key pair certificates prohibit changes from being made to this page and make the key pair field red.

## 10.3 Updating the Appliance

CloudAccess provides an update channel for keeping your appliances up to date with the latest security fixes, bug fixes, and feature updates. Updates work only if you have registered each node in the cluster. For more information, see [Section 3.2, “Registering CloudAccess,” on page 26](#).

When an update is available for one or more nodes in the cluster, the CloudAccess Admin page displays a flag icon in the upper right corner of the window. You can also configure the appliance to send an email notification when an update is available. When you click the flag icon, you can see the version of the pending update, instructions on how to apply the update, and the Release Notes associated with the update patch.

The flag icon for the update channel appears only if you are logged in to the Admin page with an administrator account. Other consoles do not display the flag icon.

CloudAccess checks the NCC channel for updates on a regular basis. You can download and install an update as soon as the flag appears on the Admin page, or you can wait for CloudAccess to download the update at 11:23:23 that night, to minimize network impact due to possible size of an update. NetIQ recommends always keeping your appliance up to date. However, updates are cumulative, so if you miss an update you can just install the next one when it is available.

---

**IMPORTANT:** If you apply an update to one node, you must apply the update to all the other nodes in the cluster. Update one node at a time. Ensure that the update was successful and the node is still working properly before you begin updating the next node. Do not perform any other administrative tasks requiring an **Apply** command, and do not switch the master node, until all nodes have been successfully updated to the same version of CloudAccess.

---

This process allows you to run in a mixed environment while updating each node. Once you have applied all available channel updates, the flag icon goes away.

To apply an update:

- 1 Take a snapshot of each node in the cluster to create a backup.
- 2 Click the desired node, then click **Apply Update**.  
CloudAccess displays status messages during the installation of the update and the rebooting of the node.
- 3 After the update completes and the node restarts, click **About** on the node to verify the updated version.
- 4 Verify the health of the updated node and all of the nodes in the cluster. Make sure all icons are green.  
For more information, see [Section 11.1, “Displaying Health,” on page 63](#).
- 5 Repeat [Step 2](#) through [Step 4](#) for each node in the cluster.
- 6 When you are sure all of the nodes in the cluster are working as expected, delete the snapshot.

## 10.4 Recovering from a Disaster

Use snapshots of the nodes to recover from a disaster. It is important to take snapshots of each node in the cluster regularly so you do not lose information.

To recover from a disaster:

- 1** On a regular basis, take snapshots of the nodes in the cluster.
  - 1a** Power off the working node, then take a snapshot. NetIQ recommends this method, but it requires that you shut down and restart the node in order to take the snapshot.  
or  
Take a snapshot of the running node, ensuring that you include the virtual machine's memory. Including the memory in the snapshot requires more time and space to store the snapshot, but taking a snapshot of a running node without the memory can result in corruption.
  - 1b** Repeat Step 1a for each node in the cluster, within a short time.
- 2** When a failure happens, restore the master node snapshot first.
- 3** Restore the other nodes in the cluster.

Use these steps only for disaster recovery. Never restore one snapshot. CloudAccess contains a database that is time-sensitive. Restoring one node only and not the others causes corruption in the appliance.



---

# 11 Troubleshooting CloudAccess

Use the information in the following sections to troubleshoot any issues you might encounter.

- ♦ [Section 11.1, “Displaying Health,” on page 63](#)
- ♦ [Section 11.2, “Troubleshooting Tools,” on page 63](#)
- ♦ [Section 11.3, “Troubleshooting Different States,” on page 65](#)
- ♦ [Section 11.4, “Provisioning Behavior,” on page 68](#)
- ♦ [Section 11.5, “Troubleshooting Authentications or Single Sign-On Issues,” on page 69](#)
- ♦ [Section 11.6, “Valid Salesforce Credentials Fail,” on page 69](#)
- ♦ [Section 11.7, “Troubleshooting the Connector for Office 365,” on page 69](#)
- ♦ [Section 11.8, “Troubleshooting Custom Connectors,” on page 70](#)

## 11.1 Displaying Health

CloudAccess displays health for each node and for the cluster on the Admin page. Hover the mouse over each node to display the health status of the node. If you want more details, click the node, then select **Show Health**.

When you click **Show Health**, CloudAccess displays the status for each component of the appliance. If the status is anything other than green (healthy), use the troubleshooting tools to determine what is wrong.

## 11.2 Troubleshooting Tools

CloudAccess provides troubleshooting tools to help you resolve problems. To access these tools:

- 1 Access the Admin page.  
For more information, see [Section 3.1, “Accessing the Administration Pages,” on page 25](#).
- 2 Under **Appliances**, click the node icon, then click **Enter Troubleshooting Mode**.
- 3 Click the node icon again, then click **Troubleshooting Tools**.
- 4 Select one or more of the troubleshooting scenarios listed.
- 5 Duplicate the error or condition.
- 6 Click **Download CloudAccess Log Files** link to download the logs.

After you obtain the logs, turn off troubleshooting mode by selecting **Exit Troubleshooting Mode**. Leaving the logs running affects the performance of your appliance.

All of the log files in [Table 11-1](#) are included in the download, no matter what scenario you select. The scenario you select determines the amount of data displayed in the log files. Search the appropriate log file for errors while troubleshooting issues.

**Table 11-1** Troubleshooting Log Files

Feature	Logs
Initialization or commands	ConfigurationReplicator.log ConfigurationReplicator_RL.log messages boot* packageoperations.log ag4c_configure.out ag4c.sh.out dserv.log firewall
Admin.html UI	adminui.log
Registration	register.log
Updates	zypper.log downloadUpdate.log afterUpdate.log beforeUpdate.log rpmsAfterUpdate.log rpmsBeforeUpdate.log rpmsUpdateDiff.log 300_appliance_ucon.sh.log
Identity Source Provisioning	bis_AD_<xxxxx>.log bis_AD_<xxxxx>_RL.log ConnectorLogs.txt bis_EDIR_h2q3p.log bis_EDIR_h2q3p_RL.log
Provisioning to the SaaS Applications	connectors_SFORCE_<xxxxx>_RL.log connectors_GOOGLEAPPS_<xxxxx>.log connectors_GOOGLEAPPS_<xxxxx>_RL.log connectors_O365_<xxxxx>.log connectors_O365_<xxxxx>_RL.log ConnectorLogs.txt



Feature	Logs
Mapping	RolesandResourceServiceDriver.log UserApplicationDriver.log
Approvals	jboss.log
Reporting	ManagedSystemGatewayDriver.log DataCollectionServiceDriver.log
Mobile Devices	mail mail.err mail.info
Custom Connectors	catalina.out

## 11.3 Troubleshooting Different States

CloudAccess displays indicators for the current state of the different appliance components. The display refreshes every five minutes. CloudAccess might not immediately display the change.

The following sections list the different components, the possible states, and troubleshooting steps you can take when the state changes.

- [Section 11.3.1, “Master Node Health,” on page 65](#)
- [Section 11.3.2, “Front Panel of the Node,” on page 65](#)
- [Section 11.3.3, “Top of the Node,” on page 66](#)
- [Section 11.3.4, “Identity Source,” on page 66](#)
- [Section 11.3.5, “SaaS Applications,” on page 67](#)

### 11.3.1 Master Node Health

The master node is responsible for all administration functions in CloudAccess. If the master node is not running, the following functions do not work: provisioning or deleting user accounts, mapping authorizations, system roles, approvals, and reporting. Other nodes in the cluster continue to capture and cache events, but do not send those events to the master node until it is running again. Similarly, event forwarding to Sentinel does not work as long as the master node is down.

### 11.3.2 Front Panel of the Node

The indicator on the front panel of the node displays the health state of the node.

**Figure 11-1** Front Panel



The states are:

**Green:** The node is healthy.

**Yellow:** The node cannot communicate with the other nodes within the five minute refresh.

**Red:** The node cannot communicate with the other nodes within two of the five minute refresh cycles.

**Clear:** The node is initializing or the state of the node is unknown.

Perform the following troubleshooting steps in the order listed if the state is anything but green.

1. Wait at least five minutes for the display to refresh and display the current state.
2. Click the node, then select **Show Health**.  
Show Health displays which part of the appliance is having issues.
3. If Show Health displays a problem, use the troubleshooting tools to gather logs.  
For more information, see [Section 11.2, “Troubleshooting Tools,”](#) on page 63.
4. Restart the appliance, then wait at least another five minute cycle for all nodes to display the current state.

### 11.3.3 Top of the Node

The indicator on the top of the node shows whether the **Apply** commands completed successfully.

**Figure 11-2** Top of the Node



The states are:

**Green:** All **Apply** commands completed successfully.

**Red:** The **Apply** commands did not complete successfully.

Perform the following troubleshooting steps in the order listed if the state is red.

1. Mouse over the top of the node to see the status of the last **Apply** command made on the node.
2. If there is not enough information in the summary, click **Enter Troubleshooting Mode** on the node, then mouse over the node again.  
The troubleshooting mode displays a details summary of the last **Apply** command made on the node.
3. Restart the appliance, then wait at least another five minute cycle for all nodes to display the current state.

### 11.3.4 Identity Source

The health indicator for the identity source is the small identity source icon.

**Figure 11-3** Identity Source Indicator



The states are:

**Green:** The connector to the identity source is healthy.

**Yellow:** The connector has communication problems with the identity source.

**Red:** The connector to the identity source is unhealthy or contains errors.

**Clear:** The state of the connector to the identity source is unknown.

Perform the following troubleshooting steps in the order listed:

1. If the connector is green, but the CloudAccess interface is not displaying users, verify that the identity source servers are running and communicating properly.
2. Use the troubleshooting tools to gather logs, then look at the identity source provisioning logs listed in [Table 11-1 on page 64](#) for errors. The `ConnectorLogs.txt` file maps the display name of the connector with the log name of the connector, if there is more than one identity source connector.
3. Click **Show Health** on the master node, then expand **Operational**.  
If these items are yellow or red, the interface displays helpful information to help troubleshoot the issue.
4. If you are using LDAPS to communicate with the identity source, verify the LDAP certificates are not expired. You refresh the certificates as follows:
  - a. Log in to the Admin page, then click **Configure** on the identity source.
  - b. Click the **Refresh** icon next to the identity source server.

### 11.3.5 SaaS Applications

The health indicator is the small cloud icon on each SaaS application connector.

**Figure 11-4** SaaS Application Indicator



The states are:

**Green:** The connectors to the SaaS applications are healthy.

**Yellow:** The connectors to the SaaS applications contain warnings.

**Red:** The connectors to the SaaS applications contain errors or cannot communicate with the SaaS applications.

**Clear:** The connectors to the SaaS applications are in an unknown state.

Perform the following troubleshooting steps in the order listed.

1. Click **Show Health** on the master node, then expand **Operational**, and check the status of **Provisioning**.

If **Provisioning** is yellow or red, CloudAccess displays helpful information to help troubleshoot the issue.

2. Use the troubleshooting tools to gather logs, then look at the provisioning logs listed in [Table 11-1 on page 64](#) for errors.

3. Make a cosmetic change to the SaaS application connector configuration, then click **Apply**.

By forcing an **Apply**, the appliance refreshes the SaaS application connector state and this can resolve the issue.

## 11.4 Provisioning Behavior

Actions taken on users and groups in the identity source might not be reflected in the SaaS applications. The following table lists the actions in the identity sources and the corresponding action in the SaaS applications.

**Table 11-2** Provisioning Actions

Identity Sources	SaaS Applications
Delete a user.	Disables the SaaS account.
Remove a user from the authorized group.	Disables the SaaS account.
Create a user.	<ul style="list-style-type: none"><li>♦ Creates an account for the user in the SaaS applications, if the user is a member of a group with mapped SaaS authorizations.</li></ul> or <ul style="list-style-type: none"><li>♦ Users are prompted to validate their information when they log in the first time.</li></ul>
Move a user from out of the search context into the search context.	Creates an account for the user in the SaaS applications, if the user is a member of a group with mapped SaaS authorizations.
Move a user out of the search context.	Disables the SaaS account.

CloudAccess establishes identity based on an internal unique ID in the identity source, not based on the user name, and does not support recreating users with the same name unless they also have the same internal unique ID. Once a user has been mapped and provisioned, if you delete the user from the identity source and then recreate that user with the same name, you will not be able to cache and activate the user in CloudAccess or provision the user to SaaS applications. When CloudAccess is unable to cache users properly, the Cached User Status Bar indicates this status with a lower number of active users than cached users.

## 11.5 Troubleshooting Authentications or Single Sign-On Issues

There can be multiple reasons why authentications to the SaaS applications fail.

**Time Synchronization:** CloudAccess depends on timestamps to function correctly. Synchronize time between the VMware host, the appliance, and the workstations. Download the authentication or single sign-on logs. In the `catalina.out` file, search for the error `clock skew`.

**SAML Authentications:** Firefox contains a SAML debug add-on you can use to view the SAML authentication between CloudAccess and the SaaS applications. Download the add-on [SAML tracer](https://addons.mozilla.org/en-US/firefox/addon/saml-tracer/) (<https://addons.mozilla.org/en-US/firefox/addon/saml-tracer/>) to view the SAML request.

**Master Node Down:** If the master node is not running, users who already have accounts can log in to SaaS applications, but CloudAccess cannot provision new users. So, if new users attempt to log in to SaaS applications and receive an error indicating they should contact their system administrator, verify that the master node is running.

## 11.6 Valid Salesforce Credentials Fail

Configuring the Connector for Salesforce may fail with valid credentials. One possible reason is that the Salesforce password expired. Log in to the Salesforce site and reset your password. You receive a new password and a new security token. Use these credentials when creating the Connector for Salesforce.

Even if your credentials are correct, you may occasionally be unable to log in to Salesforce and the Connector for Salesforce in CloudAccess may show an intermittent red status. Salesforce has API metering that limits the number of calls during a 24-hour period. For more information, see the following Salesforce resources:

- ♦ [http://www.salesforce.com/us/developer/docs/api/Content/implementation\\_considerations.htm#sforce\\_api\\_rate\\_metering](http://www.salesforce.com/us/developer/docs/api/Content/implementation_considerations.htm#sforce_api_rate_metering) ([http://www.salesforce.com/us/developer/docs/api/Content/implementation\\_considerations.htm#sforce\\_api\\_rate\\_metering](http://www.salesforce.com/us/developer/docs/api/Content/implementation_considerations.htm#sforce_api_rate_metering))
- ♦ <http://boards.developerforce.com/t5/General-Development/REQUEST-LIMIT-EXCEEDED/td-p/24901> (<http://boards.developerforce.com/t5/General-Development/REQUEST-LIMIT-EXCEEDED/td-p/24901>)

## 11.7 Troubleshooting the Connector for Office 365

There are two different types of logs for the Connector for Office 365. Follow the instructions below to obtain the different types of logs.

- ♦ [Section 11.7.1, “Obtaining the Installation Logs,” on page 69](#)
- ♦ [Section 11.7.2, “Obtaining the Provisioning Logs,” on page 70](#)

### 11.7.1 Obtaining the Installation Logs

By default, CloudAccess does not generate an installation log when you install the Connector for Office 365. If you want a log of the installation, you must launch the installer from the command line using the following commands:

```
msiexec /i netiq-office365-connector-1.0.msi /L*V "C:\log\example.log"
```

## 11.7.2 Obtaining the Provisioning Logs

The Connector for Office 365 integrates with the Windows Event Log. The Windows Event Log displays the Connector for Office 365 events as O365ConnectorEventLog. For more information about the Windows Event Log, see [Windows Event Log \(http://msdn.microsoft.com/en-us/library/windows/desktop/aa385780%28v=vs.85%29.aspx\)](http://msdn.microsoft.com/en-us/library/windows/desktop/aa385780%28v=vs.85%29.aspx).

## 11.8 Troubleshooting Custom Connectors

Custom connectors allow for authentication into other systems, but they do not provide provisioning of user accounts. Unlike the Connector for Salesforce, CloudAccess does not create a specific log for each custom connector.

CloudAccess captures all information about custom connectors in the `catalina.out` file. To troubleshoot issues with custom connectors and capture the information in the `catalina.out` file, perform the following steps:

- 1 Access the Admin page.  
For more information, see [Section 3.1, "Accessing the Administration Pages," on page 25](#).
- 2 Under **Appliances**, click the node icon, then click **Enter Troubleshooting Mode**.
- 3 Click the node icon again, then click **Troubleshooting Tools**.
- 4 Select **Authentication / Single Sign-on** to increase the logging levels.
- 5 Duplicate the error or condition.
- 6 Click **Download CloudAccess Log Files** link to download the logs.
- 7 Extract the download file and search for `catalina.out`.
- 8 Open `catalina.out` in a text editor, then search for errors in association with your custom connector.

---

# A Open Source Licenses Release Notes

- ♦ Section A.1, “Documentation,” on page 71
- ♦ Section A.2, “Open Source Components,” on page 71
- ♦ Section A.3, “Open Source Licenses,” on page 79
- ♦ Section A.4, “Obtaining a Copy of the Media,” on page 121

## A.1 Documentation

The following sources provide information about CloudAccess:

- ♦ **Installation:** *NetIQ CloudAccess Installation and Configuration Guide*
- ♦ **Online product documentation:** NetIQ CloudAccess documentation Web site ([http://www.netiq.com/documentation/cloudaccess/install\\_config/data/bookinfo.html](http://www.netiq.com/documentation/cloudaccess/install_config/data/bookinfo.html)).

## A.2 Open Source Components

- ♦ Section A.2.1, “Apache 2.2.17,” on page 72
- ♦ Section A.2.2, “Apache Commons Logging 1.1.1,” on page 72
- ♦ Section A.2.3, “Apache Portable Runtime 1.4.2,” on page 72
- ♦ Section A.2.4, “Argo 2.21,” on page 72
- ♦ Section A.2.5, “Bouncy Castle 1.5.140,” on page 73
- ♦ Section A.2.6, “dom4j 1.6.1,” on page 73
- ♦ Section A.2.7, “dovecot20-backend-pgsql-2.0.20-31.1,” on page 73
- ♦ Section A.2.8, “dovecot20-backend-mysql-2.0.20-31.1,” on page 74
- ♦ Section A.2.9, “dovecot20-backend-sqlite-2.0.20-31.1,” on page 74
- ♦ Section A.2.10, “dovecot20-2.0.20-31.1,” on page 74
- ♦ Section A.2.11, “dovecot20-devel-2.0.20-31.1,” on page 74
- ♦ Section A.2.12, “GWT 2.4.0,” on page 74
- ♦ Section A.2.13, “GWT Mosaic 0.4.0-rc4,” on page 74
- ♦ Section A.2.14, “gwtupload 0.6,” on page 75
- ♦ Section A.2.15, “Hibernate 3,” on page 75
- ♦ Section A.2.16, “httpClient 4.1.2,” on page 75
- ♦ Section A.2.17, “JavaMail 1.4.3,” on page 75
- ♦ Section A.2.18, “JavaService 2.0.10,” on page 75

- [Section A.2.19, “Jaxb 2.2,” on page 75](#)
- [Section A.2.20, “jersey 1.0.3,” on page 76](#)
- [Section A.2.21, “jgroups 2.10.0 GA,” on page 76](#)
- [Section A.2.22, “log4cxx 0.10.0,” on page 76](#)
- [Section A.2.23, “log4j 1.2.15,” on page 76](#)
- [Section A.2.24, “NTLM Library \(TCP implementation\) 1,” on page 76](#)
- [Section A.2.25, “OpenSSL 0.98j,” on page 76](#)
- [Section A.2.26, “Open-vm-tools 9.0.0-9.1,” on page 77](#)
- [Section A.2.27, “libvmtools 9.0.0-9.1,” on page 77](#)
- [Section A.2.28, “Recaptcha4j 0.0.8,” on page 77](#)
- [Section A.2.29, “Tomcat 5.5.27,” on page 77](#)
- [Section A.2.30, “Tomcat 7.7.0.27-10,” on page 78](#)
- [Section A.2.31, “Xalan 2.7.1,” on page 78](#)
- [Section A.2.32, “Xerces 2.9.1,” on page 78](#)
- [Section A.2.33, “XMLSec 1.3.0,” on page 79](#)

## **A.2.1 Apache 2.2.17**

See [Section A.3.1, “Apache 2.0 License,” on page 79](#).

Copyright (c) 2001-2009, The Apache Software Foundation

## **A.2.2 Apache Commons Logging 1.1.1**

See [Section A.3.1, “Apache 2.0 License,” on page 79](#).

Copyright The Apache Software Foundation

## **A.2.3 Apache Portable Runtime 1.4.2**

See [Section A.3.1, “Apache 2.0 License,” on page 79](#).

Copyright (c) 2009 The Apache Software Foundation. This product includes software developed by The Apache Software Foundation (<http://www.apache.org/>).

Portions of this software were developed at the National Center for Supercomputing Applications (NCSA) at the University of Illinois at Urbana-Champaign.

This software contains code derived from the RSA Data Security Inc. MD5 Message-Digest Algorithm.

This software contains code derived from UNIX V7, Copyright(C) Caldera International Inc.

## **A.2.4 Argo 2.21**

See [Section A.3.1, “Apache 2.0 License,” on page 79](#).

Copyright 2011 Mark Slater



Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except in compliance with the License. You may obtain a copy of the License at <http://www.apache.org/licenses/LICENSE-2.0>

Unless required by applicable law or agreed to in writing, software distributed under the License is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the specific language governing permissions and limitations under the License.

## A.2.5 Bouncy Castle 1.5.140

See [Section A.3.2, "BouncyCastle - Adaptation of the MIT X11 License,"](#) on page 82.

Copyright (c) 2000 - 2012 The Legion Of The Bouncy Castle (<http://www.bouncycastle.org>)

## A.2.6 dom4j 1.6.1

See [Section A.3.3, "BSD Style License,"](#) on page 83.

Copyright 2001-2005 (C) MetaStuff, Ltd. All Rights Reserved.

## A.2.7 dovecot20-backend-pgsql-2.0.20-31.1

See [Section A.3.4, "MIT,"](#) on page 83 Dovecot - MIT.

See [Section A.3.5, "LGPL V2.1,"](#) on page 84 Dovecot - LGPL V2.1.

Everything in src/lib/, src/auth/, src/lib-sql/ and src/lib-ntlm/ is under MIT license (see COPYING.MIT) unless otherwise mentioned at the beginning of the file.

Everything else is LGPLv2.1 (see COPYING.LGPL) unless otherwise mentioned at the beginning of the file.

Current exceptions are: src/lib/md5.c : Public Domain

AUTHORS file:

Timo Sirainen <tss@iki.fi>

Solar Designer <solar@openwall.com> (src/lib/md5.c, src/auth/passdb-pam.c)

Andrey Panin <pazke@donpac.ru> (src/auth/mech-apop.c, src/auth/mech-login.c, src/lib-ntlm/\*, src/auth/mech-ntlm.c, src/auth/mech-rpa.c)

Joshua Goodall <joshua@roughtrade.net> (src/auth/mech-cram-md5.c, src/doveadm/doveadm-pw.c)

Jelmer Vernooij <jelmer@samba.org> (src/auth/mech-gssapi.c)

Vaclav Haisman <v.haisman@sh.cvut.cz> (src/lib/ioloop-kqueue.c, src/lib/ioloop-notify-kqueue.c)

Portions Copyright (c) 2008 Apple Inc. All rights reserved.

Grepping 'Patch by' from ChangeLog shows up more people.

src/lib/sha1.c and sha2.c:

Copyright (C) 1995, 1996, 1997, and 1998 WIDE Project.

Copyright (C) 2005, 2007 Olivier Gay <olivier.gay@a3.epfl.ch>

src/lib/UnicodeData.txt:

Copyright (C) 1991-2007 Unicode, Inc. All rights reserved. Distributed under the Terms of Use in <http://www.unicode.org/copyright.html>.

## **A.2.8 dovecot20-backend-mysql-2.0.20-31.1**

See [Section A.3.4, “MIT,” on page 83](#) Dovecot - MIT.

See [Section A.3.5, “LGPL V2.1,” on page 84](#) Dovecot - LGPL V2.1.

See [Section A.2.7, “dovecot20-backend-pgsql-2.0.20-31.1,” on page 73](#).

## **A.2.9 dovecot20-backend-sqlite-2.0.20-31.1**

See [Section A.3.4, “MIT,” on page 83](#) Dovecot - MIT.

See [Section A.3.5, “LGPL V2.1,” on page 84](#) Dovecot - LGPL V2.1.

See [Section A.2.7, “dovecot20-backend-pgsql-2.0.20-31.1,” on page 73](#).

## **A.2.10 dovecot20-2.0.20-31.1**

See [Section A.3.4, “MIT,” on page 83](#) Dovecot - MIT.

See [Section A.3.5, “LGPL V2.1,” on page 84](#) Dovecot - LGPL V2.1.

See [Section A.2.7, “dovecot20-backend-pgsql-2.0.20-31.1,” on page 73](#).

## **A.2.11 dovecot20-devel-2.0.20-31.1**

See [Section A.3.4, “MIT,” on page 83](#) Dovecot - Mit.

See [Section A.3.5, “LGPL V2.1,” on page 84](#) Dovecot - Lgpl V2.1.

See [Section A.2.7, “dovecot20-backend-pgsql-2.0.20-31.1,” on page 73](#).

## **A.2.12 GWT 2.4.0**

See [Section A.3.1, “Apache 2.0 License,” on page 79](#).

Copyright (c) Google, Inc. 2009. All rights reserved. All other product, service names, brands, or trademarks, are the property of their respective owners.

## **A.2.13 GWT Mosaic 0.4.0-rc4**

See [Section A.3.1, “Apache 2.0 License,” on page 79](#).

Copyright (c) Google, Inc. 2009. All rights reserved. All other product, service names, brands, or trademarks, are the property of their respective owners.

## A.2.14 gwtupload 0.6

See [Section A.3.1, “Apache 2.0 License,” on page 79.](#)

Copyright 2009 Manolo Carrasco (Manuel Carrasco Moñino)

## A.2.15 Hibernate 3

See [Section A.3.5, “LGPL V2.1,” on page 84.](#)

Copyright © 2007 by Red Hat, Inc. This copyrighted material is made available to anyone wishing to use, modify, copy, or redistribute it subject to the terms and conditions of the GNU Lesser General Public License, as published by the Free Software Foundation.

## A.2.16 httpclient 4.1.2

See [Section A.3.1, “Apache 2.0 License,” on page 79.](#)

Apache HttpComponents Client Copyright 1999-2009 The Apache Software Foundation. This product includes software developed by The Apache Software Foundation (<http://www.apache.org/>).

This project contains annotations derived from JCIP-ANNOTATIONS

Copyright (c) 2005 Brian Goetz and Tim Peierls. See <http://www.jcip.net>

Apache HttpComponents Core – HttpClient

Copyright 2006-2009 The Apache Software Foundation

This product includes software developed by The Apache Software Foundation (<http://www.apache.org/>).

## A.2.17 JavaMail 1.4.3

See [Section A.3.6, “Javamail,” on page 91.](#)

Copyright © 2009 Sun Microsystems, Inc., 4150 Network Circle, Santa Clara, California 95054, U.S.A. All rights reserved.

Sun Microsystems, Inc.

## A.2.18 JavaService 2.0.10

See [Section A.3.7, “JavaService,” on page 95.](#)

See [Section A.3.5, “LGPL V2.1,” on page 84.](#)

Copyright owner John Rutter

## A.2.19 Jaxb 2.2

See [Section A.3.8, “COMMON DEVELOPMENT AND DISTRIBUTION LICENSE \(CDDL\) Version 1.0,” on page 96.](#)

See [Section A.3.9, “GPL V2 + classpath exception dual license,” on page 101.](#)

Copyright © 2010, Oracle and/or its affiliates. All rights reserved. Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

## **A.2.20 jersey 1.0.3**

See [Section A.3.8, "COMMON DEVELOPMENT AND DISTRIBUTION LICENSE \(CDDL\) Version 1.0," on page 96.](#)

See [Section A.3.9, "GPL V2 + classpath exception dual license," on page 101.](#)

Copyright © 2010, Oracle and/or its affiliates. All rights reserved. Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

## **A.2.21 jgroups 2.10.0 GA**

See [Section A.3.5, "LGPL V2.1," on page 84.](#)

Copyright (c) 2007 Free Software Foundation, Inc. <<http://fsf.org/>> Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

## **A.2.22 log4cxx 0.10.0**

See [Section A.3.1, "Apache 2.0 License," on page 79.](#)

Copyright (c) 2004-2007 The Apache Software Foundation

## **A.2.23 log4j 1.2.15**

See [Section A.3.1, "Apache 2.0 License," on page 79.](#)

Copyright (c) The Apache Software Foundation

## **A.2.24 NTLM Library (TCP implementation) 1**

See [Section A.3.10, "Microsoft Public License MS-PL," on page 106.](#)

Microsoft Public License MS-PL

Could not find an explicit copyright notice. The source code headers include the following author:

Auteur : Dominique GUERIN

\* dominiqueph.guerin@gmail.com

\* dominique.guerin@insee.fr

\* Le code est utilisable, modifiable et redistribuable à volonté sous la seule condition de ne pas supprimer ces 7 lignes.

## **A.2.25 OpenSSL 0.98j**

See [Section A.3.11, "OpenSSL License and SSLeay License," on page 107.](#)

Copyright (c) 1998-2011 The OpenSSL Project. All rights reserved.

## **A.2.26 Open-vm-tools 9.0.0-9.1**

See [Section A.3.12, “GNU LESSER GENERAL PUBLIC LICENSE Version 2.1, February 1999,” on page 109.](#)

See [Section A.3.13, “GNU GENERAL PUBLIC LICENSE Version 2,” on page 116.](#)

Copyright (C) 2009 VMware, Inc. All rights reserved.

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation version 2 and no later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA

## **A.2.27 libvmtools 9.0.0-9.1**

See [Section A.3.12, “GNU LESSER GENERAL PUBLIC LICENSE Version 2.1, February 1999,” on page 109.](#)

See [Section A.3.13, “GNU GENERAL PUBLIC LICENSE Version 2,” on page 116.](#)

See [Section A.2.26, “Open-vm-tools 9.0.0-9.1,” on page 77.](#)

## **A.2.28 Recaptcha4j 0.0.8**

See [Section A.3.1, “Apache 2.0 License,” on page 79.](#)

Copyright 2007 Soren Davidsen, Taneshare Networks.

## **A.2.29 Tomcat 5.5.27**

See [Section A.3.1, “Apache 2.0 License,” on page 79.](#)

Apache Tomcat Copyright (c) 1999-2007 The Apache Software Foundation

This product includes software developed by The Apache Software Foundation (<http://www.apache.org/>).

Java Management Extensions (JMX) support is provided by the MX4J package, which is open source software. The original software and related information is available at <http://mx4j.sourceforge.net>.

The Windows Installer is built with the Nullsoft Scriptable Install Sysem (NSIS), which is open source software. The original software and related information is available at <http://nsis.sourceforge.net>.

Java compilation software for JSP pages is provided by Eclipse, which is open source software. The original software and related information is available at <http://www.eclipse.org>.

## A.2.30 Tomcat 7.7.0.27-10

See [Section A.3.1, “Apache 2.0 License,” on page 79](#).

Copyright 1999-2012 The Apache Software Foundation

This product includes software developed by The Apache Software Foundation (<http://www.apache.org/>).

The Windows Installer is built with the Nullsoft Scriptable Install System (NSIS), which is open source software. The original software and related information is available at <http://nsis.sourceforge.net>.

Java compilation software for JSP pages is provided by Eclipse, which is open source software. The original software and related information is available at <http://www.eclipse.org>.

For the bayeux implementation

The org.apache.cometd.bayeux API is derivative work originating at the Dojo Foundation

\* Copyright 2007-2008 Guy Molinari

\* Copyright 2007-2008 Filip Hanik

\* Copyright 2007 Dojo Foundation

\* Copyright 2007 Mort Bay Consulting Pty. Ltd.

## A.2.31 Xalan 2.7.1

See [Section A.3.1, “Apache 2.0 License,” on page 79](#).

This product includes software developed by The Apache Software Foundation (<http://www.apache.org/>).

Portions of this software was originally based on the following: software copyright (c) 1999-2002, Lotus Development Corporation., <http://www.lotus.com>.

software copyright (c) 2001-2002, Sun Microsystems., <http://www.sun.com>.

software copyright (c) 2003, IBM Corporation., <http://www.ibm.com>

Voluntary contributions made by Ovidiu Predescu ([ovidiu@cup.hp.com](mailto:ovidiu@cup.hp.com)) on behalf of the Apache Software Foundation and was originally developed at Hewlett Packard Company.

## A.2.32 Xerces 2.9.1

See [Section A.3.1, “Apache 2.0 License,” on page 79](#).

This product includes software developed by The Apache Software Foundation (<http://www.apache.org/>).

Apache Xalan (Xalan serializer) Copyright 1999-2006 The Apache Software Foundation Apache XML Commons Resolver Copyright 2006 The Apache Software Foundation. Portions of this software was originally based on the following:

software copyright (c) 1999-2002, Lotus Development Corporation., <http://www.lotus.com>.

software copyright (c) 2001-2002, Sun Microsystems., <http://www.sun.com>.

software copyright (c) 2003, IBM Corporation., <http://www.ibm.com> Voluntary contributions made by Ovidiu Predescu (ovidiu@cup.hp.com) on behalf of the Apache Software Foundation and was originally developed at Hewlett Packard Company.

## A.2.33 XMLSec 1.3.0

See [Section A.3.1, "Apache 2.0 License," on page 79](#).

Copyright (c) 2002 Aleksey Sanin. All Rights Reserved.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions.

## A.3 Open Source Licenses

- ♦ [Section A.3.1, "Apache 2.0 License," on page 79](#)
- ♦ [Section A.3.2, "BouncyCastle - Adaptation of the MIT X11 License," on page 82](#)
- ♦ [Section A.3.3, "BSD Style License," on page 83](#)
- ♦ [Section A.3.4, "MIT," on page 83](#)
- ♦ [Section A.3.5, "LGPL V2.1," on page 84](#)
- ♦ [Section A.3.6, "Javamail," on page 91](#)
- ♦ [Section A.3.7, "JavaService," on page 95](#)
- ♦ [Section A.3.8, "COMMON DEVELOPMENT AND DISTRIBUTION LICENSE \(CDDL\) Version 1.0," on page 96](#)
- ♦ [Section A.3.9, "GPL V2 + classpath exception dual license.," on page 101](#)
- ♦ [Section A.3.10, "Microsoft Public License MS-PL," on page 106](#)
- ♦ [Section A.3.11, "OpenSSL License and SSLeay License," on page 107](#)
- ♦ [Section A.3.12, "GNU LESSER GENERAL PUBLIC LICENSE Version 2.1, February 1999," on page 109](#)
- ♦ [Section A.3.13, "GNU GENERAL PUBLIC LICENSE Version 2," on page 116](#)

### A.3.1 Apache 2.0 License

The Apache 2.0 license is available at <http://www.apache.org/licenses> (<http://www.apache.org/licenses/LICENSE-2.0.txt>).

Apache License

Version 2.0, January 2004

<https://www.apache.org/licenses/>

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.
3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including across-claim or



counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:
  - a. You must give any other recipients of the Work or Derivative Works a copy of this License; and
  - b. You must cause any modified files to carry prominent notices stating that You changed the files; and
  - c. You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and
  - d. If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.
6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.
7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.
8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work

(including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

## END OF TERMS AND CONDITIONS

### APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except in compliance with the License. You may obtain a copy of the License at <http://www.apache.org/licenses/LICENSE-2.0>

Unless required by applicable law or agreed to in writing, software distributed under the License is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the specific language governing permissions and limitations under the License.

## A.3.2 BouncyCastle - Adaptation of the MIT X11 License

The BouncyCastle license is available at <http://www.bouncycastle.org/license.html> (<http://www.bouncycastle.org/licence.html>).

Please note: our license is an adaptation of the MIT X11 License and should be read as such.

### LICENSE

Copyright (c) 2000 - 2012 The Legion Of The Bouncy Castle (<http://www.bouncycastle.org>)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies LICof the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR

OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

### A.3.3 BSD Style License

The BSD style license is available at <http://dom4j.sourceforge.net/dom4j-1.6.1/license.html> (<http://dom4j.sourceforge.net/dom4j-1.6.1/license.html>).

Redistribution and use of this software and associated documentation ("Software"), with or without modification, are permitted provided that the following conditions are met:

Redistributions of source code must retain copyright statements and notices. Redistributions must also contain a copy of this document.

Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

The name "DOM4J" must not be used to endorse or promote products derived from this Software without prior written permission of MetaStuff, Ltd. For written permission, please contact [dom4j-info@metastuff.com](mailto:dom4j-info@metastuff.com).

Products derived from this Software may not be called "DOM4J" nor may "DOM4J" appear in their names without prior written permission of MetaStuff, Ltd. DOM4J is a registered trademark of MetaStuff, Ltd.

Due credit should be given to the DOM4J Project - <http://dom4j.sourceforge.net>

THIS SOFTWARE IS PROVIDED BY METASTUFF, LTD. AND CONTRIBUTORS ``AS IS" AND ANY EXPRESSED OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL METASTUFF, LTD. OR ITS CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Copyright 2001-2005 (C) MetaStuff, Ltd. All Rights Reserved.

### A.3.4 MIT

The MIT license is available at <http://www.dovecot.org/doc/COPYING.MIT> (<http://www.dovecot.org/doc/COPYING.MIT>).

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

### A.3.5 LGPL V2.1

The LGPL V2.1 license is available at <http://www.dovecot.org/doc/COPYING.LGPL> (<http://www.dovecot.org/doc/COPYING.LGPL>).

GNU LESSER GENERAL PUBLIC LICENSE

Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.

59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts as the successor of the GNU Library Public License, version 2, hence the version number 2.1.]

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public Licenses are intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some specially designated software packages--typically libraries--of the Free Software Foundation and other authors who decide to use it. You can use it too, but we suggest you first think carefully about whether this license or the ordinary General Public License is the better strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

Finally, software patents pose a constant threat to the existence of any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits such linking only if the entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

## GNU LESSER GENERAL PUBLIC LICENSE

### TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

- ♦ a. The modified work must itself be a software library.
- ♦ b. You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.
- ♦ c. You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.
- ♦ d. If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

- ♦ a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)
- ♦ b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate properly with a modified version of the library, if the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.
- ♦ c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.
- ♦ d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.
- ♦ e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

- ♦ a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.
- ♦ b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.



9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we

sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

## NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

## END OF TERMS AND CONDITIONS

### How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

- ♦ <one line to give the library's name and a brief idea of what it does.> Copyright (C) <year>  
<name of author>
- ♦ This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.
- ♦ This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.
- ♦ You should have received a copy of the GNU Lesser General Public License along with this library; if not, write to the Free Software Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the library, if necessary. Here is a sample; alter the names:

- ♦ Yoyodyne, Inc., hereby disclaims all copyright interest in the library 'Frob' (a library for tweaking knobs) written by James Random Hacker.
- ♦ <signature of Ty Coon>, 1 April 1990 Ty Coon, President of Vice

That's all there is to it!

## A.3.6 Javamail

Sun Microsystems, Inc. ("Sun") ENTITLEMENT for SOFTWARE

Licensee/Company: Entity receiving Software.

Effective Date: Date of delivery of the Software to You.

Software: JavaMail 1.4.3

License Term: Perpetual (subject to termination under the SLA).

Licensed Unit: Software Copy.

Licensed unit Count: Unlimited.

Permitted Uses:

1. You may reproduce and use the Software for Your own Individual, Commercial and Research and Instructional Use only for the purposes of designing, developing, testing, and running Your applets and applications ("Programs").
2. Subject to the terms and conditions of this Agreement and restrictions and exceptions set forth in the Software's documentation, You may reproduce and distribute portions of Software identified as a redistributable in the documentation (each a "Redistributable"), provided that You comply with the following (note that You may be entitled to reproduce and distribute other portions of the Software not defined in the documentation as a Redistributable under certain other licenses as described in the THIRDPARTYLICENSEREADME, if applicable):
  - a. You distribute Redistributable complete and unmodified and only bundled as part of Your Programs,
  - b. Your Programs add significant and primary functionality to the Redistributable,
  - c. You distribute Redistributable for the sole purpose of running Your Programs,
  - d. You do not distribute additional software intended to replace any component(s) of the Redistributable,
  - e. You do not remove or alter any proprietary legends or notices contained in or on the Redistributable.
  - f. You only distribute the Redistributable subject to a license agreement that protects Sun's interests consistent with the terms contained in this Agreement, and
  - g. You agree to defend and indemnify Sun and its licensors from and against any damages, costs, liabilities, settlement amounts and/or expenses (including attorneys' fees) incurred in connection with any claim, lawsuit or action by any third party that arises or results from the use or distribution of any and all Programs and/or Redistributable.
3. Java Technology Restrictions. You may not create, modify, or change the behavior of, or authorize Your licensees to create, modify, or change the behavior of, classes, interfaces, or subpackages that are in any way identified as "java", "javax", "sun" or similar convention as specified by Sun in any naming convention designation.

4. No Diagnostic, Maintenance, Repair or Technical Support Services. The scope of Your license does not include any right, express or implied, (i) to access, copy, distribute, display or use the Software to provide diagnostic, maintenance, repair or technical support services for Sun software or Sun hardware on behalf of any third party for Your direct or indirect commercial gain or advantage, without Sun's prior written authorization, or (ii) for any third party to access, copy, distribute, display or use the Software to provide diagnostic, maintenance, repair or technical support services for Sun software or Sun hardware on Your behalf for such party's direct or indirect commercial gain or advantage, without Sun's prior written authorization. The limitations set forth in this paragraph apply to any and all error corrections, patches, updates, and upgrades to the Software You may receive, access, download or otherwise obtain from Sun.
5. Records and Documentation. During the term of the SLA and Entitlement, and for a period of three (3) years thereafter, You agree to keep proper records and documentation of Your compliance with the SLA and Entitlement. Upon Sun's reasonable request, You will provide copies of such records and documentation to Sun for the purpose of confirming Your compliance with the terms and conditions of the SLA and Entitlement. This section will survive any termination of the SLA and Entitlement. You may terminate this SLA and Entitlement at any time by destroying all copies of the Software in which case the obligations set forth in Section 7 of the SLA shall apply.

Sun Microsystems, Inc. ("Sun")

#### SOFTWARE LICENSE AGREEMENT

READ THE TERMS OF THIS AGREEMENT ("AGREEMENT") CAREFULLY BEFORE OPENING SOFTWARE MEDIA PACKAGE. BY OPENING SOFTWARE MEDIA PACKAGE, YOU AGREE TO THE TERMS OF THIS AGREEMENT. IF YOU ARE ACCESSING SOFTWARE ELECTRONICALLY, INDICATE YOUR ACCEPTANCE OF THESE TERMS BY SELECTING THE "ACCEPT" BUTTON AT THE END OF THIS AGREEMENT. IF YOU DO NOT AGREE TO ALL OF THE TERMS, PROMPTLY RETURN THE UNUSED SOFTWARE TO YOUR PLACE OF PURCHASE FOR A REFUND OR, IF SOFTWARE IS ACCESSED ELECTRONICALLY, SELECT THE "DECLINE" (OR "EXIT") BUTTON AT THE END OF THIS AGREEMENT. IF YOU HAVE SEPARATELY AGREED TO LICENSE TERMS ("MASTER TERMS") FOR YOUR LICENSE TO THIS SOFTWARE, THEN SECTIONS 1-6 OF THIS AGREEMENT ("SUPPLEMENTAL LICENSE TERMS") SHALL SUPPLEMENT AND SUPERSEDE THE MASTER TERMS IN RELATION TO THIS SOFTWARE.

1. Definitions.
  - a. "Entitlement" means the collective set of applicable documents authorized by Sun evidencing your obligation to pay associated fees (if any) for the license, associated Services, and the authorized scope of use of Software under this Agreement.
  - b. "Licensed Unit" means the unit of measure by which your use of Software and/or Service is licensed, as described in your Entitlement.
  - c. "Permitted Use" means the licensed Software use(s) authorized in this Agreement as specified in your Entitlement. The Permitted Use for any bundled Sun software not specified in your Entitlement will be evaluation use as provided in Section 3.
  - d. "Service" means the service(s) that Sun or its delegate will provide, if any, as selected in your Entitlement and as further described in the applicable service listings at [www.sun.com/service/servicelist](http://www.sun.com/service/servicelist).
  - e. "Software" means the Sun software described in your Entitlement. Also, certain software may be included for evaluation use under Section 3.
  - f. "You" and "Your" means the individual or legal entity specified in the Entitlement, or for evaluation purposes, the entity performing the evaluation.
2. License Grant and Entitlement.

Subject to the terms of your Entitlement, Sun grants you a nonexclusive, nontransferable limited license to use Software for its Permitted Use for the license term. Your Entitlement will specify (a) Software licensed, (b) the Permitted Use, (c) the license term, and (d) the Licensed Units.

Additionally, if your Entitlement includes Services, then it will also specify the (e) Service and (f) service term.

If your rights to Software or Services are limited in duration and the date such rights begin is other than the purchase date, your Entitlement will provide that beginning date(s).

The Entitlement may be delivered to you in various ways depending on the manner in which you obtain Software and Services, for example, the Entitlement may be provided in your receipt, invoice or your contract with Sun or authorized Sun reseller. It may also be in electronic format if you download Software.

### 3. Permitted Use.

As selected in your Entitlement, one or more of the following Permitted Uses will apply to your use of Software. Unless you have an Entitlement that expressly permits it, you may not use Software for any of the other Permitted Uses. If you don't have an Entitlement, or if your Entitlement doesn't cover additional software delivered to you, then such software is for your Evaluation Use.

- a. Evaluation Use. You may evaluate Software internally for a period of 90 days from your first use.
- b. Research and Instructional Use. You may use Software internally to design, develop and test, and also to provide instruction on such uses.
- c. Individual Use. You may use Software internally for personal, individual use.
- d. Commercial Use. You may use Software internally for your own commercial purposes.
- e. Service Provider Use. You may make Software functionality accessible (but not by providing Software itself or through outsourcing services) to your end users in an extranet deployment, but not to your affiliated companies or to government agencies.

### 4. Licensed Units.

Your Permitted Use is limited to the number of Licensed Units stated in your Entitlement. If you require additional Licensed Units, you will need additional Entitlement(s).

### 5. Restrictions.

(a) The copies of Software provided to you under this Agreement are licensed, not sold, to you by Sun. Sun reserves all rights not expressly granted. (b) You may make a single archival copy of Software, but otherwise may not copy, modify, or distribute Software. However if the Sun documentation accompanying Software lists specific portions of Software, such as header files, class libraries, reference source code, and/or redistributable files, that may be handled differently, you may do so only as provided in the Sun documentation. (c) You may not rent, lease, lend or encumber Software. (d) Unless enforcement is prohibited by applicable law, you may not decompile, or reverse engineer Software. (e) The terms and conditions of this Agreement will apply to any Software updates, provided to you at Sun's discretion, that replace and/or supplement the original Software, unless such update contains a separate license. (f) You may not publish or provide the results of any benchmark or comparison tests run on Software to any third party without the prior written consent of Sun. (g) Software is confidential and copyrighted. (h) Unless otherwise specified, if Software is delivered with embedded or bundled software that enables functionality of Software, you may not use such software on a stand-alone basis or use any portion of such software to interoperate with any program(s) other than Software. (i) Software may contain programs that perform automated collection of system data and/or automated software updating services. System data collected through such programs may be used by Sun, its subcontractors, and its service delivery partners for the purpose of providing you with remote system services and/or improving Sun's software and systems. (j) Software is not designed, licensed or intended for use in the design, construction, operation or

maintenance of any nuclear facility and Sun and its licensors disclaim any express or implied warranty of fitness for such uses. (k) No right, title or interest in or to any trademark, service mark, logo or trade name of Sun or its licensors is granted under this Agreement.

6. Java Compatibility and Open Source.

Software may contain Java technology. You may not create additional classes to, or modifications of, the Java technology, except under compatibility requirements available under a separate agreement available at [www.java.net](http://www.java.net).

Sun supports and benefits from the global community of open source developers, and thanks the community for its important contributions and open standards-based technology, which Sun has adopted into many of its products.

Please note that portions of Software may be provided with notices and open source licenses from such communities and third parties that govern the use of those portions, and any licenses granted hereunder do not alter any rights and obligations you may have under such open source licenses, however, the disclaimer of warranty and limitation of liability provisions in this Agreement will apply to all Software in this distribution.

7. Term and Termination.

The license and service term are set forth in your Entitlement(s). Your rights under this Agreement will terminate immediately without notice from Sun if you materially breach it or take any action in derogation of Sun's and/or its licensors' rights to Software. Sun may terminate this Agreement should any Software become, or in Sun's reasonable opinion likely to become, the subject of a claim of intellectual property infringement or trade secret misappropriation. Upon termination, you will cease use of, and destroy, Software and confirm compliance in writing to Sun. Sections 1, 5, 6, 7, and 9-15 will survive termination of the Agreement.

8. Limited Warranty.

Sun warrants to you that for a period of 90 days from the date of purchase, as evidenced by a copy of the receipt, the media on which Software is furnished (if any) will be free of defects in materials and workmanship under normal use. Except for the foregoing, Software is provided "AS IS". Your exclusive remedy and Sun's entire liability under this limited warranty will be at Sun's option to replace Software media or refund the fee paid for Software. Some states do not allow limitations on certain implied warranties, so the above may not apply to you. This limited warranty gives you specific legal rights. You may have others, which vary from state to state.

9. Disclaimer of Warranty.

UNLESS SPECIFIED IN THIS AGREEMENT, ALL EXPRESS OR IMPLIED CONDITIONS, REPRESENTATIONS AND WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT ARE DISCLAIMED, EXCEPT TO THE EXTENT THAT THESE DISCLAIMERS ARE HELD TO BE LEGALLY INVALID.

10. Limitation of Liability.

TO THE EXTENT NOT PROHIBITED BY LAW, IN NO EVENT WILL SUN OR ITS LICENSORS BE LIABLE FOR ANY LOST REVENUE, PROFIT OR DATA, OR FOR SPECIAL, INDIRECT, CONSEQUENTIAL, INCIDENTAL OR PUNITIVE DAMAGES, HOWEVER CAUSED REGARDLESS OF THE THEORY OF LIABILITY, ARISING OUT OF OR RELATED TO THE USE OF OR INABILITY TO USE SOFTWARE, EVEN IF SUN HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. In no event will Sun's liability to you, whether in contract, tort (including negligence), or otherwise, exceed the amount paid by you for Software under this Agreement. The foregoing limitations will apply even if the above stated warranty fails of its essential purpose. Some states do not allow the exclusion of incidental or consequential damages, so some of the terms above may not be applicable to you.

11. Export Regulations.

All Software, documents, technical data, and any other materials delivered under this Agreement are subject to U.S. export control laws and may be subject to export or import regulations in other countries. You agree to comply strictly with these laws and regulations and acknowledge that you have the responsibility to obtain any licenses to export, re-export, or import as may be required after delivery to you.

12. U.S. Government Restricted Rights.

If Software is being acquired by or on behalf of the U.S. Government or by a U.S. Government prime contractor or subcontractor (at any tier), then the Government's rights in Software and accompanying documentation will be only as set forth in this Agreement; this is in accordance with 48 CFR 227.7201 through 227.7202-4 (for Department of Defense (DOD) acquisitions) and with 48 CFR 2.101 and 12.212 (for non-DOD acquisitions).

13. Governing Law.

Any action related to this Agreement will be governed by California law and controlling U.S. federal law. No choice of law rules of any jurisdiction will apply.

14. Severability.

If any provision of this Agreement is held to be unenforceable, this Agreement will remain in effect with the provision omitted, unless omission would frustrate the intent of the parties, in which case this Agreement will immediately terminate.

15. Integration.

This Agreement, including any terms contained in your Entitlement, is the entire agreement between you and Sun relating to its subject matter. It supersedes all prior or contemporaneous oral or written communications, proposals, representations and warranties and prevails over any conflicting or additional terms of any quote, order, acknowledgment, or other communication between the parties relating to its subject matter during the term of this Agreement. No modification of this Agreement will be binding, unless in writing and signed by an authorized representative of each party.

Please contact Sun Microsystems, Inc. 4150 Network Circle, Santa Clara, California 95054 if you have questions.

## A.3.7 JavaService

This software is currently covered by two open source licenses:

```
/*
 * JavaService - Windows NT Service Daemon for Java applications
 *
 * Copyright (C) 2004 Multiplan Consultants Ltd.
 *
 * This library is free software; you can redistribute it and/or
 * modify it under the terms of the GNU Lesser General Public
 * License as published by the Free Software Foundation; either
 * version 2.1 of the License, or (at your option) any later version.
 *
 * This library is distributed in the hope that it will be useful,
 * but WITHOUT ANY WARRANTY; without even the implied warranty of
 * MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
 * Lesser General Public License for more details.
 *
```

```

* You should have received a copy of the GNU Lesser General Public
* License along with this library; if not, write to the Free Software
* Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA
*
*
* Information about the JavaService software is available at the ObjectWeb
* web site. Refer to http://javaservice.objectweb.org for more details.
*
*
* This software is derived from earlier work by Alexandria Software Consulting,
* (no longer contactable) which was released under a BSD-style license in 2001.
* The text of that original license is reproduced below for reference.
*
*/

/*
*
* JavaService - License
*
* By downloading and/or using this software you agree to abide by the following
license:
*
* Copyright (c) 2000, Alexandria Software Consulting
*
* All rights reserved. Redistribution and use in source and binary forms, with or
without
* modification, are permitted provided that the following conditions are met:
*
* Redistributions of source code must retain the above copyright notice, this list
of
* conditions, and the following disclaimer.
* Neither name of Alexandria Software Consulting nor the names of the contributors
may be
* used to endorse or promote products derived from this software without specific
prior
* written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
ANY
* EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
WARRANTIES
* OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO
EVENT
* SHALL THE COPYRIGHT HOLDERS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT,
* INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED
* TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS;
OR
* BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
* CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING
IN ANY
* WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH
DAMAGE.
*/

```

## A.3.8 COMMON DEVELOPMENT AND DISTRIBUTION LICENSE (CDDL) Version 1.0

The CDDL license is available at <http://glassfish.java.net/public/CDDL+GPL.html> (<http://glassfish.java.net/public/CDDL+GPL.html>).

### 1. Definitions.

1.1. "Contributor" means each individual or entity that creates or contributes to the creation of Modifications.



1.2. "Contributor Version" means the combination of the Original Software, prior Modifications used by a Contributor (if any), and the Modifications made by that particular Contributor.

1.3. "Covered Software" means (a) the Original Software, or (b) Modifications, or (c) the combination of files containing Original Software with files containing Modifications, in each case including portions thereof.

1.4. "Executable" means the Covered Software in any form other than Source Code.

1.5. "Initial Developer" means the individual or entity that first makes Original Software available under this License.

1.6. "Larger Work" means a work which combines Covered Software or portions thereof with code not governed by the terms of this License.

1.7. "License" means this document.

1.8. "Licensable" means having the right to grant, to the maximum extent possible, whether at the time of the initial grant or subsequently acquired, any and all of the rights conveyed herein.

1.9. "Modifications" means the Source Code and Executable form of any of the following:

- ♦ A. Any file that results from an addition to, deletion from or modification of the contents of a file containing Original Software or previous Modifications;
- ♦ B. Any new file that contains any part of the Original Software or previous Modification; or
- ♦ C. Any new file that is contributed or otherwise made available under the terms of this License.

1.10. "Original Software" means the Source Code and Executable form of computer software code that is originally released under this License.

1.11. "Patent Claims" means any patent claim(s), now owned or hereafter acquired, including without limitation, method, process, and apparatus claims, in any patent Licensable by grantor.

1.12. "Source Code" means (a) the common form of computer software code in which modifications are made and (b) associated documentation included in or with such code.

1.13. "You" (or "Your") means an individual or a legal entity exercising rights under, and complying with all of the terms of, this License. For legal entities, "You" includes any entity which controls, is controlled by, or is under common control with You. For purposes of this definition, "control" means (a) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (b) ownership of more than fifty percent (50%) of the outstanding shares or beneficial ownership of such entity.

## 2. License Grants.

### 2.1. The Initial Developer Grant.

Conditioned upon Your compliance with Section 3.1 below and subject to third party intellectual property claims, the Initial Developer hereby grants You a world-wide, royalty-free, non-exclusive license:

- ♦ (a) under intellectual property rights (other than patent or trademark) Licensable by Initial Developer, to use, reproduce, modify, display, perform, sublicense and distribute the Original Software (or portions thereof), with or without Modifications, and/or as part of a Larger Work; and
- ♦ (b) under Patent Claims infringed by the making, using or selling of Original Software, to make, have made, use, practice, sell, and offer for sale, and/or otherwise dispose of the Original Software (or portions thereof).

- ♦ (c) The licenses granted in Sections 2.1(a) and (b) are effective on the date Initial Developer first distributes or otherwise makes the Original Software available to a third party under the terms of this License.
- ♦ (d) Notwithstanding Section 2.1(b) above, no patent license is granted: (1) for code that You delete from the Original Software, or (2) for infringements caused by: (i) the modification of the Original Software, or (ii) the combination of the Original Software with other software or devices.

## 2.2 Contributor Grant.

Conditioned upon Your compliance with Section 3.1 below and subject to third party intellectual property claims, each Contributor hereby grants You a world-wide, royalty-free, non-exclusive license:

- ♦ (a) under intellectual property rights (other than patent or trademark) Licensable by Contributor to use, reproduce, modify, display, perform, sublicense and distribute the Modifications created by such Contributor (or portions thereof), either on an unmodified basis, with other Modifications, as Covered Software and/or as part of a Larger Work; and
- ♦ (b) under Patent Claims infringed by the making, using, or selling of Modifications made by that Contributor either alone and/or in combination with its Contributor Version (or portions of such combination), to make, use, sell, offer for sale, have made, and/or otherwise dispose of: (1) Modifications made by that Contributor (or portions thereof); and (2) the combination of Modifications made by that Contributor with its Contributor Version (or portions of such combination).
- ♦ (c) The licenses granted in Sections 2.2(a) and 2.2(b) are effective on the date Contributor first distributes or otherwise makes the Modifications available to a third party.
- ♦ (d) Notwithstanding Section 2.2(b) above, no patent license is granted: (1) for any code that Contributor has deleted from the Contributor Version; (2) for infringements caused by: (i) third party modifications of Contributor Version, or (ii) the combination of Modifications made by that Contributor with other software (except as part of the Contributor Version) or other devices; or (3) under Patent Claims infringed by Covered Software in the absence of Modifications made by that Contributor.

## 3. Distribution Obligations.

### 3.1. Availability of Source Code.

Any Covered Software that You distribute or otherwise make available in Executable form must also be made available in Source Code form and that Source Code form must be distributed only under the terms of this License. You must include a copy of this License with every copy of the Source Code form of the Covered Software You distribute or otherwise make available. You must inform recipients of any such Covered Software in Executable form as to how they can obtain such Covered Software in Source Code form in a reasonable manner on or through a medium customarily used for software exchange.

### 3.2. Modifications.

The Modifications that You create or to which You contribute are governed by the terms of this License. You represent that You believe Your Modifications are Your original creation(s) and/or You have sufficient rights to grant the rights conveyed by this License.

### 3.3. Required Notices.

You must include a notice in each of Your Modifications that identifies You as the Contributor of the Modification. You may not remove or alter any copyright, patent or trademark notices contained within the Covered Software, or any notices of licensing or any descriptive text giving attribution to any Contributor or the Initial Developer.

### 3.4. Application of Additional Terms.

You may not offer or impose any terms on any Covered Software in Source Code form that alters or restricts the applicable version of this License or the recipients' rights hereunder. You may choose to offer, and to charge a fee for, warranty, support, indemnity or liability obligations to one or more recipients of Covered Software. However, you may do so only on Your own behalf, and not on behalf of the Initial Developer or any Contributor. You must make it absolutely clear that any such warranty, support, indemnity or liability obligation is offered by You alone, and You hereby agree to indemnify the Initial Developer and every Contributor for any liability incurred by the Initial Developer or such Contributor as a result of warranty, support, indemnity or liability terms You offer.

### 3.5. Distribution of Executable Versions.

You may distribute the Executable form of the Covered Software under the terms of this License or under the terms of a license of Your choice, which may contain terms different from this License, provided that You are in compliance with the terms of this License and that the license for the Executable form does not attempt to limit or alter the recipient's rights in the Source Code form from the rights set forth in this License. If You distribute the Covered Software in Executable form under a different license, You must make it absolutely clear that any terms which differ from this License are offered by You alone, not by the Initial Developer or Contributor. You hereby agree to indemnify the Initial Developer and every Contributor for any liability incurred by the Initial Developer or such Contributor as a result of any such terms You offer.

### 3.6. Larger Works.

You may create a Larger Work by combining Covered Software with other code not governed by the terms of this License and distribute the Larger Work as a single product. In such a case, You must make sure the requirements of this License are fulfilled for the Covered Software.

## 4. Versions of the License.

### 4.1. New Versions.

Sun Microsystems, Inc. is the initial license steward and may publish revised and/or new versions of this License from time to time. Each version will be given a distinguishing version number. Except as provided in Section 4.3, no one other than the license steward has the right to modify this License.

### 4.2. Effect of New Versions.

You may always continue to use, distribute or otherwise make the Covered Software available under the terms of the version of the License under which You originally received the Covered Software. If the Initial Developer includes a notice in the Original Software prohibiting it from being distributed or otherwise made available under any subsequent version of the License, You must distribute and make the Covered Software available under the terms of the version of the License under which You originally received the Covered Software. Otherwise, You may also choose to use, distribute or otherwise make the Covered Software available under the terms of any subsequent version of the License published by the license steward.

### 4.3. Modified Versions.

When You are an Initial Developer and You want to create a new license for Your Original Software, You may create and use a modified version of this License if You: (a) rename the license and remove any references to the name of the license steward (except to note that the license differs from this License); and (b) otherwise make it clear that the license contains terms which differ from this License.

## 5. DISCLAIMER OF WARRANTY.

COVERED SOFTWARE IS PROVIDED UNDER THIS LICENSE ON AN “AS IS” BASIS, WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, WITHOUT LIMITATION, WARRANTIES THAT THE COVERED SOFTWARE IS FREE OF DEFECTS, MERCHANTABILITY, FIT FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE COVERED SOFTWARE IS WITH YOU. SHOULD ANY COVERED SOFTWARE PROVE DEFECTIVE IN ANY RESPECT, YOU (NOT THE INITIAL DEVELOPER OR ANY OTHER CONTRIBUTOR) ASSUME THE COST OF ANY NECESSARY SERVICING, REPAIR OR CORRECTION. THIS DISCLAIMER OF WARRANTY CONSTITUTES AN ESSENTIAL PART OF THIS LICENSE. NO USE OF ANY COVERED SOFTWARE IS AUTHORIZED HEREUNDER EXCEPT UNDER THIS DISCLAIMER.

## 6. TERMINATION.

6.1. This License and the rights granted hereunder will terminate automatically if You fail to comply with terms herein and fail to cure such breach within 30 days of becoming aware of the breach. Provisions which, by their nature, must remain in effect beyond the termination of this License shall survive.

6.2. If You assert a patent infringement claim (excluding declaratory judgment actions) against Initial Developer or a Contributor (the Initial Developer or Contributor against whom You assert such claim is referred to as “Participant”) alleging that the Participant Software (meaning the Contributor Version where the Participant is a Contributor or the Original Software where the Participant is the Initial Developer) directly or indirectly infringes any patent, then any and all rights granted directly or indirectly to You by such Participant, the Initial Developer (if the Initial Developer is not the Participant) and all Contributors under Sections 2.1 and/or 2.2 of this License shall, upon 60 days notice from Participant terminate prospectively and automatically at the expiration of such 60 day notice period, unless if within such 60 day period You withdraw Your claim with respect to the Participant Software against such Participant either unilaterally or pursuant to a written agreement with Participant.

6.3. In the event of termination under Sections 6.1 or 6.2 above, all end user licenses that have been validly granted by You or any distributor hereunder prior to termination (excluding licenses granted to You by any distributor) shall survive termination.

## 7. LIMITATION OF LIABILITY.

UNDER NO CIRCUMSTANCES AND UNDER NO LEGAL THEORY, WHETHER TORT (INCLUDING NEGLIGENCE), CONTRACT, OR OTHERWISE, SHALL YOU, THE INITIAL DEVELOPER, ANY OTHER CONTRIBUTOR, OR ANY DISTRIBUTOR OF COVERED SOFTWARE, OR ANY SUPPLIER OF ANY OF SUCH PARTIES, BE LIABLE TO ANY PERSON FOR ANY INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES OF ANY CHARACTER INCLUDING, WITHOUT LIMITATION, DAMAGES FOR LOST PROFITS, LOSS OF GOODWILL, WORK STOPPAGE, COMPUTER FAILURE OR MALFUNCTION, OR ANY AND ALL OTHER COMMERCIAL DAMAGES OR LOSSES, EVEN IF SUCH PARTY SHALL HAVE BEEN INFORMED OF THE POSSIBILITY OF SUCH DAMAGES. THIS LIMITATION OF LIABILITY SHALL NOT APPLY TO LIABILITY FOR DEATH OR PERSONAL INJURY RESULTING FROM SUCH PARTY’S NEGLIGENCE TO THE EXTENT APPLICABLE LAW PROHIBITS SUCH LIMITATION. SOME JURISDICTIONS DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THIS EXCLUSION AND LIMITATION MAY NOT APPLY TO YOU.

## 8. U.S. GOVERNMENT END USERS.

The Covered Software is a “commercial item,” as that term is defined in 48 C.F.R. 2.101 (Oct. 1995), consisting of “commercial computer software” (as that term is defined at 48 C.F.R. § 252.227-7014(a)(1)) and “commercial computer software documentation” as such terms are used in 48 C.F.R. 12.212 (Sept. 1995). Consistent with 48 C.F.R. 12.212 and 48 C.F.R. 227.7202-1 through 227.7202-4 (June

1995), all U.S. Government End Users acquire Covered Software with only those rights set forth herein. This U.S. Government Rights clause is in lieu of, and supersedes, any other FAR, DFAR, or other clause or provision that addresses Government rights in computer software under this License.

#### 9. MISCELLANEOUS.

This License represents the complete agreement concerning subject matter hereof. If any provision of this License is held to be unenforceable, such provision shall be reformed only to the extent necessary to make it enforceable. This License shall be governed by the law of the jurisdiction specified in a notice contained within the Original Software (except to the extent applicable law, if any, provides otherwise), excluding such jurisdiction's conflict-of-law provisions. Any litigation relating to this License shall be subject to the jurisdiction of the courts located in the jurisdiction and venue specified in a notice contained within the Original Software, with the losing party responsible for costs, including, without limitation, court costs and reasonable attorneys' fees and expenses. The application of the United Nations Convention on Contracts for the International Sale of Goods is expressly excluded. Any law or regulation which provides that the language of a contract shall be construed against the drafter shall not apply to this License. You agree that You alone are responsible for compliance with the United States export administration regulations (and the export control laws and regulation of any other countries) when You use, distribute or otherwise make available any Covered Software.

#### 10. RESPONSIBILITY FOR CLAIMS.

As between Initial Developer and the Contributors, each party is responsible for claims and damages arising, directly or indirectly, out of its utilization of rights under this License and You agree to work with Initial Developer and Contributors to distribute such responsibility on an equitable basis. Nothing herein is intended or shall be deemed to constitute any admission of liability.

#### NOTICE PURSUANT TO SECTION 9 OF THE COMMON DEVELOPMENT AND DISTRIBUTION LICENSE (CDDL)

The code released under the CDDL shall be governed by the laws of the State of California (excluding conflict-of-law provisions). Any litigation relating to this License shall be subject to the jurisdiction of the Federal Courts of the Northern District of California and the state courts of the State of California, with venue lying in Santa Clara County, California.

### A.3.9 **GPL V2 + classpath exception dual license.**

This license is available here <http://glassfish.java.net/public/CDDL+GPL.html> (<http://glassfish.java.net/public/CDDL+GPL.html>).

The GNU General Public License (GPL) Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc. 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

#### Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Library General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

#### TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:
  - a. You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

- b. You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.
- c. If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

- 3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:
  - a. Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,
  - b. Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,
  - c. Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.
5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.
6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.
7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.
9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.



10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

#### NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.
12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

#### END OF TERMS AND CONDITIONS

#### How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

One line to give the program's name and a brief idea of what it does.

#### Copyright (C)

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author

Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'. This is free software, and you are welcome to redistribute it under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program `Gnomovision' (which makes passes at compilers) written by James Hacker.

signature of Ty Coon, 1 April 1989

Ty Coon, President of Vice

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Library General Public License instead of this License.

#### "CLASSPATH" EXCEPTION TO THE GPL VERSION 2

Certain source files distributed by Sun Microsystems, Inc. are subject to the following clarification and special exception to the GPL Version 2, but only where Sun has expressly included in the particular source file's header the words "Sun designates this particular file as subject to the "Classpath" exception as provided by Sun in the License file that accompanied this code."

Linking this library statically or dynamically with other modules is making a combined work based on this library. Thus, the terms and conditions of the GNU General Public License Version 2 cover the whole combination.

As a special exception, the copyright holders of this library give you permission to link this library with independent modules to produce an executable, regardless of the license terms of these independent modules, and to copy and distribute the resulting executable under terms of your choice, provided that you also meet, for each linked independent module, the terms and conditions of the license of that module.? An independent module is a module which is not derived from or based on this library.? If you modify this library, you may extend this exception to your version of the library, but you are not obligated to do so.? If you do not wish to do so, delete this exception statement from your version.

Terms of Use; Privacy Policy; Copyright ©2008-2012 (revision 20121116.2af7adc)

## A.3.10 Microsoft Public License MS-PL

Microsoft Public License MS-PL

This license governs use of the accompanying software. If you use the software, you accept this license. If you do not accept the license, do not use the software.

### 1. Definitions

The terms "reproduce," "reproduction," "derivative works," and "distribution" have the same meaning here as under U.S. copyright law.

A "contribution" is the original software, or any additions or changes to the software.

A "contributor" is any person that distributes its contribution under this license.

"Licensed patents" are a contributor's patent claims that read directly on its contribution.

## 2. Grant of Rights

- a. Copyright Grant- Subject to the terms of this license, including the license conditions and limitations in section 3, each contributor grants you a non-exclusive, worldwide, royalty free copyright license to reproduce its contribution, prepare derivative works of its contribution, and distribute its contribution or any derivative works that you create.
- b. Patent Grant- Subject to the terms of this license, including the license conditions and limitations in section 3, each contributor grants you a non-exclusive, worldwide, royalty-free license under its licensed patents to make, have made, use, sell, offer for sale, import, and/or otherwise dispose of its contribution in the software or derivative works of the contribution in the software.

## 3. Conditions and Limitations

- a. No Trademark License- This license does not grant you rights to use any contributors' name, logo, or trademarks.
- b. If you bring a patent claim against any contributor over patents that you claim are infringed by the software, your patent license from such contributor to the software ends automatically.
- c. If you distribute any portion of the software, you must retain all copyright, patent, trademark, and attribution notices that are present in the software.
- d. If you distribute any portion of the software in source code form, you may do so only under this license by including a complete copy of this license with your distribution. If you distribute any portion of the software in compiled or object code form, you may only do so under a license that complies with this license.
- e. The software is licensed "as-is." You bear the risk of using it. The contributors give no express warranties, guarantees or conditions. You may have additional consumer rights under your local laws which this license cannot change. To the extent permitted under your local laws, the contributors exclude the implied warranties of merchantability, fitness for a particular purpose and non-infringement.

## A.3.11 OpenSSL License and SSLeay License

### LICENSE ISSUES

=====

The OpenSSL toolkit stays under a dual license, i.e. both the conditions of the OpenSSL License and the original SSLeay license apply to the toolkit. See below for the actual license texts. Actually both licenses are BSD-style Open Source licenses. In case of any license issues related to OpenSSL please contact [openssl-core@openssl.org](mailto:openssl-core@openssl.org).

OpenSSL License

-----

```
/* =====
 * Copyright (c) 1998-2008 The OpenSSL Project. All rights reserved.
 *
 * Redistribution and use in source and binary forms, with or without
 * modification, are permitted provided that the following conditions
 * are met:
 *
 * 1. Redistributions of source code must retain the above copyright
 *    notice, this list of conditions and the following disclaimer.
 *
 * 2. Redistributions in binary form must reproduce the above copyright
```

```

* notice, this list of conditions and the following disclaimer in
* the documentation and/or other materials provided with the
* distribution.
*
* 3. All advertising materials mentioning features or use of this
* software must display the following acknowledgment:
* "This product includes software developed by the OpenSSL Project
* for use in the OpenSSL Toolkit. (http://www.openssl.org/)"
*
* 4. The names "OpenSSL Toolkit" and "OpenSSL Project" must not be used to
* endorse or promote products derived from this software without
* prior written permission. For written permission, please contact
* openssl-core@openssl.org.
*
* 5. Products derived from this software may not be called "OpenSSL"
* nor may "OpenSSL" appear in their names without prior written
* permission of the OpenSSL Project.
*
* 6. Redistributions of any form whatsoever must retain the following
* acknowledgment:
* "This product includes software developed by the OpenSSL Project
* for use in the OpenSSL Toolkit (http://www.openssl.org/)"
*
* THIS SOFTWARE IS PROVIDED BY THE OpenSSL PROJECT ``AS IS'' AND ANY
* EXPRESSED OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
* PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE OpenSSL PROJECT OR
* ITS CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
* SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT
* NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
* LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
* HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT,
* STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
* ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED
* OF THE POSSIBILITY OF SUCH DAMAGE.
* =====
*
* This product includes cryptographic software written by Eric Young
* (eay@cryptsoft.com). This product includes software written by Tim
* Hudson (tjh@cryptsoft.com).
*
*/

Original SSLeay License
-----

/* Copyright (C) 1995-1998 Eric Young (eay@cryptsoft.com)
* All rights reserved.
*
* This package is an SSL implementation written
* by Eric Young (eay@cryptsoft.com).
* The implementation was written so as to conform with Netscapes SSL.
*
* This library is free for commercial and non-commercial use as long as
* the following conditions are aheared to. The following conditions
* apply to all code found in this distribution, be it the RC4, RSA,
* lhash, DES, etc., code; not just the SSL code. The SSL documentation
* included with this distribution is covered by the same copyright terms
* except that the holder is Tim Hudson (tjh@cryptsoft.com).
*
* Copyright remains Eric Young's, and as such any Copyright notices in
* the code are not to be removed.
* If this package is used in a product, Eric Young should be given attribution
* as the author of the parts of the library used.
* This can be in the form of a textual message at program startup or
* in documentation (online or textual) provided with the package.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:

```

```

* 1. Redistributions of source code must retain the copyright
* notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
* notice, this list of conditions and the following disclaimer in the
* documentation and/or other materials provided with the distribution.
* 3. All advertising materials mentioning features or use of this software
* must display the following acknowledgement:
* "This product includes cryptographic software written by
* Eric Young (eay@cryptsoft.com)"
* The word 'cryptographic' can be left out if the routines from the library
* being used are not cryptographic related :-).
* 4. If you include any Windows specific code (or a derivative thereof) from
* the apps directory (application code) you must include an acknowledgement:
* "This product includes software written by Tim Hudson (tjh@cryptsoft.com)"
*
* THIS SOFTWARE IS PROVIDED BY ERIC YOUNG ``AS IS'' AND
* ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
* ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE
* FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
* DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
* OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
* HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
* LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
* OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
* SUCH DAMAGE.
*
* The licence and distribution terms for any publically available version or
* derivative of this code cannot be changed. i.e. this code cannot simply be
* copied and put under another distribution licence
* [including the GNU Public Licence.]
*/

```

## A.3.12 GNU LESSER GENERAL PUBLIC LICENSE Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.

51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts as the successor of the GNU Library Public License, version 2, hence the version number 2.1.]

### Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public Licenses are intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some specially designated software packages--typically libraries--of the Free Software Foundation and other authors who decide to use it. You can use it too, but we suggest you first think carefully about whether this license or the ordinary General Public License is the better strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

Finally, software patents pose a constant threat to the existence of any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits such linking only if the entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

## GNU LESSER GENERAL PUBLIC LICENSE

### TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

- ♦ (a) The modified work must itself be a software library.
- ♦ (b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.
- ♦ (c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.
- ♦ (d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)



Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

- ♦ a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)
- ♦ b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate properly with a modified version of the library, if the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.
- ♦ c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.
- ♦ d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.
- ♦ e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

- ♦ a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.
- ♦ b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

#### NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

#### END OF TERMS AND CONDITIONS

#### How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

- ♦ <one line to give the library's name and a brief idea of what it does.> Copyright (C) <year>  
<name of author>
- ♦ This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.
- ♦ This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.
- ♦ You should have received a copy of the GNU Lesser General Public License along with this library; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the library, if necessary. Here is a sample; alter the names:

- ♦ Yoyodyne, Inc., hereby disclaims all copyright interest in the library 'Frob' (a library for tweaking knobs) written by James Random Hacker
- ♦ <signature of Ty Coon>, 1 April 1990 Ty Coon, President of Vice

That's all there is to it!

## A.3.13 GNU GENERAL PUBLIC LICENSE Version 2

GNU GENERAL PUBLIC LICENSE

Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,

51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

## GNU GENERAL PUBLIC LICENSE

### TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

- ♦ a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

- ♦ b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.
- ♦ c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

- ♦ a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,
- ♦ b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,
- ♦ c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

#### NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

#### END OF TERMS AND CONDITIONS

#### How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

- ♦ <one line to give the program's name and a brief idea of what it does.> Copyright (C) <year>  
<name of author>
- ♦ This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.
- ♦ This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.
- ♦ You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.



Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

- ♦ Gnomovision version 69, Copyright (C) year name of author Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'. This is free software, and you are welcome to redistribute it under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

- ♦ Yoyodyne, Inc., hereby disclaims all copyright interest in the program `Gnomovision' (which makes passes at compilers) written by James Hacker.
- ♦ <signature of Ty Coon>, 1 April 1989 Ty Coon, President of Vice

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License.

## A.4 Obtaining a Copy of the Media

The chapter lists the Open Source material contained in this release and the full text of the open source license that applies to each. NetIQ offers to provide a DVD containing the source code for each open source component included in this product governed by GPL, LGPL and CDDL licenses. The request for the source code should be addressed to: Legal Department, Novell, Inc., 1800 Novell Place, Provo, Utah 84606. With the request, please include the name of the product (CloudAccess) and the version of the product (1.1). There is a charge of \$10.00 USD for each request to cover cost of media and shipping.

