

NetIQ Directory and Resource Administrator Product Customization

May 2020

Legal Notice

For information about legal notices, trademarks, disclaimers, warranties, export and other use restrictions, U.S. Government rights, patent policy, and FIPS compliance, see <https://www.microfocus.com/about/legal/>.

© Copyright 2007-2020 Micro Focus or one of its affiliates.

The only warranties for products and services of Micro Focus and its affiliates and licensors ("Micro Focus") are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Micro Focus shall not be liable for technical or editorial errors or omissions contained herein. The information contained herein is subject to change without notice.

Contents

1 About this Guide	5
2 Product Customization Scenario Details	6
Active Directory Configuration Script:	6
User Personas	6
3 Customizing NRC Reports.....	8
Create a User Defined (UD) Context for report filtering	9
Scope.....	9
Step-by-step Guide.....	9
Creating a "Collections Status for the last seven days" Report.....	14
Scope.....	14
Step-by-step Guide.....	14
Creating a "Temporary Group Assignment" Report.....	17
Scope.....	17
Step-by-step Guide.....	17
Creating a "Virtual Attribute Associations" Report.....	19
Scope.....	19
Step-by-step Guide.....	19
Modify an Existing Report, SQL column addition	22
Scope.....	22
Step-by-step Guide.....	22
Modify an Existing Report, SQL where clause	23
Scope.....	23
Step-by-step Guide.....	23
Process for Modifying the "General Report" in NRC.....	26
Scope.....	26
Step-by-step Guide.....	26
Working with Custom Virtual Attributes.....	29
Scope.....	29
Step-by-Step Guide	29
Database Schema	30
DRA Reporting Database	30
4 Custom Triggers	71
Collect Additional Virtual Attributes and Extend Object Property Page	71
Scope.....	71
Step-by-step Guide.....	71
Enable or disable an Exchange Online user's Outlook web access when they are enabled or disabled in Active Directory	78
Scope.....	78

Step-by-step Guide.....	78
Launch Workflow from Trigger.....	81
Scope.....	81
Step-by-step Guide.....	81
Move a user to a new OU when their Office property is changed	84
Scope.....	84
Step-by-step Guide.....	84
5 Web Client Customization	88
Custom Property Page Examples;.....	88
Add Virtual Attributes to Custom Forms.....	89
Step-by-step Guide.....	89
Indicate Field (A) is Required When Field (B) has a Value at Runtime	93
Step-by-step Guide.....	93
On Form Submit, Validate Field (A) has a Value When Field (B) has a Value	94
Step-by-step Guide.....	94
Populate selection values for a field based on previous field selection	96
Step-by-step Guide.....	96
Pre-populate Value (A) Based on Value (B) Using Built-in Attribute Setting.....	101
Step-by-step Guide.....	101
Pre-populate value automatically based on custom handler.....	103
Step-by-step Guide.....	103
Validate input using a regular expression	105
Built-in example regular expressions:.....	105
Step-by-step Guide.....	106
Validate Name Uniqueness for a Specified Field Value at Run-time.....	108
Step-by-step Guide.....	108
Validate Name Uniqueness for a Specified Field Value When a Form is Submitted	113
Step-by-step Guide.....	113
6 Workflow Customization.....	117
Custom Form Workflow to delete a user.....	119
Lab Data Setup	122
HumanResources Database	122
IQMail setup	122
Load HR DB to DRA	124
ServiceNow Event Trigger.....	126

About this Guide

The *Product Customization* reference provides several examples of the capability to customize reports, triggers, object property forms, and automated workflow processes using NetIQ Directory and Resource Administrator (DRA) and its integrated components.

Intended Audience

This guide provides information for anyone using the customization features in the DRA Web Console.

Additional Documentation

This guide is part of the NetIQ Directory and Resource Administrator documentation set. For the most recent version of this guide and other DRA documentation resources, visit the [DRA Documentation website](https://www.netiq.com/documentation/directory-and-resource-administrator/index.html) (<https://www.netiq.com/documentation/directory-and-resource-administrator/index.html>).

Contact Information

We want to hear your comments and suggestions about this book and the other documentation included with this product. You can use the [comment on this topic](#) link at the bottom of each page of the online documentation, or send an email to Documentation-Feedback@microfocus.com.

For specific product issues, contact Micro Focus Customer Care at <https://www.microfocus.com/support-and-services/>.

Product Customization Scenario Details

The examples in this document are all based on a simulated company, "Keystone Steel". This page contains information about the company, network environment, and users that will be referenced in the customizations to follow.

Active Directory Configuration Script:


Use the files below from the resource kit to load the OUs. This script will load all of the OUs defined in the Keystone Steel domain. The Resource Kit is available with this document on the DRA Documentation page.

Active Directory Structure Reference:

- [PowerShell Script](#)
- [OU CSV File](#)

User Personas

Philip Jensen	CIO
Daniel Altaner the Architect	Daniel Altaner owns the "big picture" design of IAS for a large organization, providing the foundation for individual colleagues to focus on security, identity, and/or access requirements. In smaller organizations, Daniel might be the sole architect for the combined IAS solution.
Adam Mandari the Administrator	Adam Mandari takes requirements from Daniel Altaner, the IT architect, to set up and maintain the IAS solution and ensure that the infrastructure for IAS works. He helps configure the system so the enterprise knows who has access to what and the methods for ensuring security or analyzing events that might represent breaches in security. He installs and configures the backend agents and services.
Danita Olivarez in DevOps Director	Danita Olivarez is the Director of DevOps / DevSecOps
Devin in DevOps	Devin Merrill, DevOps engineer / operator
Arvanti Rana the Application/Resource Owner	Arvanti Rana is responsible for a specific application, service, or resource, such as a database or the SAP financial module. She is considered both a technical expert (SME) and business user. Arvanti administers her application, but might not understand the nuts and bolts of the organization's IAS solutions. Arvanti needs information from and provides information to the IAS solutions. She maintains and configures the applications, services, and resources that form a part of the IAS solution.



Arturo Perez the Auditor	Arturo Perez is responsible for verifying that the organization complies with established internal control procedures by examining records, reports, operating practices, and documentation. He might delegate certain tasks to his staff to ensure that the work is performed efficiently.
Ken Nagai in Compliance	Ken Nagai is responsible for architecting the IAS governance policies for an organization. He understands both the benefits and limitations of identity and access review solutions and owns the results of access certification reviews.
Isaac in IT	Isaac Torek is the IT Manager.
Mandy the Analyst	Mandy Rabani is responsible for the forensic analysis of alerts and incidents, based on information supplied by Oskar the Operator and the SIEM solution. She performs the situational assessment of what's going on based on the details that she gathers. She is also responsible for preventing data loss and service interruptions by researching new technologies that will effectively protect a network.
Oskar the Operator	Oskar Yegorov is responsible for identifying incoming alerts in the security software. He performs an initial analysis to determine whether the alerts should be escalated to a higher level of investigation. He might complete that investigation or forward it to a system or security analyst. He helps coordinate responses to computer security incidents and recommends actions for each incident to ensure that they are properly tracked, escalated, and reported.
Helen Winzen on the Help Desk	Helen Winzen provides the first line of support when an end user, such as Maria Belafonte, runs into identity, access, or software/hardware problems. She is technically astute and understand the nuts and bolts of identity and access review solutions. She also understands and works to ensure that users follow the organization's security policies.
Sarah the Supervisor / Business Line Manager	<p>Sarah Gibson directly manages a team, and is sometimes responsible for requesting or granting access to resources for her team. Sarah needs information from and provides information to access certification reviews. She can supervise one of several departments, such as Marketing or Help Desk.</p> <p>Sarah ensures that her employees understand and comply with business and government regulations, and that they use the appropriate applications, resources, and services.</p>
Maria in Marketing / End User	Maria Belafonte represents an end user on the corporate network. An end user could be any employee with a corporate identity who requires access to resources. She needs prompt access to resources with a minimum of thought or effort. Sometimes she is required to act on behalf of her Supervisor to approve or deny requests for access.

Customizing NRC Reports

This section contains customization examples and the database schema for NetIQ Reporting Center reports.

Definition of terms and components:

Term/Components	Definition
General Report	Contains the definition of all the reports available in NRC.
User Defined Context	Filter for adjusting the report results for a specific report execution.
Custom Virtual Attribute	Custom DRA extension attribute
Data Model	Available objects and attributes
Collectors	Component/Jobs for periodically collecting reporting data from DRA, Auditing, AD, and O365


Examples:

Use Case	Components for Example
Extend an existing report with new filter (UDContext) to add additional filter to fetch the data. Example	<ul style="list-style-type: none">UD Contexts
Create a new report to show all collectors runs with job collection type, start/end time and status of the job within the last 7 days. Example	<ul style="list-style-type: none">New report templates
Create a new report to list all temporary group details and its associated members. Example	<ul style="list-style-type: none">New report templates
Create a new report to list all the VA attributes and their associated object types. Example	<ul style="list-style-type: none">New report templates
Extend a default report with an additional virtual attribute Example	<ul style="list-style-type: none">Virtual Attribute ConfigurationUpdating report template (Columns returned)
Modify the existing report that fetches user account data that expires within a week to instead fetch user accounts expiring within the next 30 days. Example	<ul style="list-style-type: none">Updating report template (SQL Where clause)
Put together a database schema reference Reference	

Create a User Defined (UD) Context for report filtering

Scope

The NetIQ Reporting Center (NRC), allows for reports to be designed to accept user input at report execution time to dynamically filter and sort the information returned through the use of "**User Defined Contexts**". In this example we will demonstrate the steps to create a new User Defined Context for filtering on the User object attribute "Department". Then we will extend the "User Accounts Details" report to use the new User Defined Context to allow filtering the returned results by department.



Step-by-step Guide

1. Follow the [Process for Modifying the "General Report" in NRC](#) up to the uploading section.
2. Create a SQL query to filter Users returned by Department.

SQL Statement

```
SELECT DISTINCT DEPARTMENT
FROM     USERS
ORDER BY DEPARTMENT
```

NOTE:

You can use SQL Server Management Studio against the DRAReporting database to test the SQL statement to make sure it returns the desired results.

3. Create a DRA.Custom.UDContext.XML file if it does not exist. Update the Checkin batch file if needed.

DRA.Custom.UDContext.xml

```
<?xml version="1.0" encoding="utf-8"?>
<UDCONTEXTS>
</UDCONTEXTS>
```

Checkin Batch File

```
@echo off
REM Checkin DRA NRC Reports
if Exist "%~d0\Program Files\NetIQ\Reporting Center\Utilities\XmlCheckIn.exe" goto Checkin
echo ""%~d0\Program Files\NetIQ\Reporting Center\Utilities\XmlCheckIn.exe not found, check
path of NetIQ Reporting Center"
Goto End

:Checkin
"%~d0\Program Files\NetIQ\Reporting Center\Utilities\XmlCheckIn.exe" /S localhost
"%~d0\Program Files (x86)\NetIQ\DRA\DRA Reporting\DRADatasource.XML"
"%~d0\Program Files\NetIQ\Reporting Center\Utilities\XmlCheckIn.exe" /S localhost
"%~d0\Program Files (x86)\NetIQ\DRA\DRA Reporting\DRADatasource.XML"
"%~d0\Program Files\NetIQ\Reporting Center\Utilities\XmlCheckIn.exe" /S localhost
"%~d0\Program Files (x86)\NetIQ\DRA\DRA Reporting\DRADatasource.XML"
"%~d0\Program Files\NetIQ\Reporting Center\Utilities\XmlCheckIn.exe" /S localhost
"%~d0\Program Files (x86)\NetIQ\DRA\DRA Reporting\DRADatasource.XML"

if not exist "%~d0\Program Files (x86)\NetIQ\DRA\DRA Reporting\DRACustom.UDContext.XML"
goto SkipToReport
"%~d0\Program Files\NetIQ\Reporting Center\Utilities\XmlCheckIn.exe" /S localhost
"%~d0\Program Files (x86)\NetIQ\DRA\DRA Reporting\DRACustom.UDContext.XML"

:SkipToReport
if not exist "%~d0\Program Files (x86)\NetIQ\DRA\DRA Reporting\DRACustom.Reports.XML" goto
End
"%~d0\Program Files\NetIQ\Reporting Center\Utilities\XmlCheckIn.exe" /S localhost
"%~d0\Program Files (x86)\NetIQ\DRA\DRA Reporting\DRACustom.Reports.XML"

:End
echo DRA NRC Reporting setup Done!
```

4. Next, in the `DRA.Custom.UDContext.XML` file and add a User Defined Context definition that specifies how this configuration will be exposed in the report and then save the file.

SQL Statement

```
<UDCONTEXT ID="DRADEPARTMENTCONTEXT" DataTarget="SQL" Type="DRAResulting">
<SQLQUERY>
<! [CDATA[
    CREATE TABLE #tmpud
    (
        [udLevel] NVARCHAR(max) NULL,
        [udObject] NVARCHAR(max) NULL ,
        [udObjectParent] NVARCHAR(max) NULL,
        [udObjectName] NVARCHAR(max) NULL,
        [udObjectUIName]NVARCHAR(max) NULL,
        [udOutput] NVARCHAR(max) NULL,
        [udIcon] NVARCHAR(max) Null,
        [udSortOrder] NVARCHAR(max) Null
    )
    INSERT #tmpud (udLevel, udObject, udObjectParent, udObjectName, udObjectUIName,
udOutput, udIcon, udSortOrder)
        SELECT DISTINCT
            [udLevel] = 0,
            [udObject] = 'AllDepartments',
            [udObjectParent]= NULL,
            [udObjectName] =  'All Departments',
            [udObjectUIName]= 'All Departments',
            [udOutput]= 'All Departments',
            [udIcon] = 0,
            [udSortOrder] = 0

    INSERT #tmpud (udLevel, udObject, udObjectParent, udObjectName, udObjectUIName,
udOutput, udIcon, udSortOrder)
        SELECT DISTINCT
            [udLevel] = 1,
            [udObject] = DEPARTMENT,
            [udObjectParent]= 'AllDepartments',
            [udObjectName] =  DEPARTMENT,
            [udObjectUIName]=  DEPARTMENT,
            [udOutput]= DEPARTMENT,
            [udIcon] = 0,
            [udSortOrder] = 0
        FROM [dbo].[Users]
        ORDER BY DEPARTMENT
]]>
```


```

        SELECT * FROM #tmpud
        ORDER BY [udLevel],[udObjectName]

        DROP TABLE #tmpud
    ]]>
</SQLQUERY>
<RETURNDATA Type="SQL" Format="Set" ColumnName="" />
</UDCONTEXT>

```

5. Now open the .\Program Files (x86)\NetIQ\DR\DR Reporting\DR Report.XML file and extract the section for the "User Account Details" report to the custom report file. We will update the report definition to include the new User Defined Context that we created in the previous step.



The screenshot shows a Notepad window titled "DRA.ReportXML - Notepad". The content is the XML definition for a report named "User Account Details". It includes sections for parameters, contexts, and a query. A blue box highlights a specific part of the SQL query where a new context is being added.

```


<!DOCTYPE IQREPORT>
<IQREPORT ID="DATA REPORTS.USERACCOUNTDETAILS" Type="DRReporting"
    Description="This report displays details of the user accounts in your managed domains." Title="User Account Details">
<PARAMETERS>
<$STRING Category="Account Status" Description="Account Status" Title="Account Status" ID="AccountDisabled">
<Item>All Accounts</Item>
<Item>Enabled</Item>
<Item>Disabled</Item>
<Value>All Accounts</Value>
</STRING>
</PARAMETERS>
<CONTEXTS>
<CONTEXT TYPE="NetIQ.Reporting.Context.ConnectionContext,NRCLib" Name="DRA Reporting DataSource" ID="1"/>
<CONTEXT TYPE="NetIQ.Reporting.Context.UDContext,NRCLib" ID="1" ContextType="DRAUDCONTEXT" Title="Managed Domains and OUs" SelectAll="yes"/>
<CONTEXT TYPE="NetIQ.Reporting.Context.QueryLimitContext,NRCLib" ID="1" Title="Data Query Limit" Count="1000" ShowWarning="false"/>
<CONTEXT TYPE="NetIQ.Reporting.Context.UDContext,NRCLib" ID="2" ContextType="DRADEPARTMENTCONTEXT" Title="All Departments" SelectAll="yes"/>
</CONTEXTS>
<STANDARD ViewMode="table" NumericFormat="F0" QueryLimit="1000">
<QUERY TYPE="NetIQ.Reporting.Context.NRCQLQuery,NRCLib">
<Template>

    SET QUOTED_IDENTIFIER OFF
    SELECT DISTINCT (QueryLimitContext[1].Value)
    ACCT.[NAME] AS [Name],
    ACCT.[SAMACCOUNTNAME] AS [Sam Account Name],
    USERS.DEPARTMENT AS Department,
    CASE
        WHEN [USERS].[ACCOUNTEXPIRES] IS NULL THEN 'Never'
        WHEN [USERS].[ACCOUNTEXPIRES] &gt;= '9999-12-31' THEN 'Never'
        WHEN [USERS].[ACCOUNTEXPIRES] = '1/1/1753 12:00:00 AM' THEN 'Never'
        ELSE CONVERT(NVARCHAR(25),[USERS].[ACCOUNTEXPIRES])
    END AS [Expiration Date],
```

Edit Report

Make the following changes to the report definition:

- Add the new context inside the <CONTEXTS> tags: **<CONTEXT TYPE="NetIQ.Reporting.Context.UDContext,NRCLib" ID="2" ContextType="DRADEPARTMENTCONTEXT"**
- **Title="All Departments" SelectAll="yes"/>** Add the following line to the SQL statement as outlined in the blue box in the screenshot to the left: **USERS.DEPARTMENT AS Department, just below the ACCT.[SAMACCOUNTNAME] as [Sam Account Name],**
- Add the following line to the WHERE clause of the SQL statement as outlined in the blue box in the screenshot to the left: **AND ((1 = CASE when**
- **{UDContext[2].FLDRID} = 'AllDomains' then 1 ELSE 0 END) OR (USERS.DEPARTMENT IN ({UDContext[2].NODEID}))**



```

DRA.Report.XML - Notepad
File Edit Format View Help

WHEN [USERS].[RASPERMISSION] &gt; 7 THEN 1
ELSE 0
END AS [User Dialin Privilege],
[ACCT].[DISTINGUISHEDNAME] AS [Distinguished Name],
[ACCT].[DESCRIPTION] AS [Description],
[USERS].[WHENCREATED] AS [Time Created],
[USERS].[WHENCHANGED] AS [Time Modified]
FROM
dbo.GET_GUID_TABLE ("{UDCONTEXT[1].NODEID},{UDCONTEXT[1].FLDRID}")
INNER JOIN (SELECT objectGuid, Parent_GUID, distinguishedName, samAccountName, name, description FROM ACCOUNTS WITH (NOLOCK) WHERE CLASS_ID = 5) AS ACCT
ON GET_GUID_TABLE.GUID = ACCT.PARENT_GUID
INNER JOIN CONTEXTTABLEFOROU WITH (NOLOCK) ON GET_GUID_TABLE.GUID = CONTEXTTABLEFOROU.UOBJECTGUID
INNER JOIN USERS WITH (NOLOCK) ON ACCT.OBJECTGUID = [USERS].OBJECTGUID
INNER JOIN DOMAINS WITH (NOLOCK) ON DOMAINS.DOMAIN_ID = [USERS].DOMAIN_ID
WHERE
(
((DOMAINS.MCSISMANAGED = 1) OR (DOMAINS.MCSREQSUBSETMANAGED = 1 AND CONTEXTTABLEFOROU.ISMANAGED &gt; 2))
AND ((1 = CASE WHEN (Parameter[AccountDisabled]) = 'All Accounts' THEN 1 ELSE 0 END ) OR
(USERS.ACOUNTDISABLED = (CASE WHEN (Parameter[AccountDisabled]) = 'Enabled' THEN 0 WHEN (Parameter[AccountDisabled]) = 'Disabled' THEN 1 END ))
AND ((1 = CASE WHEN (UDContext[2].FLDRID) = AllDomains THEN 1 ELSE 0 END ) OR
(USERS.DEPARTMENT IN ((UDContext[2].NODEID))))
)
ORDER BY [Managed Domain Name], [Name]

SET QUOTED_IDENTIFIER ON
</Template>
</QUERY>
<COLUMN Source="Time Created" Format="g"/>
<COLUMN Source="Time Modified" Format="g"/>
<COLUMN Source="Expiration Date" Format="g"/>
</STANDARD>
</NOREPORT>

<NOREPORT ID="DATA REPORTS.USERACCOUNTDETAILSWITHPROPERTIES" Type="DRAReporting"

```

NOTE:

The UDContext we are adding in this step has an ID="2". Later, when the context is executed, it will be referenced as UDContext[2].

6. Save the master report file to the .\Program Files (x86)\NetIQ\DR\DR folder. Follow the final step in [Process for Modifying the "General Report" in NRC](#) uploading section.

Creating a "Collections Status for the last seven days" Report

Scope

The NetIQ Reporting Center, NRC, provides a set of standard reports that can be run to retrieve data from the SQL database. Additionally, NRC allows for the modification and addition of reports to provide a custom solution. In this example we will demonstrate the steps to create a new report that shows the status of all collector jobs executed within the last seven days.

The screenshot shows the NRC interface with the following details:

- Toolbar:** Includes icons for Report Properties, Report Permissions, Report Contexts, Initial Display Options, View Type (Table View), Data Presentation Type, Save Report As, Validate Report Contexts, Run Report, Export Report Definition, and Print/Export/Email.
- Navigation pane:** Lists categories like Services, Shares, Exchange Configuration Reports, Office 365 Reports, Summarized Activity Reports (AA Activity Details, Active, Activity By Action, Activity By Action - Chart, Activity By Action - Table, Activity By Object Type - Chart, Activity By Object Type, Activity By Object Type - Table, Collector Status Summary Table, Event Summary By Target Domain, Event Summary By Target Domain - Chart, Event Summary By Target Domain - Table, Group Membership Changes), Templates, AppManager Templates, AppManager Reports, Last Data Point, Machine Metric by Time Range, and Metric Machine by Time Range.
- Report Content:** The main area displays a report titled "Reporting Center Home\Reports\DRA Management Reports\Summarized Activity Reports\Collector Status Su...". It includes a warning message: "This report may not retrieve all data (first 1000 records). Use Data Query Li..." and a data presentation section: "Data Presentation: Type: Standard, X-Axis" Data Series: [Collector]. A table titled "Collector Status Summary Table" lists data for 296 records. The columns are: Collector, Domain, Server, Start Time, End Time, and Result. The table shows multiple entries for ADCollector with various start and end times, and a mix of Success, Failed, and Aborted results.
- Right pane:** Tasks section with options like Add New Data Source, Manage Security, Configure Reporting Se..., Delete All Cached Report, Deploy Bulk Report..., Export Reports..., Import Reports..., Report Properties, Report Permissions, Initial Display Options, View Type (Table View), Data Presentation Type, and Save Report As...

Step-by-step Guide

1. Follow the [Process for Modifying the "General Report" in NRC](#) up to the uploading section.
2. You can use SQL Server Management Studio against the DRAReporting database to test the SQL statement we will use for his report to make sure it returns the desired results.

SQL Statement

```
SELECT J1.Job_Name AS Collector,
       JH.Collector_Info AS Domain,
       JH.DRA_Server_Name AS Server,
       CONVERT(NVARCHAR(35), JH.Start_Time, 120) AS [Start Time],
       CONVERT(NVARCHAR(35), JH.End_Time, 120) AS [End Time],
       CASE WHEN JH.Result_Id = 1 THEN 'Success'
             WHEN JH.Result_Id = 2 THEN 'Failed'
             ELSE 'Aborted'
       END AS [Result]
```

```

FROM      JOB as J1 INNER JOIN
          JOBS_HISTORY AS JH ON J1.Job_Id = JH.Job_Id
WHERE    (JH.Job_Id <> 3) AND (JH.Start_Time >= DATEADD(DD, - 7, GETDATE()))
UNION ALL
SELECT  J2.Job_Name,
        RJ.Collector_Info,
        RJ.DRA_Server_Name,
        CONVERT(NVARCHAR(35), RJ.Start_Time, 120),
        NULL AS End_Time,
        'Running' AS [Result]
FROM      JOB AS J2 INNER JOIN
          RUNNING_JOBS AS RJ ON J2.Job_Id = RJ.Job_Id
WHERE    (J2.Job_Id <> 3)
ORDER BY Domain, Server, Collector, [Start Time] DESC

```

3. Open the .\Program Files (x86)\NetIQ\DR\DR Reporting\DR Report.XML file and locate the section for the "Summarized Activity Reports" group and extract it to the custom report file. Add the definition for the new report inside this section of the XML:
- <REPORTSET FOLDER="DR Management Reports\Summarized Activity Reports">

Report Definition

```

<NQREPORT ID="SUMMARIZED ACTIVITY REPORTS.COLLECTOR STATUS SUMMARY TABLE"
Type="DRAReporting"
Description="This report displays the collection job status for the last seven days."
Title="Collector Status Summary Table">
<PARAMETERS/>
<CONTEXTS>
  <CONTEXT TYPE="NetIQ.Reporting.Context.ConnectionContext,NRCLib" Name="DRA Reporting
DataSource" ID="1"/>

  <CONTEXT TYPE="NetIQ.Reporting.Context.QueryLimitContext,NRCLib"
ID="1" Title="Data Query Limit" Count="1000" ShowWarning="false"/>
</CONTEXTS>
<STANDARD ViewMode="table" NumericFormat="F0" QueryLimit="1000">
  <QUERY TYPE="NetIQ.Reporting.Context.NRCSQLQuery,NRCLib">
    <Template>
      SELECT {QueryLimitContext[1].Value}
      J1.Job_Name AS Collector,
      JH.Collector_Info AS Domain,
      JH.DRA_Server_Name AS Server,

```

```

        CONVERT(NVARCHAR(35), JH.Start_Time, 120) AS [Start Time],
        CONVERT(NVARCHAR(35), JH.End_Time, 120) AS [End Time],
        CASE WHEN JH.Result_Id = 1 THEN 'Success'
              WHEN JH.Result_Id = 2 THEN 'Failed'
              ELSE 'Aborted'
        END AS [Result]
    FROM      JOB as J1 INNER JOIN
              JOBS_HISTORY AS JH ON J1.Job_Id = JH.Job_Id
    WHERE     (JH.Job_Id < 3) AND (JH.Start_Time >= DATEADD(DD, - 7,
GETDATE()))
        UNION ALL
        SELECT   J2.Job_Name,
                  RJ.Collector_Info,
                  RJ.DRA_Server_Name,
                  CONVERT(NVARCHAR(35), RJ.Start_Time, 120),
                  NULL AS End_Time,
                  'Running' AS [Result]
    FROM      JOB AS J2 INNER JOIN
              RUNNING_JOBS AS RJ ON J2.Job_Id = RJ.Job_Id
    WHERE     (J2.Job_Id < 3)
    ORDER BY Domain, Server, Collector, [Start Time] DESC
</Template>
</QUERY>
</STANDARD>
</NOREPORT>

```

4. Save the report file to the .\Program Files (x86)\NetIQ\DRAGenerator folder. Follow the final step in [Process for Modifying the "General Report" in NRC](#) uploading section. You will see the new report located under the folder "Summarized Activity Report".

Creating a "Temporary Group Assignment" Report

Scope

The NetIQ Reporting Center, NRC, provides a set of standard reports that can be run to retrieve data from the SQL database. Additionally, NRC allows for the modification and addition of reports to provide a custom solution. In this example we will demonstrate the steps to create a new report that shows the list of temporary group assignment details.

The screenshot shows the NRC interface with the following details:

- Toolbar:** Includes icons for Report Properties, Report Permissions Properties, Report Contexts, Initial Display Options, View Type (Table View), Data Presentation Type, Save Report As, Validate Report Contexts, Run Report, Export Report Definition, and Print/Export/Email.
- Navigation pane:** Lists various report categories under "DRA Management Reports" and "DRA Configurations Reports".
- Report Content:** The main area displays a report titled "Temporary Group Assignment Details". It includes a brief description: "This report displays the temporary group assignment details." and a dropdown for "Data Presentation: Type: Standard, X-Axis: Data Series: [Name]".
- Data Table:** A table with columns: Name, Target Group, Source User, Created By, Start Time, and End Time. The data shows several entries of users being added to groups like "dra_adam" and "dra_m001".
- Bottom:** Shows navigation buttons (first, previous, next, last) and a message "Record 1 of 7".

Step-by-step Guide

1. Follow the [Process for Modifying the "General Report" in NRC up to the uploading section.](#)
2. You can use SQL Server Management Studio against the DRAResulting database to test the SQL statement we will use for his report to make sure it returns the desired results.

SQL Statement

```
SELECT TGA.NAME AS Name,
       TGA.TARGET_GROUP AS [Target Group],
       TGM.USER_PATH AS [Source User],
       TGA.ASSISTANT_ADMIN AS [Created By],
       CONVERT(NVARCHAR(35), TGA.START_TIME, 120) AS [Start Time],
       CONVERT(NVARCHAR(35), TGA.END_TIME, 120) AS [End Time],
       TGA.STATUS_MESSAGE AS Status,
       TGA.DESCRIPTION AS Description,
       TGA.CREATION_TIME as [Creation Time]
```

```

    INNER JOIN TGA_GROUP_MEMBERSHIP TGM ON TGA.TGA_ID=TGM.TGA_ID
    ORDER BY TGA.TARGET_GROUP, TGM.USER_PATH

```

3. Open the report file and locate the section for the "DRA Configurations Reports" group and extract the section to the custom report file. Place it under this section of the XML:

Report Definition

```

<NQREPORT ID="DRA CONFIGURATION REPORTS.TGADETAILS" Type="DRAReporting"
    Description="This report displays the temporary group assignment details."
    Title="Temporary Group Assignment Details">
    <PARAMETERS/>
    <CONTEXTS>
        <CONTEXT TYPE="NetIQ.Reporting.Context.ConnectionContext,NRCLib" Name="DRA
        Reporting DataSource" ID="1"/>

        <CONTEXT
            TYPE="NetIQ.Reporting.Context.QueryLimitContext,NRCLib" ID="1"
            Title="Data Query Limit" Count="1000" ShowWarning="false"/>
    </CONTEXTS>
    <STANDARD ViewMode="table" NumericFormat="F0" QueryLimit="1000">
        <QUERY TYPE="NetIQ.Reporting.Context.NRCSQLQuery,NRCLib">
            <Template>
                SELECT {QueryLimitContext[1].Value}
                    TGA.NAME AS Name,
                    TGA.TARGET_GROUP AS [Target Group],
                    TGM.USER_PATH AS [Source User],
                    TGA.ASSISTANT_ADMIN AS [Created By],
                    CONVERT(NVARCHAR(35), TGA.START_TIME, 120) AS [Start Time],
                    CONVERT(NVARCHAR(35), TGA.END_TIME, 120) AS [End Time],
                    TGA.STATUS_MESSAGE AS Status,
                    TGA.DESCRIPTION AS Description,
                    TGA.CREATION_TIME as [Creation Time]
                FROM TGA
                INNER JOIN TGA_GROUP_MEMBERSHIP TGM ON TGA.TGA_ID=TGM.TGA_ID
                ORDER BY TGA.TARGET_GROUP, TGM.USER_PATH
            </Template>
        </QUERY>
    </STANDARD>
</NQREPORT>

```

4. Save the report file to the .\Program Files (x86)\NetIQ\DRA\DRA folder. Follow the final step in [Process for Modifying the "General Report" in NRC](#) uploading section. You will see the new report located under the folder "DRA Configurations Reports".

Creating a "Virtual Attribute Associations" Report

Scope

The NetIQ Reporting Center, NRC, provides a set of standard reports that can be run to retrieve data from the SQL database. Once the report has been created, it can be sorted and/or filtered as needed. Additionally, NRC allows for the modification and addition of reports to provide a custom solution. This procedure will demonstrate the steps to create a new report that shows the list of virtual attributes and their association with classes.

The screenshot shows the NRC interface with the following details:

- Navigation pane:** On the left, under 'DRA Management Reports', the 'Virtual Attribute Associations' report is selected.
- Report pane:** The main area displays the title 'Reporting Center Home\Reports\DRA Management Reports\DRA Configurations Reports\Virtual Attribute As...' and a brief description: 'This report displays the virtual attributes and their associated object classes.' Below this is a data presentation section with 'Type: Standard, X-Axis' Data Series: [Display Name]'.
- Data grid:** A table showing the list of virtual attributes. The columns are: Display Name, Class, Description, Multi Valued, and Enabled. The data includes:

Display Name	Class	Description	Multi Valued	Enabled
vaTemporary	User	Temporary Employment	False	True
vaOtherInfo	Computer		False	True
vaOtherInfo	Contact		False	True
vaOtherInfo	Group		False	True
vaOtherInfo	msExchDynamicDistributionList		False	True
vaOtherInfo	organizationalUnit		False	True
vaOtherInfo	User		False	True
vaTempID	Contact		False	True
vaTempID	User		False	True

At the bottom of the report pane, it says 'Record 1 of 9' and has an 'Edit Filter' button.

Right-hand panels: The 'Report Contexts' panel shows a pinned connection named 'DRA Reporting DataSource'. The 'Data Source Connection' panel shows the same pinned connection. The 'Data Query Limit' panel is also visible.

Step-by-step Guide

1. Follow the [Process for Modifying the "General Report" in NRC](#) up to the uploading section.
2. You can use SQL Server Management Studio against the DRAReporting database to test the SQL statement we will use for his report to make sure it returns the desired results.

SQL Statement

```
SELECT
    VA.DisplayName as [Display Name],
    CLASS.CLASS AS [Class],
    VA.Description,
    VA.IsMultiValued AS [Multi Valued],
    VA.Enabled
```

```

FROM VIRTUAL_ATTRIBUTE VA
INNER JOIN VA_CLASS VC ON VA.VIRTUAL_ATTRIBUTE_ID=VC.VIRTUAL_ATTRIBUTE_ID
INNER JOIN CLASS ON CLASS.CLASS_ID=VC.CLASS_ID
ORDER BY VA.DisplayName, CLASS.CLASS

```

3. Open the custom report file and locate the section for the "DRA Configurations Reports" group and add the definition for the new report inside this section of the XML:

<REPORTSET FOLDER="DRA Management Reports\Summarized Activity Reports">

Report Definition

```

<NQREPORT ID="DRA CONFIGURATION REPORTS.VAASSOCIATIONDETAILS" Type="DRAReporting"

Description="This report displays the virtual attributes and their
associated object classes." Title="Virtual Attribute Associations">
<PARAMETERS/>
<CONTEXTS>
<CONTEXT TYPE="NetIQ.Reporting.Context.ConnectionContext,NRCLib" Name="DRA Reporting
DataSource" ID="1"/>

<CONTEXT TYPE="NetIQ.Reporting.Context.QueryLimitContext,NRCLib"
ID="1" Title="Data Query Limit" Count="1000" ShowWarning="false"/>
</CONTEXTS>
<STANDARD ViewMode="table" NumericFormat="F0" QueryLimit="1000">
<QUERY TYPE="NetIQ.Reporting.Context.NRCSQLQuery,NRCLib">
<Template>
SELECT {QueryLimitContext[1].Value}
VA.DisplayName as [Display Name],
CLASS.CLASS AS [Class],
VA.Description,
VA.IsMultiValued AS [Multi Valued],
VA.Enabled
FROM VIRTUAL_ATTRIBUTE VA
INNER JOIN VA_CLASS VC ON VA.VIRTUAL_ATTRIBUTE_ID=VC.VIRTUAL_ATTRIBUTE_ID
INNER JOIN CLASS ON CLASS.CLASS_ID=VC.CLASS_ID
ORDER BY VA.DisplayName, CLASS.CLASS
</Template>
</QUERY>
</STANDARD>
</NQREPORT>

```

4. Save the report file to the .\Program Files (x86)\NetIQ\DR\DR folder. Follow the final step in [Process for Modifying the "General Report" in NRC](#) uploading section. You will see the new report located under the folder "DR Configurations Reports".

Modify an Existing Report, SQL column addition

Scope

The NetIQ Reporting Center (NRC), provides a set of standard reports that can be run to retrieve data from the DRA SQL reporting database. Additionally, NRC allows for the modification and addition of reports to provide a custom solution. In this example we will add an additional column to be returned in the report.

Step-by-step Guide

1. Follow the [Process for Modifying the "General Report" in NRC](#) up to the uploading section.
2. Open the `.\Program Files (x86)\NetIQ\DRA\DRA Reporting\DRAResult.XML` file and locate the section for the "User Accounts Expiring Within a Week" report. Extract a copy to the custom report file.
3. Next, update the SQL database query return the extra column.

Edit SQL Query

Make the following changes to the SQL query:


Add `[USERS].[DeskLocation] AS [Desk Location]`,

4. Save the report file. Follow the final step in [Process for Modifying the "General Report" in NRC](#) uploading section.

Modify an Existing Report, SQL where clause

Scope

The NetIQ Reporting Center (NRC), provides a set of standard reports that can be run to retrieve data from the DRA SQL reporting database. Additionally, NRC allows for the modification and addition of reports to provide a custom solution. In this example we will modify the existing "User Accounts Expiring Within a Week" with a new custom date range of 30 days to convert the report to "User Accounts Expiring Within 30 Days".



Step-by-step Guide

1. Follow the Process for [Modifying the "General Report" in NRC](#) up to the uploading section.
2. Open report file and locate the section for the "User Accounts Expiring Within a Week" report and extract a copy to the custom report file. First we will update the contextual information for the report.

DRA.Report.XML - Notepad

```

<NQREPORT ID="DATA REPORTS.USERACCOUNTSEXPIRINGWITHINAWEEK" Type="DRAReporting"
    Description="This report displays the user accounts that are expiring within a week." Title="User Accounts
    Expiring Within a Week">
    <PARAMETERS>
        <STRING Category="Account Status" Description="Account Status" Title="Account Status" ID="AccountDisabled">
            <Item>All Accounts</Item>
            <Item>Enabled</Item>
            <Item>Disabled</Item>
            <Value>All Accounts</Value>
        </STRING>
    </PARAMETERS>
    <CONTEXTS>
        <CONTEXT TYPE="NetIQ.Reporting.Context.ConnectionContext,NRCLib" Name="DRA Reporting DataSource" ID="1"/>
        <CONTEXT TYPE="NetIQ.Reporting.Context.UDContext,NRCLib" ID="1" ContextType="DRAUDCONTEXT" Title="Managed Domains and
        OUs" SelectAll="yes"/>
        <CONTEXT TYPE="NetIQ.Reporting.Context.QueryLimitContext,NRCLib" ID="1" Title="Data Query Limit" Count="1000"
        ShowWarning="false"/>
    </CONTEXTS>
    <STANDARD ViewMode="table" NumericFormat="F0" QueryLimit="1000">
        <QUERY TYPE="NetIQ.Reporting.Context.NRCSQLQuery,NRCLib">
            <Template>
                SET QUOTED_IDENTIFIER OFF
                SELECT DISTINCT {QueryLimitContext[1].Value}
                ACCOUNTS.[NAME] as [Name],
                ACCOUNTS.SAMACCOUNTNAME as [Sam AccountName],
            </Template>
        </QUERY>
    </STANDARD>
</NQREPORT>

```

Edit Report

Make the following changes to the report definition:

- Change the entry for "Description" to **Description="This report displays the user accounts that are expiring within 30 days"**
- Change the entry to "Title" to **Title="User Accounts Expiring Within 30 Days"**

3. Next, update the SQL database query to look for accounts expiring in 30 days instead of 7 days.

DRA.Report.XML - Notepad

```

<CASE
WHEN [USERS].[RASPERMISSION] &gt; 7 THEN 1
ELSE 0
END AS [User Dialin Privilege],
[ACCOUNTS].[DISTINGUISHEDNAME] as [Distinguished Name],
ACCOUNTS.DESCRIPTION as [Description],
[USERS].[WHENCREATED] AS [Time Created],
[USERS].[WHENCHANGED] AS [Time Modified]
FROM
dbo.GET_GUID_TABLE ("{UDCONTEXT[1].NODEID},{UDCONTEXT[1].FLDRID}")
INNER JOIN ACCOUNTS WITH (NOLOCK) ON GET_GUID_TABLE.GUID = ACCOUNTS.PARENT_GUID
INNER JOIN CONTEXTTABLEFOROU on GET_GUID_TABLE.GUID = CONTEXTTABLEFOROU.UDOBJECT
INNER JOIN USERS ON ACCOUNTS.OBJECTGUID = [USERS].OBJECTGUID
INNER JOIN DOMAINS ON DOMAINS.DOMAIN_ID = [USERS].DOMAIN_ID
WHERE ((DOMAINS.MCSISMANAGED = 1) OR (DOMAINS.MCSREQSUBSETMANAGED = 1 AND CONTEXTTABLEFOROU.ISMANAGED &gt; 2))
AND [USERS].[ACCOUNTEXPIRES] &gt;= GetDate() AND [USERS].[ACCOUNTEXPIRES] <= DATEADD(day, 30, GetDate())
AND((1 = CASE when {Parameter[AccountDisabled]} = 'All Accounts' then 1 ELSE 0 END ) OR
(USERS.ACOUNTDISABLED = (case when {Parameter[AccountDisabled]} = 'Enabled' then 0 when {Parameter
[AccountDisabled]} = 'Disabled' then 1 end ) )
)

SET QUOTED_IDENTIFIER ON
</Template>
</QUERY>
<COLUMN Source="Time Created" Format="g"/>
<COLUMN Source="Time Modified" Format="g"/>
</STANDARD>

```

Edit SQL Query

Make the following changes to the SQL query:

Change **DATEADD(day, 7, GetDate())** to **DATEADD(day, 30, GetDate())**

4. Save the file. Follow the final step in [Process for Modifying the "General Report" in NRC uplo ading section.](#)

Process for Modifying the "General Report" in NRC

Scope

NetIQ Reporting Center (NRC), provides a set of standard reports that can be run to retrieve data from the SQL database. Once the report has been created, it can be sorted and/or filtered as needed. Additionally, NRC allows for the modification and addition of new reports to provide a custom solution. This procedure will cover the general mechanics of making custom reports.

Step-by-step Guide

1. Back up XML files.
2. Edit the Checkin batch file to appear like the example.

Checkin Batch File

```
@echo off
REM Checkin DRA NRC Reports
if Exist "%~d0\Program Files\NetIQ\Reporting Center\Utilities\XmlCheckIn.exe" goto Checkin
echo """%~d0\Program Files\NetIQ\Reporting Center\Utilities\XmlCheckIn.exe not found, check
path of NetIQ Reporting Center"
Goto End

:Checkin
"%~d0\Program Files\NetIQ\Reporting Center\Utilities\XmlCheckIn.exe" /S localhost
"%~d0\Program Files (x86)\NetIQ\DRA\DRA Reporting

\DRA.DataSourceType.XML"
"%~d0\Program Files\NetIQ\Reporting Center\Utilities\XmlCheckIn.exe" /S localhost
"%~d0\Program Files (x86)\NetIQ\DRA\DRA Reporting

\DRA.UDContext.xml"
"%~d0\Program Files\NetIQ\Reporting Center\Utilities\XmlCheckIn.exe" /S localhost
"%~d0\Program Files (x86)\NetIQ\DRA\DRA Reporting

\DRA.ExtDataSource.XML"
"%~d0\Program Files\NetIQ\Reporting Center\Utilities\XmlCheckIn.exe" /S localhost
"%~d0\Program Files (x86)\NetIQ\DRA\DRA Reporting

\DRAResult.XML"
if not exist "%~d0\Program Files (x86)\NetIQ\DRA\DRA Reporting\DRAResult.XML"
goto SkipToReport
```

```

"%~d0\Program Files\NetIQ\Reporting Center\Utilities\XmlCheckIn.exe" /S localhost
"%~d0\Program Files (x86)\NetIQ\DRA\DRA Reporting

\DRA.Custom.UDContext.xml"

:SkipToReport
if not exist "%~d0\Program Files (x86)\NetIQ\DRA\DRA Reporting\DRACustom.Reports.XML" goto
End
"%~d0\Program Files\NetIQ\Reporting Center\Utilities\XmlCheckIn.exe" /S localhost
"%~d0\Program Files (x86)\NetIQ\DRA\DRA Reporting

\DRACustom.Reports.XML"

```

3. Create a DRA.Custom.Report.xml file in the directory if one does not exist.

```

<?xml version="1.0" encoding="utf-8"?>
<REPORTSETS>
    <REPORTSET FOLDER="DRA Management Reports\Summarized Activity Reports">
        </REPORTSET>
    <REPORTSET FOLDER="DRA Management Reports\Activity Trends">
        </REPORTSET>
    <REPORTSET FOLDER="DRA Management Reports\Exchange Configuration Reports">
        </REPORTSET>
    <REPORTSET FOLDER="DRA Management Reports\DRAConfigurations Reports">
        </REPORTSET>
    <REPORTSET FOLDER="DRA Management Reports\AD Resources Reports">
        </REPORTSET>
    <REPORTSET FOLDER="DRA Management Reports\Office 365 Reports">
        </REPORTSET>
    <REPORTSET FOLDER="DRA Management Reports\AD Summary Reports">
        </REPORTSET>
    <REPORTSET FOLDER="DRA Management Reports\DRAResources Reports">
        </REPORTSET>
</REPORTSETS>

```

4. Edit the DRA.Custom.Report.xml file with the report to be customized.

{QueryLimitContext[x].Value} - Text like this may be in the query. It is a API (like TOP 1000) that will be filled in by NRC when the query is sent to SQL.

> or < - Html rules apply in this XML file. These will be converted to > (greater than) and < (less than) prior being sent to SQL.

UDContext - User description context used for working with data from the controls. Each UDContext used must have a unique id. Please don't modify the existing controls. See the section below for a list of existing contexts.

5. Upload report definitions by running Checkin batch file.

Working with Custom Virtual Attributes

Scope

DRA allows the extension of objects (User, Contact, Computer, Group, Organizational Unit, & Dynamic Distribution Group) through the use of custom virtual attributes. These attributes may be created and managed with custom interface pages, collected from AD LDS to a SQL database, and displayed as part of a report. This walkthrough gives end to end guidance on the process of how to setup, manage, collect, and report custom virtual attributes.

For this example, the Keystone Steel Company needs a new custom virtual attribute, DeskLocation. It will be added as a string attribute for the USER object. We will start by defining the new virtual attribute, creating a custom interface, and then adding data.

Step-by-Step Guide

1. Create new virtual attribute DeskLocation.
2. Assign DeskLocation to USER.
3. Add User page to collect data
4. Assign data to DeskLocation.
5. Setup AD Collector to collect data.
6. Follow the [Process for Modifying the "General Report" in NRC](#) up to the section titled "Uploading the Updated Master Report File".
7. Follow the [Modify an Existing Report, SQL column addition](#) to add new DeskLocation column in report.

Database Schema


- [DRA Reporting Database](#)
 - [Visual Layout](#)
 - [Tables](#)
 - [Stored Procedures](#)
 - [Functions](#)

DRA Reporting Database

This section includes a visual layout, tables, stored procedures, and functions of the database.



Visual Layout

The DRA Reporting Database stores the data collected by the DRA collectors.



LICENSES	IMPORT_CATEGORY_GROUPS	PASSWORD_POLICIES	MP_UPDATES	LAST_COLLECTED_ATTRIBUTES
<ul style="list-style-type: none"> ↳ LICENSE_ID DisplayName FinalDay Flags GraceExpirationDate GracePeriodLength LicenseType LicensedBy NumberofAgents NumberofComputers NumberofMailboxes NumberofOperations NumberofRecords NumberofServers NumberofUsers NumberofWorkstations OverdraftValue OverdraftPercentage PackageComment PackageId PackageName PackageVersion SupportsAllOperations TrialExpirationDate TrialPeriodLength TrialStartDate CompanyName CompanyId SerialNumber Comment sNodeLockOn sShared sUpgradeOnly 	<ul style="list-style-type: none"> ↳ CATEGORY_GROUP_ID CATEGORY_GROUP 	<ul style="list-style-type: none"> EnablePasswordPolicy MaxChars MaxConsecutiveAlpha MaxDigits MaxLowerChars MaxPasswordLength MaxSameCharRepeat MaxSpecial MaxUpperChars MinChars MinDigits MinLowerChars MinPasswordLength MinSpecial MinUpperChars 	<ul style="list-style-type: none"> recodNumber ClientName AccountExpires AccountDisabled Lock NetWare UserName Comment FullName PasswordModify PasswordReq PasswordChange PasswordExpire 	<ul style="list-style-type: none"> Name DataType ClassId DomainId IsVirtual
POLICIES	OPTIONTABLE	MODPROPS	INTERNAL_GuidNameMap	MMSERVERS
<ul style="list-style-type: none"> ↳ POLICIES_ID McsClass MclsContainer McsName McsNameValue McsParent McsPath McsSchema Comment Description LastModified Enabled 	<ul style="list-style-type: none"> DOMAINID OPTIONNAME VALUE 	<ul style="list-style-type: none"> samAccountName RecordNumber LoginScript WzProfilePath WzHomeDir LoginWorkstations LoginHours RasPermissions ModifiedProperties 	<ul style="list-style-type: none"> ObjectGUID ObjectName ObjectType 	<ul style="list-style-type: none"> ServerName Mode PrimaryName AccessAccount AccessTime AccessStatus LastSuccess
SERVICE_STATUS				
				<ul style="list-style-type: none"> STATE_TVFE_ID STATE_TVFE

TGA			
TGA_ID			
ASSISTANT_ADMIN			
CREATION_TIME			
DESCRIPTION			
END_TIME			
START_TIME			
STATE			
STATUS_MESSAGE			
TARGET_GROUP			
NAME			
ENABLED			
SHARE_TYPE			
SHARE_TYPE_ID			
SHARE_TYPE			
TRUSTED_DOMAINS			
DOMAIN_NAME			
TRUSTED_DOMAIN_NAME			
TRUSTED_DOMAIN_DNS_NAME			
TRIGGERS			
TRIGGER_ID			
McsNameValue			
McsName			
McsPath			
McsClass			
McsParent			
McsSchema			
Description			
Action			
CmdLineArgs			
ErrorMsg_General			
ErrorMsg_Undc			
Path			
UndoCmdLineArgs			
UndoPath			
Type			
Enabled			
RULES			
RULE_ID			
McsNameValue			
RuleSpecification			
ACTIVEVIEW_ID			
McsClass			
MclsContainer			
McsName			
McsParent			
McsPath			
McsSchema			
description			
includeFlag			
nestedFlag			
sourceFlag			
targetFlag			
RuleSpecification_MatchString			
RuleSpecification_MatchConta...			
RuleSpecification_Name			
RuleSpecification_MatchPrinte...			
RuleSpecification_Comment			
RuleSpecification_ResourceType			
RuleSpecification_AccountFilter			
RuleSpecification_Recursive			
RuleSpecification_SelectBase			
RuleSpecification_SelectMemb...			
RuleSpecification_Power			
RuleSpecification_Description			
RuleSpecification_OriginalNam...			
ASSISTANT_ADMIN_ID			
RuleSpecification_Rule1			
RuleSpecification_Rule2			
RuleSpecification_SelectSysObj			
RuleSpecification_ResourceMai...			
RuleSpecification_ResourceMai...			
RuleSpecification_Version			
RuleSpecification_containerBas...			
RuleSpecification_containerIsF...			
RuleSpecification_containerMa...			
RuleSpecification_containerMa...			
RuleSpecification_containerMa...			
RuleSpecification_containerPro...			
RuleSpecification_containerRe...			
RuleSpecification_containerSe...			
RuleSpecification_domainMat...			
RuleSpecification_domainProp...			
RuleSpecification_groupMemb...			
RuleSpecification_groupRecurs...			
RuleSpecification_groupTypeFi...			
RuleSpecification_memberIsFo...			
RuleSpecification_normalFilter			
RuleSpecification_objectMatch...			
RuleSpecification_objectMatch...			
RuleSpecification_objectMatch...			
RuleSpecification_objectMustB...			
RuleSpecification_objectProper...			
RuleSpecification_objectSelect...			
RULE_ACC_BIND_ID			



USERS	RECYCLE_BIN	USER_MAILBOXES	USER_INTERFACE_EXTENTIONS	TRUSTING_DOMAINS	ROLE_POWER_BINDINGS
objectGuid cn Domain_Id objectClass usnCreated usnChanged HasMailbox MailboxVersion nameMD3 accountExpires name memberOf manager managedObjects mail mailNickname homeDrive homeDirectory givenName displayName whenCreated description canonicalName AccountDisabled AccountLockedOut AccountNotDelegated DontRequirePwAuth EncryptTextPasswordAllowed FpwEnabled HomeDirectoryRequired nterDomainTrustAccount NormalAccount NormalAccount PasswordDoesNtExpire PasswordExpired PasswordNotRequired Script ServerTrustAccount SmartCardRequired TempDuplicateAccount TrustedForDelegation TrustedForAuthenticateForDelete UseDesKeyOnly UserAccountControl WorkstationTrustAccount whenChanged userPrincipalName sAMAccountName sAMAccountType RasPermission RasPhoneNumber WbsAllcow.ogn WbsBrokerTmcicutSettings WbsDeviceClientDefaultPrinter WbsDeviceClientDrives WbsDeviceClientPrinters WbsHomeDir WbsHomeDirDrive WbsInherInitialProgram WbsInitialProgram WbsModemCallbackPhoneNumber WbsModemCallbackSettings WbsProfilePath WbsReconnectSettings WbsRemoteHomeDir WbsShadowingSettings WbsTimeoutSettingsConnectOn WbsTimeoutSettingsDisconnectOn WbsTimeoutSettingSingle WbsWorkingDirectory ou objectCategory lastLogonTimestamp MailBoxType	RecycleBinId McDaysInRecycleBin McClass samAccountName Domain McPath McfriendlyName McOrgParentOfRecycledObj	IMPORT_TIME MinIMB_DistinguishedName MinIMB_FirstName MinIMB_Initials MinIMB_LastName MinIMB_DisplayName MinIMB_Alias MinIMB_HomeServer MinIMB_HomeSite MinIMB_NsgOutgoingLimit MinIMB_NsgIncomingLimit MinIMB_UserIdDefaults MinIMB_StoreLimitWarn MinIMB_StoreLimitProhibit MinIMB_ProhibitSendReceive MinIMB_DeliveryMechanism MinIMB_DeletedItemRetention MinIMB_RID McPath Domain	McName McPath Status	DCMAIN_NAME TRUSTING_DOMAIN_NAME TRUSTING_DOMAIN_DNS_NAME	ID POWER_NAME

VA_CLASS
VIRTUAL_ATTRIBUTE_ID
CLASS_ID

VIRTUAL_ATTRIBUTE
VIRTUAL_ATTRIBUTE_ID
McNameValue
VarType
McClass
IsMultiValued
DisplayName
Description
Enabled

DomainsIDToName
ID
Name

ADDYNAMICGROUPMEMBER
groupGUID
memberGUID
isWriteList

CUSTOM_TOOLS
CUSTOM_TOOL_ID
Name
SupportedObjects
Status
Description
Comment
AppLocation
AppParameters
AppDir
AppWinInterface
AppCloseOnExit
MenuStructure

ADVANCE_QUERIES
ADVANCE_QUERIES_ID
QueryName
QueryAuthor
QueryBasicContainer
QueryColumnsList
QueryScope
VAQueryFilter
QueryFilter
isPublic
QueryColumnsTyps

COMPUTERS
objectGUID
cn
Domain_dn
objectClass
usnCreated
usnChanged
whenCreated
whenChanged
manager
managedObjects
managedBy
mail
givenName
displayName
comment
adminDisplayName
adminDescription
sAMAccountName
AccountDisabled
AccountLockedOut
AccountNotDelegated
DontRequirePreauth
EncryptedTextPasswordAllowed
FppmEnabled
HomeDirectoryRequired
InterDomainTrustAccount
NormalAccount
PasswordDoesNotExpire
PasswordExpired
PasswordNotRequired
Script
ServerTrustAccount
SmartCardRequired
TempDuplicateAccount
TrustedForDelegation
TrustedToAuthenticateForDelete
UseDesKeyOnly
UserAccountControl
WorkstationTrustAccount
objectCategory
operatingSystemVersion
operatingSystemServicePack
operatingSystemHotfix
operatingSystem
objectVersion
name
memberOf
description

ACTIVEVIEWS
ACT_VIEW_ID
McNameValue
Comment
McParent
McPath
McSchema
Description
NumAssocDeputies
NumRules
McName
Builtin
Enabled

ACCOUNT_RULE_BINDING_STATUS
FILE_ACC_BIND_ID
HAS_MORE_OBJECTS

ASSISTANT_ADMIN_ROLE_BINDINGS
ID
ASSOC_ID
AV_ID


ASSISTANT_ADMIN_POWER_BINDINGS
ID
ASSOC_ID
AV_ID

DEVICES	DEVICE_STATUS	CONTACTS	CONTEXTTABLEFOROU	CLONE_EXCEPTION	ASSISTANTADMINS
SYSTEM_ID DOMAIN_ID DisplayName ExitCode ServiceSpecificExitCode StartMode State SystemName	STATUS_TYPE_ID STATUS_TYPE	objectGuid cn Domain_Id usrCreated objectClass usrChanged whenCreated whenChanged description comment ou name manager managedObjects mailNickname mail displayName objectCategory distinguishedName CONTACTDNCH-KSJM	UDLEVEL UDOBJECT UDOBJECTPARENT UDOBJECTNAME UDOBJECTUINAME UDOOUTPUT UDICON UDSORTORDER DOMAINID PROCESSFLAG ISMANAGED	CLONE_EXCEPTION_ID Name Description DisplayName	ASSISTANT_ADMIN_ID McNameValue Comment McName McParent McPath McSchema Description NumAssocActiveViews NumRules
ADDYNAMICGROUP	ACTIVEVIEW_ROLE_BINDINGS	ACTIVITYSUMMARY	ACCOUNT_RULE_BINDINGS	ACTIVEVIEW_ACCOUNTS	AD_ATTRIBUTE_SIZE
group6UID memberFilterGUID rootMemberGUID ldapFilter includeChildContainers	ID ASSOC_D	Date utccatetime Hour Action ObjectType EventType ReturnCode EventDescriptor OperationName dnServerGUID WhatDomain WhoUserGUID SourceObjectName SourceObjectType SourceObjectGUID SourceObjectContainerName SourceObjectContainerType SourceObjectContainerGUID TargetObjectName TargetObjectType TargetObjectGUID TargetObjectContainerName TargetObjectContainerType TargetObjectContainerGUID DestinationObjectName DestinationObjectType DestinationObjectGUID DestinationObjectContainerName DestinationObjectContainerType OperationCategory IsAutomatic EventCategoryText OperationType	RULE_ACC_BIND_ID objectGuid	ACTIVEVIEW_ID objectGuid	Attribute_Name Attribute_Size
DOMAIN_CONTROLLERS	ActionContextList	CLASS	ACCOUNTS	DomainContextList	DEVICE_STARTUP
DOMCTRL_ID Domain_Id McNameValue McPath	Action	CLASS_ID CLASS SCHEMA_CLASS	objectGuid DOMAIN_ID usrCreated usrChanged CLASS_ID Parent_GUID Parent_DN Internal_ProcessNextINCR distinguishedName samAccountName name description RID Internal_VA_Process	DomainName	STARTUP_TYPE_ID STARTUP_TYPE

ExchangeMgtToolsInstalled
ID
Name
EXCHANGE_PROXY
Domain
ProxyFqdnString
EVENTLOGS
SYSTEM_ID
DOMAIN_ID
CreationDate
LogfileName
CSimpleName
FileSize
MaxFileSize
OverwriteOutdated
OverWritePolicy
EXCHANGE_CONFIG
EXCHANGE_CONFIG_ID
McsClass
McsPath
McsSchema
AliasNamingConvention
AliasNaming_ConventionFlags
DistinguishedNameNamingConvention
DistinguishedNameNamingConventionFlags
DisplayNamesNamingConvention
DisplayNamesNamingConventionFlags
EnableExch2KSupportPolicy
EnableExch2007SupportPolicy
EnforceAliasNamingConvention
EnforceExch2KAliasNamingConvention
Exch2KAliasNamingConvention
Exch2KAliasNamingConventionFlags
IsExch2KEnabled
IsExch2KSupportInstalled
IsExch2007Enabled
IsExch2007SupportInstalled
MailboxPolicyDuringCreate
MailboxPolicyDuringDelete
MailboxPolicyDuringUpdate
ExchangeToolsInstalled
IsExch2010Enabled
IsExch2010SupportInstalled
IsExch2013Enabled
IsExch2013SupportInstalled

EVENT_TYPE
EVENT_TYPE_ID
EVENT_TYPE
DynamicDistributionGroups
objectGuid
cn
display_name
distinguishedName
domain_id
objectClass
mail
MailboxVersion
mailNickname
msExchDynamicDLBaseDN
msExchDynamicDlFilter
msExchQueryFilter
msExchQueryFilterMetadata
name
objectCategory
usnCreated
usnChanged
whenChanged
whenCreated
DOMCTRL_TYPE
DOMCTRL_TYPE_ID
DOMCTRL_TYPE
ExchangeVersion_Name
ID
Name
GROUPS
objectGuid
groupType
Domain_Id
objectClass
usnCreated
usnChanged
whenCreated
whenChanged
description
displayName
name
sAMAccountName
objectCategory
memberOf
cn
member
managedObjects
managedBy
mail
mailNickname
lastKnownParent
isDynamicGroup
groupAttributes

GuidNameMap
ObjectGUID
ObjectName
ObjectType
GroupMembershipByDN
GroupDomainId
GroupGUID
MemberDN
MemberDomainId
EXPORT_ERRORS
EXPORT_SEQ
CLASS
CODE
MESSAGE
EA
Group_Membership
Group_GUID
Member_GUID
DOMAIN_ID
IMPORT_CATEGORIES
CATEGORY_ID
CATEGORY
CATEGORY_GROUP_ID
SEQUENCE



Tables

Table Name	Column Name	DATA_TYPE	Max Character Length	Is Nullable
ACCOUNT_RULE_BINDING_STATUS	HAS_MORE_OBJECTS	bit		Yes
	RULE_ACC_BIND_ID	int		No
ACCOUNT_RULE_BINDINGS	objectGuid	uniqueidentifier		Yes
	RULE_ACC_BIND_ID	int		No
ACCOUNTS	CLASS_ID	int		Yes
	description	nvarchar	1024	Yes
	distinguishedName	nvarchar	-1	Yes
	DOMAIN_ID	int		Yes
	Internal_ProcessNextINCR	bit		Yes
	Internal_VA_Process	bit		Yes
	name	nvarchar	255	Yes
	objectGuid	uniqueidentifier		No
	Parent_DN	nvarchar	-1	Yes
	Parent_GUID	uniqueidentifier		Yes
ActionContextList	RID	int		Yes
	samAccountName	nvarchar	255	Yes
	usnChanged	bigint		Yes
	usnCreated	bigint		Yes
	Action	nvarchar	50	No
	ACTIVEVIEW_ACCOUNTS	ACTIVEVIEW_ID	int	No
	objectGuid	uniqueidentifier		Yes
ACTIVEVIEW_ASSISTANT_ADMIN_BINDINGS	ASSOC_ID	int		Yes
	ID	int		No
ACTIVEVIEW_ROLE_BINDINGS	ASSOC_ID	int		Yes
	ID	int		No
ACTIVEVIEWS	ACTIVEVIEW_ID	int		No
	BuiltIn	int		Yes
	Comment	ntext	1073741823	Yes
	Description	ntext	1073741823	Yes
	Enabled	bit		Yes
	McsName	nvarchar	255	Yes
	McsNameValue	nvarchar	255	Yes
	McsParent	nvarchar	255	Yes
	McsPath	ntext	1073741823	Yes
	McsSchema	ntext	1073741823	Yes
	NumAssocDeputies	int		Yes

Table Name	Column Name	DATA_TYPE	Max Character Length	Is Nullable
	NumRules	int		Yes
ActivityCounts	Action	nvarchar	64	Yes
	Count	int		Yes
	Date	datetime		Yes
	DestinationObjectContainerName	nvarchar	255	Yes
	DestinationObjectContainerType	nvarchar	100	Yes
	draServerGUID	uniqueidentifier		Yes
	EventType	int		Yes
	Hour	int		Yes
	ObjectType	nvarchar	50	Yes
	OperationName	nvarchar	100	Yes
ActivitySummary	TargetObjectContainerName	nvarchar	255	Yes
	TargetObjectContainerType	nvarchar	100	Yes
	WhatDomain	nvarchar	250	Yes
	WhoUserGUID	uniqueidentifier		Yes
	Action	nvarchar	64	Yes
	Date	datetime		Yes
	DestinationObjectContainerGUID	uniqueidentifier		Yes
	DestinationObjectContainerName	nvarchar	255	Yes
	DestinationObjectContainerType	nvarchar	100	Yes
	DestinationObjectGUID	uniqueidentifier		Yes
EventLog	DestinationObjectName	nvarchar	255	Yes
	DestinationObjectType	nvarchar	255	Yes
	draServerGUID	uniqueidentifier		Yes
	EventCategoryText	nvarchar	50	Yes
	EventDescription	nvarchar	512	Yes
	EventType	int		Yes
	Hour	int		Yes
	IsAutomatic	bit		Yes
	ObjectType	nvarchar	50	Yes
	OperationCategory	nvarchar	50	Yes
EventLogDetail	OperationName	nvarchar	100	Yes
	OperationType	int		Yes
	ReturnValue	int		Yes
	SourceObjectContainerGUID	uniqueidentifier		Yes
	SourceObjectContainerName	nvarchar	255	Yes
	SourceObjectContainerType	nvarchar	100	Yes
	SourceObjectGUID	uniqueidentifier		Yes

Table Name	Column Name	DATA_TYPE	Max Character Length	Is Nullable
	SourceObjectName	nvarchar	255	Yes
	SourceObjectType	nvarchar	255	Yes
	TargetObjectContainerGUID	uniqueidentifier		Yes
	TargetObjectContainerName	nvarchar	255	Yes
	TargetObjectContainerType	nvarchar	100	Yes
	TargetObjectGUID	uniqueidentifier		Yes
	TargetObjectName	nvarchar	255	Yes
	TargetObjectType	nvarchar	100	Yes
	utcdatetime	datetime		Yes
	WhatDomain	nvarchar	250	Yes
	WhoUserGUID	uniqueidentifier		Yes
AD_Attribute_size	Attribute_Name	nvarchar	255	Yes
	Attribute_Size	int		Yes
ADDynamicGroup	groupGUID	uniqueidentifier		No
	includeChildContainers	bit		No
	ldapFilter	ntext	1073741823	No
	memberFilterGUID	uniqueidentifier		No
	rootMemberGUID	uniqueidentifier		No
ADDynamicGroupMember	groupGUID	uniqueidentifier		No
	isWhiteList	bit		No
	memberGUID	uniqueidentifier		No
ADVANCE_QUERIES	ADVANCE_QUERIES_ID	int		No
	isPublic	nvarchar	20	Yes
	QueryAuthor	nvarchar	-1	Yes
	QueryBaseContainer	nvarchar	-1	Yes
	QueryColumnsList	nvarchar	-1	Yes
	QueryColumnType	int		Yes
	QueryFilter	nvarchar	-1	Yes
	QueryName	nvarchar	-1	Yes
	QueryScope	int		Yes
	VAQueryFilter	nvarchar	-1	No
ASSISTANT_ADMIN_POWER_BINDINGS	ASSOC_ID	int		Yes
	AV_ID	int		Yes
	ID	int		No
ASSISTANT_ADMIN_ROLE_BINDINGS	ASSOC_ID	int		Yes
	AV_ID	int		Yes
	ID	int		No
ASSISTANT_admins	ASSISTANT_ADMIN_ID	int		No

Table Name	Column Name	DATA_TYPE	Max Character Length	Is Nullable
	Comment	ntext	1073741823	Yes
	Description	ntext	1073741823	Yes
	McsName	nvarchar	255	Yes
	McsNameValue	nvarchar	255	Yes
	McsParent	nvarchar	255	Yes
	McsPath	ntext	1073741823	Yes
	McsSchema	ntext	1073741823	Yes
	NumAssocActiveViews	int		Yes
	NumRules	int		Yes
CLASS	CLASS	nvarchar	-1	No
	CLASS_ID	int		No
	SCHEMA_CLASS	nvarchar	-1	No
CLONE_EXCEPTION	CLONE_EXCEPTION_ID	int		No
	Description	nvarchar	2048	Yes
	DisplayName	nvarchar	512	Yes
	Name	nvarchar	50	Yes
COMPUTERS	AccountDisabled	int		Yes
	AccountLockedOut	int		Yes
	AccountNotDelegated	int		Yes
	adminDescription	nvarchar	2048	Yes
	adminDisplayName	nvarchar	512	Yes
	cn	nvarchar	128	Yes
	comment	nvarchar	2048	Yes
	description	nvarchar	2048	Yes
	displayName	nvarchar	512	Yes
	Domain_Id	int		Yes
	DontRequirePreauth	int		Yes
	EncryptedTextPasswordAllowed	int		Yes
	FpnwEnabled	int		Yes
	givenName	nvarchar	128	Yes
	HomeDirectoryRequired	int		Yes
	InterDomainTrustAccount	int		Yes
	mail	nvarchar	512	Yes
	managedBy	nvarchar	-1	Yes
	managedObjects	nvarchar	-1	Yes
	manager	nvarchar	-1	Yes
	memberOf	nvarchar	-1	Yes
	name	nvarchar	255	Yes

Table Name	Column Name	DATA_TYPE	Max Character Length	Is Nullable
	NormalAccount	int		Yes
	objectCategory	nvarchar	-1	Yes
	objectClass	nvarchar	-1	Yes
	objectGuid	uniqueidentifier		No
	objectVersion	int		Yes
	operatingSystem	nvarchar	-1	Yes
	operatingSystemHotfix	nvarchar	-1	Yes
	operatingSystemServicePack	nvarchar	-1	Yes
	operatingSystemVersion	nvarchar	-1	Yes
	PasswordDoesNotExpire	int		Yes
	PasswordExpired	int		Yes
	PasswordNotRequired	int		Yes
	sAMAccountName	nvarchar	255	Yes
	Script	int		Yes
	ServerTrustAccount	int		Yes
	SmartCardRequired	int		Yes
	TempDuplicateAccount	int		Yes
	TrustedForDelegation	int		Yes
	TrustedToAuthenticateForDelegation	int		Yes
	UseDesKeyOnly	int		Yes
	UserAccountControl	int		Yes
	usnChanged	bignint		Yes
	usnCreated	bignint		Yes
	whenChanged	datetime		Yes
	whenCreated	datetime		Yes
	WorkstationTrustAccount	int		Yes
CONTACTS	cn	nvarchar	128	Yes
	comment	nvarchar	2048	Yes
	CONTACTDNCHKSUM	int		Yes
	description	nvarchar	2048	Yes
	displayName	nvarchar	512	Yes
	distinguishedName	nvarchar	-1	Yes
	Domain_Id	int		Yes
	mail	nvarchar	512	Yes
	mailNickname	nvarchar	-1	Yes
	managedObjects	nvarchar	-1	Yes
	manager	nvarchar	-1	Yes
	name	nvarchar	255	Yes

Table Name	Column Name	DATA_TYPE	Max Character Length	Is Nullable
	objectCategory	nvarchar	-1	Yes
	objectClass	nvarchar	-1	Yes
	objectGuid	uniqueidentifier		No
	ou	nvarchar	128	Yes
	usnChanged	bigint		Yes
	usnCreated	bigint		Yes
	whenChanged	datetime		Yes
	whenCreated	datetime		Yes
CONTEXTTABLEFOROU	DOMAINID	int		Yes
	ISMANAGED	int		Yes
	PROCESSFLAG	bit		Yes
	UDICON	int		Yes
	UDLEVEL	int		Yes
	UDOBJECT	nvarchar	-1	Yes
	UDOBJECTNAME	nvarchar	-1	Yes
	UDOBJECTPARENT	nvarchar	-1	Yes
	UDOBJECTUINAME	nvarchar	-1	Yes
	UDOUTPUT	nvarchar	-1	Yes
	UDSORTORDER	int		Yes
CUSTOM_TOOLS	AppCloseOnExit	bit		Yes
	AppDir	nvarchar	-1	Yes
	AppLocation	nvarchar	-1	Yes
	AppParameters	nvarchar	-1	Yes
	AppWinInterface	bit		Yes
	Comment	ntext	1073741823	Yes
	CUSTOM_TOOL_ID	int		No
	Description	ntext	1073741823	Yes
	MenuStructure	nvarchar	-1	Yes
	Name	nvarchar	-1	Yes
	Status	nvarchar	10	Yes
	SupportedObjects	nvarchar	120	Yes
DEVICE_STARTUP	STARTUP_TYPE	nvarchar	10	Yes
	STARTUP_TYPE_ID	smallint		No
DEVICE_STATUS	STATUS_TYPE	nvarchar	20	Yes
	STATUS_TYPE_ID	int		No
DEVICES	DisplayName	nvarchar	255	Yes
	DOMAIN_ID	int		No
	ExitCode	int		Yes

Table Name	Column Name	DATA_TYPE	Max Character Length	Is Nullable
	ServiceSpecificExitCode	int		Yes
	StartMode	int		Yes
	State	int		Yes
	SYSTEM_ID	uniqueidentifier		No
	SystemName	nvarchar	255	Yes
DOMAIN_CONTROLLERS	Domain_Id	int		Yes
	DOMCTRL_ID	int		No
	McsNameValue	nvarchar	255	Yes
	McsPath	nvarchar	255	Yes
DomainContextList	DomainName	nvarchar	250	No
DOMAINS	Description	ntext	1073741823	Yes
	DOMAIN_ID	int		No
	McsClass	nvarchar	255	Yes
	McsDnsFlatName	nvarchar	255	Yes
	McsDnsName	nvarchar	255	Yes
	McsExists	bit		Yes
	McsIsManaged	bit		Yes
	McsIsNativeMode	bit		Yes
	McsIsRecycleBinTurnedOn	bit		Yes
	McsName	nvarchar	255	No
	McsPath	nvarchar	255	Yes
	McsReqManaged	bit		Yes
	McsReqSubsetManaged	bit		Yes
	McsTypeDom	int		Yes
	Name	nvarchar	255	Yes
DomainsIDToName	ID	int		No
	Name	nvarchar	50	Yes
DOMCTRL_TYPE	DOMCTRL_TYPE	nvarchar	50	Yes
	DOMCTRL_TYPE_ID	int		No
draview_AA_GuidNameMap	ObjectGUID	uniqueidentifier		No
	ObjectName	nvarchar	255	No
draview_Activeview_Accounts	ACCOUNT_DESCRIPTION	nvarchar	1024	Yes
	ACCOUNT_FULLNAME	nvarchar	255	Yes
	ACCOUNT_NAME	nvarchar	255	Yes
	ACCOUNT_TYPE	nvarchar	-1	No
	ACTIVEVIEW_NAME	nvarchar	255	Yes
	DOMAIN_NAME	nvarchar	255	Yes
	ISMANAGED	int		Yes

Table Name	Column Name	DATA_TYPE	Max Character Length	Is Nullable
	McsIsManaged	bit		Yes
	MCSREQSUBSETMANAGED	bit		Yes
draview_Server_GuidNameMap	ObjectGUID	uniqueidentifier		No
	ObjectName	nvarchar	255	No
DynamicDistributionGroups	cn	nvarchar	512	Yes
	displayName	nvarchar	512	Yes
	distinguishedName	nvarchar	-1	Yes
	Domain_Id	int		Yes
	mail	nvarchar	512	Yes
	MailboxVersion	int		Yes
	mailNickname	nvarchar	-1	Yes
	msExchDynamicDLBaseDN	nvarchar	-1	Yes
	msExchDynamicDLFilter	nvarchar	-1	Yes
	msExchQueryFilter	nvarchar	-1	Yes
	msExchQueryFilterMetadata	nvarchar	-1	Yes
	name	nvarchar	512	Yes
	objectCategory	nvarchar	-1	Yes
	objectClass	nvarchar	-1	Yes
	objectGuid	uniqueidentifier		No
	usnChanged	bigint		Yes
	usnCreated	bigint		Yes
	whenChanged	datetime		Yes
	whenCreated	datetime		Yes
EVENT_TYPE	EVENT_TYPE	nvarchar	15	Yes
	EVENT_TYPE_ID	int		No
EVENTLOG_WRAP_TYPE	OverWritePolicy	nvarchar	50	Yes
	OverWritePolicy_ID	smallint		No
EVENTLOGS	CreationDate	datetime		Yes
	CSName	nvarchar	-1	Yes
	DOMAIN_ID	int		No
	FileSize	int		Yes
	LogfileName	nvarchar	-1	Yes
	MaxFileSize	int		Yes
	OverwriteOutDated	int		Yes
	OverWritePolicy	int		Yes
	SYSTEM_ID	uniqueidentifier		No
EXCHANGE_CONFIG	AliasNamingConvention	nvarchar	255	Yes
	AliasNamingConventionFlags	int		Yes

Table Name	Column Name	DATA_TYPE	Max Character Length	Is Nullable
	DirNameNamingConvention	nvarchar	255	Yes
	DirNameNamingConventionFlags	int		Yes
	DisplayNameNamingConvention	nvarchar	255	Yes
	DisplayNameNamingConventionFlags	int		Yes
	EnableExch2007SupportPolicy	int		Yes
	EnableExch2KSupportPolicy	int		Yes
	EnforceAliasNamingConvention	int		Yes
	EnforceExch2KAliasNamingConvention	int		Yes
	Exch2KAliasNamingConvention	nvarchar	255	Yes
	Exch2KAliasNamingConventionFlags	int		Yes
	EXCHANGE_CONFIG_ID	int		No
	ExchangeToolsInstalled	int		Yes
	IsExch2007Enabled	int		Yes
	IsExch2007SupportInstalled	int		Yes
	IsExch2010Enabled	int		Yes
	IsExch2010SupportInstalled	int		Yes
	IsExch2013Enabled	int		Yes
	IsExch2013SupportInstalled	int		Yes
	IsExch2KEnabled	int		Yes
	IsExch2KSupportInstalled	int		Yes
	MailboxPolicyDuringCreate	int		Yes
	MailboxPolicyDuringDelete	int		Yes
	MailboxPolicyDuringUpdate	int		Yes
	McsClass	nvarchar	255	Yes
	McsPath	nvarchar	255	Yes
	McsSchema	ntext	1073741823	Yes
EXCHANGE_PROXY	Domain	nvarchar	150	Yes
	ProxyFormatString	nvarchar	-1	Yes
ExchangeMgtToolsInstalled	ID	int		Yes
	Name	nvarchar	50	Yes
ExchangeVersion_Name	ID	int		Yes
	Name	nvarchar	50	Yes
EXPORT_ERRORS	CLASS	nvarchar	30	Yes
	CODE	int		Yes
	EA	nvarchar	255	Yes
	EXPORT_SEQ	int		No
	MESSAGE	ntext	1073741823	Yes

Table Name	Column Name	DATA_TYPE	Max Character Length	Is Nullable
Group_Membership	DOMAIN_ID	int		Yes
	Group_GUID	uniqueidentifier		No
	Member_GUID	uniqueidentifier		Yes
GroupMembershipByDN	GroupDomainId	int		No
	GroupGUID	uniqueidentifier		No
	MemberDN	nvarchar	-1	No
	MemberDomainId	int		No
GROUPS	cn	nvarchar	128	Yes
	description	nvarchar	2048	Yes
	displayName	nvarchar	512	Yes
	Domain_Id	int		Yes
	groupAttributes	int		Yes
	groupType	int		Yes
	isDynamicGroup	bit		Yes
	lastKnownParent	nvarchar	-1	Yes
	mail	nvarchar	512	Yes
	mailNickname	nvarchar	-1	Yes
	managedBy	nvarchar	-1	Yes
	managedObjects	nvarchar	-1	Yes
	member	nvarchar	-1	Yes
	memberOf	nvarchar	-1	Yes
	name	nvarchar	255	Yes
GuidNameMap	objectCategory	nvarchar	-1	Yes
	objectClass	nvarchar	-1	Yes
	objectGuid	uniqueidentifier		No
	sAMAccountName	nvarchar	255	Yes
	usnChanged	bigint		Yes
	usnCreated	bigint		Yes
	whenChanged	datetime		Yes
	whenCreated	datetime		Yes
	ObjectGUID	uniqueidentifier		No
	ObjectName	nvarchar	255	No
IMPORT_CATEGORIES	ObjectType	nvarchar	50	Yes
	CATEGORY	nvarchar	30	Yes
	CATEGORY_GROUP_ID	smallint		Yes
	CATEGORY_ID	smallint		No
IMPORT_CATEGORY_GROUPS	SEQUENCE	smallint		Yes
	CATEGORY_GROUP	nvarchar	50	Yes

Table Name	Column Name	DATA_TYPE	Max Character Length	Is Nullable
	CATEGORY_GROUP_ID	smallint		No
IMPORT_ERRORS	CLASS	nvarchar	200	Yes
	CODE	int		Yes
	EA	ntext	1073741823	Yes
	IMPORT_SEQ	int		No
	MESSAGE	ntext	1073741823	Yes
INTERNAL_ActivitySummary	Action	nvarchar	64	Yes
	Date	datetime		Yes
	DestinationObjectContainerGUID	uniqueidentifier		Yes
	DestinationObjectContainerName	nvarchar	255	Yes
	DestinationObjectContainerType	nvarchar	100	Yes
	DestinationObjectGUID	uniqueidentifier		Yes
	DestinationObjectName	nvarchar	255	Yes
	DestinationObjectType	nvarchar	255	Yes
	draServerGUID	uniqueidentifier		Yes
	EventCategoryText	nvarchar	50	Yes
	EventDescription	nvarchar	512	Yes
	EventType	int		Yes
	Hour	int		Yes
	IsAutomatic	bit		Yes
	ObjectType	nvarchar	50	Yes
	OperationCategory	nvarchar	50	Yes
	OperationName	nvarchar	100	Yes
	OperationType	int		Yes
	ReturnCode	int		Yes
	SourceObjectContainerGUID	uniqueidentifier		Yes
	SourceObjectContainerName	nvarchar	255	Yes
	SourceObjectContainerType	nvarchar	100	Yes
	SourceObjectGUID	uniqueidentifier		Yes
	SourceObjectName	nvarchar	255	Yes
	SourceObjectType	nvarchar	255	Yes
	TargetObjectContainerGUID	uniqueidentifier		Yes
	TargetObjectContainerName	nvarchar	255	Yes
	TargetObjectContainerType	nvarchar	100	Yes
	TargetObjectGUID	uniqueidentifier		Yes
	TargetObjectName	nvarchar	255	Yes
	TargetObjectType	nvarchar	100	Yes
	utcdatetime	datetime		Yes

Table Name	Column Name	DATA_TYPE	Max Character Length	Is Nullable
	WhatDomain	nvarchar	250	Yes
	where_draserver_name	nvarchar	255	Yes
	Who_Name	nvarchar	255	Yes
	WhoUserGUID	uniqueidentifier		Yes
INTERNAL_GuidNameMap	ObjectGUID	uniqueidentifier		No
	ObjectName	nvarchar	255	No
	ObjectType	nvarchar	50	Yes
INTERNAL_ProcessMovedorRenamedContainers	containerDN	nvarchar	-1	No
	containerGUID	uniqueidentifier		No
	DOMAIN_ID	int		Yes
	IsProcessed	bit		Yes
InternalDomainInfo	DCName	nvarchar	255	Yes
	DOMAIN_ID	int		No
	DomainName	nvarchar	-1	No
	highestADUSN	bigint		Yes
	highestDeletedUSN	bigint		Yes
	highestVAUSN	bigint		Yes
	InvocationId	binary	16	Yes
	IsRequiredContextTbFullCollection	bit		Yes
	NumOfComputers	bigint		Yes
	NumOfContacts	bigint		Yes
	NumOfGroups	bigint		Yes
	NumOfOus	bigint		Yes
	NumOfTrustedDomains	bigint		Yes
	NumOfTrustingDomains	bigint		Yes
	NumOfUsers	bigint		Yes
InternalOUStructure	CNTAINER_GUID	uniqueidentifier		No
	DOMAIN_ID	int		No
JOB	Execution_window_size	int		Yes
	Job_Id	int		No
	Job_Name	nvarchar	50	Yes
JOBS_HISTORY	Collector_Info	nvarchar	400	No
	DRA_Server_Name	nvarchar	400	No
	End_Time	datetime		Yes
	Job_Id	int		No
	Message	ntext	1073741823	Yes
	Result_Id	int		Yes

Table Name	Column Name	DATA_TYPE	Max Character Length	Is Nullable
	Start_Time	datetime		No
LAST_COLLECTED_ATTRIBUTES	ClassId	int		No
	DataType	int		No
	DomainId	int		No
	IsVirtual	bit		No
	Name	nvarchar	50	No
LICENSES	Comment	ntext	1073741823	Yes
	CompanyId	nvarchar	255	Yes
	CompanyName	nvarchar	255	Yes
	DisplayName	nvarchar	150	Yes
	FinalDay	datetime		Yes
	Flags	int		Yes
	GraceExpirationDate	datetime		Yes
	GracePeriodLength	int		Yes
	IsNodeLockOn	bit		Yes
	IsShared	bit		Yes
	IsUpgradeOnly	bit		Yes
	LICENSE_ID	int		No
	LicensedBy	int		Yes
	LicenseType	int		Yes
	NumberOfAgents	int		Yes
	NumberOfComputers	int		Yes
	NumberOfMailboxes	int		Yes
	NumberOfOperations	int		Yes
	NumberOfRecords	int		Yes
	NumberOfServers	int		Yes
	NumberOfUsers	int		Yes
	NumberOfWorkstations	int		Yes
	OverdraftPercentage	int		Yes
	OverdraftValue	int		Yes
	PackageComment	nvarchar	255	Yes
	PackageId	int		Yes
	PackageName	nvarchar	255	Yes
	PackageVersion	nvarchar	50	Yes
	SerialNumber	nvarchar	255	Yes
	SupportsAllOperations	bit		Yes
	TrialExpirationDate	datetime		Yes
	TrialPeriodLength	int		Yes

Table Name	Column Name	DATA_TYPE	Max Character Length	Is Nullable
	TrialStartDate	datetime		Yes
MANAGED_DOMAINS	ID	int		No
	McsDnsName	nvarchar	255	Yes
ManagedContainers	DOMAIN_ID	int		Yes
	objectGUID	uniqueidentifier		Yes
MEMBERS	GROUP_ID	int		Yes
	MEMBER_ID	int		Yes
MMCACHE	CacheName	nvarchar	255	No
	PrimaryName	nvarchar	255	Yes
	RefreshStatus	int		Yes
	RefreshTime	datetime		Yes
	SecondaryName	nvarchar	255	No
MMREPLICATION	CacheName	nvarchar	255	No
	LastSuccess	datetime		Yes
	PrimaryName	nvarchar	255	Yes
	ReplicationStatus	int		Yes
	ReplicationTime	datetime		Yes
	SecondaryName	nvarchar	255	No
MMSERVERS	AccessAccount	nvarchar	255	Yes
	AccessStatus	int		Yes
	AccessTime	datetime		Yes
	LastSuccess	datetime		Yes
	Mode	int		Yes
	PrimaryName	nvarchar	255	Yes
	ServerName	nvarchar	255	No
MODPROPS	LoginHours	int		Yes
	LoginScript	int		Yes
	LoginWorkstations	int		Yes
	ModifiedProperties	ntext	1073741823	Yes
	RasPermissions	int		Yes
	RecordNumber	int		No
	samAccountName	nvarchar	255	Yes
	WtsHomeDir	int		Yes
	WtsProfilePath	int		Yes
MP_UPDATES	AccountDisabled	bit		No
	AccountExpires	bit		No
	ClientName	nvarchar	255	No
	Comment	bit		No

Table Name	Column Name	DATA_TYPE	Max Character Length	Is Nullable
	FullName	bit		No
	Lock	bit		No
	NetWare	bit		No
	PasswordChange	bit		No
	PasswordExpire	bit		No
	PasswordModify	bit		No
	PasswordReq	bit		No
	recordNumber	int		Yes
	UserName	bit		No
ObjectTypeContextList	ObjectType	nvarchar	50	Yes
OPTIONSTABLE	DOMAINID	int		Yes
	OPTIONNAME	nvarchar	255	Yes
	VALUE	nvarchar	-1	Yes
OUS	cn	nvarchar	128	Yes
	co	nvarchar	256	Yes
	description	nvarchar	2048	Yes
	displayName	nvarchar	512	Yes
	distinguishedName	nvarchar	-1	Yes
	DNCHKSUM	int		Yes
	Domain_Id	int		Yes
	lastKnownParent	nvarchar	-1	Yes
	managedBy	nvarchar	-1	Yes
	managedObjects	nvarchar	-1	Yes
	memberOf	nvarchar	-1	Yes
	name	nvarchar	255	Yes
	objectCategory	nvarchar	-1	Yes
	objectClass	nvarchar	-1	Yes
	objectGuid	uniqueidentifier		No
	objectVersion	int		Yes
	ou	nvarchar	128	Yes
	usnChanged	bigint		Yes
	usnCreated	bigint		Yes
	whenChanged	datetime		Yes
	whenCreated	datetime		Yes
PASSWORD_POLICIES	EnablePasswordPolicy	bit		Yes
	MaxChars	int		Yes
	MaxConsecutiveAlpha	int		Yes
	MaxDigits	int		Yes

Table Name	Column Name	DATA_TYPE	Max Character Length	Is Nullable
	MaxLowerChars	int		Yes
	MaxPasswordLength	int		Yes
	MaxSameCharRepeat	int		Yes
	MaxSpecial	int		Yes
	MaxUpperChars	int		Yes
	MinChars	int		Yes
	MinDigits	int		Yes
	MinLowerChars	int		Yes
	MinPasswordLength	int		Yes
	MinSpecial	int		Yes
POLICIES	MinUpperChars	int		Yes
	Comment	ntext	1073741823	Yes
	Description	ntext	1073741823	Yes
	Enabled	bit		No
	LastModified	nvarchar	50	Yes
	McsClass	nvarchar	255	Yes
	McsIsContainer	bit		No
	McsName	nvarchar	255	Yes
	McsNameValue	nvarchar	255	No
	McsParent	nvarchar	255	Yes
	McsPath	ntext	1073741823	Yes
	McsSchema	ntext	1073741823	Yes
	POLICIES_ID	int		No
POWERS	Comment	ntext	1073741823	Yes
	depth	int		Yes
	description	ntext	1073741823	Yes
	Path	nvarchar	255	Yes
	Power	nvarchar	255	No
	POWER_ID	int		No
PRINTER_STATUS	PRINTER_STATUS	nvarchar	50	Yes
	PRINTER_STATUS_ID	int		Yes
PRINTERS	attributes	int		Yes
	AveragePagesPerMinute	int		Yes
	comment	ntext	1073741823	Yes
	defaultPriority	int		Yes
	DOMAIN_ID	int		No
	driverName	nvarchar	255	Yes
	JobCountSinceLastReset	int		Yes

Table Name	Column Name	DATA_TYPE	Max Character Length	Is Nullable
	location	nvarchar	255	Yes
	Name	nvarchar	-1	Yes
	parameters	nvarchar	255	Yes
	PortName	nvarchar	255	Yes
	PrinterState	int		Yes
	printProcessor	nvarchar	255	Yes
	priority	int		Yes
	SeparatorFile	nvarchar	255	Yes
	startTime	datetime		Yes
	SYSTEM_ID	uniqueidentifier		No
RECYCLE_BIN	systemname	nvarchar	-1	Yes
	untilTime	datetime		Yes
	Domain	nvarchar	255	Yes
	McsClass	nvarchar	255	Yes
	McsDaysInRecycleBin	int		Yes
	McsFriendlyName	nvarchar	255	Yes
	McsOrigParentOfRecycledObj	ntext	1073741823	Yes
	McsPath	nvarchar	255	Yes
	RecycleBinID	int		No
	samAccountName	nvarchar	255	Yes
RECYCLEBIN	CLASS_ID	int		No
	description	nvarchar	1024	Yes
	DOMAIN_ID	int		No
	New_Name	nvarchar	255	Yes
	objectGUID	uniqueidentifier		No
	Orig_DN	nvarchar	-1	Yes
	Orig_Name	nvarchar	255	Yes
	Orig_ParentDN	nvarchar	-1	Yes
	Orig_ParentGUID	uniqueidentifier		Yes
	sAMAccountName	nvarchar	255	Yes
Resource_Computer	uSNChanged	bigint		No
	whenDeleted	datetime		Yes
	DOMAIN_ID	int		No
	Name	nvarchar	-1	No
RESOURCE_TYPE	objectGUID	uniqueidentifier		No
	RESOURCE	nvarchar	10	Yes
RESULT	Result	nvarchar	50	Yes
	Result_Id	int		No

Table Name	Column Name	DATA_TYPE	Max Character Length	Is Nullable
ROLE_BINDINGS	ASSOC_ID	int		Yes
	ID	int		Yes
ROLE_POWER_BINDINGS	ID	int		Yes
	POWER_NAME	nvarchar	255	Yes
ROLES	Comment	ntext	1073741823	Yes
	Creator	nvarchar	255	Yes
	Description	ntext	1073741823	Yes
	Flags	int		Yes
	LastModified	nvarchar	50	Yes
	McsClass	nvarchar	255	Yes
	McsIsContainer	bit		Yes
	McsName	nvarchar	255	Yes
	McsNameValue	nvarchar	255	Yes
	McsParent	nvarchar	255	Yes
	McsPath	ntext	1073741823	Yes
	McsSchema	ntext	1073741823	Yes
	NumAssocDTB	int		Yes
	NumLocalPowers	int		Yes
	NumNestedRoles	int		Yes
	NumOwnerRoles	int		Yes
	ROLES_ID	int		No
RULES	ACTIVEVIEW_ID	nvarchar	150	Yes
	ASSISTANT_ADMIN_ID	nvarchar	150	Yes
	description	ntext	1073741823	Yes
	includeFlag	bit		Yes
	McsClass	nvarchar	255	Yes
	McsIsContainer	bit		Yes
	McsName	nvarchar	255	Yes
	McsNameValue	nvarchar	255	Yes
	McsParent	nvarchar	255	Yes
	McsPath	ntext	1073741823	Yes
	McsSchema	ntext	1073741823	Yes
	nestedFlag	bit		Yes
	RULE_ACC_BIND_ID	int		Yes
	RULE_ID	int		No
	RuleSpecification	nvarchar	255	Yes
	RuleSpecification_AccountFilter	nvarchar	255	Yes
	RuleSpecification_Comment	nvarchar	255	Yes

Table Name	Column Name	DATA_TYPE	Max Character Length	Is Nullable
	RuleSpecification_containerBaseFilter	int		Yes
	RuleSpecification_containerIsFocus	bit		Yes
	RuleSpecification_containerMatchAny	bit		Yes
	RuleSpecification_containerMatchMethod	int		Yes
	RuleSpecification_containerMatchValue	nvarchar	255	Yes
	RuleSpecification_containerProperty	nvarchar	255	Yes
	RuleSpecification_containerRecursive	bit		Yes
	RuleSpecification_containerSelectBase	bit		Yes
	RuleSpecification_Description	nvarchar	255	Yes
	RuleSpecification_domainMatchValue	nvarchar	255	Yes
	RuleSpecification_domainProperty	nvarchar	255	Yes
	RuleSpecification_groupMemberFilter	int		Yes
	RuleSpecification_groupRecursive	bit		Yes
	RuleSpecification_groupTypeFilter	int		Yes
	RuleSpecification_MatchContainerString	nvarchar	255	Yes
	RuleSpecification_MatchPrinterString	nvarchar	255	Yes
	RuleSpecification_MatchString	nvarchar	255	Yes
	RuleSpecification_memberIsFocus	bit		Yes
	RuleSpecification_Name	nvarchar	255	Yes
	RuleSpecification_normalFilter	int		Yes
	RuleSpecification_objectMatchAny	bit		Yes
	RuleSpecification_objectMatchMethod	int		Yes
	RuleSpecification_objectMatchvalue	nvarchar	255	Yes
	RuleSpecification_objectMustBeInContainer	bit		Yes
	RuleSpecification_objectProperty	nvarchar	255	Yes
	RuleSpecification_objectSelectBase	bit		Yes
	RuleSpecification_OriginalNameOfObject	nvarchar	255	Yes
	RuleSpecification_Power	nvarchar	255	Yes
	RuleSpecification_Recursive	nvarchar	255	Yes
	RuleSpecification_ResourceMailboxType	nvarchar	255	Yes
	RuleSpecification_ResourceMailboxSelect	int		Yes
	RuleSpecification_ResourceType	nvarchar	255	Yes
	RuleSpecification_Rule1	nvarchar	255	Yes
	RuleSpecification_Rule2	nvarchar	255	Yes

Table Name	Column Name	DATA_TYPE	Max Character Length	Is Nullable
RUNNING_JOBS	RuleSpecification_SelectBase	nvarchar	255	Yes
	RuleSpecification_SelectMembers	nvarchar	255	Yes
	RuleSpecification_SelectSysObj	bit		Yes
	RuleSpecification_Version	int		Yes
	sourceFlag	bit		Yes
	targetFlag	bit		Yes
SCOPES	Collector_Info	nvarchar	400	No
	DRA_Server_Name	nvarchar	400	Yes
	Job_Id	int		No
	Last_Update	datetime		Yes
	Start_Time	datetime		Yes
SERVICE_STARTUP	Status	nvarchar	20	Yes
	McsPolicy	nvarchar	255	No
	McsPolicyPath	nvarchar	255	No
	McsRule	nvarchar	255	No
	McsScopeType	nvarchar	255	No
SERVICE_STATUS	SCOPE_ID	int		No
	STARTMODE_TYPE	nvarchar	20	Yes
	STARTMODE_TYPE_ID	int		Yes
	STATE_TYPE	nvarchar	20	No
SERVICES	STATE_TYPE_ID	int		No
	Caption	nvarchar	512	Yes
	Checkpoint	int		Yes
	Description	ntext	1073741823	Yes
SYSTEM_ID	DesktopInteract	bit		Yes
	DisplayName	nvarchar	255	Yes
	DOMAIN_ID	int		No
	ErrorControl	nvarchar	255	Yes
	ExitCode	int		Yes
	PathName	nvarchar	255	Yes
	ServiceSpecificExitCode	bigint		Yes
	ServiceType	nvarchar	150	Yes
	StartMode	int		Yes
	StartName	nvarchar	255	Yes
SystemName	State	int		Yes
	SYSTEM_ID	uniqueidentifier		No
	SystemName	nvarchar	255	Yes
	WaitHint	int		Yes

Table Name	Column Name	DATA_TYPE	Max Character Length	Is Nullable
SHARE_TYPE	SHARE_TYPE	nvarchar	50	Yes
	SHARE_TYPE_ID	bigint		Yes
SHARES	AllowMaximum	bit		Yes
	Computer	nvarchar	255	Yes
SHARES	Description	nvarchar	-1	Yes
	DOMAIN_ID	int		No
SHARES	MaximumAllowed	int		Yes
	Name	nvarchar	-1	Yes
SHARES	Path	nvarchar	-1	Yes
	SYSTEM_ID	uniqueidentifier		No
SHARES	Type	bigint		Yes
STATUS	CollectionStatus	nvarchar	255	Yes
	CollectionType	nvarchar	255	Yes
STATUS	Domain	nvarchar	255	No
	EndTime	datetime		Yes
STATUS	id	int		No
	StartTime	datetime		Yes
sysdiagrams	definition	varbinary	-1	Yes
	diagram_id	int		No
sysdiagrams	name	nvarchar	128	No
	principal_id	int		No
sysdiagrams	version	int		Yes
TGA	ASSISTANT_ADMIN	nvarchar	255	Yes
	CREATION_TIME	datetime		Yes
TGA	DESCRIPTION	ntext	1073741823	Yes
	ENABLED	int		Yes
TGA	END_TIME	datetime		Yes
	NAME	nvarchar	255	Yes
TGA	START_TIME	datetime		Yes
	STATE	int		Yes
TGA	STATUS_MESSAGE	ntext	1073741823	Yes
	TARGET_GROUP	nvarchar	-1	Yes
TGA	TGA_ID	int		No
TGA_GROUP_MEMBERSHIP	TGA_ID	int		No
	USER_PATH	nvarchar	-1	Yes
TRIGGER_SCOPES	McsNameValue	nvarchar	255	Yes
	OperationScope	nvarchar	255	Yes
TRIGGER_SCOPES	TRIGGER_ID	int		Yes

Table Name	Column Name	DATA_TYPE	Max Character Length	Is Nullable
	TriggerType	nvarchar	255	Yes
TRIGGERS	Action	nvarchar	255	Yes
	CmdLineArgs	nvarchar	255	Yes
	Description	ntext	1073741823	Yes
	Enabled	int		Yes
	ErrorMsg_General	ntext	1073741823	Yes
	ErrorMsg_Undo	ntext	1073741823	Yes
	McsClass	nvarchar	255	Yes
	McsName	nvarchar	255	Yes
	McsNameValue	nvarchar	255	Yes
	McsParent	nvarchar	255	Yes
	McsPath	ntext	1073741823	Yes
	McsSchema	ntext	1073741823	Yes
	Path	nvarchar	255	Yes
	TRIGGER_ID	int		No
	Type	int		Yes
	UndoCmdLineArgs	nvarchar	255	Yes
	UndoPath	nvarchar	255	Yes
TRUSTED_DOMAINS	DOMAIN_NAME	nvarchar	255	Yes
	TRUSTED_DOMAIN_DNS_NAME	nvarchar	255	Yes
	TRUSTED_DOMAIN_NAME	nvarchar	255	Yes
TRUSTING_DOMAINS	DOMAIN_NAME	nvarchar	255	Yes
	TRUSTING_DOMAIN_DNS_NAME	nvarchar	255	Yes
	TRUSTING_DOMAIN_NAME	nvarchar	255	Yes
USER_INTERFACE_EXTENTIONS	McsName	nvarchar	100	No
	McsPath	nvarchar	-1	Yes
	Status	nvarchar	50	Yes
USER_MAILBOXES	Domain	nvarchar	255	Yes
	IMPORT_TIME	real		Yes
	McsPath	ntext	1073741823	Yes
	MiniMB_Alias	nvarchar	68	Yes
	MiniMB_DeletedItemRetention	bit		No
	MiniMB_DeliveryMechanism	nvarchar	50	Yes
	MiniMB_DisplayName	nvarchar	255	Yes
	MiniMB_DistinguishedName	nvarchar	255	Yes
	MiniMB_FirstName	nvarchar	68	Yes
	MiniMB_HomeServer	nvarchar	50	Yes
	MiniMB_HomeSite	nvarchar	50	Yes

Table Name	Column Name	DATA_TYPE	Max Character Length	Is Nullable
	MiniMB_Initials	nvarchar	8	Yes
	MiniMB_LastName	nvarchar	68	Yes
	MiniMB_MsgIncomingLimit	int		Yes
	MiniMB_MsgOutgoingLimit	int		Yes
	MiniMB_ProhibitSendReceive	int		Yes
	MiniMB RID	int		Yes
	MiniMB_StoreLimitProhibit	int		Yes
	MiniMB_StoreLimitWarn	int		Yes
	MiniMB_UsesSDefaults	bit		No
USERS	AccountDisabled	int		Yes
	accountExpires	datetime		Yes
	AccountLockedOut	int		Yes
	AccountNotDelegated	int		Yes
	canonicalName	nvarchar	-1	Yes
	cn	nvarchar	128	Yes
	description	nvarchar	2048	Yes
	displayName	nvarchar	512	Yes
	Domain_Id	int		Yes
	DontRequirePreauth	int		Yes
	EncryptedTextPasswordAllowed	int		Yes
	FpnwEnabled	int		Yes
	givenName	nvarchar	128	Yes
	HasMailbox	int		Yes
	homeDirectory	nvarchar	-1	Yes
	HomeDirectoryRequired	int		Yes
	homeDrive	nvarchar	-1	Yes
	homeMDB	nvarchar	-1	Yes
	InterDomainTrustAccount	int		Yes
	lastLogonTimestamp	datetime		Yes
	mail	nvarchar	512	Yes
	MailBoxType	int		Yes
	MailboxVersion	int		Yes
	mailNickname	nvarchar	-1	Yes
	managedObjects	nvarchar	-1	Yes
	manager	nvarchar	-1	Yes
	memberOf	nvarchar	-1	Yes
	name	nvarchar	255	Yes
	NormalAccount	int		Yes

Table Name	Column Name	DATA_TYPE	Max Character Length	Is Nullable
	objectCategory	nvarchar	-1	Yes
	objectClass	nvarchar	-1	Yes
	objectGuid	uniqueidentifier		No
	ou	nvarchar	128	Yes
	PasswordDoesNotExpire	int		Yes
	PasswordExpired	int		Yes
	PasswordNotRequired	int		Yes
	RasPermission	int		Yes
	RasPhonenumber	nvarchar	-1	Yes
	sAMAccountName	nvarchar	255	Yes
	sAMAccountType	int		Yes
	Script	int		Yes
	ServerTrustAccount	int		Yes
	SmartCardRequired	int		Yes
	TempDuplicateAccount	int		Yes
	TrustedForDelegation	int		Yes
	TrustedToAuthenticateForDelegation	int		Yes
	UseDesKeyOnly	int		Yes
	UserAccountControl	int		Yes
	userPrincipalName	nvarchar	-1	Yes
	usnChanged	bigint		Yes
	usnCreated	bigint		Yes
	whenChanged	datetime		Yes
	whenCreated	datetime		Yes
	WorkstationTrustAccount	int		Yes
	WtsAllowLogon	int		Yes
	WtsBrokenTimeoutSettings	int		Yes
	WtsDeviceClientDefaultPrinter	int		Yes
	WtsDeviceClientDrives	int		Yes
	WtsDeviceClientPrinters	int		Yes
	WtsHomeDir	nvarchar	-1	Yes
	WtsHomeDirDrive	nvarchar	-1	Yes
	WtsInheritInitialProgram	int		Yes
	WtsInitialProgram	nvarchar	-1	Yes
	WtsModemCallbackPhoneNumber	nvarchar	-1	Yes
	WtsModemCallbackSettings	int		Yes
	WtsProfilePath	nvarchar	-1	Yes
	WtsReconnectSettings	int		Yes

Table Name	Column Name	DATA_TYPE	Max Character Length	Is Nullable
	WtsRemoteHomeDir	int		Yes
	WtsShadowingSettings	int		Yes
	WtsTimeoutSettingsConnections	int		Yes
	WtsTimeoutSettingsDisconnections	int		Yes
	WtsTimeoutSettingsIdle	int		Yes
	WtsWorkingDirectory	nvarchar	-1	Yes
VA_CLASS	CLASS_ID	int		No
	VIRTUAL_ATTRIBUTE_ID	int		No
VIRTUAL_ATTRIBUTE	Description	ntext	1073741823	Yes
	DisplayName	nvarchar	50	Yes
	Enabled	nchar	10	Yes
	IsMultiValued	nvarchar	20	Yes
	McsClass	nvarchar	-1	Yes
	McsNameValue	nvarchar	50	Yes
	VarType	nchar	10	Yes
	VIRTUAL_ATTRIBUTE_ID	int		No

Stored Procedures

Stored Procedure name	Parameter name	Parameter Data Type	Parameter Max Bytes	Is Output Parameter	Is Nullable
CONSTRUCTOUTREE	@OUOBJECTGUID	nvarchar	-1	No	Yes
	@START	int		No	Yes
	@UDLEVEL	int		No	Yes
	@VDOMAINID	int		No	Yes
CONSTRUCTOUTREEINCR	@DomainID	int		No	Yes
DRA_Accounts_HasGuid	@vObjectGUID	uniqueidentifier		No	Yes
DRA_AccountsAndOUs_MergeDomain	@vClassTypeid	int		No	Yes
	@vDomainDN	nvarchar	-1	No	Yes
	@vDomainGUID	uniqueidentifier		No	Yes
	@vDomainId	int		No	Yes
DRA_ADD_DomainToAccountsAndOUs	@vClassType	int		No	Yes
	@vDomainDN	nvarchar	-1	No	Yes
	@vDomainGUID	uniqueidentifier		No	Yes
	@vDomainId	int		No	Yes
DRA_ADDJOB	@vCollector_Info	nvarchar	800	No	Yes
	@vDRA_Server_Name	nvarchar	800	No	Yes
	@vJob_Id	int		No	Yes
	@vLast_Update	datetime		No	Yes
	@vStart_Time	datetime		No	Yes
	@vStatus	nvarchar	40	No	Yes
DRA_ADDMovedorRenamedContainer	@vcontainerDN	nvarchar	-1	No	Yes
	@vcontainerGUID	uniqueidentifier		No	Yes
	@vDomainID	int		No	Yes
DRA_AddToRecycleBin	@vClassType	int		No	Yes
	@vdescription	nvarchar	510	No	Yes
	@vDomainId	int		No	Yes
	@vName	nvarchar	510	No	Yes
	@vObjectGuid	uniqueidentifier		No	Yes
	@vsamAccountName	nvarchar	510	No	Yes
	@vUSNChanged	bigint		No	Yes
DRA_CLEARALLADTABLES	@vDomainId	int		No	Yes
DRA_ClearAllResourceCollectorTables	@vDomainId	int		No	Yes
DRA_ClearGroupMembershipForAGroup	@vGroupGUID	uniqueidentifier		No	Yes

Stored Procedure name	Parameter name	Parameter Data Type	Parameter Max Bytes	Is Output Parameter	Is Nullable
DRA_ClearRunningJobs	@DRAServerName	char		No	Yes
	@JobId	int		No	Yes
DRA_ContactGetGUID	@vContactDN	nvarchar	-1	No	Yes
	@vContactName	nvarchar	256	No	Yes
	@vDomainID	int		No	Yes
	@vObjectGUID	uniqueidentifier		Yes	Yes
DRA_DELETE_LAST_COLLECTION_VA_ATTRIBUTES	@vClassId	int		No	Yes
	@vDomainId	int		No	Yes
DRA_DeleteContainersFromInternalTable	@vdomainID	int		No	Yes
DRA_DeleteDynamicGroup	@vGroupGUID	uniqueidentifier		No	Yes
DRA_DeleteDynamicGroupMember	@vGroupGUID	uniqueidentifier		No	Yes
	@vMemberGUID	uniqueidentifier		No	Yes
DRA_DeleteFromGroupMembership	@vmemberGUID	uniqueidentifier		No	Yes
DRA_DeleteFromRecycleBin	@vObjectGuid	uniqueidentifier		No	Yes
DRA_DeleteLastCollectedAttributes	@vClassId	int		No	Yes
	@vDomainId	int		No	Yes
DRA_DeleteManagedContainers	@vDomainId	int		No	Yes
DRA_DOMAINS_HasDomainId	@vDomainId	int		No	Yes
DRA_GetandUpdateParentGUID	@vObjectGUID	uniqueidentifier		No	Yes
DRA_GetClassInfo	@vId	int		Yes	Yes
	@vName	nvarchar	-1	No	Yes
DRA_GetContainerChildren	@vParentGUID	uniqueidentifier		No	Yes
DRA_GetContainersToProcess	@vDomainId	int		No	Yes
DRA_GetDomainId	@vDomainId	int		Yes	Yes
	@vDomainName	nvarchar	-1	No	Yes
DRA_GetDomainIdFromDomains	@vDomainId	int		Yes	Yes
	@vDomainName	nvarchar	-1	No	Yes
DRA_GetDomainInfo	@vId	int		Yes	Yes
	@vName	nvarchar	-1	No	Yes
DRA_GetDuplicateAVRuleInfo	@RuleAccountBindId	int		Yes	Yes
	@RuleId	int		No	Yes
	@RuleSpecification	varchar		No	Yes

Stored Procedure name	Parameter name	Parameter Data Type	Parameter Max Bytes	Is Output Parameter	Is Nullable
DRA_GetGroups	@vClassType	int		No	Yes
	@vDomainID	int		No	Yes
	@vLastADUSN	bigint		No	Yes
DRA_GetINCRObjects	@vDomainID	int		No	Yes
	@vLastUSN	bigint		No	Yes
DRA_GetInvocationIdDCName	@vDomainID	int		No	Yes
	@vprevDCName	nvarchar	2048	Yes	Yes
	@vprevInvocationId	binary		Yes	Yes
DRA_GetJobExecutionWindowSize	@vExecutionWindowSize	int		Yes	Yes
	@vJob_Id	int		No	Yes
DRA_GetJobID	@vJob_Id	int		Yes	Yes
	@vJob_Name	nvarchar	100	No	Yes
DRA_GetLastUSN	@ADUSN	bigint		Yes	Yes
	@DeletedUSN	bigint		Yes	Yes
	@vAUSN	bigint		Yes	Yes
	@vDomainName	nvarchar	-1	No	Yes
DRA_GetManagedContainersInfo	@vDomainId	int		No	Yes
DRA_GetObjectsOldDN	@vContainerDN	nvarchar	-1	Yes	Yes
	@vObjectGUID	uniqueidentifier		No	Yes
DRA_GetObjectsToProcessForVA	@vClassTypes	nvarchar	800	No	Yes
	@vDomainID	int		No	Yes
DRA_GetOptionValue	@vDomainId	int		No	Yes
	@vOptionName	nvarchar	-1	No	Yes
	@vValue	nvarchar	-1	Yes	Yes
DRA_GetPreviousINCRGroups	@vDomainID	int		No	Yes
DRA_GetRequiredContextFullCollectionInfo	@vDomainId	int		No	Yes
	@vIsRequiredContextTbFullCollection	bit		Yes	Yes
DRA_GetRunningJobsDetails	@inJobName	nvarchar	100	No	Yes
DRA_GetStartTimeOfJob	@inCollectorInfo	nvarchar	800	No	Yes
	@inJob_Id	int		No	Yes
	@inServerName	nvarchar	800	No	Yes
	@outStartTime	datetime		Yes	Yes
DRA_InsertDynamicGroup	@vGroupGUID	uniqueidentifier		No	Yes

Stored Procedure name	Parameter name	Parameter Data Type	Parameter Max Bytes	Is Output Parameter	Is Nullable
	@vIncludeChildContainers	bit		No	Yes
	@vLdapFilter	nvarchar	-1	No	Yes
	@vMemberFilterGUID	uniqueidentifier		No	Yes
	@vRootMemberGUID	uniqueidentifier		No	Yes
DRA_InsertDynamicGroupMember	@vGroupGUID	uniqueidentifier		No	Yes
	@vIsWhiteList	bit		No	Yes
	@vMemberGUID	uniqueidentifier		No	Yes
DRA_InsertInInternalOUStructure	@vDomainId	int		No	Yes
	@vObjectGUID	uniqueidentifier		No	Yes
DRA_InsertMemberByDN	@vGroupDomainID	int		No	Yes
	@vGroupGUID	uniqueidentifier		No	Yes
	@vMemberDN	nvarchar	-1	No	Yes
	@vMemberDomainId	int		No	Yes
DRA_InsertMembers	@vDomainID	int		No	Yes
	@vGroupGUID	uniqueidentifier		No	Yes
	@vMemberGUIDS	nvarchar	-1	No	Yes
DRA_InserttoDomainContextList	@DomainName	nvarchar	500	No	Yes
DRA_INTERNAL_ProcessMovedOrRenamedContainers_Merge	@vContainerDN	nvarchar	-1	No	Yes
	@vContainerGuid	uniqueidentifier		No	Yes
	@vDomainId	int		No	Yes
DRA_InternalOUStructure_Merge	@vDomainId	int		No	Yes
	@vObjectGUID	uniqueidentifier		No	Yes
DRA_IsMemberPresent	@vObjectGUID	uniqueidentifier		No	Yes
	@vOUTGUID	uniqueidentifier		Yes	Yes
DRA_LastCollectedAttributesInfo	@vClassType	int		No	Yes
	@vDomainId	int		No	Yes
DRA_MarkGroupforNextINCR	@vGroupGUID	uniqueidentifier		No	Yes
DRA_MarkGroupProcessed	@vGroupGUID	uniqueidentifier		No	Yes
DRA_MoveToJobHistory	@vCollector_Info	nvarchar	800	No	Yes
	@vDomain_Name	nvarchar	800	No	Yes
	@vEnd_Time	datetime		No	Yes
	@vJob_Id	int		No	Yes
	@vMessage	ntext		No	Yes

Stored Procedure name	Parameter name	Parameter Data Type	Parameter Max Bytes	Is Output Parameter	Is Nullable
	@vResult_Id	int		No	Yes
DRA_PopulateDomainSummaryInformation	@vDomainId	int		No	Yes
DRA_PopulateTrustDomainSummaryInformation	@vDomainId	int		No	Yes
DRA_ReadRecycleBinObjects	@vDomainId	int		No	Yes
	@vuSNChanged	bigint		No	Yes
DRA_RecycleBin_Merge	@vClassTypeid	int		No	Yes
	@vdescription	nvarchar	-1	No	Yes
	@vDomainId	int		No	Yes
	@vName	nvarchar	-1	No	Yes
	@vObjectGuid	uniqueidentifier		No	Yes
	@vsamAccountName	nvarchar	-1	No	Yes
	@vUSNChanged	bigint		No	Yes
DRA_Set_Internal_VA_Process	@vObjectGUID	uniqueidentifier		No	Yes
	@vProcess	bit		No	Yes
DRA_SetInvocationIdDCName	@vDCName	nvarchar	2048	No	Yes
	@vDomainID	int		No	Yes
	@vInvocationId	binary		No	Yes
DRA_SetLastUSN	@ADUSN	bigint		No	Yes
	@DELETEDUSN	bigint		No	Yes
	@VAUSN	bigint		No	Yes
	@vDomainName	nvarchar	-1	No	Yes
DRA_SetOptionValue	@vDomainId	int		No	Yes
	@vOptionName	nvarchar	-1	No	Yes
	@vValue	nvarchar	-1	No	Yes
DRA_Table_HasDomainId	@vDomainId	int		No	Yes
	@vTableName	nvarchar	100	No	Yes
DRA_Table_UpdateTypeAndStoredProcedure	@vCreateSP	nvarchar	-1	No	Yes
	@vCreateType	nvarchar	-1	No	Yes
	@vTableName	nvarchar	100	No	Yes
DRA_Update_IsRequiredContextTbFullCollectionValue	@vDomainId	int		No	Yes
	@vIsRequiredContextTbFullCollection	bit		No	Yes
DRA_UpdateContainerAsProcessed	@vcontainerGUID	uniqueidentifier		No	Yes

Stored Procedure name	Parameter name	Parameter Data Type	Parameter Max Bytes	Is Output Parameter	Is Nullable
DRA_UpdateContainerChildrenForNewDN	@vobjectDN	nvarchar	-1	No	Yes
	@vobjectGUID	uniqueidentifier		No	Yes
	@vparentDN	nvarchar	-1	No	Yes
DRA_UpdateContainerDN	@vobjectDN	nvarchar	-1	No	Yes
	@vobjectGUID	uniqueidentifier		No	Yes
DRA_UpdateIsDynamicGroupFlag	@vGroupGUID	uniqueidentifier		No	Yes
	@vIsDynamicGroup	bit		No	Yes
DRA_UpdateJob	@vCollector_Info	nvarchar	100	No	Yes
	@vJob_Id	int		No	Yes
	@vLast_Update	datetime		No	Yes
	@vStatus	nvarchar	40	No	Yes
DRA_UpdateRecycleBin	@vObjectGuid	uniqueidentifier		No	Yes
	@vorigDN	nvarchar	-1	No	Yes
	@vorigName	nvarchar	510	No	Yes
	@vorigOUDN	nvarchar	-1	No	Yes
	@vorigOUGUID	uniqueidentifier		No	Yes
DRA_UpdateToRecycleBin	@vwhenDeleted	datetime		No	Yes
	@vClassType	int		No	Yes
	@vdescription	nvarchar	510	No	Yes
	@vDomainId	int		No	Yes
	@vName	nvarchar	510	No	Yes
	@vObjectGuid	uniqueidentifier		No	Yes
SetChildNodes	@vsamAccountName	nvarchar	510	No	Yes
	@vUSNChanged	bigint		No	Yes
	@OUOBJECTGUID	nvarchar	-1	No	Yes
	@vDomainName	nvarchar	-1	No	Yes
sp_InsertIntoInternalDomainInfo	@highestADUSN	bigint		No	Yes
	@highestDeleted	bigint		No	Yes
	@highestVAUSN	bigint		No	Yes
	@DomainName	nvarchar	-1	No	Yes
SPLIT_CONTEXT	@COLUMNNAME	nvarchar	-1	No	Yes
	@CONTEXT	nvarchar	-1	No	Yes
	@RESULTSTRING	nvarchar	-1	Yes	Yes
SPLIT_CONTEXT_CHANGES	@CONTEXT1	nvarchar	-1	No	Yes
	@RESULTDRACHANGE	int		Yes	Yes
	@RESULTSTRING	nvarchar	-1	Yes	Yes

Functions

Function Name	Parameter Name	Parameter Data Type	Parameter Max Bytes	Returns Parameter
BIGINTTODATETIME		datetime		True
	@INPUT	bigint		False
fn_diagramobjects		int		True
FN_PARSETEXT2TABLE	@P_SOURCETEXT	nvarchar	-1	False
	@P_DELIMETER	nvarchar	200	False
GET_GUID_TABLE	@CONTEXT	nvarchar	-1	False

Custom Triggers

This section contains examples for custom triggers.

Examples:

Use Case	Context
Collect Additional Virtual Attributes and Extend Object Property Page	<ul style="list-style-type: none">Virtual AttributePowerShell TriggerPost Task TriggerExchange OnlineCustom Web ClientProperty Page
Enable or disable an Exchange Online user's Outlook web access when they are enabled or disabled in Active Directory	<ul style="list-style-type: none">PowerShell TriggerPost Task TriggerExchange Online
Move a user to a new OU when their Office property is changed and change their 'City' attribute to match their new office location	<ul style="list-style-type: none">PowerShell TriggerPreTask TriggerPost Task Trigger
Launch Workflow from Trigger	<ul style="list-style-type: none">PreTask TriggerWorkflow


Collect Additional Virtual Attributes and Extend Object Property Page

Scope

This example demonstrates how to define virtual attributes in DRA, collect the virtual attribute values through a post task trigger and add extend an objects property page.

Step-by-step Guide

- Start by creating a virtual attribute in the Delegation and Configuration Console:
 - On the "Configuration Management" node, navigate to the "Virtual Attributes" section
 - Select the option "New Virtual Attribute" from the "Managed Attributes" subheading




Define Attributes


Create the following four attributes with the wizard:

- 'Name' = "va-ActiveSyncEnabled", 'Type' = Boolean
- 'Name' = "va-OWAEnabled", 'Type' = Boolean
- 'Name' = "va-MAPIEnabled", 'Type' = Boolean
- 'Name' = "va-EwsEnabled", 'Type' = Boolean

2. Associate the four new Virtual Attributes with the User object class.



3. Add a new post task trigger to the UserGetInfo() task that will execute a PowerShell command to collect the values of the new virtual attributes.



Post Task Trigger

```
#####
#
# This is a post-task trigger that will collect additional Exchange Online Mailbox settings
and expose them as additionalAttributes
#
#####

#####
#
# Function to convert DN (CN=Fred Smith,OU=North America,DC=ks,DC=com) to domain FQDN
(keystone.com)
#
#####
function Convert-DN-To-FQDN([string] $dn)
{
    [array]$ADObjectDNArray = $dn -Split(",")
    [int]$DomainNameFECOUNT = 0
    ForEach ($ADObjectDNArrayItem in $ADObjectDNArray)
    {
        if ($DomainNameFECOUNT -gt 0)
        {
            [string]$ADObjectDNArrayItemDomainName += $ADObjectDNArrayItem + "."
        }

        $DomainNameFECOUNT++
    }
    return $ADObjectDNArrayItemDomainName.Substring(0,$ADObjectDNArrayItemDomainName.Length-1)
}

#####
#
# Verify the operation name is UserGetInfo, in other cases return $true
#
#####

$operation = $InVarSet.get("In.OperationName")

if ($operation -ne "UserGetInfo")
{
    return $true
}

#####
#
# Execute the script only if varset contains any of the keys ("In.ActiveSyncEnabled" ,
# "In.OWAEnabled" , "In.MAPIEnabled" , "In.EwsEnabled"
#
#####

$ActiveSyncEnabled = $InVarSet.get("In.Properties.va-ActiveSyncEnabled")
$OWAEnabled = $InVarSet.get("In.Properties.va-OWAEnabled")
$MAPIEnabled = $InVarSet.get("In.Properties.va-MAPIEnabled")
$EwsEnabled = $InVarSet.get("In.Properties.va-EwsEnabled")

if (!($ActiveSyncEnabled-eq "") -and !($OWAEnabled-eq "") -and !($MAPIEnabled-eq ""))
    -and !($EwsEnabled-eq ""))
{
    return $true
}
```

```

$userDN = $InVarSet.get("In.User").Replace("OnePoint://", "")
$domainFQDN = Convert-DN-To-FQDN($userDN)

Import-Module -Name NetIQ.DRA.PowerShellExtensions
$user = Get-DRAUser -DRARestServer localhost -DRAHostServer localhost ` 
    -Domain $domainFQDN -Identifier $userDN ` 
    -Attribute "displayName","mailboxType" ` 
    -IgnoreCertificateErrors ` 
    -Force

if ($error.Count -gt 0)
{
    $errorMsg = "Failed to get $userDN displayname, error: $error[0]"
    $InVarset.Put("Out.ErrorMsg.Script", $errorMsg)
    return $false
}

if (!($user.MailboxType -band 64))
{
    # User doesn't have an online mailbox
    return $true
}

$userDisplayName = $user.DisplayName

#####
#
# For this example we are using a plain text username and password
#
#####
$securePassword = ConvertTo-SecureString <Password> -AsPlainText -Force
$credentials = New-Object System.Management.Automation.PSCredential(<0365-Account>,
$securePassword)

#####
#
# Create the Exchange Online session
#
#####
$session = New-PSSession -ConfigurationName Microsoft.Exchange ` 
    -ConnectionUri https://outlook.office365.com/powershell-liveid/ ` 
    -Credential $credentials -Authentication Basic -AllowRedirection
Import-PSSession $Session -DisableNameChecking

#####
#
# Assume it will succeed
#
#####
$succeeded = $true

#####
#
# Execute command-let related O365 Mailbox
#
#####

$data = Get-CasMailbox -Identity $userDisplayName

#####
#
# Populate the out varset based on requested attribute
#
#####

```

```

if ($ActiveSyncEnabled -eq "")
{
    $InVarSet.Put("Out.Properties.va-ActiveSyncEnabled", $data.ActiveSyncEnabled)
}

if ($OWAEnabled -eq "")
{
    $InVarSet.Put("Out.Properties.va-OWAEnabled", $data.OWAEnabled)
}
if ($MAPIEnabled -eq "")
{
    $InVarSet.Put("Out.Properties.va-MAPIEnabled", $data.MAPIEnabled)
}

if ($EwsEnabled -eq "")
{
    $InVarSet.Put("Out.Properties.va-EwsEnabled", $data.EwsEnabled)
}

#####
#
# Cleanup
#
#####
Remove-PSSession -Session (Get-PSSession)

#####
#
# If the trigger failed send back an error message
#
#####
if ($error.Count -gt 0)
{
    $errorMsg = "Failed to get additional mailbox values for user: $userDN error: $error[0]"
    $InVarset.Put("Out.ErrorMsg.Script", $errorMsg)
    $succeeded = $false
}

return $succeeded

```

- To add the properties to the User Property Page, start by customizing the User Create Page and add a new 'Checkbox' field for each of the four properties.

The screenshot shows the DRA Administration interface with the 'USER' configuration page open. The 'GENERAL' tab is selected under the 'CUSTOMIZATION' section. The 'ADD FIELD' dropdown is open, showing categories like General, Account, Profile, Member Of, Email, and Mailbox. Several fields are listed on the right, each with a description:

- First Name: The first name of the user (givenName)
- Initials: The initials of the user (initials)
- Last Name: The last name of the user (sn)
- Full Name: The full name of the user (displayName)
- Create In: The location where the user will be created
- User Logon Name: The account logon ID or user name and domain for the user (userPrincipalName)
 - Select domain suffix: A dropdown menu currently set to 'Select domain suffix'.
- User Logon Name (pre-Windows 2000): The pre-Windows 2000 account logon ID or user name and domain for the user (sAMAccountName)
- Description: A text input field for a description.

At the bottom of the screen, there are buttons for 'OK', 'APPLY', 'FORM PROPERTIES', and 'CANCEL'.

5. Configure each of the new fields for the new Virtual Attributes that we extended on the User object class.

Configure Form Fields

Configure the fields that were added to the form in the previous step as follows:

- Checkbox Field, Label: "Active Sync Enabled", 'Attribute' = "additionalAttributes.va-ActiveSyncEnabled"
- Checkbox Field, Label: "OWA Enabled", 'Attribute' = "additionalAttributes.va-OWAEnabled"
- Checkbox Field, Label: "MAPI Enabled", 'Attribute' = "additionalAttributes.va-MAPIEnabled"
- Checkbox Field, Label: "va-EWS Enabled", 'Attribute' = "additionalAttributes.va-EwsEnabled"

User Logon Name (pre-Windows 2000) *

The pre-Windows 2000 account logon ID or user name and domain for the user (sAMAccountName)

Description

Employee ID

The employee ID of the user (employeeID). The maximum character length for this field is 16.

Active Sync Enabled
 OWA Enabled
 MAPI Enabled
 va-EWS Enabled

Enable or disable an Exchange Online user's Outlook web access when they are enabled or disabled in Active Directory

Scope

This example demonstrates how to define add a custom post task trigger to Enable or disable an Exchange Online user's Outlook web access when they are enabled or disabled in Active Directory.

Step-by-step Guide

Add a new post task trigger to the UserSetInfo() task that will execute a PowerShell command to update the users Outlook web access when they are enabled or disabled in Active Directory.

Post Task Trigger

```
#####
#
# This is a post-task trigger for the UserEnable operation. The UserEnable
# operation is used to enable and disable users.
#
# We will enable or disable the user's Outlook web access when they are
# enabled or disabled.
#
#####
#
# Function to convert DN (CN=Fred Smith,OU=North America,DC=ks,DC=com) to domain FQDN (keystone.com)
#
#####
function Convert-DN-To-FQDN([string] $dn)
{
    [array]$ADObjectDNArry = $dn -Split(",DC=")

    [int]$DomainNameFECOUNT = 0

    ForEach ($ADObjectDNArryItem in $ADObjectDNArry)
    {
        if ($DomainNameFECOUNT -gt 0)
        {
            [string]$ADObjectDNArryItemDomainName += $ADObjectDNArryItem + "."
        }

        $DomainNameFECOUNT++
    }

    return $ADObjectDNArryItemDomainName.Substring(0,$ADObjectDNArryItemDomainName.Length-1)
}

#
# This is a quirk of DRA. To get a pre/post task trigger to fire on the
# UserEnable operation you actually have to specify the UserSetInfo operation
# when you configure your trigger. That means we need to make sure the operation
# is actually UserEnable
#
#
$operation = $InVarSet.get("In.OperationName")
```

```

if ($operation -ne "UserEnable")
{
    return $true
}

#####
#
# Get the user's mailboxType and displayName. If they don't have an online
# mailbox just return.
#
# We need to the user's display name to use as the -Identity value when we
# call Exchange Online.
#
#####
$userDN = $InVarSet.get("In.User").Replace("OnePoint://", "")
$domainFQDN = Convert-DN-To-FQDN($userDN)

Import-Module -Name NetIQ.DRA.PowerShellExtensions

$user = Get-DRAUser -DRARestServer localhost -DRAHostServer localhost ` 
-Domain $domainFQDN -Identifier $userDN ` 
-Attribute "displayName","mailboxType" ` 
-IgnoreCertificateErrors ` 
-Force

if ($error.Count -gt 0)
{
    $errorMsg = "Failed to move $userDN to OU ${ouToMoveTo}: $error[0]"
    $InVarset.Put("Out.ErrorMsg.Script", $errorMsg)
    return $false
}

if (!($user.MailboxType -band 64))
{
    # User doesn't have an online mailbox
    return $true
}

$userDisplayName = $user.DisplayName

#####
#
# See if we are enabling or disabling the user
#
#####
$enableOWA = $InVarSet.get("In.Enable")

#####
#
# For this example we are using a plain text username and password
#
#####
$securePassword = ConvertTo-SecureString <Password> -AsPlainText -Force
$credentials = New-Object System.Management.Automation.PSCredential(<user@domain>, $securePassword)

#####
#
# Create the Exchange Online session
#
#####
$session = New-PSSession -ConfigurationName Microsoft.Exchange ` 
-ConnectionUri https://outlook.office365.com/powershell-liveid/ ` 
-Credential $credentials -Authentication Basic -AllowRedirection
Import-PSSession $Session -DisableNameChecking

#####
#

```

```

# Assume it will succeed
#
#####
$succeeded = $true

#####
#
# See if OWA is enabled.
#
#####
$enabled = Get-CasMailbox -Identity $userDisplayName | Select-Object -ExpandProperty OWAEnabled

#####
#
# Only enable or disable it if we need to
#
#####
if ($enabled -ne $enableOWA)
{
    #####
    #
    # Enable or disable the user's Outlook web access
    #
    #####
    Set-CasMailbox -Identity $userDisplayName -OWAEnabled $enableOWA

    #####
    #
    # Validate it was changed
    #
    #####
    $enabled = Get-CasMailbox -Identity $userDisplayName | Select-Object -ExpandProperty OWAEnabled

    if ($enabled -ne $enableOWA)
    {
        $succeeded = $false
    }
}

#####
#
# Cleanup
#
#####
Remove-PSSession -Session (Get-PSSession)

#####
#
# If the trigger failed send back an error message
#
#####
if ($succeeded -eq $false)
{
    $enableOrDisable = if ($enableOWA) { "enable" } else { "disable" }

    if ($error.Count -gt 0)
    {
        $errorMsg = "Failed to $enableOrDisable Outlook web access for ${userDisplayName}: $error[0]"
    }
    else
    {
        $errorMsg = "Failed to $enableOrDisable Outlook web access for $userDisplayName"
    }

    $InVarset.Put("Out.ErrorMsg.Script", $errorMsg)
}

return $succeeded

```

Launch Workflow from Trigger

Scope

This example demonstrates how to define add a custom pre task trigger to launch a workflow.

Step-by-step Guide

1. Define a workflow that will update the manager when object is moved from one OU to another OU.
2. Add a new pre task trigger to launch the custom work.

Pre-Task Trigger

```
$operation = $InVarSet.get("In.OperationName")

if ($operation -ne "OUMoveHere")
{
    return $true
}

#####
#
# Find the Target Container
#
#####
$targetOU = $InVarSet.get("In.Container")

#####
#
# Find the object which is moving
#
#####

$movingObject = $InVarSet.get("In.Object")

#####
#
# Create server and varset Object
#
#####
$ea1 = New-Object -comobject EaServer.EaServe.1
$NewVarSet = New-Object -comobject NetIQDraVarSet.VarSet.1
```

```

#
# Populate the Varset based on workItem attribute defined in Aegis
# here UserDN is the workitem attribute to represent User which is moving to different
container
#
#####
$NewVarSet.put("Properties.UserDN", $movingObject)

#####

#
# Populate the Varset based on workItem attribute defined in Aegis
# here managerDN is the workitem attribute to represent manager the value has
# to be DN format
#
#####
$NewVarSet.put("Properties.managerDN", "cn=admin400_vino,ou=vino_400,dc=drdom400,dc=lab")

#####

#
# Populate the Varset for RequestID which is unique ID generated by randomonly
#
#####
$NewVarSet.put("RequestID", "upot66f5wfaxktvga4vn43kq")

#####

#
# Populate the Varset for WorkflowID , it is unique path of the Aegis workflow
#
#####
$NewVarSet.put("WorkflowID", "/PG_TopLevelContainer=PG/PG_Process=7d6fb8d9-b2c1-4478-b263-
61468e121d79")

#####

$succeeded = $true

#Submit the varset
$vsOut1 = $ea1.ScriptSubmit($NewVarSet)

```

```
$error = $vsOut1.Get("Errors.NumErrors")

If ($error -gt 0){
    $succeeded = $false
}
Else{
    $succeeded = $true
}

return $succeeded
```

Move a user to a new OU when their Office property is changed

Scope

This example demonstrates how to define add a custom pre & post task trigger to Move a user to a new OU when their Office property is changed and change their 'City' attribute to match their new office location.

Step-by-step Guide

1. Add a new pre task trigger to validate there is an OU matching the 'Office' attribute and update the 'City' attribute in the input VARSET.

Pre Task Trigger

```
#####
#
# This is a pre-task trigger that will make sure there is a matching OU when a user's Office
property is changed.
# It will also make sure the user's City property is changed to match the Office property.
#
# There is a corresponding post-task trigger that will move the user to the new OU.
#
# 1. Make sure we have an OU with the same name as the Office
(In.Properties.physicalDeliveryOfficeName).
#     -- If we don't find a matching OU return $false.
# 2. Change the City property ("1") to match the Office property
#
#####
#
# See if the office value was changed
#
#####
$office = $InVarSet.get("In.Properties.physicalDeliveryOfficeName")

if (!$office)
{
    return $true
}

#####
#
# Get the user's domain
```

```

#####
$userDN = $InVarSet.get("In.User").Replace("OnePoint://", "")
$domain = $userDN.Substring($userDN.indexOf("DC"))

#####
#
# Make a call to DRA to see if we can find an OU matching the office
#
#####

Import-Module -Name NetIQ.DRA.PowershellExtensions

$ous = Find-DRAObjects -DRARestServer localhost -DRAHostServer localhost `

    -ContainerDN "OnePoint://$domain" `

    -OUAndFilter @{{FriendlyName="$office"}}

    -OUOrFilter @{{ShowInAdvancedViewOnly=$false}} `

    -Attributes "Path" `

    -IncludeChildContainers `

    -IgnoreCertificateErrors `

    -Force

if ($ous.TotalObjectCount -ne 1)
{
    $InVarset.Put("Out.ErrorMsg.Script", "Could not find an OU named $office")
    return $false
}

#####
#
# Store the DN of the OU so we can use it in the post-task trigger
#
#####

$InVarSet.put("WorkArea.OUToMoveTo", $ous.Items[0].Path.Replace("OnePoint://", ""))

#####
#
# Update the City property
#
#####

$InVarSet.put("In.Properties.1", $office)

return $true

```

2. Add a new post task trigger to move the user to the new OU if their 'Office' attribute changed

Post Task Trigger

```
#####
#
# This is a post-task trigger that will move a user to the OU specified in the Office
property
#
# There is a corresponding pre-task trigger that will set WorkArea.OutOfMoveTo if the user
needs to be moved.
#
#####
#
#
# Function to convert DN (CN=Fred Smith,OU=North America,DC=ks,DC=com) to domain FQDN
(keystone.com)
#
#####
function Convert-DN-To-FQDN([string] $dn)
{
    [array]$ADObjectDNArray = $dn -Split(",DC=")

    [int]$DomainNameFECOUNT = 0

    ForEach ($ADObjectDNArrayItem in $ADObjectDNArray)
    {
        if ($DomainNameFECOUNT -gt 0)
        {
            [string]$ADObjectDNArrayItemDomainName += $ADObjectDNArrayItem + "."
        }

        $DomainNameFECOUNT++
    }

    return $ADObjectDNArrayItemDomainName.Substring(0,$ADObjectDNArrayItemDomainName.Length-1)
}

#####
#
# See if the pre-task trigger set an OU for us to move the user to
```

```

#
#####
$ouToMoveTo = $InVarSet.get("WorkArea.OUToMoveTo")

if (!$ouToMoveTo)
{
    return $true
}

#####
#
# Get the domain FQDN to use in the Move-DRAUser cmdlet
#
#####
$userDN = $InVarSet.get("In.User").Replace("OnePoint://", "")
$domainFQDN = Convert-DN-To-FQDN($userDN)

#####
#
# Make a call to DRA to move the user to the office OU
#
#####
Import-Module -Name NetIQ.DRA.PowerShellExtensions

Move-DRAUser -DRARestServer localhost -DRAHostServer localhost `

    -Domain $domainFQDN -Identifier $userDN -TargetContainer $ouToMoveTo `

    -IgnoreCertificateErrors `

    -Force

if ($error.Count -gt 0)
{
    $errorMsg = "Failed to move $userDN to OU ${ouToMoveTo}: $error[0]"
    $InVarset.Put("Out.ErrorMsg.Script", $errorMsg)
    return $false
}

return $true

```

Web Client Customization

This section contains examples for customizing object property pages in the Web Console

Custom Property Page Examples;

Use Case	Context
Pre-populate property values in form: Pre-populate Value (A) Based on Value (B) Using Built-in Attribute Setting Pre-populate value automatically based on custom handler	<ul style="list-style-type: none">• On Attribute Change• On Load• Script Custom Handler• Built-in attribute function
Performing custom validation on form submit: On Form Submit, Validate Field (A) has a Value When Field (B) has a Value Validate Name Uniqueness for a Specified Field Value When a Form is Submitted	<ul style="list-style-type: none">• On Submit• LDAP Query Custom Handler
Performing custom validation on property value change: Indicate Field (A) is Required When Field (B) has a Value at Runtime Validate Name Uniqueness for a Specified Field Value at Run-time	<ul style="list-style-type: none">• On Attribute• Change Messagebox
Additional form customization scenarios: Populate selection values for a field based on previous field selection Add Virtual Attributes to Custom Forms	<ul style="list-style-type: none">• On Attribute Change• LDAP Query custom handler• Custom Script Handler• Virtual attributes
Working with regular expressions in form properties Validate input using a regular expression	<ul style="list-style-type: none">• Built-in attribute function

Add Virtual Attributes to Custom Forms


This example demonstrates how to define virtual attributes in DRA and add them to the user create page. We will define three new virtual attributes of different type ("dra-isContractEmployee", "dra-cubicleNumber" and "dra-orgResourceIDList") and associate them with a user property page.

Step-by-step Guide

The screenshot shows the DRA Management interface with the 'CREATE USER' form open. The 'General' tab is selected in the sidebar. The 'User Logon Name' field is populated with 'User Principal Name'. The 'User Logon Name (pre-Windows 2000)' field is populated with 'sAMAccountName'. The 'Description' field is empty. The 'Employee ID' field is populated with 'Employee ID'. The 'Cubical Number' field contains '22'. The 'Resource' field contains 'jdoe12'. A checked checkbox labeled 'Contract Employee' is present. At the bottom, there are 'NEXT', 'CREATE', and 'CANCEL' buttons.

1. Start by creating a virtual attribute in the Delegation and Configuration Console:

- On the "Configuration Management" node, navigate to the "Virtual Attributes" section
- Select the option "New Virtual Attribute" from the "Managed Attributes" subheading




Define Attributes

Create the following three attributes with the wizard:

- 'Name' = "dra-isContractEmployee", 'Type' = Boolean
- 'Name' = "dra-cubicleNumber", 'Type' = Integer
- 'Name' = "dra-orgResourceIDList", 'Type' = String, Multi Value = True

2. Associate the three new Virtual Attributes with the User object class.



3. To add the properties to the User Create page, start by customizing the User Create page in the Web Console and add new fields for each property by navigating to Administration > Customization > Property Pages and edit the User > Create Object.

Add Property Fields

Add the following three fields to the form on the 'General Tab':

- Field Type = 'Checkbox'
- Field Type = 'Number'
- Field Type = 'Multi Valued Text'

- Configure each of the new fields for the new Virtual Attributes that we extended on the User object class.

GENERAL CHECKBOX OPTIONS INLINE FIELDS SUB FIELDS CUSTOM HANDLERS

Label *

Contract Employee

Attribute *

additionalAttributes.dra-isContractEmployee

This is a form only attribute
This attribute is only available on the local form and its value will not be loaded from or submitted to the server

Hidden

Read only

Extend control content to the label area (label will be hidden, if applicable)

Do not retrieve the source object's current value when cloning

OK CANCEL

Configure Form Fields

Configure the fields that were added to the form in the previous step as follows:


- Checkbox Field: "Contract Employee", 'Attribute' = "additionalAttributes.dra-isContractEmployee"
- Number Field: "Cubical Number", 'Attribute' = "additionalAttributes.dra-cubicleNumber"
- Multi Valued Field: 'Label' = "Resource", 'Attribute' = "additionalAttributes.dra-orgResourceIDList"

Indicate Field (A) is Required When Field (B) has a Value at Runtime

This example demonstrates how to make a field required at runtime as soon as a second field on the form has a value entered. We'll customize the User Create pages to make Last Name required whenever the user enters a value for First Name. Now when the user enters a value for First Name the Last Name field is marked as required and the form cannot be submitted until either a Last Name is entered or First Name is cleared.

Step-by-step Guide

1. Start by customizing the User Create pages; edit  the properties of the First Name field, and add a Script handler on the Custom Handlers tab. Click **Add > Script** to configure the script.



The screenshot shows the 'Custom Handlers' tab of a form configuration. At the top, there's a checkbox labeled 'Execute custom handlers every time the field value changes'. Below it, under 'Execution Time', is a dropdown menu set to 'Execute handler when the field loses focus'. In the 'Custom Handlers' section, there's a note: '(1) Custom handlers are executed in the order listed'. A red box highlights the '+ ADD' button. Below this, a table lists one handler: '1 Script Yes Custom Script'. To the right of the table, several options are listed in boxes:

- DRA Query**: Submits an operation to the DRA server using the dra/operations/varset/post endpoint of the DRA REST service.
- LDAP Query**: Executes an LDAP query on the specified domain controller.
- Message Box**: Displays a message box to the user.
- REST Query**: Sends a payload to a RESTful interface.
- Script**: Executes custom JavaScript code enabling you to extend the form page's behavior using custom logic. This box is also highlighted with a red border.

NOTE:

To allow customizations to include custom JavaScript code add `allowCustomJavaScript="true"` to the `<cc onsoleConfiguration>` element found in `%ProgramD ata%\NetIQ\DRARESTProxy\restProxy.config` on the web server.

2. This script will set the required state of the lastName field to equal the truthiness of the firstName field.

```
draApi.fieldRequiredStates.lastName = Boolean(draApi.fieldValues.firstName);
```

On Form Submit, Validate Field (A) has a Value When Field (B) has a Value

This example demonstrates how to validate a form 'on submit' to verify the user has entered a value for a field whenever a second field was filled in. In this example we'll customize the User Create pages to make sure that if the user fills in the First Name field that they also fill in the Last Name field. When the user attempts to create a user with a first name but not a last name they are shown a warning message indicating that the last name field needs to be entered before the form can be submitted.

The screenshot shows the 'CREATE USER' form in the DRA Management interface. The form includes fields for First Name (Turanga), Initials, Last Name, Full Name, Create In, User Logon Name, User Logon Name (pre-Windows 2000), Description, and Employee ID. The 'User Logon Name' field has a dropdown menu for 'Select domain suffix'. At the bottom right are buttons for 'NEXT', 'CREATE', and 'CANCEL'.

Step-by-step Guide

1. Start by customizing the User Create page; open the Form Properties dialog, and add a Script custom handler in the Form Submit Handlers tab. Click **Add > Script** to create the script.

The screenshot shows the 'USER' form properties dialog with the 'FORM SUBMIT HANDLERS' tab selected. It lists custom handlers, with one entry highlighted. To the right is a list of available custom handlers: DRA Query, LDAP Query, Message Box, REST Query, and Script. The 'Script' option is also highlighted.

NOTE:

To allow customizations to include custom JavaScript code add `allowCustomJavaScript="true"` to the `<consoleConfiguration>` element found in `%ProgramD ata%\NetIQ\DRARESTProxy\restProxy.config` on the web server.

You will need to log out of the console and log back in to see this dialog go away

2. This script will check if the value of the `firstName` field is truthy but `lastName` field is not. If the condition returns true, we will cancel the form submission and inform the user they need to enter a value for Last Name.


**Script**

```
if (draApi.fieldValues.firstName && !draApi.fieldValues.lastName) {
    flowControl.cancel('Last Name is required when First Name is specified. Please enter a
    value for Last Name');
}
```

Populate selection values for a field based on previous field selection

This example shows how to use custom handlers in the DRA web client to populate selection objects based on a previous selection and checkbox. The OU structure that this is based on can be seen in the image to the right. This custom page starts at the Keystone Steel level within the tree and provides the values of the Region to the first selection object, the second selection gets the cities based on the first selection, and the third selection provides a list of the departments based on both the first and second selection, and the checkbox. The checkbox is used to determine if the selection for department should be in either the O365 Users or Users OU. Only the First and Second selection objects require any custom handlers, and the first selection is the only one that requires an LDAP query on the options tab.

The following pages will contain screen captures of each setting for each of the selection objects and the checkbox in a Workflow Automation Request form.



DRA MANAGEMENT TASKS ADMINISTRATION

REQUESTS TEMPORARY GROUP ASSIGNMENTS

SUBMIT REQUEST Get OU Properties


Region: EMEA

City: London

Department: Accounting


Office 365 Users

SUBMIT CANCEL



Step-by-step Guide

1. Navigate to Administration > Customization > Requests, and click **Create**.



DRA MANAGEMENT TASKS ADMINISTRATION

CONFIGURATION CUSTOMIZATION

Property Pages Requests

+ CREATE

No data found

2. In the General tab, name the form, select the icon type and **Trigger Workflow by Event** option, enter an event name for the trigger, and click **OK** to save the form. The new form is added with a blank page titled, “New Tab”.

NEW REQUEST FORM

GENERAL ASSISTANT ADMIN GROUPS

Form Display Name *

Icon

Form is hidden
Users logging into the Web Console will not see hidden actions but they are still available for editing

Configure Workflow* Launch Specific Workflow Trigger Workflow by Event

Select a specific workflow that should be executed when this form is submitted.

Workflow Process event name *

Submit a named workflow trigger event containing all of the form attributes defined to the Workflow Engine. All workflow templates configured to trigger on an event with the event name specified will be executed.

OK **CANCEL**

3. Open **Properties** for the page from the ellipsis icon to rename the page and select an icon for the page.
4. From the Add Field drop-down menu, add the checkbox ("Office 365 User") and the three list selection (*Select field*) ("Region", "City", "Department") controls to the custom form.

CHECKBOX

GENERAL CHECKBOX OPTIONS INLINE FIELDS SUB FIELDS CUSTOM HANDLERS

Label *

Attribute *

This is a form only attribute
This attribute is only available on the local form and its value will not be loaded from or submitted to the server

Description

Hidden
 Read only
 Extend control content to the label area (label will be hidden, if applicable)

OK **CANCEL**

GENERAL **SELECT OPTIONS** **CUSTOM HANDLERS**

Label *

Attribute *

This is a form only attribute
This attribute is only available on the local form and its value will not be loaded from or submitted to the server

Description

Hidden
 Required
 Read only
 Extend control content to the label area (label will be hidden, if applicable)

OK **CANCEL**

- Configure the "Region" selection list field to populate with base selection values by defining a "Dynamic" LDAP query on the Select Options tab. When configuring the Query Parameters, enter the base distinguished name for the Region OU, choose One Level for the Scope, enter name for the Attributes, and add the string below for the Filter.

Region Options tab LDAP query

```
(&(objectCategory=organizationalUnit)(objectClass=organizationalUnit))
```

SELECT

GENERAL **SELECT OPTIONS** **CUSTOM HANDLERS**

No Selection Text

Options

Options Labels	Query Attribute <input type="text" value="name"/>
Options Values	Query Attribute <input type="text" value="name"/>

+ ADD

ORDER	TYPE	BUILTIN	DETAILS
-------	------	---------	---------

Required

OK **CANCEL**

- Add a Custom "LDAP Query" to the "Region" selection list field from the "Custom Handlers" tab and configure the Pre-Query and Post-Query logic, using the same settings as the Select Options in Query Parameters.



Region Custom Handler Pre-query LDAP script

```

ldapOptions.baseDn = 'ou=' + draApi.fieldValues.region + ',ou=Keystone_Steel,dc=ks,dc=lab';

ldapOptions.filter =
'(&(objectCategory=organizationalUnit)(objectClass=organizationalUnit))';

```

Region Custom Handler Post-query LDAP script

```

var labels = [];
var values = [];
var attrName;
var attrValue;

for (var i = 0; i < results.length; i++) {
    labels.push(results[i].attributes[0].values[0]);
    values.push(results[i].attributes[0].values[0]);
}

draApi.fieldOptionLabels.city = labels;
draApi.fieldOptionValues.city = values;

```

- When configuring the new Select field for City, leave the Select Options tab at Static and use a placeholder for the Add Option.
- Add a Custom "LDAP Query" to the "City" selection list field from the Properties field dialog on the "Custom Handlers" tab and configure the Pre-Query and Post-Query logic. Use the same configuration in Query Parameters as before, but with the addition of distinguishedName in the Attributes field.



City Custom Handler Pre-query LDAP script

```

if (draApi.fieldValues.0365) {
    ldapOptions.baseDn = 'ou=0365 Users,ou=' + draApi.fieldValues.city + ',ou=' +
    draApi.fieldValues.region + ',ou=Keystone Steel,dc=ks,dc=lab';
} else {
    ldapOptions.baseDn = 'ou=Users,ou=' + draApi.fieldValues.city + ',ou=' +
    draApi.fieldValues.region + ',ou=Keystone Steel,dc=ks,dc=lab';
}

```

City Custom Handler Post-query LDAP script

```

var labels = [];
var values = [];
var attrName;
var attrValue;

for (var i = 0; i < results.length; i++) {
    for(var x = 0; x < results[i].attributes.length; x++) {
        attrName = results[i].attributes[x].attrName;
        attrValue = results[i].attributes[x].values[0];
        if (attrName.toLowerCase() === 'name') {
            labels.push(attrValue);
        } else if (attrName.toLowerCase() === 'distinguishedname') {
            values.push(attrValue);
        }
    }
}

draApi.fieldOptionLabels.department = labels;
draApi.fieldOptionValues.department = values;

```

Pre-populate Value (A) Based on Value (B) Using Built-in Attribute Setting

Example of how to pre-populate a field value based on another property field value using the built-in attribute setting customization "Generate value automatically based on other values". In this example we will pre-populate the 'Description' of a User with his 'Department' name in the User Properties page as "Department-<Department Name>".

Step-by-step Guide

1. Start by customizing the User Create page and edit the 'Description' property.

The screenshot shows the DRA Administration interface. The top navigation bar includes 'DRA', 'MANAGEMENT', 'TASKS', and 'ADMINISTRATION'. The 'ADMINISTRATION' tab is selected, showing 'CONFIGURATION' and 'CUSTOMIZATION' tabs, with 'CUSTOMIZATION' being the active one. The 'Object Type: User' and 'Operations: Create Object' are displayed. On the left, a sidebar titled 'USER' lists 'General', 'Account', 'Profile', 'Member Of', 'Email', and 'Mailbox'. The main panel displays fields for 'Full Name', 'Create In', 'User Logon Name', 'User Logon Name (pre-Windows 2000)', 'Description', and 'Employee ID'. The 'Description' field is highlighted, indicating it is being customized. A 'Properties' button is visible next to the 'Description' input field. At the bottom are 'OK', 'APPLY', 'FORM PROPERTIES', and 'CANCEL' buttons.

2. Select the "Generate value automatically based on other values" option in the Text Area Options tab.

The screenshot shows the 'TEXT AREA' configuration screen. The 'TEXT AREA OPTIONS' tab is selected. Under 'GENERAL', the 'Number of Rows' is set to 3. Under 'TEXT AREA OPTIONS', there is a section for 'Validate input using a regular expression' with fields for 'Regular Expression Type' (set to 'Custom'), 'Regular Expression', 'Match is case insensitive', and 'Test Input'. Below this is a section for 'Generate value automatically based on other values*' which has a red border around its checkbox. At the bottom are 'ADD FIELD' and 'ADD TEXT' buttons, and at the very bottom are 'OK' and 'CANCEL' buttons.

- Specify the value(s) that the field should be defaulted to. For this example we will add a static text string "Department" and a reference to the value of another property "Department" in the form. In this case the Department property was a customization previously added to the form.

NOTE: Adding a space '' at the end of the static text string adds a break between concatenated parts of the default value. If you want to add a break between two property values, you can add an additional text element configured with a ''.

TEXT AREA

GENERAL TEXT AREA OPTIONS CUSTOM HANDLERS

Number of Rows: 3

Validate input using a regular expression

Regular Expression Type: Custom

Regular Expression:

Match is case sensitive

Test Input: Department

Generate value automatically based on other values*

ADD FIELD **ADD TEXT**

Text*	Department
Field*	SELECT A FIELD Required

Preview: Department

OK CANCEL

Pre-populate value automatically based on custom handler

This example demonstrates how to pre-populate the manager field of a user with the assistant administrator who is creating the user.

Step-by-step Guide

1. Start by customizing the User Create page and add a new Managed Object Browser Field for manager.

The screenshot shows the 'MANAGED OBJECT BROWSER' configuration dialog. The 'GENERAL' tab is selected. The 'Label' field contains 'Manager'. The 'Attribute' field contains 'manager'. Below these fields are several checkboxes:

- This is a form only attribute
This attribute is only available on the local form and its value will not be loaded from or submitted to the server
- Hidden
- Required
- Extend control content to the label area (label will be hidden, if applicable)
- Do not retrieve the source object's current value when cloning

At the bottom right are 'OK' and 'CANCEL' buttons.


2. After adding the manager field, open the Form Properties and navigate to Form Load Handlers. Add a script Handler. Click **Add > Script** to configure the script.

The screenshot shows the 'FORM LOAD HANDLERS' tab in the Form Properties dialog. A radio button is selected for 'Execute custom handlers when the form is initially loaded'. Below this, there is a 'Custom Handlers' section with a note: 'Custom handlers are executed in the order listed'. A red box highlights the '+ ADD' button. To the right, a list of available handlers is shown in a sidebar:

- DRA Query**: Submits an operation to the DRA server using the dra/operations/varset/post endpoint of the DRA REST service.
- LDAP Query**: Executes an LDAP query on the specified domain controller.
- Message Box**: Displays a message box to the user.
- REST Query**: Sends a payload to a RESTful interface.
- Script**: Executes custom JavaScript code enabling you to extend the form page's behavior using custom logic. This item is also highlighted with a red box.

NOTE: To allow customizations to include custom JavaScript code add `allowCustomJavaScript="true"` to the `<c onsoleConfiguration>` element found in `%ProgramD ata%\NetIQ\DRARESTProxy\restProxy.config` on the web server.

3. In Configure Script editor, assign the value of the current assistant administrator's distinguished name to the manager field. We use `draApi.fieldValues` and `draApi.constants.ConsoleUserDistinguishedName` APIs.



Configure Script

```
draApi.fieldValues.manager = draApi.constants.ConsoleUserDistinguishedName;
```

Validate input using a regular expression

The web client supports regular expressions based on JavaScript syntax, here are some reference documents:

- https://developer.mozilla.org/en-US/docs/Web/JavaScript/Guide/Regular_Expressions
- <http://www.regular-expressions.info/javascript.html>

NOTE:

JavaScript doesn't support the \p Unicode category expression, Unicode support in JavaScript's regular expressions is limited to single character matches. The following expression gets close to the behavior of \p: [w.\-]*

NOTE:

you will not need the anchor tags since the whole expression is a single class of characters repeated any number of times. Any matching string will have to start and end with a character in that class.


Built-in example regular expressions:

Use Case	Regular Expression
All Major Credit Cards	^(?>4[0-9]{12}(?:[0-9]{3})? 5[1-5][0-9]{14} 6011[0-9]{12} 3(?:0[0-5][68][0-9])[0-9]{11} 3[47][0-9]{13})\$
Alpha-Numeric String	^[a-zA-Z0-9]*\$
Alpha-Numeric String With Spaces	^[a-zA-Z0-9\s]*\$
One Or More Digits	^\d+\$
Email Address	^@[a-zA-Z!#\$%^+=?^`{ }~.-]+@[a-zA-Z]([a-zA-Z-]*[a-zA-Z])?(.[a-zA-Z]([a-zA-Z-]*[a-zA-Z])?)*\$
Mail Alias	^@[a-zA-Z0-9!#\$%^+=?^`{ }~.-]+@[^#]+@[^#]+@[^#]\$
URL	^@[a-zA-Z][a-zA-Z\d.+-]*:(?:[@+]?[@+])+@?(?:[^\s:/#]+ [a-f\d:]*) (?:\d+)?(?:/[^\?#]*)(?:\?[\^#]*)?(?:\:[^\#]*)(?:\:#.)?\$/
Number	^\d*(\.\d+)?(\d+ (\d*(\.\d*)))((eE)[+-]\?\d+)?\d*\$
ISO Date	^\d{4}-[01]\d-[0-3]\dT[0-2]\d:[0-5]\d\.\d+([+-][0-2]\d:[0-5]\d[Z]\$
IP Address (version 4)	^(?:25[0-5] 2[0-4][0-9][01]?[0-9][0-9]?)\.(?:25[0-5] 2[0-4][0-9][01]?[0-9][0-9]?)\$
IP Address (version 6)	^((([0-9A-Fa-f]{1,4}):){7}(([0-9A-Fa-f]{1,4}):)) (([0-9A-Fa-f]{1,4}):{6}([0-9A-Fa-f]{1,4}) ((25[0-5] 2[0-4])\d 1\d d)([1-9]?d)(.25[0-5] 2[0-4]\d 1\d d 1\d d [1-9]?d)(3)) (([0-9A-Fa-f]{1,4}):{5}((:[0-9A-Fa-f]{1,4})(1,2)) ((25[0-5] 2[0-4])\d 1\d d [1-9]?d)(.25[0-5] 2[0-4]\d 1\d d 1\d d [1-9]?d)(3)) (([0-9A-Fa-f]{1,4}):{4}((:[0-9A-Fa-f]{1,4})(1,3)) ((:[0-9A-Fa-f]{1,4})?((25[0-5] 2[0-4])\d 1\d d [1-9]?d)(.25[0-5] 2[0-4]\d 1\d d 1\d d [1-9]?d)(3)) (([0-9A-Fa-f]{1,4}):{3}((:[0-9A-Fa-f]{1,4})(1,4)) ((:[0-9A-Fa-f]{1,4})(0,2)((25[0-5] 2[0-4]\d 1\d d [1-9]?d)(.25[0-5] 2[0-4]\d 1\d d 1\d d [1-9]?d)(3))) (([0-9A-Fa-f]{1,4})?((:[0-9A-Fa-f]{1,4})(1,4)) (25[0-5] 2[0-4]\d 1\d d [1-9]?d)(.25[0-5] 2[0-4]\d 1\d d 1\d d [1-9]?d)(1,5)) (:([0-9A-Fa-f]{1,4})(0,3)((25[0-5] 2[0-4]\d 1\d d [1-9]?d)(.25[0-5] 2[0-4]\d 1\d d 1\d d [1-9]?d)(3))(1,6)) (:([0-9A-Fa-f]{1,4})(0,4)((25[0-5] 2[0-4]\d 1\d d [1-9]?d)(.25[0-5] 2[0-4]\d 1\d d 1\d d [1-9]?d)(3))) (:((:[0-9A-Fa-f]{1,4})(1,7)) (:([0-9A-Fa-f]{1,4})(0,5)((25[0-5] 2[0-4]\d 1\d d [1-9]?d)(.25[0-5] 2[0-4]\d 1\d d [1-9]?d)(3)))) (%.+)?\$

This example demonstrates how to validate that a group name entered by a user begins with only specific characters, say it should begin with "GRP". When a group name is entered and if the given name doesn't begin with "GRP", then the name field will outlined with red that indicates input is invalid and the form cannot be submitted.

Step-by-step Guide


1. Start by customizing the Group Create page. Open the properties of the Name field, and select the "Validate input using a regularexpression" check box.




2. For this example we will be implementing a custom regular expression that will require the property value to begin with "GRP":

- Set the 'Regular Expression Type' to 'Custom'
- Enter the regular expression value "^GRP[a-zA-Z0-9_]*\$"
- Set the option regular expression option 'Match is case sensitive' (for strict capitalization checking)

NOTE: You can select one of the default regular expressions as a starting point or select custom to create your own.



3. The regular expression can be tested by entering a test value to verify it is working as intended.



Validate Name Uniqueness for a Specified Field Value at Run-time

This example demonstrates how to validate that a group name entered by a user does not already exist in Active Directory at run-time. It will also demonstrate using multiple handlers in sequence and controlling the execution flow of those handlers. When a group with the given name does exist, an alert is shown to the user informing them of the issue. Note that the alert is only informational and the form can still be submitted after the message is cleared by the user.

The screenshot shows the DRA (Dynamic Rule Administration) interface. In the top navigation bar, 'MANAGEMENT' is selected. Below it, the 'CREATE GROUP' dialog is open. The 'Name' field contains 'Account Admins'. A modal window titled 'GROUP ALREADY EXISTS' is centered over the dialog, displaying the message 'A group with this name already exists. Enter a unique name.' with an 'OK' button. Other fields visible include 'Email Address', 'Group Scope', 'Group Type' (Security selected), 'Group Name (pre-Windows 2000)', 'Create In' (marked as required), and 'Description'.

Step-by-step Guide

1. Start by customizing the Group Create page and open the properties of the Name field. Add an LDAP Query handler on the Custom Handlers tab and set the Execution Time to execute the handler when the field loses focus (otherwise it will be executed after every key stroke). Finally, click **Add > LDAP Query** to configure the LDAP query.

WARNING: Running LDAP, REST, or DRA queries in a change handler for validation like this is generally not recommended and as a best practice should be done in the form's On Submit handler if possible.

TEXT

GENERAL TEXT OPTIONS CUSTOM HANDLERS

Execute custom handlers every time the field value changes

Execution Time

Execute handler when the field loses focus

Custom Handlers

Custom handlers are executed in the order listed

+ ADD

ORDER	TYPE	BUILTIN	DETAILS

OK CANCEL

- Specify the name of the domain controller where you want the LDAP Query to execute in the Connection Information section.

CONFIGURE LDAP QUERY

HELP

CONNECTION INFORMATION QUERY PARAMETERS PRE-QUERY ACTION POST-QUERY ACTION

Host Name * VLAB019670

LDAP Server host name or IP address

Port Number * 389

Connection Timeout (seconds) 30

Use UDP connection

OK CANCEL

- Specify the Query Parameter configuration:

- Set 'Base Distinguished Name' to the distinguished name of the domain to be searched
- Set 'Scope' to Subtree so our search will be recursive and include all child OUs and containers in the domain
- Set 'Attributes' to return the name value of the group
- Leave the 'Filter' empty (we need to generate it dynamically based on the users input in the form)

CONFIGURE LDAP QUERY

(?) HELP

CONNECTION INFORMATION	QUERY PARAMETERS	PRE-QUERY ACTION	POST-QUERY ACTION
Base Distinguished Name *	DC=KS,DC=LAB		
<i>The DN of the object at which to start the query (i.e. DC=MYCOMPANY,DC=COM)</i>			
Scope *	Subtree		
Attributes *	name X Type in a value and hit Enter		
Filter			

OK **CANCEL**

4. In the Pre-Query Action we need to create the LDAP query using the name entered by the user. We use the draApi.fieldValues API to access the value of the name field and build the query string which we then set as the query filter using the ldapOptions.filter API.


NOTE: To verify uniqueness, we're only interested if the query returns 1 or more results, so we'll just have the query return the name attribute of any matching group.

NOTE: There are 3 possible options for Scope:


- Base - The search is limited to the object specified by the Base Distinguished Name. This is useful if you want to see if that object exists.
- One Level - The search is limited to the Base Distinguished Name.
- Subtree - The search is recursive and will include all children of the object specified by the Base Distinguished Name. More details can be found here:<https://docs.microsoft.com/en-us/windows/desktop/ad/search-scope>

Pre-Query Action

```
ldapOptions.filter = '(&(objectCategory=group)(objectClass=group)(name=' +
draApi.fieldValues.name + '))'
```



- In the Post-Query Action we'll store the number of matching objects so we can use it in a later handler. The results are returned as an array of objects that matched the query so we'll store the length of that array in a variable we can reference later using the variables API. The value passed to this API is just an arbitrary name that we decide to use that describes that information it holds.




Post-Query Action


```
// store the number of matches in resultCount so we
// can reference it in other handlers
variables.resultCount = results.length;
```

- After clicking OK to save the LDAP query, we'll now add a Message Box handler.

7. Click **Add > Message Box** to configure the handler. We'll configure the message box to have a descriptive title, an informative message, and set its style to Error.



8. The Before-Show Action is where we can execute some custom code before the message box is shown to the user. We'll use this to check the value of our resultCount variable and then only display the message box if the resultCount is greater than 0. In order to prevent the message box from being shown when the resultCount is 0 we'll call the flowControl.exit() API which will tell the Web Console to stop processing this handler and to not process any remaining handlers if there were any.



Before-Show Action

```


if (variables.resultCount === 0) {
  // if we didn't match any existing groups we can exit our handler
  // to prevent our message box from being shown to the user
  flowControl.exit();
}

// execution will continue here when our query did match at least
// one existing group so our message box will be shown to the user

```


Validate Name Uniqueness for a Specified Field Value When a Form is Submitted

This example demonstrates how to validate that a group name entered by a user does not already exist in Active Directory when the form is submitted. When a group with the given name does exist a notification is presented to the user informing them of the issue and the form is not submitted to the server.



Step-by-step Guide

1. Start by customizing the Group Create page and open the Form Submit Handlers tab on the Form Properties dialog. Click **Add > LDAP Query** to configure the LDAP query.



2. Specify the name of the domain controller where you want the LDAP Query to execute in the Connection Information section.

CONFIGURE LDAP QUERY

CONNECTION INFORMATION **QUERY PARAMETERS** **PRE-QUERY ACTION** **POST-QUERY ACTION**

Host Name *

LDAP Server host name or IP address

Port Number *

Connection Timeout (seconds)

Use UDP connection

OK **CANCEL**

3. Specify the Query Parameter configuration:

- Set 'Base Distinguished Name' to the distinguished name of the domain to be searched
- Set 'Scope' to Subtree so our search will be recursive and include all child OUs and containers in the domain
- Set 'Attributes' to return the name value of the group
- Leave the 'Filter' empty (we need to generate it dynamically based on the users input in the form)

CONFIGURE LDAP QUERY

CONNECTION INFORMATION **QUERY PARAMETERS** **PRE-QUERY ACTION** **POST-QUERY ACTION**

Base Distinguished Name *

The DN of the object at which to start the query (i.e. DC=MYCOMPANY,DC=COM)

Scope *

Attributes * Type in a value and hit Enter

Filter

OK **CANCEL**

NOTE: To verify uniqueness, we're only interested if the query returns 1 or more results, so we'll just have the query return the name attribute of any matching group.

NOTE: There are 3 possible options for Scope:

- Base - The search is limited to the object specified by the Base Distinguished Name. This is useful if you want to see if that object exists. One Level –
- The search is limited to the immediate children of the object specified by the Base Distinguished Name.
- Subtree - The search is recursive and will include all children of the object specified by the Base Distinguished Name.


More details can be found here:

<https://docs.microsoft.com/en-us/windows/desktop/ad/search-scope>

4. In the Pre-Query Action we need to create the LDAP query using the name entered by the user. We use the draApi.fieldValues API to access the value of the Name field and build the query string which we then set as the query filter using the ldapOptions.filter API.

Pre-Query Action


```
ldapOptions.filter = '(&(objectCategory=group)(objectClass=group)(name=' + draApi.fieldValues.name +'))';
```



5. In the Post-Query Action we'll check the results returned by the query. The results are returned as an array of objects that matched the query so we just need to check if the length of the array is greater than 0. When a matching group is found we use the flowControl.cancel() API to cancel the form submission passing the API an optional message to display to the user.

Post-Query Action

```
if (results.length > 0) {  
    flowControl.cancel('A group with that name already exists, please enter a unique name.');//  
}
```




Workflow Customization

This section contains examples for customizing automated workflow forms in the Web Console.

Custom Workflow Examples:


Solution	Use Case	Components for Example	Notes
This solution will be broken into 3 sub-workflows	Create and modify a user account	Legacy DRA activity Built-in DRA REST Activity Custom DRA REST (Include parsing JSON response)	Core Business logic, we may add additional use cases in the future. This workflow will have a corresponding Workflow form in the DRA web client so that it can be launched manually.
	Service Now Integration	Trigger workflow based on ServiceNow ticket Call Sub-workflow Update ServiceNow with details from processing ticket	Create ServiceNow Change Request, add the request information. When approved, update ticket information and state
	Approval Workflow	Lookup group owner/manager IQMail EWS approval email request/response	Send EWS email to a user and wait for email reply.
Load users information from Human Resources database to DRA	Bulk Load User Accounts	Load HR DB to DRA	

Delete User Workflow




Custom Form Workflow to delete a user


A DRA Custom Form launch the workflow "Delete User by DN" to delete a user. The user DN is supplied by setting workflow customer workitem attribute User DN. Approver's email is also read from the work




Workitem Attributes used:




Create a new ServiceNow ChangeRequest ticket:



When the workflow finishes, the Task ID is returned and can be used to update ticket activity.





Lab Data Setup

User information is stored in HumanResources database. The database can be populated by the attached SQL script.

- CreateDB.sql
- CreateTables.sql
- LoadData.sql
- CreateSprocs.sql


HumanResources Database

dbo.GetAllEmployeesAsJson() return all the employees as User JSON payload which can be used to call DRA Rest create user API.

```
{"user":{"container":"OU=Seattle,OU=North America,OU=Keystone  
Steel,DC=ks,DC=lab","name":"Jennifer.Whalen","firstName":"Jennifer","lastName":"Whalen","createEmail":true,"emailAddress":"je  
nnifer.whalen@aedom310.lab","department":"Administration","streetAddress":"2004 Charade  
Rd","city":"Seattle","state":"Washington","country":"US","postalCode":"98199","telephoneNumber":"515.123.4444"}  
{"user":{"container":"OU=Toronto,OU=North America,OU=Keystone  
Steel,DC=ks,DC=lab","name":"Michael.Hartstein","firstName":"Michael","lastName":"Hartstein","createEmail":true,"emailAd  
dress":"michael.hartstein@aedom310.lab","department":"Marketing","streetAddress":"147 Spadina  
Ave","city":"Toronto","state":"Ontario","country":"CA","postalCode":"M5V 2L7","telephoneNumber":"515.123.5555"}  
{"user":{"container":"OU=Toronto,OU=North America,OU=Keystone  
Steel,DC=ks,DC=lab","name":"Pat.Fay","firstName":"Pat","lastName":"Fay","createEmail":true,"emailAddress":"pat.fay@aedom31  
0.lab","department":"Marketing","streetAddress":"147 Spadina  
Ave","city":"Toronto","state":"Ontario","country":"CA","postalCode":"M5V 2L7","telephoneNumber":"603.123.6666"}  
{"user":{"container":"OU=Seattle,OU=North America,OU=Keystone  
Steel,DC=ks,DC=lab","name":"Den.Raphaely","firstName":"Den","lastName":"Raphaely","createEmail":true,"emailAddress":  
"den.ra phaely@aedom310.lab","department":"Purchasing","streetAddress":"2004 Charade  
Rd","city":"Seattle","state":"Washington","country":"US","postalCode":"98199","telephoneNumber":"515.127.4561"}}}
```


IQMail setup

If Email Server Host is blank, Select Email Server Type to EWS, Test Email Connection will autodiscover the exchange server URL. If user ID and password word is left blank, Aegis server account is gong to be used to connect to the exchange server.




Load HR DB to DRA


The workflow calls HumandResources sproc dbo.GetAllEmployeesAsJson to query all users information and returns json format.




Get All Employees:



Create User:



ServiceNow Event Trigger



Trigger:

The screenshot displays two windows related to the "Start of Workflow" activity.

Activity Properties - Start of Workflow (Top Window):

- General Tab:** Shows "Associated Triggers (in evaluation order)".

Name	Type	Revision	Description
Manual Trigger	Manual	1.0	Trigger the workflow manually by user or activity
ServerNowEventTrigger	User Defined	1.*	
- Trigger Tab:** Shows a timeline from 900 to 1100. A vertical bar is positioned between 1000 and 1100.

View Trigger Revision (Bottom Window):

- General Tab:** Shows "Trigger Name: ServerNowEventTrigger", "Trigger Revision Version: 1.0", and "Actions" dropdown.
- Trigger Definition Tab:** Shows trigger rules:
 - "Initiate New Work Item If" (checkbox)
 - "Block New Work Item If" (checkbox)
 - "Append to Previous Work Item If" (checkbox)
 - "Custom Attributes" (button)

Has All of the following (Time window: 2 Minutes)

 - One ServiceNow.Event event

How to get event locator:

