

---

# SecureLogin 8.5

## Overview Guide

October, 2016

## Legal Notice

For information about NetIQ legal notices, disclaimers, warranties, export and other use restrictions, U.S. Government restricted rights, patent policy, and FIPS compliance, see <https://www.netiq.com/company/legal/>.

**© 2016 NetIQ Corporation. All Rights Reserved.**

For information about NetIQ trademarks, see <https://www.netiq.com/company/legal/>. All third-party trademarks are the property of their respective owners.

---

# Contents

<b>About This Guide</b>	<b>5</b>
<b>1 About SecureLogin</b>	<b>7</b>
<b>2 SecureLogin Interface</b>	<b>9</b>
2.1 SecureLogin Client Utility . . . . .	9
2.2 The Administrative Management Utilities . . . . .	10
2.2.1 iManager . . . . .	10
2.2.2 SLManager . . . . .	12
2.2.3 Microsoft Management Console Snap-In. . . . .	12
2.3 SecureLogin Icon . . . . .	12
2.4 Application Types and Descriptions . . . . .	13
2.5 The Applications Pane . . . . .	14
2.5.1 The Details Tab . . . . .	15
2.5.2 The Definition Tab . . . . .	15
2.5.3 The Settings Tab . . . . .	16
2.6 The Logins Pane . . . . .	16
2.7 The Preferences Properties Table . . . . .	17
2.7.1 Configuring Preferences Introduced In SecureLogin Version 6. . . . .	17
2.8 The Password Policy Properties Table. . . . .	36
2.9 The Advanced Settings Pane. . . . .	40
2.10 The Passphrase Policy Properties Table . . . . .	41
2.11 The Distribution Pane. . . . .	45
<b>3 SecureLogin Components</b>	<b>47</b>
3.1 SecureLogin Management Utilities . . . . .	47
3.2 Application Definition Wizard . . . . .	48
3.3 Add New Login Wizard. . . . .	49
3.4 Terminal Launcher . . . . .	49
<b>4 Enabling Applications and Web Sites for Single Sign-On</b>	<b>51</b>
4.1 Applications Excluded for Single Sign-On . . . . .	52
4.1.1 Modifying the List. . . . .	52
<b>5 Operational Environment</b>	<b>55</b>
5.1 Supported Environments . . . . .	55
5.1.1 Operating Systems . . . . .	55
5.1.2 Terminal Servers . . . . .	55
5.1.3 Directories . . . . .	55
5.1.4 Browsers . . . . .	56
5.1.5 Others . . . . .	56
5.1.6 Flash . . . . .	56
5.2 Windows. . . . .	56
5.3 Terminal Emulators . . . . .	57
5.4 Web or Internet. . . . .	58



---

# About This Guide

This document provides to you an overview of the features, functionality, customizing, and administration of SecureLogin.

## Additional Documentation

For the latest version of SecureLogin guides, see [www.netiq.com/documentation/securelogin/](http://www.netiq.com/documentation/securelogin/)

## Contacting Sales Support

For questions about products, pricing, and capabilities, contact your local partner. If you cannot contact your partner, contact our Sales Support team.

<b>Worldwide:</b>	<a href="http://www.netiq.com/about_netiq/officelocations.asp">www.netiq.com/about_netiq/officelocations.asp</a>
<b>United States and Canada:</b>	1-888-323-6768
<b>Email:</b>	<a href="mailto:info@netiq.com">info@netiq.com</a>
<b>Web Site:</b>	<a href="http://www.netiq.com">www.netiq.com</a>

## Contacting Technical Support

For specific product issues, contact our Technical Support team.

<b>Worldwide:</b>	<a href="http://www.netiq.com/support/contactinfo.asp">www.netiq.com/support/contactinfo.asp</a>
<b>North and South America:</b>	1-713-418-5555
<b>Europe, Middle East, and Africa:</b>	+353 (0) 91-782 677
<b>Email:</b>	<a href="mailto:support@netiq.com">support@netiq.com</a>
<b>Web Site:</b>	<a href="http://www.netiq.com/support">www.netiq.com/support</a>

## Contacting Documentation Support

Our goal is to provide documentation that meets your needs. If you have suggestions for improvements, click **Add Comment** at the bottom of any page in the HTML versions of the documentation posted at [www.netiq.com/documentation](http://www.netiq.com/documentation). You can also email [Documentation-Feedback@netiq.com](mailto:Documentation-Feedback@netiq.com). We value your input and look forward to hearing from you.

## Contacting the Online User Community

Qmunity, the NetIQ online community, is a collaborative network connecting you to your peers and NetIQ experts. By providing more immediate information, useful links to helpful resources, and access to NetIQ experts, Qmunity helps ensure you are mastering the knowledge you need to realize the full potential of IT investments upon which you rely. For more information, visit <http://community.netiq.com>.

---

# 1 About SecureLogin

In large enterprises and organizations, employees must interact with multiple applications and access sensitive information. Each application has its own authentication methods that require users to specify different usernames and passwords. This forces the users to maintain and manage different usernames and passwords to each of the numerous applications, which can be inconvenient and difficult.

To resolve these issues, a solution is needed to avoid the necessity of users remembering numerous passwords while simultaneously providing users access to the required sensitive data without compromising on security.

SecureLogin is a single sign-on product that provides this kind of ease for password management.

SecureLogin utilities and components are designed to enable single sign-on for Windows, Web, Java, and terminal emulator applications.

It supports both username and password authentication, and also multi-factor authentication such as smart card, token, or biometric authentication at the network and application levels.

SecureLogin has the following features:

- ♦ Eliminates the requirement for users to remember multiple usernames and passwords beyond their initial login. It stores usernames and passwords and automatically specifies them for users when required. With this feature, users are no longer required to remember and manually provide their credentials to log in to an application.
- ♦ It quickly retrieves and specifies user credentials, which results in faster login.
- ♦ It helps reduce calls to the Help Desk about locked accounts and forgotten usernames and passwords.
- ♦ It makes use of multiple integrated security systems that provide authentication and single sign-on to networks and applications.

It provides a single entry point to the corporate network and its user resources, which increases security and enhances compliance with corporate security policies.

- ♦ It stores and encrypts user credentials in the directory: eDirectory, Active Directory, or other LDAP-compliant directories, and optionally caches them in an encrypted format on the local workstation.

With this level of encryption, an administrator with complete rights cannot view a user's credentials.

If required, an administrator can set a new password under some circumstances, such as disaster recovery, but cannot view the existing password.

- ♦ Client Login Extension 3.7 provides password recovery for network login credentials. The password recovery support through Client Login Extension tool is also available for locked workstations and for workstations in which user operations are controlled by Desktop Automation Services (DAS).
- ♦ It employs two methods of fault tolerance:
  - ♦ It uses local encrypted caching to ensure that the network downtime does not affect the single sign-on performance. If the corporate network is down, caching enables application logins to continue uninterrupted.
  - ♦ It uses application definitions to cater to different login conditions and errors during the login.

It maintains single sign-on integrity for all mobile and remote users by locally encrypting the cache regardless of the network connectivity. If permitted, mobile users can update their single sign-on credentials when they are disconnected from the network and update the directory with these details when they attach later.

Because SecureLogin is a directory-enabled product, users can:

- ♦ Log in from anywhere and get capabilities as if they were working from their own desks.
- ♦ Log in and log out quickly because they authenticate only to the directory, and not to Windows itself.
- ♦ Roam the enterprise and log in to different machines during the day.
- ♦ Work on a laptop in a disconnected mode because their login credentials are saved to a local, encrypted cache.
- ♦ Securely use a shared, kiosk-type workstation where many people log in temporarily for quick work, then log out.

SecureLogin includes wizards, directory console plug-in, and tools which make it easy to centrally configure for use on the corporate network.

Includes management utilities that allows the administrators and end-users to view their single sign-on details and, if permitted enable single sign-on applications.



---

# 2 SecureLogin Interface

This section consists of the following sections:

- ♦ [Section 2.1, “SecureLogin Client Utility,” on page 9](#)
- ♦ [Section 2.2, “The Administrative Management Utilities,” on page 10](#)
- ♦ [Section 2.3, “SecureLogin Icon,” on page 12](#)
- ♦ [Section 2.4, “Application Types and Descriptions,” on page 13](#)
- ♦ [Section 2.5, “The Applications Pane,” on page 14](#)
- ♦ [Section 2.6, “The Logins Pane,” on page 16](#)
- ♦ [Section 2.7, “The Preferences Properties Table,” on page 17](#)
- ♦ [Section 2.8, “The Password Policy Properties Table,” on page 36](#)
- ♦ [Section 2.9, “The Advanced Settings Pane,” on page 40](#)
- ♦ [Section 2.10, “The Passphrase Policy Properties Table,” on page 41](#)
- ♦ [Section 2.11, “The Distribution Pane,” on page 45](#)

## 2.1 SecureLogin Client Utility

SecureLogin Client Utility interface consists of a title bar, menu bar, panes, and properties tables.

When a folder in the navigation tree is selected, the related information is displayed in the right pane. To display the objects associated with the folders in the navigation tree, click the plus (+) symbol next to the icon to expand its contents.

The navigation tree in the left pane contains the following:

- ♦ **Applications**
- ♦ **My Logins**
- ♦ **Preferences**
- ♦ **Password Policies**

Changes made by using SecureLogin Client Utility on the local workstation apply only to the currently logged-in user's single sign-on and they override the settings made in the directory.

SecureLogin Client Utility is used for:

- ♦ Providing the users with the capability to configure the SecureLogin environment and view their credentials.
- ♦ Testing SecureLogin configuration before mass deployment.
- ♦ Creating and modifying the application definitions for testing.
- ♦ Managing credentials and applications when installed in Standalone mode.
- ♦ Troubleshooting.

For more information see, the [NetIQ SecureLogin Administration Guide](#).

## 2.2 The Administrative Management Utilities

SecureLogin consists of an administrative management utility and plugin-ins for integration with NetIQ and Microsoft directory management utilities.

Through the Administrative Management utilities you can set up and administer SecureLogin for a user.

---

**IMPORTANT:** The **Install Directory administration tools** option must be selected during SecureLogin installation.

---

The directory administration tools are:

- ♦ [Section 2.2.1, “iManager,” on page 10](#)
- ♦ [Section 2.2.2, “SLManager,” on page 12](#)
- ♦ [Section 2.2.3, “Microsoft Management Console Snap-In,” on page 12](#)

### 2.2.1 iManager

iManager is a state-of-the-art Web-based administration console for eDirectory environments, that provides customized secure access to network administration utilities and content from any location in the world. With a global view of your network from one browser-based tool, you can proactively assess and respond to changing network demands.

---

**IMPORTANT:** Throughout this document, we refer to iManager as the Administrative management Utility to explain the various administration procedures.

The graphics also represent iManager set up.

---

### Starting iManager

Accessing iManager varies based on the iManager version (server-based or workstation) and the platform on which iManager is running.

#### Accessing Server-Based iManager

- 1 Review the list of [Supported Browsers](https://www.netiq.com/documentation/imanager/imanager_admin/data/bouqsqh.html) ([https://www.netiq.com/documentation/imanager/imanager\\_admin/data/bouqsqh.html](https://www.netiq.com/documentation/imanager/imanager_admin/data/bouqsqh.html)). In a supported Web browser, type the following in the Address (URL) field:

`http://server_IP_address/nps/iManager.html`

For example:

`http://127.0.0.1/nps/iManager.html`

You might be redirected to an HTTPS secure page

---

**IMPORTANT:** The URL is case sensitive.

---




- 2 Log in using your username, password, and eDirectory tree name.

You can substitute the IP address of an eDirectory server for the tree name.

To have full access to all iManager features, you must log in as a user with administrator-equivalent rights to the tree.

For details on accessing iManager, go to the [NetIQ Documentation Web site for iManager](https://www.netiq.com/documentation/) (<https://www.netiq.com/documentation/>)


- 3 Click **OK**. The Roles and Tasks page is displayed. Scroll down to the Manage SecureLogin SSO and then browse to an object in the tree. The SecureLogin SSO page with single sign-on options is displayed.

**Manage SecureLogin SSO:**  Writer.novell  

**SecureLogin SSO**

[Applications](#) | [Logins](#) | [Distribution](#) | [Password policies](#) | [Preferences](#) | [Advanced Settings](#)

**Applications**

All 

[New](#) | [Edit](#) | [Delete](#)

<input type="checkbox"/>	Application	Id	Type	Source
--------------------------	-------------	----	------	--------

OK Cancel Apply

## Accessing iManager on a Workstation

- 1 Browse to the iManager set up on your workstation.
- 2 Execute `imanager\bin\iManager.bat`.
- 3 Log in by using your username, password, and tree name.
- 4 Select an object. The SecureLogin SSO properties are displayed.

The navigation tree in the top consists of the following options:

- ♦ **Applications**
- ♦ **Logins**
- ♦ **Distribution**
- ♦ **Password Policies**
- ♦ **Preferences**
- ♦ **Advanced Settings**

---

**NOTE:** The same options are available in SecureLogin Manager too.


---

## 2.2.2 SLManager

- 1 Click **Start > Programs > SecureLogin > SecureLogin Manager**.

The SecureLogin Manager is displayed.

- 2 From the **Object** drop-down list, select the object or specify the full distinguished name (DN) of the user object, container, or the organizational unit for administration.

Alternatively, use the  icon to navigate to the appropriate object.

- 3 Press Enter to submit the entry specified in the object field.

Clicking **OK** closes the dialog box and cancels the specified entry.

## 2.2.3 Microsoft Management Console Snap-In

Use the Microsoft Management Console (MMC) snap-in for Active Directory deployments.




### Starting MMC

- 1 On the Windows **Start** menu, select **Programs > Administrative Tools > Active Directory Users and Computers**. The Microsoft Management Console is displayed.
- 2 Browse or search for the desired directory object and open its properties. A new tab is displayed with the SecureLogin icon displayed. Select this tab to configure SecureLogin information for this object.

## 2.3 SecureLogin Icon

SecureLogin icon appears on the workstation's notification area (system tray) and provides quick access to common functions in the management utilities and wizards. When you left click the icon, the list of application window that are available for single sign-on, is displayed.

*Table 2-1 SecureLogin Icon Status*

If	Then
SecureLogin is active.	SecureLogin icon appears on the notification area as  .
SecureLogin is inactive.	SecureLogin icon appears on the notification area as  <b>NOTE:</b> In this case, SecureLogin does not perform single sign-on functions such as decrypting and passing credentials to applications.
SecureLogin caches applications	SecureLogin icon appears on the notification area as  .

Following are the options that are available by right-clicking SecureLogin icon on the notification area.

*Table 2-2 SecureLogin Icon Menu Options*

Option	Function
<b>Add Application</b>	Launches the Add Application Wizard.

Option	Function
Manage Logins	Launches SecureLogin Client Utility.
New Login	Launches the Add New Login Wizard.
Advanced	Has some advanced SecureLogin management options. See <a href="#">Table 2-3 on page 13</a> .
Active	Displays a check ( ✓ ) mark when SecureLogin is active on the workstation.
About	Displays information about SecureLogin and your system.
Log Off User	Allows you to shut down all programs, including SecureLogin, and log out the user from the workstation.
Close	Closes SecureLogin on the workstation.

Following are the options available on the **Advanced** menu:


**Table 2-3** SecureLogin Advanced Menu Options






Option	Function
Change Preferences	Launches SecureLogin Client Utility with the <b>Preferences</b> properties table displayed.
Change Passphrase	Displays the <b>Passphrase</b> dialog box. It enables users to change their passphrase answer.
Refresh Cache	Manually executes the synchronization of data between the local cache and directory data.
Backup User Information	Enables the user to backup SecureLogin information to an encrypted XML file.  The backup can include applications, credentials, and/or settings that are defined for the currently logged in user.
Restore User Information	Allows the restoration of a users SecureLogin information from an encrypted XML file generated with the Backup User Information option.
Work Offline / Work Online	Toggles between offline and online network access.  Displays whether the user is connected to the network or not.  <b>NOTE:</b> This is not displayed in standalone mode.

## 2.4 Application Types and Descriptions

The following table describes the application type icons as available in SecureLogin Manager:



**Table 2-4** Application Types and Description

Icon	Application Type	Description
	Generic	The name of the application executable.

Icon	Application Type	Description
	Java	<ul style="list-style-type: none"> <li>♦ The Web page URL containing the JavaScript login, for example, <code>http://javaboutique.internet.com/KiserPassword</code>.</li> <li>♦ Class name of the application (if it is a stand-alone Java application).</li> </ul>
	Startup	This must be configured in the application definition editor. For more information, see the <a href="#">NetIQ SecureLogin Application Definition Guide</a> .
	Terminal Emulator	The name of the emulator. For example, <code>PLAY3270.A3D</code> .
	Web	<p>All or part of the URL of the Web page or an application. The name can apply to an entire Web site or a specific Web page.</p> <p>For example, the domain name <code>www.novell.com</code> activates SecureLogin application definition on any page on the NetIQ Web site. Alternatively, <code>www.novell.com/</code> activates the application definition solely on the specified Web page.</p>
	Windows	The ID of the application that will define whether the application definition applies to DotNet or a Windows executable. For example, Windows executable displays the ID as <code>notepad.exe</code> and .Net application displays the ID as <code>notepad</code> .


The following table describes the application details icons as available in SecureLogin Manager:

**Table 2-5** *Application Details*

Icon	Description
	A red triangle in the lower right corner of an application icon indicates that the application definition is inherited from some other object in the directory. For example the users organization unit.
	An application icon without the red triangle in the lower corner is an application definition or a predefined application that is not inherited from a higher-level object.

## 2.5 The Applications Pane

**Figure 2-1** *The Applications Pane in SecureLogin Manager*




From the applications pane, users can create and modify SecureLogin application definitions that enable the single sign-on. For details, see the [NetIQ SecureLogin Application Definition Guide](#).

To display a specific application, double-click an application in the navigation tree or in the Application pane. The Application pane for that specific application is displayed. It contains three tabs:

- ♦ [Section 2.5.1, “The Details Tab,” on page 15](#)
- ♦ [Section 2.5.2, “The Definition Tab,” on page 15](#)
- ♦ [Section 2.5.3, “The Settings Tab,” on page 16](#)

## 2.5.1 The Details Tab

*Figure 2-2 The Details Tab in SecureLogin Manager*



The **Details** tab contains:

- ♦ The Application description that uniquely identifies the application definition or the predefined application along with the type of the application. The application definition or the predefined application definition is either the name given by SecureLogin or the name specified by the user.
- ♦ Identity of the Application. The identity differs depending on the application definition type (.NET type, JAVA class name, URL or application name).
- ♦ The credentials (login) linked to the application and tools to create, edit, and delete these credentials.

## 2.5.2 The Definition Tab

The Definition tab contains the application definition. An application definition directs how SecureLogin responds to various screens (dialog boxes, web pages, etc.) returned by the application. The details displayed vary depending on the type of application definition. For applications generated by the SecureLogin add application wizard the wizard details and parameters will be displayed. For pre-built, converted wizard, or manually created definitions, the application script will be displayed.

---

**NOTE:** Predefined Web applications such as eBay and Hotmail under the **Type** option are titled **Web** and not **Advanced Web**. There is no difference between a Web application definition and an Advanced Web application definition.

---

## 2.5.3 The Settings Tab

The **Settings** tab contains the advanced options for the predefined application or the application definition.

The following table describes the settings for Terminal Emulator, Windows, Startup, Java, and Generic Applications:

**Table 2-6** Settings for the Windows Applications

Item	Description
<b>Prompt for device reauthentication for this application</b>	If <b>Yes</b> is selected, users are prompted for device reauthentication for the application.
<b>Reauthentication Method</b>	Allows the user to re-authenticate against an advanced authentication device. For example a smart card.

The following table describes the settings for Web applications:

**Table 2-7** Settings for Web Applications

Item	Description
<b>Allow web page to load while Application Definition is running (Web applications only)</b>	<p>This applies to Microsoft Internet Explorer and the application definitions created for Web pages and JavaScript logins that are executed in a Web page.</p> <p>By default, this option is set to <b>No</b>. This suspends the completion of any other Internet Explorer tasks until the login is completed.</p> <p>If this option is set to <b>Yes</b>, then the Internet Explorer continues to function while SecureLogin is executing the login.</p>
<b>Password field must exist on Internet Explorer page for Application Definition to run (Web applications only)</b>	<p>This applies to the Microsoft Internet Explorer and application definitions created for the Web pages and JavaScripts within the Web pages.</p> <p>If <b>Yes</b> is selected, it ensures that SecureLogin does not execute the automated login on pages without the password field.</p> <p>If <b>No</b> is selected, SecureLogin will continually scan all pages when loaded regardless of whether there is a password field or not. This allows for the ability to script for automation of status messages or other user related activities. For example, a change password successful or failure message.</p>

## 2.6 The Logins Pane

The **My Logins** pane in SecureLogin Client Utility manages the logins that applications require to log in, along with their associated credentials, including:

- ♦ Username
- ♦ User ID



- ♦ Login ID
- ♦ Password
- ♦ PINs
- ♦ Domain
- ♦ Database names
- ♦ Server IP address

Through the Logins pane, the user can:

- ♦ Link the logins manually, including the host IP addresses to the applications.
- ♦ Configure the credential sets at the Group policy, organizational unit, container, and the user object level.
- ♦ Enable the group of users to be configured with seamless login access to an application with one account or by logging in with the username and password.

## 2.7 The Preferences Properties Table

The **Preferences** properties table provides settings to configure the parameters of the user's SecureLogin environment. This table includes the applications that are permitted to be enabled for single sign-on and includes access to SecureLogin management and administration tools.

For more information about the various options or preferences that are available for SecureLogin Client Utility, SecureLogin Manager, and iManager, see [Table 2-9](#) to [Table 2-12](#). The description includes the information on whether the specified preference is available for all management utilities or only a specific management utility.

### 2.7.1 Configuring Preferences Introduced In SecureLogin Version 6

Prior to configuring preferences, administrators should refer to the [Configuring](#) section of the [NetIQ SecureLogin Administration Guide](#) for important information regarding SecureLogin functionality using different datastore versions. This is important in environments that include pre-SecureLogin 6.0 clients.


SecureLogin version 6 introduced a range of new security features and preferences, including the storage of single sign-on credentials on the user's smart card, encryption of the data store using Public Key Infrastructure (PKI)-based credentials and support for the Advanced Encryption Standard (AES) encryption algorithm. These new preferences required changes to SecureLogin 6.0 datastore format to support them.

#### Viewing and modifying application definitions

The **Preferences** are displayed on the right pane when **Preferences** is clicked in the Management utility.

Click the plus (+) symbol next to the names of the preferences to expand the preference options.

Figure 2-3 The Preferences



In previous versions of SecureLogin, the application definition preference was a single preference called **Allow users to view and modify application definitions**. This is now split into two preferences:

- ♦ **Allow application definition to be modified by users**
- ♦ **Allow application definition to be viewed by users**

When you upgrade from a previous version of SecureLogin to the latest version, if you are using the legacy directory data (that is, data from SecureLogin 6.0 or 3.5) and if the **Allow users to view and modify application definition to be modified by users** option was set to **No**, then the new **Allow application definition to be modified by users** for the latest SecureLogin is disabled and dimmed.

Administrators must reset the **Allow application definition to be viewed by users** option to **Yes** before users can modify the application definitions.

The Preferences has the following categories:

- ♦ Table 2-8, "The .Net Preferences," on page 19
- ♦ Table 2-9, "The General Preferences Properties Table," on page 19
- ♦ Table 2-10, "The Java Preferences Properties Table," on page 31
- ♦ Table 2-11, "The Web Preferences Properties Table," on page 32
- ♦ Table 2-12, "The Windows Preferences Properties Table," on page 34

User or the administrators can change the value of the Preferences in the Administrative Management utility or SecureLogin Client Utility unless otherwise specified.

The administrators can restrict the user's access to this table through the centrally controlled administrative preferences.

---

**NOTE:** The **Security** preferences are not available in SecureLogin Client Utility.

---

**Table 2-8** The .Net Preferences

Preference	Possible Values	Description	Default Value
Allow single sign-on to WindowsAutomation (DotNet) applications	Yes/No/Default	<p>This preference allows single sign-on to the .Net applications.</p> <p>If this preference is set to <b>No</b> then, the application will not be available for single sign-on.</p>	The default value is <b>Yes</b> .
Add application prompts for WindowsAutomation (DotNet) applications	Yes/No/Default	<p>This preference prompts to add a .Net application for defining the application definition.</p> <p>If this preference is set to <b>No</b> then, the Add Application window is not launched when you launch any .Net application.</p>	The default value is <b>Yes</b> .
Start the WindowsAutomation (DotNet) monitor/automation worker	Yes/No/Default	<p>This preference will start the DotNetSSO process.</p> <p>The <b>Start the WindowsAutomation (DotNet) monitor/automation worker</b> preference replaces the DISABLE_DOTNETSSO registry setting.</p>	The default value is <b>Yes</b> .

**Table 2-9** The General Preferences Properties Table

Preference	Possible Values	Description	Default Value
Allow "Close" option via system tray	Yes/No/Default	<p>This preference controls whether users can access the <b>Close</b> option from SecureLogin icon on the notification area (system tray).</p> <p>If the option is set to <b>No</b>, the <b>Close</b> option is shown as disabled in the SecureLogin notification area (system tray) icon.</p> <p>If this option is set to <b>Yes</b> or <b>Default</b>, the <b>Close</b> option is displayed and accessible in the SecureLogin notification area (system tray) icon.</p> <p><b>NOTE:</b> This preference requires SecureLogin 6.0 datastore if the value is changed.</p> <p>This preference is available through the administrative management utilities (iManager, SLManager, and MMC snap-ins).</p>	The default value is <b>Yes</b> .

Preference	Possible Values	Description	Default Value
Allow "Refresh Cache" option via system tray	Yes/No/Default	<p>This preference controls whether users can refresh cache using the <b>Advanced &gt; Refresh Cache</b> option from the SecureLogin icon on the notification area (system tray).</p> <p>If this option is set to <b>Yes</b>, the <b>Refresh Cache</b> option is displayed and accessible in the notification area (system tray) icon.</p> <p>If this option is set to <b>No</b> or <b>Default</b>, the <b>Refresh Cache</b> option is not displayed in the notification area (system tray) icon.</p> <p><b>NOTE:</b> This preference requires SecureLogin 6.0 datastore if the value is changed.</p> <p>This preference is available through the administrative management utilities (iManager, SLManager, and MMC snap-ins).</p>	The default value is <b>No</b> .
Allow "Log Off" option via system tray	Yes/No/Default	<p>This preference controls if users can log out from a session using <b>Log Off User</b> option from the SecureLogin icon on the notification area (system tray).</p> <p>If this option is set to <b>No</b>, the <b>Log Off User</b> option is not displayed and accessible in the SecureLogin notification area (system tray) icon.</p> <p>If this option is set to <b>Yes</b> or <b>Default</b>, the <b>Log Off User</b> option is displayed and accessible in the SecureLogin notification area (system tray) icon.</p> <p>This preference is available through the administrative management utilities (iManager, SLManager, and MMC snap-ins).</p>	The default value is <b>Yes</b> .
Allow "Work Offline" option via system tray	Yes/No/Default	<p>This preference controls whether users can work in offline cache mode using the <b>Advanced &gt; Work Offline</b> option.</p> <p>If this option is set to <b>Yes</b> or <b>Default</b>, the <b>Work Offline</b> option is displayed in the notification area (system tray) icon.</p> <p>If this option is set to <b>No</b>, the <b>Work Offline</b> option is not displayed in the notification area (system tray) icon.</p> <p>This preference is available through the administrative management utilities (iManager, SLManager, and MMC snap-ins).</p>	The default value is <b>Yes</b> .

Preference	Possible Values	Description	Default Value
Allow application definition to be modified by users	Yes/No/Default	<p>This preference controls whether users can modify application definitions using the <b>Definitions</b> tabs in the Applications pane of the SecureLogin Client Utility.</p> <p>If this option is set to <b>Yes</b> or <b>Default</b>, the end user can view and modify their application definitions.</p> <p>If this option is set to <b>No</b>, the end user cannot change their application definitions.</p> <p><b>NOTE:</b> If the Allow application definition to be viewed by users is set to No, then this option is cannot be edited.</p> <p>Disabling this preference does not disable the users from creating new applications through the wizards.</p> <p>This preference requires SecureLogin 6.0 datastore if the value is changed.</p> <p>This preference is available through the administrative management utilities (iManager, SLManager, and MMC snap-ins).</p>	The default option is <b>Yes</b> .
Allow application definition to be viewed by users	Yes/No/Default	<p>This preference controls whether users can view application definitions using the <b>Definitions</b> tabs in the Applications pane of the SecureLogin Client Utility.</p> <p>If this option is set to <b>Yes</b> or <b>Default</b>, users can view the application definition.</p> <p>If this option is set to <b>No</b>, users cannot view the application definition.</p> <p>This preference is available through the administrative management utilities (iManager, SLManager, and MMC snap-ins).</p>	The default value is <b>Yes</b> .

Preference	Possible Values	Description	Default Value
Allow credentials to be deleted by users through the GUI	Yes/No/Default	<p>This preference controls whether users can delete their credentials using the SecureLogin Client Utility available from Manage Logins from the SecureLogin icon in the notification area (system tray).</p> <p><b>NOTE:</b> If Allow credentials to be modified by users through the GUI is set to <b>No</b>, then this option is automatically set to <b>No</b> and not editable.</p> <p>This preference requires SecureLogin 6.0 datastore if the value is changed.</p> <p>If this option is set to <b>Yes</b> or <b>Default</b>, users can delete their credentials through the GUI.</p> <p>If this option is set to <b>No</b>, users cannot delete their credentials.</p> <p>This preference is available through the administrative management utilities (iManager, SLManager, and MMC snap-ins).</p>	The default value is <b>Yes</b> .
Allow credentials to be modified by users through the GUI	Yes/No/Default	<p>This preference controls whether users can modify their credentials using the SecureLogin Client Utility available from Manage Logins from the SecureLogin icon in the notification area (system tray).</p> <p>If this option is set to <b>Yes</b> or <b>Default</b>, users can modify their credentials through the GUI.</p> <p>If this option is set to <b>No</b>, users cannot modify their credentials through the GUI. They can only view the credentials.</p> <p>This preference is available through the administrative management utilities (iManager, SLManager, and MMC snap-ins).</p>	The default value is <b>Yes</b> .

Preference	Possible Values	Description	Default Value
Allow users to (de) activate SSO via system tray	Yes/No/Default	<p>This preference controls whether users can activate or deactivate SecureLogin through the SecureLogin icon in the notification area (system tray).</p> <p>If this option is set to <b>Yes</b> or <b>Default</b>, users can switch between active and inactive modes of SecureLogin.</p> <p>If this option is set to <b>No</b>, users cannot switch between active and inactive modes.</p> <ul style="list-style-type: none"> <li>♦ If SecureLogin status was active when this preference was applied, it remains as active and the user cannot de-activate SecureLogin.</li> <li>♦ If SecureLogin status was inactive when this preference was applied, it remains as inactive and the user cannot change SecureLogin status to <b>Active</b>.</li> </ul> <p>This preference requires SecureLogin 6.0 datastore if the value is changed.</p> <p>This preference is available through the administrative management utilities (iManager, SLManager, and MMC snap-ins).</p>	The default value is <b>Yes</b> .
Allow users to backup/restore	Yes/No/Default	<p>This preference controls whether users can backup and restore their information from the <b>Advanced</b> menu of the SecureLogin icon on the notification area (system tray).</p> <p>If this option is set to <b>Yes</b> or <b>Default</b>, users can back up and restore their single sign-on information.</p> <p>If this option is set to <b>No</b>, users cannot back up and restore their single sign-on configuration.</p> <p>This preference is available through the administrative management utilities (iManager, SLManager, and MMC snap-ins).</p>	The default value is <b>Yes</b> .

Preference	Possible Values	Description	Default Value
Allow users to change passphrase	Yes/No/Default	<p>This preference controls whether users can change their passphrase question and answer. The <b>Change Passphrase</b> option is available from the <b>Advanced</b> menu of the SecureLogin icon on the notification area (system tray).</p> <p>If this option is set to <b>Yes</b> or <b>Default</b>, users can change their passphrase through the notification area (system tray) icon.</p> <p>If this option is set to <b>No</b>, users cannot change their passphrase through the notification area (system tray) icon.</p> <p>This preference is available through the administrative management utilities (iManager, SLManger, and MMC snap-ins).</p>	The default value is <b>Yes</b> .
Allow users to modify names of Applications and Logins	Yes/No/Default	<p>This preference controls whether users can edit the names of their Application login credentials using the <b>Details</b> tab &gt; <b>Edit</b> function in the SecureLogin Client Utility.</p> <p>If this option is set to <b>Yes</b> or <b>Default</b>, the user can edit the names of their credentials (either by right-clicking on the credential and selecting Rename, or by a slow double-click on the credential name).</p> <p>If this option is set to <b>No</b>, the use cannot edit the names of the credentials.</p> <p>This preference is available through the administrative management utilities (iManager, SLManger, and MMC snap-ins).</p>	The default value is <b>No</b> .
Allow users to view and change Preferences	Yes/No/Default	<p>This preference controls whether users can view and update their preferences.</p> <p>If this option is set to <b>Yes</b> or <b>Default</b>, users can view and change their preferences.</p> <p>If this option is set to <b>No</b>, users cannot view and change their preferences.</p> <p><b>NOTE:</b> Create a separate ou for administrators to ensure that they are not adversely affected by the general user configuration preferences at the ou level.</p> <p>This preference is available through the administrative management utilities (iManager, SLManger, and MMC snap-ins).</p>	The default value is <b>Yes</b> .



Preference	Possible Values	Description	Default Value
Allow users to view and modify API preferences	Yes/No/Default	<p>This preference controls whether users can view and modify API options using the Preferences pane of the SecureLogin Client Utility.</p> <p>The API preference defines the following options for users to:</p> <ul style="list-style-type: none"> <li>♦ Enter an API license key(s).</li> <li>♦ Provide API access.</li> </ul> <p>If this option is set to <b>Yes</b> or <b>Default</b> users can view and modify the API preference.</p> <p>If this option is set to <b>No</b>, users cannot view and modify the API preference.</p> <p><b>NOTE:</b> This preference affects what is displayed in the SecureLogin Client Utility using Change Preferences from the Advanced menu.</p> <p>This preference is available through the administrative management utilities (iManager, SLManager, and MMC snap-ins).</p>	The default value is <b>Yes</b> .
Allow users to view passwords	Yes/No/Default	<p>This preference controls whether users can view their passwords using <b>Show Passwords</b> in the <b>Application</b> pane &gt; <b>Details</b> of the SecureLogin Client Utility.</p> <p>If this option is set to <b>Yes</b> or <b>Default</b>, users can view their passwords.</p> <p>If this option is set to <b>No</b>, users cannot view their passwords.</p> <p><b>NOTE:</b> Allowing users to view their passwords gives them an opportunity to view and record passwords if they need to reset the SecureLogin configuration.</p> <p>This preference is available through the administrative management utilities (iManager, SLManager, and MMC snap-ins).</p>	The default value is <b>Yes</b> .
Change the cache refresh interval (in minutes)	5	<p>This preference defines the time in minutes the synchronization of user data and directory on the local workstation.</p> <p>This preference is available in both the SecureLogin Client Utility and the administrative management utilities (iManager, SLManager, and MMC snap-ins).</p>	The default value is set to <b>5</b> minutes.

Preference	Possible Values	Description	Default Value
Detect incorrect passwords	Yes/No/Default	<p>Predefined applications generally include commands to respond to incorrect password dialogs. This preference enables SecureLogin to respond to incorrect passwords for web applications. SecureLogin will monitor the time period between successive attempts to enter the credential information into the same application. If the time period is too short SecureLogin assumes that the login is failing due to bad credentials.</p> <p>If this option is set to <b>Yes</b> or <b>Default</b>, incorrect passwords for Web applications are detected.</p> <p>If this option is set to <b>No</b>, incorrect passwords for Web applications are not detected.</p> <p>This preference is available in both the SecureLogin Client Utility and the administrative management utilities (iManager, SLManager, and MMC snap-ins).</p>	The default value is <b>Yes</b> .
Disable single sign-on	Yes/No/Default	<p>This preference controls the users access to running SecureLogin.</p> <p>If this option is set to <b>Yes</b>, access to SecureLogin is disabled and it will not start when run either automatically at startup or when run manually.</p> <p>If this option is set to <b>No</b> or <b>Default</b>, access to SecureLogin is enabled and will start normally.</p> <p>This preference is available through the administrative management utilities (iManager, SLManager, and MMC snap-ins).</p>	The default value is <b>No</b> .
Display splash screen on startup	Yes/No/Default	<p>This preference controls the display of the SecureLogin splash screen during startup.</p> <p>If this option is set to <b>Yes</b> or <b>Default</b>, the splash screen appears when SecureLogin startup.</p> <p>If this option is set to <b>No</b>, the splash screen is hidden and users cannot see the splash screen when SecureLogin startup.</p> <p><b>NOTE:</b> This preference requires SecureLogin 6.0 datastore if the value is changed.</p> <p>This preference is available through the administrative management utilities (iManager, SLManager, and MMC snap-ins).</p>	The default value is <b>Yes</b> .

Preference	Possible Values	Description	Default Value
Display the system tray icon	Yes/No/Default	<p>This preference controls the display of SecureLogin icon in the notification area (system tray).</p> <p>If this option is set to <b>Yes</b> or <b>Default</b>, the SecureLogin icon appears on the notification area (system tray).</p> <p>If this option is set to <b>No</b>, the SecureLogin icon does not appear on the notification area (system tray).</p> <p><b>NOTE:</b> When the SecureLogin icon is visible, users can double-click the icon on the notification area (system tray) to launch the SecureLogin Client Utility.</p> <p>When the SecureLogin is not visible, users can start the SecureLogin Client Utility through <b>Start &gt; Programs &gt; SecureLogin &gt; SecureLogin</b></p> <p>This preference is available through the administrative management utilities (iManager, SLManager, and MMC snap-ins).</p>	The default value is <b>Yes</b> .
Enable cache file	Yes/No/Default	<p>This preference controls creating and updating of a SecureLogin cache file on the local workstation. The cache file stores all user configuration data; local and inherited.</p> <p>Set this option to <b>Yes</b> or <b>Default</b>, the cache file is saved on the local workstation in the directory that was specified during install.</p> <p>Users with roaming profiles should always have this setting as <b>Yes</b>.</p> <p>Set this option to <b>No</b> if you cannot store cache files locally or if this causes conflicts with your organizational security policy.</p> <p>This preference is available in both the SecureLogin Client Utility and the administrative management utilities (iManager, SLManager, and MMC snap-ins).</p>	The default value is <b>Yes</b> .

Preference	Possible Values	Description	Default Value
Enable logging to Windows Event log	Yes/No/Default	<p>This preference controls sending the log events to Windows Event Log.</p> <p>If set to <b>Yes</b> or <b>Default</b>, log events are sent automatically to Windows Event Log.</p> <p>If set to <b>No</b>, the log events are not sent to Windows Event Log.</p> <p>Only the following events are logged:</p> <ul style="list-style-type: none"> <li>◆ SSO client started</li> <li>◆ SSO client exited</li> <li>◆ SSO client activated by user</li> <li>◆ SSO client deactivated by user</li> <li>◆ Password provided to an application by a script</li> <li>◆ Password changed by the user in response to a change password command</li> <li>◆ Password changed automatically in response to a change password command.</li> </ul> <p><b>NOTE:</b> This preference requires SecureLogin 6.0 datastore if the value is changed.</p> <p>This preference is available through the administrative management utilities (iManager, SLManager, and MMC snap-ins).</p>	The default value is <b>Yes</b> .
Enable the New Login Wizard on the system tray icon	Yes/No/Default	<p>This preference controls whether users can create multiple logins on the same application using the <b>New Login &gt; Add New Login</b> option from the SecureLogin icon on the notification area (system tray).</p> <p>If this option is set to <b>Yes</b> or <b>Default</b>, the New Login menu option is enabled and users can create multiple logins.</p> <p>If this option is set to <b>No</b>, New Login menu option is disabled and users cannot create multiple logins.</p> <p>This preference is available through the administrative management utilities (iManager, SLManager, and MMC snap-ins).</p>	The default value is <b>Yes</b> .

Preference	Possible Values	Description	Default Value
<b>Enforce passphrase use</b>	Yes/No/Default	<p>This preference forces users to set up a passphrase question and answer when SecureLogin is launched by a user for the first time.</p> <p>If this option is set to <b>Yes</b>, users must complete setting up their passphrase before they proceed with any other activity on the workstation.</p> <p>If this option is set to <b>No</b> or <b>Default</b>, users can postpone setting up the passphrase. If the users clicks <b>Cancel</b> or closes the dialog, then SecureLogin does not start.</p> <p>This preference is available through the administrative management utilities (iManager, SLManager, and MMC snap-ins).</p>	The default value is <b>No</b> .
<b>Enter API license key(s)</b>	Specify API license key(s)	<p>Specify the API license key(s) provided by SecureLogin to activate the API functionality for an application.</p> <p>You can add more than one API license key.</p> <p>This preference is available through the administrative management utilities (iManager, SLManager, and MMC snap-ins).</p>	Specify the API license key
<b>Password protect the system tray icon</b>	Yes/No/Default	<p>This preference restricts the users from accessing the SecureLogin icon menu option (from the notification area (system tray) without their network login password.</p> <p>If this option is set to <b>Yes</b>, the SecureLogin icon on the notification area (system tray) is password protected.</p> <p>If this option is set to <b>No</b> or <b>Default</b>, the SecureLogin icon on the notification area (system tray) is not password protected.</p> <p>This preference is available in both the SecureLogin Client Utility and the administrative management utilities (iManager, SLManager, and MMC snap-ins).</p>	The default value is <b>No</b> .
<b>Provide API Access</b>	Yes/No/Default	<p>This preference controls the API functionality use.</p> <p>If this option is set to <b>Yes</b>, the API access is enabled.</p> <p>If this option is set to <b>No</b> or <b>Default</b>, the API access is disabled.</p> <p>This preference is available in both the SecureLogin Client Utility and the administrative management utilities (iManager, SLManager, and MMC snap-ins).</p>	The default value is <b>No</b> .

Preference	Possible Values	Description	Default Value
Stop walking here	Yes/No/Default	<p>This preference controls the inheritance of settings from higher level containers or organizational units.</p> <p>If this option is set to Yes, the inheritance of settings from higher level containers or organizational units is disabled.</p> <p>Set the option to <b>Yes</b> during phased upgrades when higher levels might have a different version of SecureLogin implemented.</p> <p>If this option is set to <b>No</b> or <b>Default</b>, the inheritance of settings from higher level containers or organizational units is enabled.</p> <p>This preference does not apply when SecureLogin is installed in eDirectory environment. The Corporate redirection functionality; that is, the inheritance settings from higher level container or organizational units is bypassed in an eDirectory environment.</p> <p>This preference is available through the administrative management utilities (iManager, SLManager, and MMC snap-ins).</p>	The default value is <b>No</b> .
Wizard mode	Administrator/ User/Disabled	<p>This preference controls the access to the application definition wizard.</p> <p>If this option is set to <b>Administrator</b>, it gives users' complete access to the application definition wizard. Users can create their own application definitions.</p> <p>If this option is set to <b>User</b>, users are only allowed to create new login credential sets for new applications using the auto-detection settings.</p> <p>If this option is set to <b>Disabled</b>, the application definition wizard is not launched.</p> <p><b>NOTE:</b> This preference requires SecureLogin 6.0 datastore if the value is changed.</p> <p>This preference is available through the administrative management utilities (iManager, SLManager, and MMC snap-ins).</p>	The default value is <b>Administrator</b> .

**Table 2-10** The Java Preferences Properties Table

Preference	Possible Values	Description	Default Value
<b>Add application prompts for Java applications</b>	<b>Yes/No/Default</b>	<p>This preference controls whether SecureLogin detects Java application.</p> <p>If the preference is set to <b>Yes</b> or <b>Default</b>, SecureLogin prompts to create a script when a Java application login page is loaded.</p> <p>If the preference is set to <b>No</b>, SecureLogin will not prompt when Java application login page is loaded.</p> <p>This preference is available in both the SecureLogin Client Utility and all the administrative management utilities (iManager, SLManager, and MMC snap-ins).</p>	The default value is <b>Yes</b> .
<b>Allow single sign-on to Java applications</b>	<b>Yes/No/Default</b>	<p>This preference controls whether SecureLogin allows single sign-on for Java applications.</p> <p>If the preference is set to <b>Yes</b> or <b>Default</b>, SecureLogin prompts the user to enter credentials (if none already exist), or submits existing credentials on the Java application login page.</p> <p>If this option is set to <b>No</b>, Java applications are not enabled for single sign-on.</p> <p>This preference is available in both the SecureLogin Client Utility and all the administrative management utilities (iManager, SLManager, and MMC snap-ins).</p>	The default value is <b>Yes</b> .

**Table 2-11** The Web Preferences Properties Table

Preference	Possible Values	Description	Default Value
Add application prompts for Internet Explorer	Yes/No/Default	<p>This preference controls the display of the Web login detection wizard and confirmation dialog box when a Web application is detected and recognized by Internet Explorer.</p> <p>If you select <b>Yes</b> or <b>Default</b>, the user is initially prompted to enable the application and enter the credentials for the application (if not done previously).</p> <p><b>NOTE:</b> When you set the preference to <b>Yes</b>, the information that is displayed for the users depend on the settings of the <b>Wizard mode</b> preference.</p> <p>On subsequent runs of the application, the user is not prompted for credentials and single sign-on occurs seamlessly.</p> <p>If you select <b>No</b>, SecureLogin skips enabling the application for single sign-on, the user is never be prompted to enable the application.</p> <p>This preference is available in both the SecureLogin Client Utility and all the administrative management utilities (iManager, SLManager, and MMC snap-ins).</p>	The default value is <b>Yes</b> .
Add application prompts for Mozilla Firefox	Yes/No/Default	<p>This preference controls the display of Web login detection wizard and confirmation dialog box when a Web application is detected and recognized by Mozilla Firefox.</p> <p><b>NOTE:</b> When you set the preference to <b>Yes</b>, the information that is displayed to the users depend on the settings of the <b>Wizard mode</b> preference.</p> <p>If you select <b>Yes</b> or <b>Default</b>, the user is initially prompted to enable the application and enter the credentials for the application (if not done previously). On subsequent runs of the application, the user is not prompted for credentials and single sign-on occurs seamlessly.</p> <p>If you select <b>No</b>, SecureLogin skips enabling the application for single sign-on on this instance. You are prompted to enable the application when you launch it the next time.</p> <p>This preference is available in both the SecureLogin Client Utility and all the administrative management utilities (iManager, SLManager, and MMC snap-ins).</p>	The default value is <b>Yes</b> .



Preference	Possible Values	Description	Default Value
<b>Add application prompts for Google Chrome</b>	Yes/No/Default	<p>This preference controls the display of Web login detection wizard and confirmation dialog box when a Web application is detected and recognized by Google Chrome.</p> <p>If you select <b>Yes</b> or <b>Default</b> the specified credentials are saved and the application is enabled for single sign-on.</p> <p>If you select <b>No</b>, SecureLogin skips enabling the application for single sign-on on this instance. You are prompted to enable the application when you launch it the next time.</p> <p>This preference is available in both the SecureLogin Client Utility and all the administrative management utilities (iManager, SLManager, and MMC snap-ins).</p>	The default value is <b>Yes</b> .
<b>Allow single sign-on to Internet Explorer</b>	Yes/No/Default	<p>This preference defines single sign-on access to Web application using Internet Explorer.</p> <p>If you select <b>Yes</b> or <b>Default</b> the specified credentials are saved and the application is enabled for single sign-on.</p> <p>If you select <b>No</b>, SecureLogin does not prompt for credentials (if none exist or are incorrect) and does not submit credentials into the application.</p> <p>This preference is available in both the SecureLogin Client Utility and all the administrative management utilities (iManager, SLManager, and MMC snap-ins).</p>	The default value is <b>Yes</b> .
<b>Allow single sign-on Mozilla Firefox</b>	Yes/No/Default	<p>This preference defines single sign-on access to Web application using Mozilla Firefox.</p> <p>If you select <b>Yes</b> or <b>Default</b> the specified credentials are saved and the application is enabled for single sign-on.</p> <p>If you select <b>No</b>, SecureLogin does not prompt for credentials (if none exists or are incorrect) and does not submit credentials into the application.</p> <p>This preference is available in both the SecureLogin Client Utility and all the administrative management utilities (iManager, SLManager, and MMC snap-ins).</p>	The default value is <b>Yes</b> .

Preference	Possible Values	Description	Default Value
Allow single sign-on Google Chrome	Yes/No/Default	<p>This preference defines single sign-on access to Web application using Google Chrome.</p> <p>If you select <b>Yes</b> or <b>Default</b> the specified credentials are saved and the application is enabled for single sign-on.</p> <p>If you select <b>No</b>, SecureLogin skips enabling the application for single sign-on on this instance. You are prompted to enable the application when you launch it the next time.</p> <p>This preference is available in both the SecureLogin Client Utility and all the administrative management utilities (iManager, SLManager, and MMC snap-ins).</p>	The default value is <b>Yes</b> .

**Table 2-12** The Windows Preferences Properties Table

Preference	Possible Values	Description	Default Value
Add application prompts for Windows applications	Yes/No/Default	<p>This preference controls the display of a Windows login detection and confirmation message when a Windows application is detected and recognized.</p> <p>If you select <b>Yes</b> or <b>Default</b>, the user is prompted to enable the application and to enter the credentials for the application (if not done previously).</p> <p>On subsequent runs of the application, the user is not prompted for credentials and single sign-on occurs seamlessly.</p> <p>If you select <b>No</b>, SecureLogin does not prompt the user to add the application for single sign-on skips enabling the application for single sign-on for this instance. You are prompted to enable single sign-on for subsequent runs of the application.</p> <p>This preference is available in both the SecureLogin Client Utility and all the administrative management utilities (iManager, SLManager, and MMC snap-ins).</p>	The default value is <b>Yes</b> .

Preference	Possible Values	Description	Default Value
<b>Allow single sign-on to Windows applications</b>	<b>Yes/No/Default</b>	<p>This preference defines single sign-on access to Windows applications.</p> <p>If you select <b>Yes</b> or <b>Default</b> the specified credentials are saved and the application is enabled for single sign-on.</p> <p>If you select No, SecureLogin will not prompt for credentials (if none exist or are incorrect) and will not submit credentials into the application.</p> <p>This preference is available in both the SecureLogin Client Utility and all the administrative management utilities (iManager, SLManager, and MMC snap-ins).</p>	The default value is <b>Yes</b> .

## 2.8 The Password Policy Properties Table

Figure 2-4 The Password Policy Properties Table

Password Policies	
Setting Description	Value
Minimum length	<input type="text"/>
Maximum length	<input type="text"/>
Minimum punctuation characters	<input type="text"/>
Maximum punctuation characters	<input type="text"/>
Minimum uppercase characters	<input type="text"/>
Maximum uppercase characters	<input type="text"/>
Minimum lowercase characters	<input type="text"/>
Maximum lowercase characters	<input type="text"/>
Minimum numeric characters	<input type="text"/>
Maximum numeric characters	<input type="text"/>
Disallow repeated characters	No <input type="button" value="v"/>
Disallow duplicate characters	No <input type="button" value="v"/>
Disallow sequential characters	No <input type="button" value="v"/>
Begins with an uppercase character	No <input type="button" value="v"/>
Ends with an uppercase character	No <input type="button" value="v"/>
Prohibited characters	<input type="text"/>
Begins with any character	No <input type="button" value="v"/>
Begins with a Number	No <input type="button" value="v"/>
Begins with a special character	No <input type="button" value="v"/>
Ends with any character	No <input type="button" value="v"/>
Ends with a Number	No <input type="button" value="v"/>
Ends with a special character	No <input type="button" value="v"/>

The Password Policies pane contains a list of all the password policies. Through this pane, a user can create a new policy or delete an existing password policy.

Organizations and applications often have rules about the content of passwords, including the required number and type of characters. The Password Policy properties table helps the users to create and enforce these password rules through a password policy, then apply this policy to one or more application logins.

**Table 2-13** *The Password Policy Properties Table*

<b>Policy</b>	<b>Value To Be provided</b>	<b>Description</b>
<b>Minimum length</b>	Whole number	Defines the minimum length of the password; that is, the number of characters required for the password.
<b>Maximum length</b>	Whole number	Defines the maximum length of the password; that is, the maximum number of characters allowed in password.
<b>Minimum punctuation characters</b>	Punctuation characters	Defines the minimum number of punctuation characters allowed in a password. This should be a whole number.
<b>Maximum punctuation characters</b>	Punctuation characters	Defines the maximum number of punctuation characters allowed in a password. This should be a whole number.
<b>Minimum uppercase characters</b>	Whole number	Defines the minimum number of uppercase characters allowed in a password.
<b>Maximum uppercase characters</b>	Whole number	Defines the maximum number of uppercase characters allowed in a password.
<b>Minimum lowercase characters</b>	Whole number	Defines the minimum number of lowercase characters allowed in a password.
<b>Maximum lowercase characters</b>	Whole number	Defines the maximum number of lowercase characters allowed in a password.
<b>Minimum numeric characters</b>	Whole number	Defines the minimum number of numeric characters allowed in a password.
<b>Maximum numeric characters</b>	Whole number	Defines the maximum number of numeric characters allowed in a password.
<b>Disallow repeat characters</b>	<b>No/Yes/Yes, case insensitive</b>	<p>Disallows the use of repeated characters, or the use of the same successive characters.</p> <p>If this option is set to <b>No</b>, characters can be repeated. This is the default value.</p> <p>If this option is set to <b>Yes</b>, same alphabetic characters in a different case are considered as different characters. For example, A and a are different.</p> <p>If this option is set to <b>Yes, case insensitive</b>, the successive use of the same alphabetic characters in a different case is not allowed.</p>

Policy	Value To Be provided	Description
Disallow duplicate characters	No/Yes/Yes, case insensitive	<p>Disallows the use of the same non-successive characters.</p> <p>If this option is set to <b>No</b>, duplicate characters are allowed. This is the default value.</p> <p>If this option is set to <b>Yes</b>, the same alphabetic characters in a different case are considered as different characters. For example, A (uppercase) and a (lowercase) are different.</p> <p>If this option is set to <b>Yes, case insensitive</b>, duplication of the same alphabetic characters in a different case is not allowed.</p>
Disallow sequential characters	No/Yes/Yes, case insensitive	<p>Disallows the use of successive characters in an alphabetical order.</p> <p>If this option is set to <b>No</b>, sequential characters are allowed. This is the default value.</p> <p>If this option is set to <b>Yes</b>, sequential characters in a different case are considered as non-sequential. For example, a and B are non-sequential.</p> <p>If this option is set to <b>Yes, case insensitive</b>, sequential characters in different cases is disallowed.</p>
Begin with an uppercase character	No/Yes	<p>Enforces the use of an uppercase alphabetic character as the beginning character of a password.</p> <p>The default value is <b>No</b>.</p> <p>If this option is set to <b>Yes</b>, all other policies that indicate that a password must begin with a particular character or in a specific manner are disabled.</p> <p><b>IMPORTANT:</b> Only one type of character can be designated as the first value of a password.</p>
End with an uppercase character	No/Yes	<p>Enforces the use of an uppercase letter at the end of a password.</p> <p>The default value is <b>No</b>.</p> <p>If this option is set to <b>Yes</b>, all other policies that indicate that a password must end with a particular character or in a specific manner are disabled.</p>
Prohibited characters	Keyboard characters	<p>Defines a list of characters that cannot be used in a password.</p> <p><b>NOTE:</b> There is no need of a separator in the list of prohibited characters. For example, @#\$%&amp;</p>

Policy	Value To Be provided	Description
Begin with any Alpha character	No/Yes	<p>Enforces the use of an alphabetic character at the beginning of a password.</p> <p>The default value is <b>No</b>.</p> <p>If this option is set to <b>Yes</b>, it automatically disables all other policies that specify what the first character of the password should be.</p>
Begin with any number	No/Yes	<p>Enforces the use of a numeric character as the first character of the password.</p> <p>The default value is <b>No</b>.</p> <p>If this option is set to <b>Yes</b>, it automatically disables all other policies that specify what the first character of the password should be.</p>
Begin with any symbol	No/Yes	<p>Enforces the use of a symbol character as the first character of the password.</p> <p>The default value is <b>No</b>.</p> <p>If this option is set to <b>Yes</b>, it automatically disables all other policies that specify what the first character of the password should be.</p>
End with any Alpha character	No/Yes	<p>Enforces the use of an alphabetic character as the last character of the password.</p> <p>The default value is <b>No</b>.</p> <p>If this option is set to <b>Yes</b>, it automatically disables all other policies that specify what the password should end with.</p>
End with any number	No/Yes	<p>Enforces the use of a numeric character as the last character of the password.</p> <p>The default value is <b>No</b>.</p> <p>If this option is set to <b>Yes</b>, it automatically disables all other policies that specify what the password should end with.</p>
End with any symbol	No/Yes	<p>Enforces the use of a symbol character as the last character of the password.</p> <p>The default value is <b>No</b>.</p> <p>If this option is set to <b>Yes</b>, it automatically disables all other policies that specify what the password should end with.</p>

## 2.9 The Advanced Settings Pane

Figure 2-5 The Advanced Settings Pane with the Passphrase Option

The screenshot shows the 'SecureLogin SSO' window with the 'Advanced Settings' tab selected. The 'Passphrase' sub-tab is active. It features a list box for 'Corporate passphrase questions' with 'New...', 'Edit...', and 'Delete...' buttons. Below this is a 'User-defined passphrase questions' dropdown set to 'Default'. The 'Customized Passphrase Prompt' section has a checkbox for 'Modify the passphrase prompt window text'. The 'Passphrase Policy' section has a checkbox for 'Use a passphrase policy' and an 'Edit Policy' button. At the bottom are 'OK', 'Cancel', and 'Apply' buttons.

The **Advanced Settings** page contains the following three tabs:

Table 2-14 The Advanced Settings Pane

Tab Name	Description
<b>Passphrase</b>	This page contains fields for: <ul style="list-style-type: none"><li>♦ Creating, editing, and deleting corporate passphrase questions.</li><li>♦ Customizing passphrase prompts.</li><li>♦ Editing passphrase policies.</li></ul>
<b>Datastore</b>	This is used for: <ul style="list-style-type: none"><li>♦ Selecting directory data version details (for mixed mode environments by using the earlier versions of the client software).</li><li>♦ Deleting SecureLogin configuration for a datastore object.</li></ul>
<b>Corporate Redirection</b>	This is used for managing configuration from one directory object when multiple container or organizational units require the same SecureLogin environment.



**NOTE:** The **Advanced Settings** option is not available in SecureLogin Client Utility.

# 2.10 The Passphrase Policy Properties Table

Figure 2-6 The Passphrase Policy Properties Table

Passphrase Policy	
Setting Description	Value
Minimum length	<input type="text"/>
Maximum length	<input type="text"/>
Minimum punctuation characters	<input type="text"/>
Maximum punctuation characters	<input type="text"/>
Minimum uppercase characters	<input type="text"/>
Maximum uppercase characters	<input type="text"/>
Minimum lowercase characters	<input type="text"/>
Maximum lowercase characters	<input type="text"/>
Minimum numeric characters	<input type="text"/>
Maximum numeric characters	<input type="text"/>
Disallow repeated characters	No <input type="button" value="v"/>
Disallow duplicate characters	No <input type="button" value="v"/>
Disallow sequential characters	No <input type="button" value="v"/>
Begins with an uppercase character	No <input type="button" value="v"/>
Ends with an uppercase character	No <input type="button" value="v"/>
Prohibited characters	<input type="text"/>
Begins with any character	No <input type="button" value="v"/>
Begins with a Number	No <input type="button" value="v"/>
Begins with a special character	No <input type="button" value="v"/>
Ends with any character	No <input type="button" value="v"/>
Ends with a Number	No <input type="button" value="v"/>
Ends with a special character	No <input type="button" value="v"/>

Organizations and applications often have rules about the content of a passphrase, including the required number and type of characters. The Passphrase policy properties table helps the user or the administrator to create and enforce these passphrase rules through a passphrase policy.

**Table 2-15** The Passphrase Policy Properties Table


Policy	Value To Be provided	Description
Minimum length	Whole number	Defines the minimum length of the passphrase; that is, the number of characters required for the passphrase.
Maximum length	Whole number	Defines the maximum length of the passphrase; that is, the maximum number of characters allowed in passphrase.
Minimum punctuation characters	Punctuation characters	Defines the minimum number of punctuation characters allowed in a passphrase. This should be a whole number.
Maximum punctuation characters	Punctuation characters	Defines the maximum number of punctuation characters allowed in a passphrase. This should be a whole number.
Minimum uppercase characters	Whole number	Defines the minimum number of uppercase characters allowed in a passphrase.
Maximum uppercase characters	Whole number	Defines the maximum number of uppercase characters allowed in a passphrase.
Minimum lowercase characters	Whole number	Defines the minimum number of lowercase characters allowed in a passphrase.
Maximum lowercase characters	Whole number	Defines the maximum number of lowercase characters allowed in a passphrase.
Minimum numeric characters	Whole number	Defines the minimum number of numeric characters allowed in a passphrase.
Maximum numeric characters	Whole number	Defines the maximum number of numeric characters allowed in a passphrase.
Disallow repeat characters	No/Yes/Yes, case insensitive	<p>Disallows the use of repeated characters, or the use of the same successive characters.</p> <p>If this option is set to <b>No</b>, characters can be repeated. This is the default value.</p> <p>If this option is set to <b>Yes</b>, same alphabetic characters in a different case are considered as different characters. For example, A and a are different.</p> <p>If this option is set to <b>Yes, case insensitive</b>, the successive use of the same alphabetic characters in a different case is not allowed.</p>

Policy	Value To Be provided	Description
Disallow duplicate characters	No/Yes/Yes, case insensitive	<p>Disallows the use of the same non-successive characters.</p> <p>If this option is set to <b>No</b>, duplicate characters are allowed. This is the default value.</p> <p>If this option is set to <b>Yes</b>, the same alphabetic characters in a different case are considered as different characters. For example, A (uppercase) and a (lowercase) are different.</p> <p>If this option is set to <b>Yes, case insensitive</b>, duplication of the same alphabetic characters in a different case is not allowed.</p>
Disallow sequential characters	No/Yes/Yes, case insensitive	<p>Disallows the use of successive characters in an alphabetical order.</p> <p>If this option is set to <b>No</b>, sequential characters are allowed. This is the default value.</p> <p>If this option is set to <b>Yes</b>, sequential characters in a different case are considered as non-sequential. For example, a and b and non-sequential.</p> <p>If this option is set to <b>Yes, case insensitive</b>, sequential characters in different cases is disallowed.</p>
Begin with an uppercase character	No/Yes	<p>Enforces the use of an uppercase alphabetic character as the beginning character of a passphrase.</p> <p>The default value is <b>No</b>.</p> <p>If this option is set to <b>Yes</b>, all other policies that indicate that a passphrase must begin with a particular character or in a specific manner are disabled.</p> <p><b>IMPORTANT:</b> Only one type of character can be designated as the first value of a passphrase.</p>
End with an uppercase character	No/Yes	<p>Enforces the use of an uppercase letter at the end of a passphrase.</p> <p>The default value is <b>No</b>.</p> <p>If this option is set to <b>Yes</b>, all other policies that indicate that a passphrase must end with a particular character or in a specific manner are disabled.</p>
Prohibited characters	Keyboard characters	<p>Defines a list of characters that cannot be used in a passphrase.</p> <p><b>NOTE:</b> There is no need of a separator in the list of prohibited characters. For example, @#\$%&amp;</p>

Policy	Value To Be provided	Description
Begin with any Alpha character	No/Yes	<p>Enforces the use of an alphabetic character at the beginning of a passphrase.</p> <p>The default value is <b>No</b>.</p> <p>If this option is set to <b>Yes</b>, it automatically disables all other policies that specify what the first character of the passphrase should be.</p>
Begin with any number	No/Yes	<p>Enforces the use of a numeric character as the first character of the passphrase.</p> <p>The default value is <b>No</b>.</p> <p>If this option is set to <b>Yes</b>, it automatically disables all other policies that specify what the first character of the passphrase should be.</p>
Begin with any symbol	No/Yes	<p>Enforces the use of a symbol character as the first character of the passphrase.</p> <p>The default value is <b>No</b>.</p> <p>If this option is set to <b>Yes</b>, it automatically disables all other policies that specify what the first character of the passphrase should be.</p>
End with any Alpha character	No/Yes	<p>Enforces the use of an alphabetic character as the last character of the passphrase.</p> <p>The default value is <b>No</b>.</p> <p>If this option is set to <b>Yes</b>, it automatically disables all other policies that specify what the passphrase should end with.</p>
End with any number	No/Yes	<p>Enforces the use of a numeric character as the last character of the passphrase.</p> <p>The default value is <b>No</b>.</p> <p>If this option is set to <b>Yes</b>, it automatically disables all other policies that specify what the passphrase should end with.</p>
End with any symbol	No/Yes	<p>Enforces the use of a symbol character as the last character of the passphrase.</p> <p>The default value is <b>No</b>.</p> <p>If this option is set to <b>Yes</b>, it automatically disables all other policies that specify what the passphrase should end with.</p>

## 2.11 The Distribution Pane

Figure 2-7 The Distributions Pane



The **Distribution** pane provides access to:

- ♦ The Load dialog box
- ♦ The Save dialog box
- ♦ The Copy dialog box

The Load and Save dialog boxes help the administrator to import and export the SecureLogin configurations. For more information, see [Copying a Configuration Across Organizational Units](#)

The Copy dialog box help the administrator to copy an object's SecureLogin configuration from one object to another. For more information, see [Exporting and Importing Configurations](#)

---

**NOTE:** The **Distribution** pane is not available for SecureLogin Client Utility.

---



---

# 3 SecureLogin Components

This section discusses the following topics:

- ♦ [Section 3.1, “SecureLogin Management Utilities,” on page 47](#)
- ♦ [Section 3.2, “Application Definition Wizard,” on page 48](#)
- ♦ [Section 3.3, “Add New Login Wizard,” on page 49](#)
- ♦ [Section 3.4, “Terminal Launcher,” on page 49](#)

## 3.1 SecureLogin Management Utilities

**Table 3-1** *SecureLogin Management Utilities*

Use This Utility	To Manage These Users
SecureLogin Management Utility (slmanager)	This tool can be used in any supported SecureLogin environment to globally manage SecureLogin information on user objects, groups, policies, containers, or organizational objects at the tree/domain level.
SecureLogin Client Utility (manage logins)	<p>The manage logins interface of the SecureLogin client allows users to modify the SecureLogin applications, credentials, and settings for the currently logged in user. This utility has similar functionality as the SecureLogin management utility, excluding some preference options that relate to only the directory environment. Administrators can disable users from accessing this utility and or limit the capabilities provided by default within this user interface.</p> <p>For example "Allow users to view application definitions set to No would restrict the user from viewing the application definition from within the client utility.</p> <p>For more information, see <a href="#">Section 2.1, “SecureLogin Client Utility,” on page 9</a></p>
iManager plug-in	This tool extends the capabilities of iManager to include management of SecureLogin information when running within an eDirectory environment.
MMC snap-in	This tool extends the capabilities of the Microsoft Management Console (MMC) to include management of SecureLogin information when running within an Active Directory (AD) environment.

Use This Utility	To Manage These Users
Active Directory Users and Computers Snap-in	<p>Using the Active Directory users and computer snap-in you can manage users in the Microsoft Active Directory environment.</p> <p>If during the installation of the SecureLogin client in Active Directory mode, the option <b>Install Directory Administration Tools</b> was selected, then the installation routine copies and registers the SecureLogin Snap-In for Active Directory Users and Computers. In addition to the MMC snap-in being installed, the SecureLogin Administrative Management utility is also copied to the SecureLogin program folder.</p> <p><b>NOTE:</b> If you select the <b>Enable Microsoft Active Directory Group Policies</b> option during the installation, you can administer SecureLogin by using the Group Policy object.</p>

## 3.2 Application Definition Wizard

Application definitions specify how SecureLogin interacts with an application using your single sign-on (SSO) credentials. The Application Definition Wizard assists you in creating an application definition.

---

**IMPORTANT:** You can use the Application Definition Wizard only if the administrator has given you permission. The administrator can restrict users' access to the Application Definition Wizard. Depending on the preferences set by the administrator, you might be allowed to create application definitions for new applications or you might not have access at all.

---

In most instances the Application Definition Wizard opens automatically when it detects a new login screen, but you can also choose to create or modify application definitions using the wizard to automate the handling of notification screens including prompts to change your password and error messages.

For information on using the Application Definition Wizard to create application definitions and enabling applications for single sign-on, refer [NetIQ SecureLogin Application Definition Wizard Administration Guide](#)

The Application Definition Wizard helps you to create and change the application definition responses for the following:

- ♦ The Login Screen
- ♦ The Login Notification Screen
- ♦ The Change Password Screen
- ♦ The Change Password Notification Screen
- ♦ Application windows or pages that are not recognized by the Application Definition Wizard automatically.




## 3.3 Add New Login Wizard

The Add New Login Wizard helps users to create multiple logins for the same application. The Wizard contains a list of available credential sets from which users can choose the desired login.

An alternative to using the Wizard to add a new login, the script commands `PickListAdd` and `PickListDisplay` can be used within an application script to prompt the user for the desired login. For example, if all users in an IT group require three different logins for a help desk application, the administrator can modify the script for the help desk application to include the `PickList` commands. This way all users of the help desk application will be prompted to choose one of the three valid logins before the application login occurs.

## 3.4 Terminal Launcher

Figure 3-1 The Terminal Launcher



Terminal emulator application definitions are invoked by the utility called Terminal Launcher (tlaunch.exe or tlaunch64.exe). Configuration of SecureLogin to provide Single Sign-on to terminal sessions is typically implemented in one of three ways:

- ♦ Users launch the emulator via the tlaunch utility (GUI)

- ♦ A shortcut is created on the users desktop that will execute tlaunch with the correct parameters to start the emulator with the desired terminal emulator application definition.
- ♦ A windows application definition is created for the emulator executable that will invoke tlaunch with the proper parameters to connect to the emulator session and Terminal Emulator application definition

For detailed information on enabling single sign-on for terminal services, see “[Enabling Terminal Emulator Applications](#)” in the *NetIQ SecureLogin Administration Guide*.

---

# 4 Enabling Applications and Web Sites for Single Sign-On

SecureLogin has predefined applications for single sign-on access to a wide range of commercially available applications.

SecureLogin detects applications for which a predefined application exists. For example, if SecureLogin detects Novell GroupWise Messenger dialog box, then it prompts the user to allow SecureLogin to enable single sign-on for the application.

Predefined applications for some commonly used applications are incorporated with SecureLogin, and with each new version, more applications are developed and made available to the customers.

SecureLogin provides application definition wizard to facilitate single sign-on to almost any new or proprietary application, if a predefined application is unavailable. For details refer the [NetIQ SecureLogin Application Definition Wizard Administration Guide](#).

SecureLogin also supports enabling single sign-on for terminal emulator applications.

- ◆ Users can enable single sign-on for terminal emulators by using the terminal launcher tool.
- ◆ SecureLogin has additional tools such as, Window Finder and LoginWatch, which help the user to enable single sign-on for even the most difficult applications. For details, refer to the [NetIQ SecureLogin Application Definition Guide](#).

SecureLogin stores the login information requirements for applications including the following:

---

Credentials, but not limited to:

- ◆ Username
- ◆ UserID
- ◆ LoginID
- ◆ Password
- ◆ PINs
- ◆ Domain
- ◆ Database names
- ◆ Server IP address

Responses to dialog boxes, messages, and window events such as:

- ◆ Login
  - ◆ Incorrect credentials
  - ◆ Password expiration, including non-compliance to password rules
  - ◆ Account locked
  - ◆ Database unavailable
- 

Before SecureLogin can enable an application for single sign-on for a particular user, it must learn a user's application credentials so that it can encrypt and store them for future logins unless it is used in conjunction with Identity Management solutions such as Identity Manager.

When a user starts an application for the first time after it is enabled for single sign-on, SecureLogin prompts the user for application credentials, then encrypts and stores them in the directory against the user object. The credentials are passed automatically to the application for subsequent logins.

Automated single sign-on is achieved by using the proprietary application definitions. The application definitions are managed in directory environments through SecureLogin administrative management utilities. In local and standalone deployments, the application definitions are managed in SecureLogin Client Utility or distributed by using the advanced offline signed and encrypted method.

The single sign-on applications are created, modified, and deleted in the Applications pane. Users can also create application definitions with SecureLogin Wizard. There are a wide range of options in SecureLogin to enable applications. Regardless of the origin of the application definition, when an application is enabled for single sign-on, it is added and maintained in the **Applications** properties table.

## 4.1 Applications Excluded for Single Sign-On

Although SecureLogin facilitates you to enable single sign-on for Windows, Web, and Java applications; some applications cannot be enabled for single sign-on. The applications that cannot be enabled include certain installers, SecureLogin and Windows system files. Enabling these applications might affect your computer's performance or create a security risk.

These applications are hard-coded and are excluded from single sign-on.

**Table 4-1** Applications excluded from Single Sign-On

setup.exe	Nwadm95.exe	acsagent.exe
_isdel.exe	loginw95.exe	adamconfig.exe
msiexec.exe	NWTray.exe	rdbgwiz.exe
MSDEV.exe	loginw32.exe	ProtocomSysTray.exe
devenv.exe	scrnlock.scr	ac.aac.run.exe
SLBroker.EXE	MMC.EXE	SLBroker64.EXE
tlaunch.exe	slwinssso.exe	slwinssso64.exe
SLProto.exe	SLManager.exe	SLManager64.exe
nswebsso.exe	sllock.scr	tlaunch64.exe
Nwadm32.exe	ConsoleOne.exe	SLProto64.exe
Nwadm95.exe	SLLauncher.exe	

### 4.1.1 Modifying the List

Although the applications disabled for single sign-on are hardcoded, you can modify the behavior by creating a text file at the SecureLogin installation path. For example, at C:\Program Files\Novell\SecureLogin\ and name it exclude.ini.

**NOTE:** Despite its extension, the exclude.ini file is not in an .ini file format.

You can open this file in any text editor and make the changes. You can extend or modify the list.

You can modify the file in the following ways:

- ♦ “Extending the List of Applications” on page 53
- ♦ “Including Applications for Single Sign-On” on page 53
- ♦ “Disabling the Default Behavior” on page 53

## Extending the List of Applications

If you want to disable more applications apart from the hardcoded applications, add the names of the application to the `exclude.ini` file. For example, you can add `grpwise.exe` to the `exclude.ini` file. With this, GroupWise is also disabled for single sign-on.

---

**NOTE:** If you add an existing application to the list of applications in the `exclude.ini` file, it does not impact the original list. For example, if you add `SLProto.exe` to the `exclude.ini` file, it does not impact the function although it is listed twice.

---

## Including Applications for Single Sign-On

If you want to enable only a set of applications for single sign-on, use `Include` keyword in `exclude.ini` file

In the `exclude.ini` file add the `Include` keyword to enable an executable for single sign-on. By including the `Include` keyword, the list is converted to an include list.

For example, when you add

```
Include
```

```
Trillian.exe
```

Trillian application is enabled for single sign-on. The next time you log in, you are prompted to enable single sign-on.

If you use the `include` keyword you must list all of the desired applications you want to use SecureLogin with. All other applications will be ignored. For more information see, [TID 7009238](http://www.novell.com/support/kb/doc.php?id=7009238) (<http://www.novell.com/support/kb/doc.php?id=7009238>)

## Disabling the Default Behavior

If you want to define a custom list for disabling the applications for single sign-on, include the `NoDefault` keyword. When you include the `NoDefault` keyword, the hardcoded applications are overridden.

For example, if you modify the list as:

```
NoDefault
```

```
NMCL32.exe
```

the hardcoded applications that are disabled for single sign-on is not read by SecureLogin. Instead, the executables listed with the `NoDefault` keyword in the `exclude.ini` file are considered and all the applications listed in the file are disabled for single sign-on.



---

# 5 Operational Environment

This section contains information on the following:

- ♦ [Section 5.1, “Supported Environments,” on page 55](#)
- ♦ [Section 5.2, “Windows,” on page 56](#)
- ♦ [Section 5.3, “Terminal Emulators,” on page 57](#)
- ♦ [Section 5.4, “Web or Internet,” on page 58](#)

## 5.1 Supported Environments

- ♦ [Section 5.1.1, “Operating Systems,” on page 55](#)
- ♦ [Section 5.1.2, “Terminal Servers,” on page 55](#)
- ♦ [Section 5.1.3, “Directories,” on page 55](#)
- ♦ [Section 5.1.4, “Browsers,” on page 56](#)
- ♦ [Section 5.1.5, “Others,” on page 56](#)
- ♦ [Section 5.1.6, “Flash,” on page 56](#)

### 5.1.1 Operating Systems

- ♦ Windows 10
- ♦ Windows 8.1/Server 2012 R2
- ♦ Windows 7/Server 2008 R2

### 5.1.2 Terminal Servers

- ♦ Citrix Receiver 4.5 and above
- ♦ Citrix XenDesktop or XenApp 7.6 and above
- ♦ Microsoft Terminal Services clients, Remote Desktop Protocol 7.0 and above

### 5.1.3 Directories

- ♦ Active Directory installed on Windows 2008 R2 or 2012 R2
- ♦ eDirectory 8.8.x installed on Open Enterprise Server, Windows or SUSE Linux Enterprise System
- ♦ eDirectory 9.0 installed on Open Enterprise Server, Windows or SUSE Linux Enterprise System

---

**NOTE:** SecureLogin can be installed on any LDAP v3-compliant directory.

---

## 5.1.4 Browsers

- ♦ Internet Explorer 8.0 to 11.0
- ♦ Mozilla Firefox 50 and above.
- ♦ Google Chrome 45 and above

## 5.1.5 Others

- ♦ iManager 2.7.7 and above
- ♦ .NET framework 4.0 and above
- ♦ Java Runtime Environment 1.4 and above
- ♦ Supported Smartcard Middleware
  - ♦ ActivClient 6.x and 7.x
- ♦ Microsoft Smart Card Base Cryptographic Service Provider (CSP) Minidriver
- ♦ Advanced Authentication 5.3 and 5.4

## 5.1.6 Flash

- ♦ Adobe Flash Player 10.1 or later.

# 5.2 Windows

The following is a list of predefined applications for Windows applications:

- ♦ ActiveSync
- ♦ Cisco VPN
- ♦ Citrix Program Neighborhood
- ♦ Citrix Program Neighborhood - Farm Login Failure
- ♦ Citrix Program Neighborhood - Server
- ♦ Citrix Program Neighborhood - Agent
- ♦ Citrix Program Neighborhood - Agent v10.x
- ♦ GroupWise Windows Application v5.5, v6.0, v7.0, and v8.0
- ♦ Lotus Notes R8
- ♦ MEDITECH x and 4.x

---

**NOTE:** The support for MEDITECH 3.x and 4.x is dependant on the presence of the MEDITECH `mrwscript.dll` file. The `.dll` file is provided by MEDITECH and must be installed during the installation of the MEDITECH application workstation.

---

- ♦ Microsoft Internet Explorer 6, 7, and 8
- ♦ Microsoft Networking Client
- ♦ Microsoft Outlook
- ♦ Microsoft Outlook Express
- ♦ Microsoft SQL



- ♦ Microsoft Windows Live ID
- ♦ MSN Messenger 4.5 and 4.7
- ♦ Novell Groupwise Messenger 2.0
- ♦ Novell Groupwise Notify Client
- ♦ Novell Groupwise 7.0 Web Login
- ♦ iManager Web Login
- ♦ Quick Finder
- ♦ SAP - SAPlogon.exe
- ♦ SAP R/3 Login
- ♦ Trillian
- ♦ VNC 3.0 and 4.0
- ♦ Windows Live Messenger 5.0, 6.0, 7.5, 8.1, and 2009
- ♦ Windows Remote Desktop 6
- ♦ Yahoo! Messenger 8.1
- ♦ Yahoo! Messenger 8.1 Alternate

If SecureLogin does not prompt to enable single sign-on for applications, use the Application Definition Wizard to build an application.

## 5.3 Terminal Emulators

SecureLogin provides single sign-on support for the applications running on any back end system for example, UNIX, RACF, CICS, ACF2 using the following emulators:

- ♦ AbsoluteTelnet
- ♦ Attachmate Extra
- ♦ Attachmate Extra 2000
- ♦ Attachmate KEA!
- ♦ Attachmate Personal Client
- ♦ Chameleon HostLink
- ♦ CRT
- ♦ Eicon Aviva
- ♦ GLink
- ♦ HBO Star Navigator
- ♦ IBM Personal Communications
- ♦ IDXTerm Healthcare
- ♦ Info Connect
- ♦ Microsoft Telnet 2000
- ♦ Microsoft Telnet NT
- ♦ Microsoft Telnet Win 9x
- ♦ Mocha W32 Telnet
- ♦ NetTerm 4.2

- ♦ NS/Elite
- ♦ Passport TN 3270E
- ♦ PowerTerm
- ♦ QVT
- ♦ QWS3270 Plus
- ♦ SDI TN3270
- ♦ TeraTermPro
- ♦ TinyTERM
- ♦ ViewNow
- ♦ Wall Data Rumba
- ♦ Wall Data Rumba 2000
- ♦ Wall Data Rumba Web To Host
- ♦ WinComm
- ♦ Window Telnet VT
- ♦ WRQ Reflection
- ♦ Attachmate EXTRA X-treme
- ♦ Microsoft Telnet Vista

## 5.4 Web or Internet

SecureLogin provides predefined applications for a number of Web applications with embedded login fields including:

- ♦ Citrix Web Portal
- ♦ CNN Member Services
- ♦ eBay
- ♦ Fidelity.com Web Login
- ♦ Hotmail
- ♦ Onebox.com
- ♦ Qantas Frequent Flyer
- ♦ Yahoo! Mail
- ♦ Monster.com

SecureLogin prompts you if a predefined application is available. You can also use the Application Definition Wizard to build an application definition for the application.

# Glossary

**administrative management utility.** The utility available in SecureLogin to manage the users in a directory environment. The slmanagertool.exe provides additional functionality that is not available in SecureLogin Client Utility.

**application programming Interface.** Enables programmatic communication with the application.

**application definition.** SecureLogin configuration data that enables the single sign-on for a specific application's login and other events.

**cache.** The cache encrypts the local copy of SecureLogin data so that a user can continue to use SecureLogin even if the directory is unavailable. In a standalone mode (non-directory) mode, the cache contains all SecureLogin single sign-on data for a user.

User data includes credentials, preferences, password policies, and application definitions. By default, SecureLogin cache is created on the local hard drive. In a corporate implementation, this data is also stored in the directory. The data in the directory and the workstation cache are regularly synchronized to ensure that the user data is current.

**container.** Object in a directory environment that contains other objects.

**corporate configuration/redirection.** Allows the administrators in a directory environment to configure where SecureLogin setting on objects are inherited from.

**credentials.** Usernames, passwords, and other data that uniquely identifies and authenticates a user to an application.

**Directory Services.** Structured repository that identifies all aspects of a network. It is made up of users, software, hardware, and any rights or policies assigned.

**distinguished name.** The full name of a directory object, including the domain name and organizational units to which the user belongs.

**domain.** A security boundary that groups users or devices. Domain objects are defined by schema, configuration, and security policies of the network.

**Group policy.** The Group policy enables the centralized configuration and management of selected objects. User or computers are selected by the administrators to be included in the group policy group for collective administration.

**High Level Language Application Programming Interface (HLLAPI).** The API that enables a terminal emulator screen to read and be interpreted by an application and enables the keyboard input to be processed by the emulator.

**Lightweight Directory Access Protocol (LDAP).** The protocol used for updating and searching directories running over TCP/IP.

**login.** The set of credentials (such as username and password) stored in SecureLogin.

**management utility.** SecureLogin's management utility. It generically refers to the administrative management utilities and SecureLogin Client Utility.

**object.** In a directory environment, a set of attributes that identifies a user, hardware, or an application.

**organizational unit (ou).** In a directory environment, a domain subgroup that has administrative control of all the associated objects.

**passphrase.** A combination of a question and answer used to protect the user credentials from unauthorized use.

**password policy.** One or more password rule grouped under a unique name.

**password rule.** A password parameter configured in the Password Policies properties table. Password rules are grouped under a Password policy.

**SecureLogin Client Utility.** Provides user administration tools to the user from his or her desktop.

**predefined application.** Automates single sign-on for many commercially available applications.

**Schema.** A database for the classes (tables). It defines the objects and the attributes (columns) and stores the object data.

**SecureLogin.** The application that allows users to access a wide range of applications, Web sites, and mainframe sessions. With this, users need not log in to the application separately.

**SecureLogin Attribute Provisioning (SLAP).** The tool that enables SecureLogin to leverage user data from an organization's provisioning system.

**Single Sign-On-Enabled.** When an application is enabled for single sign-on for a user, the user need not specify his or her credentials to log in to the application. When the user launches an application, SecureLogin transparently manages the login process.