

NetIQ Security Manager 6.0 Firewall solution datasheet					
Component:	to Component:	Ports:	Direction:	Description:	
Central Computer	OnePoint DB	TCP 1433	Outbound	Standard SQL port is 1433. Instances use alternate ports.	
	[All DB's]	(UDP 1434)	Outbound	If using a SQL instance, the browser service is required on UDP 1433.	
	Log Archive Server	TCP 8989	Bidirectional	Used by Security Manager business services (configurable)	
		TCP 1801	Outbound	Used by MSMQ push from CC to LAS	
	Central Computer	TCP 1270	Bidirectional	Used for correlation between CC's	
		TCP 1625	Bidirectional	Used during forensic queries from UI connected CC to remote CC's	
Log Archive Server	Reporting Server	TCP 1433	Outbound	Standard SQL port is 1433. Instances use alternate ports.	
	[SMCubeDepot]	UDP 1434	Outbound	If using a SQL instance, the browser service is required on UDP 1433.	
Reporting Server	Database Server	TCP 1433	Outbound	Standard SQL port is 1433. Instances use alternate ports.	
	[OnePoint]	UDP 1434	Outbound	If using a SQL instance, the browser service is required on UDP 1433.	
	*[SMCubeDepot]	Reporting Server	TCP 2383	Outbound	Analysis Services communications used by SSIS job
		[SMReporting]	TCP 2382	Outbound	If using a SQL instance, Analysis Services Browser for instances used by SSIS job
					*Currently all reporting components are on the SM Reporting Server.
Agent Communication:					
Central Computer	MS Windows	TCP 1270	Inbound	From agent to CC default encrypted communications (configurable)	
		(TCP 51515)	Inbound	Optional unencrypted configuration	
	UNIX	TCP 1622	Outbound	Requests for log manager (archival) data	
		TCP 1636	Inbound	Alert communication from UNIX	
	iSeries	TCP 1622	Outbound	Requests for log manager (archival) data	
		TCP 1636	Inbound	Alert communication from iSeries	
User Interfaces:					
Control Center	Central Computer	TCP 8737	Outbound	Used for business services communications	
Control Center	Reporting Server	TCP 2383	Outbound	Analysis Services communications	
	[SMReporting]	TCP 2382	Outbound	Analysis Services Browser for instances	
Monitor and Development Consoles	Central Computer	TCP 135	Outbound	SCM discover of DCOM listening port	
		TCP (random)	Outbound	Random RPC port used by Windows DCOM (per boot) 1024-65535 See Microsoft KB's 300083 and 826852 to set static port usage.	
Web Console	Central Computer (WebConsole server)	TCP 1271	Outbound	Port used by Security Manager site.	
Reporting Console	Reporting Server	TCP 80	Outbound	Port used by Microsoft Reporting services site.	