



PlateSpin Forge[®] 11.0

Upgrade Guide

July 30, 2014

Legal Notice

THIS DOCUMENT AND THE SOFTWARE DESCRIBED IN THIS DOCUMENT ARE FURNISHED UNDER AND ARE SUBJECT TO THE TERMS OF A LICENSE AGREEMENT OR A NON-DISCLOSURE AGREEMENT. EXCEPT AS EXPRESSLY SET FORTH IN SUCH LICENSE AGREEMENT OR NON-DISCLOSURE AGREEMENT, NETIQ CORPORATION PROVIDES THIS DOCUMENT AND THE SOFTWARE DESCRIBED IN THIS DOCUMENT "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SOME STATES DO NOT ALLOW DISCLAIMERS OF EXPRESS OR IMPLIED WARRANTIES IN CERTAIN TRANSACTIONS; THEREFORE, THIS STATEMENT MAY NOT APPLY TO YOU.

For purposes of clarity, any module, adapter or other similar material ("Module") is licensed under the terms and conditions of the End User License Agreement for the applicable version of the NetIQ product or software to which it relates or interoperates with, and by accessing, copying or using a Module you agree to be bound by such terms. If you do not agree to the terms of the End User License Agreement you are not authorized to use, access or copy a Module and you must destroy all copies of the Module and contact NetIQ for further instructions.

This document and the software described in this document may not be lent, sold, or given away without the prior written permission of NetIQ Corporation, except as otherwise permitted by law. Except as expressly set forth in such license agreement or non-disclosure agreement, no part of this document or the software described in this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, or otherwise, without the prior written consent of NetIQ Corporation. Some companies, names, and data in this document are used for illustration purposes and may not represent real companies, individuals, or data.

This document could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein. These changes may be incorporated in new editions of this document. NetIQ Corporation may make improvements in or changes to the software described in this document at any time.

U.S. Government Restricted Rights: If the software and documentation are being acquired by or on behalf of the U.S. Government or by a U.S. Government prime contractor or subcontractor (at any tier), in accordance with 48 C.F.R. 227.7202-4 (for Department of Defense (DOD) acquisitions) and 48 C.F.R. 2.101 and 12.212 (for non-DOD acquisitions), the government's rights in the software and documentation, including its rights to use, modify, reproduce, release, perform, display or disclose the software or documentation, will be subject in all respects to the commercial license rights and restrictions provided in the license agreement.

© 2014 NetIQ Corporation. All Rights Reserved.

For information about NetIQ trademarks, see <https://www.netiq.com/company/legal/>.

Contents

About NetIQ Corporation	5
About this Book and the Library	7
1 Upgrade Overview	9
1.1 Possible Forge Configurations	9
1.2 The Upgrade Paths	10
1.3 The Forge 11 Upgrade Media Kit and Its Contents	11
1.4 Important Upgrade Information	12
1.5 Upgrade Precautions	13
1.6 Upgrade Prerequisites	13
1.7 Forge Components Changed by the Upgrade	14
1.8 Summary of Forge Upgrade Tasks	15
2 Upgrade Tasks	17
2.1 Backing Up the Forge Management VM	17
2.1.1 Preparing for the Backup	17
2.1.2 Performing the Forge Backup	18
2.2 Rebuilding the Forge Appliance	20
2.2.1 About the Forge 11 Rebuild Process	20
2.2.2 What You Need	21
2.2.3 Installing the Hypervisor and Forge Components	21
2.2.4 Licensing Microsoft Products on the Forge Management VM	25
2.2.5 Licensing the ESXi 5.5 Hypervisor	27
2.2.6 Running the Forge Appliance Configurator	28
2.2.7 Backing Up the Factory VM	28
2.2.8 Restarting the Appliance	29
2.2.9 Configuring the Appliance for Immediate Use	29
2.2.10 Launching the PlateSpin Forge Web Client	29
2.2.11 Product Licensing	30
2.3 Post-Setup Tasks	31
2.4 Restoring the Appliance	32
2.5 Confirming Appliance Data and Resuming Protection	34
3 Troubleshooting the Upgrade	35
3.1 Overview of the Restore/Backup Utility	35
3.2 Upgrade Utility Parameters	35
3.3 Generated Files in the /output Directory	38
3.3.1 Generated File Locations	39
3.4 Errors Occurring During ESXi Installation	39
3.5 Log File Locations	40
3.6 Troubleshooting Specific Issues	41
3.7 Known Issues	45
A Upgrading Forge 3.x Appliance 2	47
A.1 Upgrade Procedure	47
A.2 Post-Upgrade Tasks	47

About NetIQ Corporation

We are a global, enterprise software company, with a focus on the three persistent challenges in your environment: Change, complexity and risk—and how we can help you control them.

Our Viewpoint

Adapting to change and managing complexity and risk are nothing new

In fact, of all the challenges you face, these are perhaps the most prominent variables that deny you the control you need to securely measure, monitor, and manage your physical, virtual, and cloud computing environments.

Enabling critical business services, better and faster

We believe that providing as much control as possible to IT organizations is the only way to enable timelier and cost effective delivery of services. Persistent pressures like change and complexity will only continue to increase as organizations continue to change and the technologies needed to manage them become inherently more complex.

Our Philosophy

Selling intelligent solutions, not just software

In order to provide reliable control, we first make sure we understand the real-world scenarios in which IT organizations like yours operate — day in and day out. That's the only way we can develop practical, intelligent IT solutions that successfully yield proven, measurable results. And that's so much more rewarding than simply selling software.

Driving your success is our passion

We place your success at the heart of how we do business. From product inception to deployment, we understand that you need IT solutions that work well and integrate seamlessly with your existing investments; you need ongoing support and training post-deployment; and you need someone that is truly easy to work with — for a change. Ultimately, when you succeed, we all succeed.

Our Solutions

- ♦ Identity & Access Governance
- ♦ Access Management
- ♦ Security Management
- ♦ Systems & Application Management
- ♦ Workload Management
- ♦ Service Management

Contacting Sales Support

For questions about products, pricing, and capabilities, contact your local partner. If you cannot contact your partner, contact our Sales Support team.

Worldwide:	www.netiq.com/about_netiq/officelocations.asp
United States and Canada:	1-888-323-6768
Email:	info@platespin.com
Web Site:	www.netiq.com

Contacting Technical Support

For specific product issues, contact our Technical Support team.

Worldwide:	www.netiq.com/support/contactinfo.asp
North and South America:	1-800-858-4000
Europe, Middle East, and Africa:	+353 (0) 91-782 677
Email:	support@platespin.com
Web Site:	www.netiq.com/support

Contacting Documentation Support

Our goal is to provide documentation that meets your needs. The documentation for this product is available on the NetIQ Web site in HTML and PDF formats on a page that does not require you to log in. If you have suggestions for documentation improvements, click **Add Comment** at the bottom of any page in the HTML version of the documentation posted at www.netiq.com/documentation. You can also email Documentation-Feedback@netiq.com. We value your input and look forward to hearing from you.

Contacting the Online User Community

NetIQ Communities, the NetIQ online community, is a collaborative network connecting you to your peers and NetIQ experts. By providing more immediate information, useful links to helpful resources, and access to NetIQ experts, NetIQ Communities helps ensure you are mastering the knowledge you need to realize the full potential of IT investments upon which you rely. For more information, visit <http://community.netiq.com>.

About this Book and the Library

The *Upgrade Guide* provides conceptual information about upgrading the PlateSpin Forge Appliance from version 3.1, 3.3, 3.4, or 4.0 to version 11.0.

Intended Audience

This book provides information for individuals responsible for upgrading PlateSpin Forge.

Other Information in the Forge Documentation Library

The library provides the following information resources:

Getting Started Guide

Provides detailed planning and installation information.

User Guide

This book also provides an overview of the user interfaces and step-by-step guidance for many administration tasks.

Help

Provides context-sensitive information and step-by-step guidance for common tasks, as well as definitions for each field on each window.

1 Upgrade Overview

You can upgrade your Forge appliance and software from version 4.0 to version 11.0. This section provides general information you can use prior to upgrading your PlateSpin Forge appliance.

- ♦ [Section 1.1, “Possible Forge Configurations,” on page 9](#)
- ♦ [Section 1.2, “The Upgrade Paths,” on page 10](#)
- ♦ [Section 1.3, “The Forge 11 Upgrade Media Kit and Its Contents,” on page 11](#)
- ♦ [Section 1.4, “Important Upgrade Information,” on page 12](#)
- ♦ [Section 1.5, “Upgrade Precautions,” on page 13](#)
- ♦ [Section 1.6, “Upgrade Prerequisites,” on page 13](#)
- ♦ [Section 1.7, “Forge Components Changed by the Upgrade,” on page 14](#)
- ♦ [Section 1.8, “Summary of Forge Upgrade Tasks,” on page 15](#)

1.1 Possible Forge Configurations

The configuration of the Dell hardware used for the Forge platform has changed as new versions of the Forge software and the accompanying Forge Appliance have been released. Hardware type is a major factor you need to consider when determining the version of PlateSpin Forge to which you can upgrade.

In addition to PlateSpin Forge software, the PlateSpin Forge Appliance includes a VMware ESX hypervisor and a virtual machine that runs a Windows operating system (Forge versions, 3.x to 4.0 implement a VM that runs on the Windows 2003 OS; the Forge 11.0 VM runs on the Windows 2012 OS).

The combination of the hypervisor version and the version of the Windows virtual machine (a.k.a., the Forge Management VM) determines the *appliance version* of your PlateSpin Forge Appliance, as illustrated in the table below.

Supported Dell Hardware for Forge	Shipped VM Version	Possible Forge Appliance Version	Forge Versions Supported
Dell PowerEdge 1950	ESX 3.5	Appliance 1	PlateSpin Forge 3.0, 3.0.1, and 3.0.2
Dell PowerEdge 2950	ESX 3.5	Appliance 1	PlateSpin Forge 3.0, 3.0.1, and 3.0.2
	ESX 4.1 (after upgrade)	Appliance 2 (after upgrade)	PlateSpin Forge 3.1, 3.3, 3.4, and 4.0
Dell PowerEdge R610	ESX 4.1	Appliance 3	PlateSpin Forge 11.0
Dell PowerEdge R620	ESX 4.1	Appliance 3	PlateSpin Forge 11.0
Dell PowerEdge R710	ESX 4.1	Appliance 3	PlateSpin Forge 11.0
Dell PowerEdge R720	ESX 4.1	Appliance 3	PlateSpin Forge 11.0

1.2 The Upgrade Paths

Depending on the version of Forge you currently use and the version of Forge to which you want to upgrade, you might need to follow an incremental upgrade path. The table below lists the steps your upgrade path might include.

Current Forge Version	Highest Version Upgrade Path	Upgrade Steps
3.0, 3.0.1 <ul style="list-style-type: none"> ◆ Appliance 1 ◆ Dell 1950 	3.0.2 <ul style="list-style-type: none"> ◆ Appliance 1 	<ol style="list-style-type: none"> Upgrade Forge software to version 3.0.2. <ul style="list-style-type: none"> ◆ Run <code>PlateSpinForgeSetup-3.0.2.2497.exe</code>. To obtain a copy of this software, contact PlateSpin Support.
3.0, 3.0.1, 3.0.2 <ul style="list-style-type: none"> ◆ Appliance 1 ◆ Dell 2950 	4.0 <ul style="list-style-type: none"> ◆ Appliance 1 	<ol style="list-style-type: none"> Upgrade PlateSpin Forge software to version 3.1. <ul style="list-style-type: none"> ◆ Run <code>PlateSpinForgeSetup-3.1.0.3050.exe</code> from the <i>Forge 4 Upgrade Kit</i>. ◆ Run <code>PlateSpinForgeSetup-4.0.0.x.exe</code> from the <i>Forge 4 Upgrade Kit</i>. ◆ See <i>Upgrading Forge 3.x Appliance 1</i> in the Forge 4 Upgrade Guide for more information.
3.1, 3.3 <ul style="list-style-type: none"> ◆ Appliance 1 ◆ Dell R610, R620, R710, R720 	4.0 <ul style="list-style-type: none"> ◆ Appliance 2 	<ol style="list-style-type: none"> Upgrade PlateSpin Forge software to version 3.1. <ul style="list-style-type: none"> ◆ Run <code>PlateSpinForgeSetup-3.1.0.3050.exe</code> from the <i>Forge 4 Upgrade Kit</i>. ◆ See <i>Upgrading Forge 3.x Appliance 1</i> in the Forge 4 Upgrade Guide for more information. Use the Forge 3.1 Backup mechanism to back up the Forge 3.x Appliance 1 database. <ul style="list-style-type: none"> ◆ Run <code>PlateSpin.ForgeUpgrade.exe /backup</code>, included in <code>PlateSpin.ForgeUpgrade_4.0.0.xxxx.zip</code>, part of the <i>Forge 4 Upgrade Kit</i>. ◆ See Section 2.1, "Backing Up the Forge Management VM," on page 17 for more information. Use the Forge 4.0 Restore mechanism to restore data from the Appliance 1 database to the Appliance 2 database. <ul style="list-style-type: none"> ◆ Run <code>PlateSpin.ForgeUpgrade.exe /restore</code>, included in <code>PlateSpin.ForgeUpgrade_4.0.0.xxxx.zip</code>, part of the <i>Forge 11 Upgrade Kit</i>. ◆ See Section 2.4, "Restoring the Appliance," on page 32 for more information.
3.1, 3.3, 3.4 <ul style="list-style-type: none"> ◆ Appliance 2 ◆ Dell R610, R620, R710, R720 	4.0 <ul style="list-style-type: none"> ◆ Appliance 2 	<ol style="list-style-type: none"> Upgrade PlateSpin Forge software to version 4.0. <ul style="list-style-type: none"> ◆ Run <code>PlateSpinForgeSetup-4.0.0.x.exe</code> from the <i>Forge 4 Upgrade Kit</i>. ◆ See Appendix A, "Upgrading Forge 3.x Appliance 2," on page 47 for more information.

Current Forge Version	Highest Version Upgrade Path	Upgrade Steps
4.0 <ul style="list-style-type: none"> ◆ Appliance 2 ◆ Dell R610, R620, R710, R720 	11.0 <ul style="list-style-type: none"> ◆ Appliance 3 	<ol style="list-style-type: none"> 1. Use the Forge 11.0 Backup mechanism to back up the Appliance 2 database. <ul style="list-style-type: none"> ◆ Run <code>PlateSpin.ForgeUpgrade.exe /backup</code>, included in <code>PlateSpin.ForgeUpgrade_11.0.0.xxxx.zip</code>, part of the <i>Forge 11 Upgrade Kit</i>. ◆ See Section 2.1, “Backing Up the Forge Management VM,” on page 17 for more information. 2. Use the Forge 11.0 Restore mechanism to restore data from the Appliance 2 database to the Appliance 3 database. <ul style="list-style-type: none"> ◆ Run <code>PlateSpin.ForgeUpgrade.exe /restore</code>, included in <code>PlateSpin.ForgeUpgrade_11.0.0.xxxx.zip</code>, part of the <i>Forge 11 Upgrade Kit</i>. ◆ See Section 2.4, “Restoring the Appliance,” on page 32 for more information.

1.3 The Forge 11 Upgrade Media Kit and Its Contents

The *Forge 11 Upgrade Kit* is intended for customers who want to update their PlateSpin Forge 4 Appliance 2 installation to PlateSpin Forge 11.0.0 Appliance 3. The table below lists the media included in the upgrade kit, along with a listing of the files on each medium. One or more of these files are required to accomplish the upgrade, depending on the upgrade scenario.

Table 1-1 *Forge 11 Upgrade Kit Media and Contents*

Label	Medium Type and Storage Used	Included Contents and Purpose
<i>Forge 11 Rebuild Kit</i>	13+ GB of storage accessible by the administrative computer	<ol style="list-style-type: none"> 1. Contents of the 13 GB storage includes a <code>/VM</code> folder with the following files: <ul style="list-style-type: none"> <code>PLATESPINFORGE01.mf</code> <code>PLATESPINFORGE01.ovf</code> <code>PLATESPINFORGE01-disk1.vmdk</code> <code>PLATESPINFORGE01-disk2.vmdk</code> <code>PLATESPINFORGE01-file1.flp</code> 2. The Forge 11 installation ISO, which is used during a rebuild of the Forge Appliance Host. <ul style="list-style-type: none"> ◆ The VM <code>.ovf</code> file is the same as the file used in the PlateSpin Forge 11.0.0.x release build. You will mount this <code>.ovf</code> file during the installation process to import the Forge VM into ESXi. ◆ For more information, see Section 2.2.2, “What You Need,” on page 21 and Section 2.2.3, “Installing the Hypervisor and Forge Components,” on page 21.

Label	Medium Type and Storage Used	Included Contents and Purpose
<i>Forge 11 Rebuild Kit</i>	CD 678 MB	<ol style="list-style-type: none"> The PlateSpin Forge 11.0.0.x ISO image. <ul style="list-style-type: none"> This CD is included in the <i>Forge 11 Upgrade Kit</i> for your convenience. Use it as the boot media to install the latest ESXi version and to import the Forge VM (from the VM folder on the USB flash drive) to the Forge Appliance Host. See Section 2.2.3, "Installing the Hypervisor and Forge Components," on page 21 for more information.
<i>Forge 11 Upgrade - Disk 1</i>	DVD 2.83 GB	<ol style="list-style-type: none"> PlateSpin.Forge_11.0.0_UpgradeGuide.pdf <ul style="list-style-type: none"> This manual, which includes information about upgrade scenarios, upgrade tasks, and troubleshooting tips you need for the Forge 11 upgrade. PlateSpinForgeSetup-4.0.0.xxxx.exe <ul style="list-style-type: none"> The Forge 11.0.0 installation/upgrade program. Use this program to update Forge 3.x software (appliance 2 only) to Forge 4 software. For more information, see Appendix A, "Upgrading Forge 3.x Appliance 2," on page 47. PlateSpinForgeUpgrade_11.0.0.xxxx.zip <ul style="list-style-type: none"> The Forge 11.0.0 backup/restore utility, PlateSpin.ForgeUpgrade.exe

1.4 Important Upgrade Information

You need to understand the following facts as you upgrade to PlateSpin Forge 11.0:

- ◆ Ongoing protection contracts are supported, such as
 - ◆ X2V or Sync2V
 - ◆ Live or Idle workload states
 - ◆ Windows or Linux workloads
- ◆ Failover VM locations can be a local datastore (ds), an external ds, or a combination of both.
- ◆ Failover VM components locations
 - ◆ .vmx files can be located on a local ds, an external ds, or a combination of both.
 - ◆ .vmdk files can be located on a local ds, an external ds, or a combination of both
- ◆ Although the [administrative computer](#) you use to run the backup does not need to be the same machine that you use to run the restore, the [outputdirectory](#) of the backup (including all of its the generated subdirectories and files) should be the same outputdirectory used in the restore.

The machine needs to have access to the [outputdirectory](#) specified in the backup and restore operations.

The machine needs to have access to the same USB storage media for the restore process as that which it accessed for the backup process.

1.5 Upgrade Precautions

The upgrade process to Forge 11 might require you to monitor conditions and make adjustments as needed:

- ♦ Prior to the Backup stage, all Forge datastores must use default naming:
 - ♦ **Appliance 2:** datastore1 and ForgeSystem

TIP: Use the following steps if you want to check the datastore name:

1. Open the VMware Client program to your Forge Appliance Host.
 2. From the client, select the address or DNS name of your Forge Appliance Host.
 3. Click the **Configuration** tab to open the Configuration page.
 4. In the Configuration page **Hardware** table, select **Storage**.
 5. In the **Identification** column, verify the datastore name.
-

- ♦ Prior to the Backup and Restore stages, you should run the `net use` command to mount the volume and then to clean up the mount point prior to the restore or backup. The command ensures the success of these operations. For example, if drive letter `P:` is available on the administrative computer, you would use the command like this:

```
net use P: \\<forge_appliance_vm_address>\ADMIN$
net use P: /delete
```

- ♦ Due to firewall restrictions, the VM's IP address might have to reside in the same VLAN as the administrative computer.
- ♦ Following the rebuild, appliance version 2 carries forward any user-modified settings from appliance version 1.

The user might have modified these settings:

- ♦ ESX server
 - ♦ Datastores added that are backed by external storage
 - ♦ Networking changes: vSwitches, portgroups, VM kernel ports
 - ♦ Windows domain membership or Active Directory authentication
 - ♦ Clock or NTP settings
 - ♦ Local account usernames and passwords
- ♦ Forge VM
 - ♦ Network or firewall settings
 - ♦ Domain or workgroup membership
 - ♦ Local Windows usernames and passwords
 - ♦ Windows updates
- ♦ Following the Restore stage, the Appliance host network IP must be static. DHCP settings are not supported in appliance version 2.

1.6 Upgrade Prerequisites

Before you start the upgrade, make sure that check for the following:

- ♦ The Forge Appliance, version 2.

- ♦ The Forge Configuration Worksheet, available at the [PlateSpin Forge 11 documentation web site](#).
- ♦ Forge rebuild instructions, as detailed in [Rebuilding the Forge Appliance](#) in this guide.
- ♦ The ESXi 5.5 License Key (an old ESX 5.1 key will not be valid after the upgrade) you obtained with Forge 11. For details, see [“Licensing the ESXi 5.5 Hypervisor” on page 27](#).
- ♦ A Microsoft SQL 2014 Standard Edition license that you obtained with Forge 11. Contact PlateSpin support if you require help.
- ♦ A Windows license for the Forge VM 2012 Server that you obtained with Forge 11. Contact PlateSpin support if you require help.
- ♦ The VMware client program. See [“Downloading the vSphere Client Program”](#) in the *PlateSpin Forge 11.0 User Guide*.
- ♦ For systems currently at version Forge 3.x or earlier, an upgrade to Forge 4.0 is required. For upgrade instructions, see [Appendix A, “Upgrading Forge 3.x Appliance 2,” on page 47](#).
- ♦ A Forge [administrative computer](#) with the following:
 - ♦ Windows 2003 (or later) operating system
 - ♦ 3 GB hard disk space for applications
 - ♦ 13 GB disk space on media for OVF templates
 - ♦ Microsoft .NET 3.5 framework installed
 - ♦ Network connectivity to the [Forge Appliance](#). This can be established by using a direct cable to the [Appliance Host](#) or through the Appliance Host’s Windows network.
- ♦ The *PlateSpin Forge 11.0 Upgrade Kit*, available from [PlateSpin Support](#). For more information about upgrade media, see [Section 1.3, “The Forge 11 Upgrade Media Kit and Its Contents,” on page 11](#).
- ♦ **External USB Storage:** Use this storage for backing up Forge failover VMs residing on the appliance local storage. You can restore Forge from this storage.
 - ♦ **USB space and quantity:** Examples of the USB backup arrangements that work:
 - ♦ To back up 900 MB of Forge failover VMs, a single 1 TB USB drive or a set of two 500 MB drives is sufficient.
 - ♦ To back up 3.8 GB of Forge failover VMs, two 2 TB USB drives are sufficient.
 - ♦ **USB power:** We recommend an externally-powered (AC) USB drive. Plug this drive directly into the administrative computer.
 - ♦ **USB 3.0:** We recommend USB 3.0 to speed up the data transfer. You might need to consult with your hardware vendor to ensure that your administrative computer supports USB 3.0.
- ♦ **Web Browser Compatibility:** The Forge Appliance Configuration Console (Forge ACC) supports the following Web browsers:
 - ♦ *Google Chrome*, version 34.0 and later
 - ♦ *Microsoft Internet Explorer*, version 11.0 and later
 - ♦ *Mozilla Firefox*, version 29.0 and later

1.7 Forge Components Changed by the Upgrade

Some components of the Forge Appliance change after the end-to-end is completed. The changes are apparent in either the Forge Web Client, the appliance management software, the appliance console, the Forge VM console, or the vSphere Client connected to ESXi.

The table below lists the affected components.

Table 1-2 Forge components affected by upgrade.

Item	State at Pre-upgrade	State at Post-upgrade	Changed?
Forge Appliance version	version 2	version 3	Yes
ESX version	4.1 Update 1 4.1 Update 3	ESXi 5.5	Yes
Forge VM hardware version	version 4	version 7	Yes
Forge software version	4.0.0.xxxx	11.0.0	Yes
Forge local datastore name	forge:datastore1	forge:datastore1	No
Forge local datastore version	VMFS 3.46	VMFS 5.54	Yes
Existence of ForgeSystem datastore	Yes	Yes	No
Failover VM hardware version	4	4	No
Forge Host credentials	forgeuser	forgeuser	No
Appliance Host network IP	Static	Static only	Yes

1.8 Summary of Forge Upgrade Tasks

To upgrade your Forge appliance, you need to perform the following tasks in order:

1. Make sure all prerequisites are met. See [Section 1.6, “Upgrade Prerequisites,” on page 13](#) for more information.
2. Prepare for backup.
3. Backup.
4. Rebuild Forge Appliance to version 3.
5. Manually restore and confirm Forge Appliance settings.
6. Prepare for restore.
7. Restore.
8. Resume workload protection.

For complete information of tasks/phases of the upgrade, see [Chapter 2, “Upgrade Tasks,” on page 17](#).

2 Upgrade Tasks

This section provides detailed information about the steps required to complete the upgrade. The following information is included:

- [Section 2.1, “Backing Up the Forge Management VM,” on page 17](#)
- [Section 2.2, “Rebuilding the Forge Appliance,” on page 20](#)
- [Section 2.3, “Post-Setup Tasks,” on page 31](#)
- [Section 2.4, “Restoring the Appliance,” on page 32](#)
- [Section 2.5, “Confirming Appliance Data and Resuming Protection,” on page 34](#)

2.1 Backing Up the Forge Management VM

The following information is included in this section:

- [Section 2.1.1, “Preparing for the Backup,” on page 17](#)
- [Section 2.1.2, “Performing the Forge Backup,” on page 18](#)

2.1.1 Preparing for the Backup

Before you back up the Forge Management VM, you need to ensure that all of the upgrade [prerequisites](#) have been met and that you have a completed [PlateSpin Forge 11.0 Configuration Worksheet](#) to document your current environment, and that you retain the worksheet to list changes needed for Forge 11.0 configuration.

NOTE: If you are upgrading from version 3.x of PlateSpin Forge, you need to upgrade the appliance VM software prior to the backup. To do so, you should request the *Forge 11.0 Upgrade Kit* (available from PlateSpin Support) and extract the Forge 4.0 Setup Utility (PlateSpinForgeSetup-4.0.0.xxxx.exe) from the kit, then use the instructions in [Appendix A, “Upgrading Forge 3.x Appliance 2,” on page 47](#) to bring the appliance up to date prior to backup.

Use the following steps to prepare for the backup:

- 1 Extract the contents of the *Forge 11.0 Upgrade Kit* from the USB media (D:\forgebackup\11.0_kit\Forge_11.0_Upgrade_kit.zip) to a storage area on the [administrative computer](#) with sufficient free space. The location where you extract the upgrade kit becomes the [working directory](#). For example, D:\forge_backup\11.0_kit.
- 2 Pause all protection contracts. Workloads should be in an “Idle” or “Live” state.

NOTE: The upgrade utility also attempts to pause protection contracts.

- 3 On any Windows machine that can connect to the Forge Appliance (such as the administrative computer), obtain information for the VMs registered on the VMware server.
 - 3a Launch VMware Infrastructure Client and connect to the Forge Appliance.
 - 3b In the left pane of the Infrastructure Client, select the root of the inventory (representing the ESX host), then select the **Virtual Machines** tab.
 - 3c Click **File > Export > Export List**, select the file format you in which you want to save the list (for example, .csv), then save the file list to an [output directory](#). For example, you could save VM-list.csv to `D:\forge_backup\out\`.

NOTE: You will use this same output directory in the backup stage (see [Step 4 on page 18](#)) and in the restore stage (see [Step 3 on page 32](#)) of the upgrade.

You also need to prepare the USB backup media:

- ♦ Remember that you can attach USB storage devices to the administrative computer to back up any virtual machines located locally on the ESXi host, prior to rebuilding the appliance. For more information, see [Section 1.6, “Upgrade Prerequisites,” on page 13](#).
- ♦ Ensure that your backup media are the only USB storage devices attached to the administrative computer. Detach any other USB medium.

IMPORTANT: The USB drives that are attached to the administrative computer are formatted as part of the backup process.

2.1.2 Performing the Forge Backup

Use the following steps to perform the backup:

- 1 From the [administrative computer](#), open a command prompt window and change to the working directory you created in [Step 1 on page 17](#).

NOTE: You must have administrator rights to run the backup command successfully.

To set this privilege from the administrative computer:

1. From the Windows administrative computer desktop, click **Start > All Programs > Accessories**, right-click the Command Prompt start icon, then select **Run as administrator** to launch the command prompt as Administrator.

TIP: If you want to set the *Run as administrator* mode as the default, follow Step 1 above, but after the right-click, select **Properties > Shortcut > Advanced > Run as administrator**.

- 2 From the location where you extracted the contents of the *Forge 11 Upgrade kit*, unzip the *Forge 11.0 Upgrade Utility* (PlateSpin.ForgeUpgrade_11.0.zip) to the same working directory.
- 3 In the working directory, change to the newly created \PlateSpin.ForgeUpgrade_11.0 subdirectory.
- 4 Run the backup utility from the command line, entering data you obtain from the *Configuration Worksheet*. For example:

```
PlateSpin.ForgeUpgrade /backup /psserver=10.99.160.72 /username=admininstrator
/esx_address=10.99.163.200 /esx_username=forgeuser
/outputfolder=D:\forge_backup\out
```

NOTE: If you are unfamiliar with the backup utility parameters, you can learn more by accessing its help: `PlateSpin.ForgeUpgrade.exe /help`.

- 5 (Conditional) If you chose not to use the available parameters for supplying passwords via a file, enter those passwords when prompted:

```
Starting task "Validate user input".
Step 1 of 6: Setting Default Values
Step 2 of 6: Getting Required Passwords
  Please enter the password for PlateSpin server user 'administrator':*****

  Please enter the Forge Virtual Host password for user 'forgeuser': *****

  Please enter the Forge Virtual Host superuser/root password: *****
```

- 6 Enter y (yes) at the following prompt:

```
Step 4 of 6: Validating Contract Export
  All scheduled contracts will be paused. Continue? [y|n] y
```

- 7 (Optional) If you want to backup the failover VMs to USB drives, enter y (yes) at the following prompt:

```
Step 5 of 6: Confirming that failover VMs should be backed up
  These failover VMs can be backed up:
```

```
AS-WINA--01-04F_VM
AS-SL10S3-A-02.PLATESPIN.COM_VM
```

```
  Would you like to backup VMs on local storage to USB drives? [y|n] y
```

The failover VM names eligible for backup are listed at this prompt. Note that only VMs stored locally are listed here. For more information about the USB drives you can use for backup, see [Section 1.6, "Upgrade Prerequisites," on page 13](#).

IMPORTANT: The VM backup process to USB storage might take up to six days to complete, depending on the number and size of the VMs.

VERY IMPORTANT: If you do not choose this option, any failover VMs on local storage are **not** saved. You will need to re-add each source machine currently configured to replicate to local storage back to Forge after the upgrade.

The backup utility displays an information screen:

```
Please ensure that external USB storage is plugged in. All data on external USB
storage will be wiped out before backup. Press any key to continue...
```

The backup process also displays a confirmation list of the drive names of all attached storage on the administrative computer that are about to be formatted.

- 8 Press any key to display the final warning screen:

```
Step 6 of 6: Confirming backup
  Do you wish to begin the backup process?
```

```
  Please note that this process can take up to 6 days to complete, depending
  on the size of your protected workloads. During this time, incremental
  replications will be stopped. Do not disrupt this process or use the appliance
  until the backup has completed. [y|n] y
```

- 9 Enter y (yes) to display this information:

```
Step 2 of 3: Pausing scheduled contracts
```

The utility begins pausing the scheduled contracts.

When the backup process has completed successfully, you will see output at the command prompt similar to this:

The task Back up Forge failover VMs completed successfully.

Backup Summary:

The task "Validate user input" completed successfully.
Step Setting Default Values completed successfully.
Step Getting Required Passwords completed successfully.
Step Validating Parameters completed successfully.
Step Validating Contract Export completed successfully.
Step Confirming that failover VMs should be backed up completed successfully.
Step Confirming backup completed successfully.
The task "Back up contracts" completed successfully.
Step Gathering information about the Forge appliance completed successfully.
Step Pausing scheduled contracts completed successfully.
Step Exporting Forge Server Contracts completed successfully.
The task Back up Forge failover VMs completed successfully.
Step Enable ssh for root user on ESX completed successfully.
Step Validate external USB disks completed successfully.
Step Partition and format external USB disks completed successfully.
Step Backup of ESX configuration completed successfully.
Step Shut down Forge failover VMs completed successfully.
Step Backup of Forge failover VMs on local storage completed successfully.

2.2 Rebuilding the Forge Appliance

When you have completed the backup of the Forge appliance, use the *Forge 11 Upgrade Kit* to rebuild it from version 2 to version 3. Before you begin this process, make sure that you have your ESXi 5.5 license available (the older ESX 5.1 license will not be valid after you upgrade).

This section includes the following information:

- ♦ [Section 2.2.1, "About the Forge 11 Rebuild Process," on page 20](#)
- ♦ [Section 2.2.2, "What You Need," on page 21](#)
- ♦ [Section 2.2.3, "Installing the Hypervisor and Forge Components," on page 21](#)
- ♦ [Section 2.2.4, "Licensing Microsoft Products on the Forge Management VM," on page 25](#)
- ♦ [Section 2.2.5, "Licensing the ESXi 5.5 Hypervisor," on page 27](#)
- ♦ [Section 2.2.6, "Running the Forge Appliance Configurator," on page 28](#)
- ♦ [Section 2.2.7, "Backing Up the Factory VM," on page 28](#)
- ♦ [Section 2.2.8, "Restarting the Appliance," on page 29](#)
- ♦ [Section 2.2.9, "Configuring the Appliance for Immediate Use," on page 29](#)
- ♦ [Section 2.2.10, "Launching the PlateSpin Forge Web Client," on page 29](#)
- ♦ [Section 2.2.11, "Product Licensing," on page 30](#)

2.2.1 About the Forge 11 Rebuild Process

At a high level, the Forge 11.0, Appliance Version 2 rebuild process consists of the following major steps:

- ♦ Re-installing the hypervisor

- ♦ Re-deploying Forge software (including the Forge Management VM and the Appliance Configuration Console (ACC))
- ♦ Re-licensing all components

NOTE: The rebuild process erases all data in the Forge appliance's local storage.

2.2.2 What You Need

Before you start rebuilding Forge, make sure that you have the following prerequisites:

A Forge 11.0 Rebuild Kit, containing:	Contact PlateSpin Support to request a kit.
<ul style="list-style-type: none"> ♦ Forge 11.0 media containing the OVF template. ♦ Forge 11.0 Installation CD/DVD ♦ Rebuild instructions 	
A VMware ESXi 5.5 license	Contact PlateSpin Support for help to retrieve your license.
A Microsoft license for the Forge VM operating system (Windows Server 2012)	Contact PlateSpin Support for help to retrieve your license.
A Microsoft license for the Forge database (SQL Server 2014)	Contact PlateSpin Support for help to retrieve your license.
A PlateSpin Forge 11.0 license	Post-rebuild requirement for unlocking the product's business functionality.
	See "Product Licensing" in the <i>PlateSpin Forge 11.0 User Guide</i> .

2.2.3 Installing the Hypervisor and Forge Components

This section provides information about installing the hypervisor and Forge software components in your appliance.

- ♦ ["Installing VMware ESXi 5.5.0 to the Appliance" on page 21](#)
- ♦ ["Connecting the Forge Administrative Computer" on page 22](#)

Installing VMware ESXi 5.5.0 to the Appliance

PlateSpin Forge requires VMware ESXi 5.5 to control the Forge Management VM. You need to make sure that you have the *PlateSpin Forge 11.0.0 Installation* CD to proceed with the installation.


To install VMware ESXi 5.5.0 to the Forge Appliance:

- 1 Power on the appliance and press F11 at the boot prompt.
- 2 While at the boot prompt, insert the installation CD into the CD-ROM drive.
It might take some time for the *Boot Manager* utility to be displayed.
- 3 On the *Boot Manager Main Menu*, select **BIOS Boot Menu** to launch the *BIOS Boot Manager*.
- 4 In the *BIOS Boot Manager* utility, navigate to the option that lets you boot from an optical device (for example, a SATA optical drive), then press Enter.

NOTE: The name of the optical device might vary, depending on the device driver installed on the appliance.

- 5 On the Forge *ESXi build* installation menu, select **ESX Scripted Install for the Forge Appliance**, then press Enter to load the ESXi installer.

The installation progress updates on the screen and moves through several stages. When the process is completed, the following dialog box is displayed prior to the system reboot:



NOTE: If you choose not to attend the installation, the system reboots on its own. You will see the ESXi console when you return.

If you encounter problems during the installation, see [Section 3.4, “Errors Occurring During ESXi Installation,” on page 39](#) of this guide.

- 6 In the dialog box, press Enter to reboot the system (or let the system reboot itself), then continue with the instructions in [“Connecting the Forge Administrative Computer” on page 22](#).

Connecting the Forge Administrative Computer

To continue with the installation and configuration of the appliance, you need to connect directly to it through another computer, an “administrative computer.” You should have been using a Windows notebook computer (that is, a “laptop”) for this purpose in the past.

This section includes the following information:

- ♦ [“Connecting the Appliance and the Administrative Computer” on page 22](#)
- ♦ [“Deploying the OVF Template” on page 24](#)

Connecting the Appliance and the Administrative Computer

For licensing and configuration tasks in this section, use the following procedure to connect your administrative computer to the Forge hardware appliance. This requires setting up a physical connection, configuring with a static IP address in the same subnet as Forge, then re-connecting the administrative computer to the Forge appliance. It also includes establishing a management connection, which enables the administrative computer to configure aspects of the Forge appliance software.

This section includes the following information:


- ♦ [“Establishing a Physical Connection” on page 23](#)
- ♦ [“Establishing a Management Connection through the vSphere Client” on page 23](#)

Establishing a Physical Connection


To establish a physical connection between the administrative computer and the Forge Appliance:

- 1 Use one of these methods:

Connection through a Network Switch: Connect both units to a network switch or a hub through an Ethernet network cable:



Direct Connection: Connect your PlateSpin Forge appliance and the computer directly through a crossover cable:



- 2 Turn on the power at the Forge appliance. Wait at least 10 minutes for the system to fully start before trying to connect.
- 3 Access the TCP/IP properties of the administrative computer's wired LAN adapter and assign it an IP address (192.168.1.205) and an associated subnet mask (255.255.255.0).

NOTE: Do not use the following IP addresses:

- ♦ 192.168.1.200 - used by the hypervisor
- ♦ 192.168.1.210 - used by the Forge VM (assigned by an automatic appliance configuration utility).

-
- 4 Save the settings and close the LAN Properties applet.

Establishing a Management Connection through the vSphere Client

When the administrative computer has been connected physically, you need to establish the management connection between the administrative computer and the ESXi hypervisor and the Forge Management VM. The connection is enabled through the VMware vSphere Client on the administrative computer. By using the vSphere client on the administrative computer, you can access the ESXi hypervisor and the Forge Management VM.

You already installed ESXi 5.5 on the Forge Appliance. From the administrative computer's physical connection to the Forge Appliance, you can access and download the vSphere Client.

NOTE: You will need a connection to the Internet for the download to be successful. You can either copy the link location and download the client while you are connected, or you can manually download the vSphere Client from the VMware download site (see the procedure below).

On the administrative computer, use the following steps to install the VMware Infrastructure Client program:

- 1 From a browser, enter the Forge Host address to open the *VMware ESXi 5.5 Welcome* page, then select **Download vSphere Client**.
- 2 At the download location, run the vSphere Client installation .exe.
- 3 Launch the vSphere Client login, then connect to the PlateSpin Forge using these parameters:

IP address: 192.168.1.200

User name: root

Password: Password1

The vSphere Client opens, connected to the hypervisor.

Deploying the OVF Template

Included in the *PlateSpin Forge 11 Appliance Build Kit* USB Flash Drive (available from PlateSpin Support) is the The VM .ovf file used in the PlateSpin Forge 11.0.0.x release build. You will access this .ovf file during the installation process to import the Forge VM into ESXi.

Use the following steps to deploy the OVF template:

- 1 From the *PlateSpin Forge 11 Appliance Build Kit* media, copy the PlateSpin Forge 11.0 Appliance VM folder, with all its contents, to the administrative computer.
- 2 In the vSphere Client (see [“Installing VMware ESXi 5.5.0 to the Appliance” on page 21](#)), click **File > Deploy OVF Template**.
- 3 In the *Deploy OVF Template* dialog box, browse to the location where you downloaded the .ovf file, then click **Next**.
- 4 In the **Name** field of the *Name and Location* view, enter PLATESPINFORGE01 as the name for the imported PlateSpin Forge Management VM, then click **Next**.
- 5 From the *Storage* view, select **ForgeSystem** as the destination storage location, then click **Next**.
- 6 From the *Disk Format* view, select **Thick Provision Eager Zeroed**, then click **Next**.
- 7 From the *Ready to Complete* view, select **Power on after deployment**, then click **Finish**.

The VM import process should complete after approximately 15 minutes.

- 8 In the vSphere client, locate the Forge Management VM (PLATESPINFORGE01), right-click the VM, then rename it to PlateSpin Forge Management VM.
- 9 In the vSphere client, click the **Console** tab, then click inside the remote console window.
- 10 At the *Product Key Settings* page, enter the product key.
- 11 On the *Administrator Account Settings* page, set the administrator password as Password1, click **Finish**, then log in (ensure that you press Ctrl+Alt+Insert to log in to the VM).

2.2.4 Licensing Microsoft Products on the Forge Management VM

NetIQ subscribes to a Microsoft Volume Licensing agreement, allowing us to pre-install Windows Server 2012 and SQL Server 2014 on the Forge Management VM without activating a license for either installation. You are not required to obtain a license from Microsoft yourself. Contact NetIQ Support for assistance with questions or issues regarding Microsoft product licensing.

Licensing Windows Server 2012


There are two methods you can use to activate the Windows Server 2012 license:

- ♦ [“Offline License Activation by Phone” on page 25](#)
- ♦ [“Multiple Activation Key License Activation” on page 26](#)

Offline License Activation by Phone


To license Windows Server 2012 offline for the Forge Management VM and log in for the first time:

- 1 In the program tree view of the vSphere client (on the administrative computer), select the **PlateSpin Forge Management VM** item and click the green **Play** button to power it on (if it is not already on).



- 2 Click the **Console** tab, then click inside the remote console window.
- 3 On the Windows Server 2012 desktop, right-click the Start button, then select **Command Prompt (Admin)** to open the command line interface with administrative privileges.
- 4 At the command line, enter `slui 4`.
The command launches the Software Licensing User Interface (Wizard) used for calling Microsoft for manual license activation.
- 5 In the interface, select your country or region, dial the toll-free number provided by Microsoft, write down the confirmation ID provided by the Microsoft automated phone system, then click **Enter confirmation ID**.

- 6 In the *Enter your confirmation ID* Wizard page of the interface, enter the confirmation ID you obtained from Microsoft, then click **Activate Windows**.




Multiple Activation Key License Activation

As an OEM provider, you might have already made Volume Licensing arrangements with Microsoft to automate and manage the activation process of Volume Licensing media. Under such an arrangement, you could have a Multiple Activation Key License (MAK) that allows the use of a command line licensing tool.

To license Windows Server 2012 for the Forge Management VM using a command line:

- 1 In the program tree view of the vSphere client (on the administrative computer), select the **PlateSpin Forge Management VM** item and click the green **Play** button to power it on (if it is not already on).



- 2 Click the **Console** tab, then click inside the remote console window.
- 3 On the Windows Server 2012 desktop, right-click the Start button, then select **Command Prompt (Admin)** to open the command line interface with administrative privileges.
- 4 At the command line, enter `slmgr.vbs /ipk <MultipleActivationKey>`.
The command launches a a visual basic script that configures licensing on the Windows 2012 Server. After the script executes, a pop-up dialog box confirms that the product key is installed successfully.
- 5 In the dialog box, click **OK** to finish the key installation.

Licensing the SQL Server 2014

To license the SQL Server 2014 for the Forge Management VM:

- 1 Open the remote console window of the running Forge Management VM, click **Start**, then select the Apps arrow located at the lower-left corner of the *Start* screen.
- 2 In the **Apps** tiles array, expand the list, then scroll right to find **SQL Server 2014 Installation Center**.

IMPORTANT: Do NOT select the *SQL Server Installation Center* app listed in the **Microsoft SQL Server 2008** category.

- 3 In this Installation Center app, click **Maintenance > Edition Upgrade**.
- 4 On the *Edition Upgrade* dialog box, select **Enter the product key**, then enter the product key you obtained from Microsoft to activate the SQL Server 2014 OEM license on the Forge Management VM.
- 5 On subsequent upgrade dialog boxes, click **Next** or **Upgrade** until the licensing process is complete, then close the licensing application.

IMPORTANT: The Microsoft SQL Upgrade window does not display a progress bar. Because upgrading might take a few minutes, you need to wait for an indication that the upgrade completed before you close the dialog box.

2.2.5 Licensing the ESXi 5.5 Hypervisor

NetIQ subscribes to a VMware Volume Licensing agreement, allowing us to pre-install ESXi 5.5 on the Forge Management VM without activating a license for the installation. As the OEM reseller and NetIQ partner, you need to activate the vSphere OEM license as you prepare each Forge Appliance for shipping.

Obtaining the vSphere Product Key


To obtain the OEM Product Keys:

- 1 Contact VMware Support, using one of regional telephone numbers listed on its [Support Contacts page](https://www.vmware.com/support/contacts/us_support.html) (https://www.vmware.com/support/contacts/us_support.html).
- 2 Advise the support representative of the VMware Customer number for NetIQ (supplied in the *Forge 11 Appliance Build Kit*) and that you are activating a license for PlateSpin Forge.
The representative will provide an ESXi 5.5 OEM product key.
- 3 Write down the ESXi 5.5 OEM product key for later use.

Activating the ESXi 5.5 License

To activate the ESXi 5.5 license for the Forge Management VM:

- 1 In the tree view of the VIC client, select the ESXi server node, click the **Configuration** tab, then click **Licensed Features**.



- 2 In the upper right corner of the client interface, click **Edit** and select **Assign a new license key to this host**.
- 3 In the *Assign License* dialog box, enter your license key and click **OK**.
- 4 Click **OK** and exit the vSphere Client program.

2.2.6 Running the Forge Appliance Configurator

After its components are installed, the Forge Appliance is ready for configuration.

To configure the Forge Appliance after installation:

- 1 On the Windows desktop of the Forge Management VM, double-click the **Configure Forge Appliance** shortcut.

The tool runs for about two minutes. The configuration is complete when the system console displays a **SUCCESS** message at the command prompt.

- 2 Shut down the Forge Management VM in Windows (**Settings > Power > Shut down**).

2.2.7 Backing Up the Factory VM


As a precaution after the installation and configuration, you need to back up the Forge Management VM (a.k.a. the “Factory VM”) on the Forge Appliance.

To back up the Factory VM:

- 1 Verify that the Forge Factory VM is shut down.
- 2 At the local console of the Forge Appliance (that is, the Dell Server iDRAC), press Alt+F1.
- 3 Log in as root (password: Password1).
- 4 At the console prompt, enter the following command:

```
python /opt/platespin/config/backup_forge_vm.py -f
```

Wait for the Python script to complete the factory backup process:



```
iDRAC6 KVM
File View Macros Tools Help
[root@forgeToronto ~]# python /usr/bin/forge/backup_forge_vm.py -f
Shutting down the Forge VM
Start to backup. It will take about 30 minutes to finish.
Backup completed.
[root@forgeToronto ~]# _
```

2.2.8 Restarting the Appliance

To restart the Forge appliance software:

Some aspects of the appliance configuration do not take effect until the next boot. You must reboot the appliance to complete the rebuild process.

- 1 Remove the *Forge 11.0 Installation CD*.
- 2 At the console prompt, enter the `reboot` command and press Enter.
The shutdown sequence switches screens, hiding the shutdown process.
- 3 Press `Alt+F2` to return to the screen displaying the shutdown sequence.
Forge is now rebuilt and is in the same state as it was when it left the factory.

2.2.9 Configuring the Appliance for Immediate Use

To begin the configuration of the appliance, reconnect your administrative computer and use the browser-based Forge Appliance Configuration Console (Forge ACC) utility.

To configure the appliance:

- 1 Power on the appliance hardware.
- 2 Configure Forge by following the instructions in the “[Appliance Configuration Procedure](#)” section of the *PlateSpin Forge 11.0 Getting Started Guide*.

NOTE: The *Getting Started Guide* is posted online at (https://www.netiq.com/documentation/platespin-forge-11/forge_getstart/data/bookinfo.html).

2.2.10 Launching the PlateSpin Forge Web Client

Most of your interaction with the appliance takes place through the browser-based PlateSpin Forge Web Client.

The supported browsers are:

- ♦ *Google Chrome*, version 34.0 and later

- ♦ *Microsoft Internet Explorer*, version 11.0 and later
- ♦ *Mozilla Firefox*, version 29.0 and later

NOTE: JavaScript (Active Scripting) must be enabled in your browser:

- ♦ **Chrome:** From the Chrome menu, select **Settings**, scroll to and select **Show advanced settings...**, select **Content Settings > Allow all sites to run JavaScript**.
 - ♦ **IE:** From the Tools menu, select **Internet Options > Security**, click **Custom level. . .**, scroll to and select **Active scripting**, select **Enable**, select **Yes** at the warning dialog box, click **OK**, click **Apply > OK**.
 - ♦ **Firefox:** Click **Tools > Options > Content**, then select the **Enable JavaScript** option.
-

To launch the PlateSpin Forge Web Client from any computer:

- 1 Open a web browser and go to:

`http://<hostname | IP_address>/Forge`

Replace `<hostname | IP_address>` with the hostname or the IP address of your Forge VM.

If SSL is enabled, use `https` in the URL.

The first time you log into PlateSpin Forge, the browser is automatically redirected to the License Activation page.

2.2.11 Product Licensing

To license PlateSpin Forge 11.0, you must have a license activation code. If you do not have a PlateSpin Forge license activation code, request one through the [Customer Center website \(http://www.netiq.com/center/\)](http://www.netiq.com/center/). A license activation code will be emailed to you.

You have two options for activating your product license: online or offline.

- ♦ [“Online License Activation” on page 30](#)
- ♦ [“Offline License Activation” on page 31](#)

Online License Activation

For online activation, PlateSpin Forge Web must have Internet access.

NOTE: HTTP proxies might cause failures during online activation. Offline activation is recommended for users in HTTP proxy environments.

To activate a Forge license online:

- 1 In the PlateSpin Forge Web Client, click **Settings > Licenses > Add License**. The License Activation page is displayed.

- 2 Select **Online Activation**, specify the email address that you provided when placing your order and the activation code you received, then click **Activate**.

The system obtains the required license over the Internet and activates the product.

Offline License Activation

For offline activation, you need to obtain a license key over the Internet by using a machine that has Internet access.

NOTE: To obtain a license key, you must have a Customer Center account. If you are an existing PlateSpin customer and you don't have a Customer Center account, you must first create one. Use your existing PlateSpin username (a valid email address registered with PlateSpin) as input for your Customer Center account username.

To activate a Forge license when offline:

- 1 In the PlateSpin Forge Web interface, click **Settings > License**, then click **Add license**. The License Activation page is displayed.
- 2 Select **Offline Activation**.
- 3 Use your hardware ID to create a license key file at the [PlateSpin Product Activation website \(http://www.platespin.com/productactivation/ActivateOrder.aspx\)](http://www.platespin.com/productactivation/ActivateOrder.aspx). This also requires a user name, password, the email address that you provided when placing your order and the activation code you received.
- 4 Type the path to the file or browse to its location and click **Activate**.

The license key file is saved and the product is activated based on this file.

2.3 Post-Setup Tasks

1. Check the following:
 - ♦ If you connected the administrative computer to external USB storage during [backup](#), you need to reconnect it to the same external storage.
 - ♦ Ensure that all ESX network (or portgroup) names are the same they were as prior to upgrade.
 - ♦ Ensure that the current Forge Hostname and IP address are the same as the previous Forge 4 host name and IP address.
 - ♦ Ensure that the current ESXi hostname is the same as the previous Forge 4 ESX hostname.
2. (Optional; for international versions) Set up PlateSpin Forge and your browser for use in a specific supported language. See "[Language Setup for International Versions of PlateSpin Forge](#)" in the *PlateSpin Forge 11.0 User Guide*.

3. Configure appliance host networking to separate replication or failover traffic from your main production network. See “[Setting up Appliance Host Networking](#)” in the *PlateSpin Forge 11.0 User Guide*.
4. Configure SMTP settings and add email notification recipients. For information, see “[Setting Up Automatic Email Notifications of Events and Reports](#)” in the *PlateSpin Forge 11.0 User Guide*.
5. (Optional) Add additional data storage capacity to Forge. See “[Using External Storage Solutions with PlateSpin Forge](#)” in the *PlateSpin Forge 11.0 User Guide*.
6. Familiarize yourself with the PlateSpin Forge Web Interface (see “[Up and Running](#)” in your *User Guide*), as well as the workload protection life cycle (“[Basic Workflow for Workload Protection and Recovery](#)” in the *PlateSpin Forge 11.0 User Guide*).

2.4 Restoring the Appliance

Before you begin restoring the appliance, make sure that you do the following:

- ♦ Connect your administrative computer to the appliance, as explained in [Step 1 on page 23](#).
- ♦ Make sure that the administrative computer has the output folder that was generated and collected during the backup (see [Step 3 on page 18](#)).
- ♦ If you connected external USB storage to the administrative computer at backup time, you need to reconnect the same external storage to the administrative computer for restore.
- ♦ Make sure you have access to the `PlateSpin.ForgeUpgrade_11.0.zip` utility, part of the [PlateSpin Forge 11 Upgrade Kit](#) available from PlateSpin Support.
- ♦ You must be able to run the `net use` command referenced in [Section 2.1.2, “Performing the Forge Backup,” on page 18](#). If the command fails, you might need to add some exceptions to the firewall for file sharing, or you might need to disable the firewall altogether during the upgrade process.
- ♦ Reattach any external storage you might have previously used with the appliance.

Use the following steps to restore the appliance:

- 1 From the command prompt on the administrative computer, change the directory to the working directory. For information about the backup directory, see [Section 1.5, “Upgrade Precautions,” on page 13](#).
- 2 If you have not already done so, extract the contents of `PlateSpin.ForgeUpgrade_11.0.zip` into to the same volume where the output directory resides (for example, `D:\forge_backup`), then change directory to the `\PlateSpin.ForgeUpgrade_11.0` subdirectory.
- 3 Run the restore utility from the command line, entering data you obtain from the configuration worksheet. For example:

```
PlateSpin.ForgeUpgrade.exe /restore /psserver=151.155.168.226 /  
username=administrator /esx_address=151.155.168.225 /esxusername=forgeuser /  
outputfolder=D:\forge_backup\out
```

NOTE: You need to know the following as you run this utility:

- ♦ If you are unfamiliar with the restore utility parameters, you can learn more by accessing its help: `PlateSpin.ForgeUpgrade.exe /help`.
 - ♦ You must specify a path pointing to the `/outputfolder` specified in the backup utility (see [Step 4 on page 18](#)).
-
- 4 (Conditional) If you chose not to use the available parameters for supplying passwords via a file, enter those passwords when prompted:

Starting task "Validate user input".

Step 1 of 5: Setting Default Values

Step 2 of 5: Getting Required Passwords

Please enter the password for PlateSpin server user 'administrator':

Please enter the Forge Virtual Host password for user 'forgeuser': *****

Please enter the Forge Virtual Host superuser/root password: *****

5 Enter y (yes) at the following prompt:

Step 3 of 5: Validating Parameters

Step 4 of 5: Confirming restore

Do you wish to begin the restore process?

Please note that this process can take up to 4 days to complete, depending on the size of your protected workloads that were backed up to local USB storage. During this time, the protection contracts will not have been restored. Once the failover VMs have been restored, all existing contract data will be overwritten. Do not disrupt this process or use the appliance until the restore has completed. [y|n] y

6 (Optional) If you previously backed up the failover VMs to USB drives, enter y (yes) at the following prompt:

Step 5 of 5: Confirming that failover VMs should be restored

Proceed with restore Forge failover VMs from external USB storage? If so, please attach it now and answer "yes" to continue. If you answer "no" then USB restore will be skipped. [y|n] y

IMPORTANT: If you choose this option, you might have to wait up to four days for the restore process to complete. Otherwise, the wait time should be much less, maybe a few hours.

The restore utility runs. When its process is completed the console displays an information screen like this:

The task Restore Forge failover VMs completed successfully.

Restore Summary:

The task "Validate user input" completed successfully.

Step Setting Default Values completed successfully.

Step Getting Required Passwords completed successfully.

Step Validating Parameters completed successfully.

Step Confirming restore completed successfully.

Step Confirming that failover VMs should be restored completed successfully.

The task Restore previously backed up Forge failover VMs completed successfully.

Step Enable ssh for root user on ESX completed successfully.

Step Enable USB in ESX COS completed successfully.

Step Validate external USB disks completed successfully.

Step Gather list of Forge failover VMs to restore completed successfully.

Step Restore Forge failover VMs from external USB storage completed successfully.

Step Register VMs on shared storage completed successfully.

Step Disable ssh for root user on ESX completed successfully.

The task Restore Forge failover VMs completed successfully.

Step Update contracts completed successfully.

Step Importing Forge Server Contracts completed successfully.

Step Refreshing Forge ESX Server container completed successfully.

The first line of the output indicates that the utility ran successfully.

2.5 Confirming Appliance Data and Resuming Protection

When the restore for Forge 11 appliance version 3 is complete, you can confirm the appliance data and resume workload protection. Use these steps to confirm:

- 1 From any Windows machine that can connect to the appliance, use the vSphere Client to log in to the ESXi 5.5 server, then compare the details of the VMs registered on the server:
 - 1a Launch the vSphere Client and connect to the Forge Appliance.
 - 1b Click on the root of the inventory in the left pane, which represents the ESX host
 - 1c Select the **Virtual Machines** tab, then open the `VM-list.csv` file that you saved when preparing for the backup.
 - 1d Compare the number of VMs in the vSphere client with the VMs listed at time of backup, as detailed in `VM-list.csv`. The number should match.
- 2 Launch the Forge Web Client and complete the following:
 - 2a Ensure all workloads are listed
 - 2b (Conditional) If workload schedules are still paused, resume contract replication.
- 3 In the Forge Web Client, click **Settings > Containers**, then ensure that this new appliance is listed correctly as a VMware ESXi Server version 5.5.

3 Troubleshooting the Upgrade

This section includes information that you can use to help you troubleshoot the Forge upgrade process.

- ♦ [Section 3.1, “Overview of the Restore/Backup Utility,” on page 35](#)
- ♦ [Section 3.2, “Upgrade Utility Parameters,” on page 35](#)
- ♦ [Section 3.3, “Generated Files in the /output Directory,” on page 38](#)
- ♦ [Section 3.4, “Errors Occurring During ESXi Installation,” on page 39](#)
- ♦ [Section 3.5, “Log File Locations,” on page 40](#)
- ♦ [Section 3.6, “Troubleshooting Specific Issues,” on page 41](#)
- ♦ [Section 3.7, “Known Issues,” on page 45](#)

3.1 Overview of the Restore/Backup Utility

The backup or restore process can take a number of days. The following table provides some statistics that might give you some idea of the length of time required to run the Backup and Restore processes on 4TB of data, with 2TB of local VM backup and two USB drives of 2TB each.

Utility	Length of time to complete
Backup	<ul style="list-style-type: none">♦ Full Backup: 140 hours (5.83 days)♦ 2TB Backup: 70 hours
Restore	<ul style="list-style-type: none">♦ Full Restore: 93 hours (3.87 days)♦ 2TB Backup: 46 hours

In case of disruption during this process (for example, a network failure occurs between the administrative computer and the appliance or any other failure that prevents backup or restore from completing) the process is interrupted.

Should this occur, the utility allows for skipping some of previously completed steps. You can analyze the logs to determine which steps have completed successfully and which steps need to be re-run. For more information, see [Section 3.3, “Generated Files in the /output Directory,” on page 38](#) and [Section 3.5, “Log File Locations,” on page 40](#).

3.2 Upgrade Utility Parameters

The following table includes the details of the command line parameters you can use with the `PlateSpin.ForgeUpgrade.exe` utility. There are four types of parameters:

- ♦ **Mandatory:** Parameters that must be included in the command line.

- ♦ **Optional:** Parameters that can be optionally included in the command line.
- ♦ **Hidden:** Parameters that are not included in the list of commands via the /help parameter, but can be used for troubleshooting.
- ♦ **Debug:** Parameters that are used by PlateSpin Development to debug and test the utility.

Parameter	Type	Description
/help		Displays help for the utility.
/backup		Backs up all contracts from the specified server.
/restore		Restores previously backed up contracts to the specified server.
/psserver	Mandatory	Specifies the address of the PlateSpin Server: <ul style="list-style-type: none"> ♦ The PlateSpin Server is the Forge Server that is running on the Forge Management VM. ♦ The address can be specified as IP, hostname, or FQDN. ♦ The value should be specified on the configuration worksheet as the <i>Forge Mgmt VM network settings</i> (Item 5).
/username	Mandatory	Specifies the username used to connect to the PlateSpin Server: <ul style="list-style-type: none"> ♦ Use IP address only. ♦ The value can be specified as username, DOMAIN\username or username@DOMAIN. ♦ The value should be specified on the configuration worksheet as the <i>Local Administrator Password</i> (Item 9).
/esx_address	Mandatory	Specifies the address of the ESX Server. <ul style="list-style-type: none"> ♦ The value should be specified as IP only. ♦ The value should be specified on the configuration worksheet as the <i>Appliance Host Network Information</i> (Item 2).
/esx_username	Mandatory (for Backup only)	Specifies the username used to connect to the ESX Server. <ul style="list-style-type: none"> ♦ The default value is <code>forgeuser</code>. For the Restore function, this value (<code>forgeuser</code>) is hard coded. ♦ The value should be specified on the configuration worksheet as <i>Forge Host Credentials</i> (part of Item 3).
/debugmode	Optional	This parameter prompts the user for the execution of each step of the upgrade. You can choose the next step to execute from the ESX task.
/esx_pwdfile	Optional	Use this parameter to specify the path to a file with the ESX server password in its first line. <ul style="list-style-type: none"> ♦ You can find the <code>/esx_pwdfile</code> value on the configuration worksheet as <i>Forge Host Credentials</i> (part of Item 3).

Parameter	Type	Description
<code>/esx_rootpwdfile</code>	Optional	<p>Use this parameter to specify the path to a file with the ESX server root password in its first line.</p> <ul style="list-style-type: none"> You can find the <code>/esx_rootpwdfile</code> value on the configuration worksheet as <i>Forge Superuser/root</i> (part of Item 1).
<code>/outputfolder</code>	Optional	<p>Specifies the location where all generated and collected files are to be stored.</p> <p>If you do not use this parameter or if you use it and do not add a value for the parameter, the upgrade utility's location is used as the output location.</p>
<code>/pwdfile</code>	Optional	<p>Use this parameter to specify the path to a file with the PlateSpin Server password in its first line.</p> <ul style="list-style-type: none"> You can find the <code>/pwdfile</code> value on the configuration worksheet as the <i>Local Administrator Password</i> (part of Item 9).
<code>/vmPrompt</code>	Optional	<p>Use this parameter to specify the VMs that are to be backed up and restored from USB storage.</p> <p>This parameter applies to VMs on the local datastore.</p>
<code>/zipfile</code>	Optional	<p>This parameter specifies the path to export (that is, back up) or to import (that is, restore) protection contracts.</p> <p>For the backup function, the utility creates the file. For the restore function, the file should already exist.</p>
<code>/noninteractive</code>	Hidden	<p>Use this parameter when you are scripting or redirecting console output. The following is a list of characteristics of this mode when applied to the utility:</p> <ul style="list-style-type: none"> When typed, passwords are not hidden. The progress indicator is suppressed. The mode is not precisely "non-interactive," though that is its name: you are still prompted for action during the process.
<code>/usehttps</code>	Hidden	<p>Use this parameter when you use the HTTPS protocol to connect to the PlateSpin Server.</p> <p>The utility applies the parameter when you add it. For example, if you are constructing a URL to the Protect Web services for the purpose of pausing all contracts before export.</p>
<code>/skipesx</code>	Debug	Use this parameter to skip the ESX task in the upgrade workflow.
<code>/skiperversioncheck</code>	Debug	Use this parameter to skip the version check of the Forge Server.
<code>/skipforge</code>	Debug	<p>Use this parameter to skip the Forge task in the upgrade workflow.</p> <p>WARNING: Applying this parameter might delete the contracts <code>.zip</code> file. For example, when you are prompted that the file will be overwritten, and you answer yes, the file is deleted. A new file is not created because the Forge part is skipped</p>

Parameter	Type	Description
/process	Optional	Use this parameter to specify whether to process checksums asynchronously (<code>async</code>) or synchronously (<code>sync</code>) as the files are being downloaded. Depending on the total size of the files, this could save some time. The default value is asynchronously.
/protocol	Optional	Use this parameter to specify whether to use SCP (<code>scp</code>) or SFTP (<code>sftp</code>) for file transfers. SCP is the default.
/skipformat	Optional	Use this parameter to skip formatting the USB devices on backup. Skipping the formatting allows re-running the backup process in the event of a failure without having to re-download all of the virtual machine files.

3.3 Generated Files in the `/output` Directory

This section includes the names and descriptions of files that are generated during the upgrade process.

File Name	Description
<code>esx-<date_and_time>.tgz</code>	The ESX diagnostics bundle generated during Backup.
<code>ExportLogs</code>	Logs from the PlateSpin Protect and PlateSpin Forge export utilities.
<code>ForgeUpgrade.log</code>	The main log file. The content rolls over on each execution of utility and at 1 MB. Upon rollover, older logs are renamed as <code>ForgeUpgrade.log.<n></code> , where <i>n</i> is a number from 1 through 9.
<code>ForgeUpgrade.zip</code>	These files contain the exported data from the Forge database. If you gave the rebuilt Forge 11.0 appliance a different hostname, you can search and replace the old values in these files.
<code>ForgeUpgrade.zip.orig</code>	This file contains contract data – backup of original after the main file has appliance version 1 local datastore references changed to appliance version 2.
<code>ForgeVMsOnSharedStorageBackupManifest.txt</code>	The paths to the VMs with VMX files that are located on a shared storage datastore.
<code>VM_FILE_MANIFEST</code>	All of the Virtual Machine files that were copied to the USB device(s) from the ESXi server at backup time.
<code>GetForgeVMInfo_Console.txt</code>	Data discovered on the Forge Server: hostname, domain registration, network settings and Windows groups.
<code>GetForgeVMInfo_Debug.log</code>	Log file for remote execution of <code>GetForgeVMInfo</code> .
<code>GetForgeVMInfo_Result.xml</code>	Data discovered on the Forge Server: hostname, domain registration, network settings and Windows groups. Formatted in xml.
<code>ImportLogs</code>	Logs from the PlateSpin Protect and PlateSpin Forge import utilities.

File Name	Description
RefreshContainer.log	Log file for remote execution of RefreshContainer.

3.3.1 Generated File Locations

The location of the files generated during the upgrade depends on the path you that you specified in the `/outputfolder` upgrade parameter or the `/zipfile` upgrade parameter. It also depends on the combination of parameters you used when running the utility. The following table illustrates these cases:

Upgrade Parameter Applied	File Location
Neither the <code>/outputfolder</code> parameter nor the <code>/zipfile</code> parameter were specified when running the upgrade utility.	All files are located in the utility's location.
Only the <code>/outputfolder</code> parameter was specified when running the upgrade utility.	All files are located in the path specified by this parameter.
The <code>/outputfolder</code> parameter and the <code>/zipfile</code> parameter were both specified when running the upgrade utility.	The contract data (<code>.zip</code>) file, the Export and Import logs and RefreshContainer.log are located at the <code>/zipfile</code> location, all others are located at the <code>/outputfolder</code> location.
Only the <code>/zipfile</code> parameter was specified when running the upgrade utility.	The contract data (<code>.zip</code>) file, the Export and Import logs and RefreshContainer.log are located at the <code>/zipfile</code> location, all others are located at the utility's location.

There are some ESX locations where you can find some files:

Server Location	Description
<code>/root</code>	<ul style="list-style-type: none"> Most shell scripts are copied here before execution. Location of <code>backup_and_restore.log</code> and <code>vmcopy.log</code>
<code>/home/forgeuser</code>	Only one shell script is copied here before execution.

3.4 Errors Occurring During ESXi Installation

An error has occurred while parsing the installation script

Source: When you are performing the [VMware ESXi configuration](#), you might see the following error:

```
Error (see log for more info):
An error has occurred while parsing the installation
script

error:/vmfs/volumes/mpx.vmhba33:C0:T0:L0/KICK/KS.CFG:
line 37: "/pre" script returned with an error.

Press <Enter> to continue
```

Explanation: This is a symptom of the hardware model verification script that is failing.

Action: You need to gather information from the installation to understand the corrective actions you need to take.

- 1 Press Alt+F11. This command displays the ESXi alert messages related to the installation failure.
- 2 Press Alt+F1. This command displays the ESXi shell, where you can log in to locate the relevant diagnostic log file:
 - 2a Log in with these credentials:
username: root
password: press Enter for an "empty" password (this is the beginning of the ESXi install, so no root password is set).
 - 2b When logged in, navigate to `/var/log/forge/forge.log`.
This file can provide clues to reasons behind the failure of the install.

3.5 Log File Locations

Use these installation logs to help you diagnose problems with the configuration of the Forge Appliance:

- ♦ The automated ESXi installer writes log files located at `/var/log/messages`.
- ♦ Forge installation logs are located at `/var/log/forge/`.

For log location information specific to the Forge Upgrade utility, see [Section 3.3, "Generated Files in the /output Directory," on page 38](#).

3.6 Troubleshooting Specific Issues

This section includes some of the issues you might encounter while performing a Forge upgrade. The issues and actions you can take to correct or work around them include the following:

- ♦ “Importing Forge Server contracts fails” on page 41
- ♦ “The task “Back up contracts” failed. Could not find a part of the <some_path>\GetForgeVmInfo_Result.xml path” on page 41
- ♦ “Please stop all jobs or wait for them to complete before running the upgrade” on page 42
- ♦ ““Validate user input” failed. Unable to connect to the Forge Server.” on page 42
- ♦ ““Validate user input” failed. Failed to log in. Please check your credentials and try again” on page 42
- ♦ ““Validate user input” failed. Unable to connect to the PlateSpin Server at <IP_address>” on page 43
- ♦ ““Validate user input” failed. Unable to connect to the Forge ESX Server at <IP_address>” on page 43
- ♦ ““Validate user input” failed. The administrator user does not have access to the PlateSpin Server” on page 43
- ♦ ““Validate user input” failed. The password file does not exist” on page 43
- ♦ “Authentication for user root failed” on page 43
- ♦ “Backup or Restore using USB drive fails with error about read-only device” on page 44
- ♦ “Backup to the USB storage fails because it cannot detect the attached USB devices” on page 44
- ♦ “Error when using external shared storage such as a NAS” on page 44

Importing Forge Server contracts fails

Explanation: The following message is displayed:

```
Step 2 of 2: Importing Forge Server Contracts
```

```
The task failed.
```

```
"C:\bin\PlateSpin.ForgeUpgrade\11.0.0.5180\PlateSpin.ForgeUpgrade  
\ForgeUpgrade.zip" Could not be found.
```

Possible Cause: Exported data is not in the location it should be.

Action: If you are using the /outfolder parameter, make sure that it points to the folder where the backup output is located.

If you are not using the /outfolder parameter, make sure that the backup output is in the same folder as the executable.

The task “Back up contracts” failed. Could not find a part of the

<some_path>\GetForgeVmInfo_Result.xml path

Possible Cause: This could be an indication that you are attempting to run the Forge Upgrade utility from a network path. In the ForgeUpgrade.log file, you might see this manifest as:

```
Type: System.IO.DirectoryNotFoundException
```

Please stop all jobs or wait for them to complete before running the upgrade

Error Display: You might see the following message:

```
There are jobs running. Please stop all jobs or wait for them to
complete before running the upgrade.
```

Explanation: The PlateSpin Server is busy with running operations.

Action: Pause all replications and wait for all operations to complete, or abort the running operations.

"Validate user input" failed. Unable to connect to the Forge Server.

Explanation: During the validation phase of the [Backup](#) or [Restore](#), the authentication is failing although the password you entered is correct.

Possible Cause: This is a symptom of having a firewall on the Forge Server, which is preventing access.

Action: Try one of the following:

- ♦ Modify the firewall settings to enable file sharing on the Forge Host for the network on which the administrative computer resides, then try again.
- ♦ Temporarily disable the firewall, then try again.
- ♦ Run the tool from a machine within the same subnet as the PlateSpin Server.

"Validate user input" failed. Failed to log in. Please check your credentials and try again

Error Display: You might see the following message:

```
Step 3 of 5: Validating Parameters
The task "Validate user input" failed. Failed to login. Please
check your credentials and try again.
```

Logs: You might see an exception like this in the stack trace of the main log file:

```
Message: Multiple connections to a server or shared resource by
the same user, using more than one user name, are not allowed.
Disconnect all previous connections to the server or shared
resource and try again
```

Other Symptoms: If you run the net use command on the administrative computer, you might see a message formatted like this:

```
Disconnected          \\<psserver>\d$          Microsoft Windows Network
```

Where <psserver> represents the value specified for the psserver parameter.
For example:

```
Disconnected          \\10.99.160.72\d$          Microsoft Windows Network
```

Possible Cause: A net use connection already exists, probably because you attempted to run the utility previously.

Action: Run the net use <connection> command where <connection> contains relevant content. For example:

```
net use \\10.99.160.72\d$ /d
```

"Validate user input" failed. Unable to connect to the PlateSpin Server at <IP_address>

Error Display: You might see a message like this:

```
The task "Validate user input" failed. Unable to connect to the
PlateSpin server at '10.99.160.72'.
Verify that the address is correct
```

Possible Cause: A domain user is being used to connect to the PlateSpin Server.

Action: Enter the PlateSpin Server credentials of either a non-Domain user or a Domain Administrator.

"Validate user input" failed. Unable to connect to the Forge ESX Server at <IP_address>

Error Display: You might see a message like this:

```
The task "Validate user input" failed. Unable to connect to the
Forge ESX server at '10.99.163.112'.
Please ensure that the address, username, and password are correct
and retry
```

Possible Cause: Credentials for forgeuser (or equivalent) are invalid.

Action: Enter the valid ESX Server credentials.

"Validate user input" failed. The administrator user does not have access to the PlateSpin Server

Error Display: You might see the following message:

```
The task "Validate user input" failed. The user 'administrator'
does not have access to the PlateSpin server at '10.99.160.72'.
Verify that the username and password are correct
```

Explanation: You entered the wrong password for the administrator.

Action: Enter the correct password.

"Validate user input" failed. The password file does not exist

Error Display: You might see the following message:

```
The task "Validate user input" failed. An exception occurred while
reading the password file. Error: {0}
```

Explanation: A password file either does not exist or cannot be read.

Action: Check all of the password files.

Authentication for user root failed

Error Display: You might see the following message:

```
The task Back up Forge failover VMs failed. Authentication for
user "root" failed with result: FAILED
```

Explanation: You entered the wrong password for the superuser or root user.

Action: Enter the correct password for the root user.

Backup or Restore using USB drive fails with error about read-only device

Context: The USB drive is relatively new, but was used in previous backup/restore operations.

Possible Cause: USB drive mount status can change to read-only midway through the backup process. This might occur if the USB drive goes bad.

Action: Try the operation again or try a new USB device.

Backup to the USB storage fails because it cannot detect the attached USB devices

Explanation: Backup fails with an error stating that USB devices not detected. You are prompted to attach the USB devices.

Possible Cause: USB device detection on ESX (in general) is unreliable.

Action: Try these steps:

- 1 Shut down the administrative computer.
- 2 Attach the USB devices.
- 3 Power on the administrative machine.

Error when using external shared storage such as a NAS

Explanation: The upgrade utility displays errors that indicate it is not able to import the VMs. For example:

```
Step 6 of 7: Register VMs on shared storage -
23 Apr 2014 10:00:14,560 WARN - Failed to register VM
<vm_name>.vmx on NAS datastore <nas_name>|
23 Apr 2014 10:00:14,968 WARN - Failed to process VM
<vm_name>.vmx. Exception: System.ApplicationException: Could not
find virtual machine <vm_name>.vmx
```

Possible Cause: The shared storage was not added prior to the restore.

Action: Follow these steps to import the VMs:

- 1 Launch the restore process again.
- 2 Repeat the restore process, using the same options as during your previous attempt, until the following is displayed:

```
Step 5 of 5: Confirming that failover VMs should be restored
Proceed with restore Forge failover VMs from external USB
storage? If so, please attach it now and answer "yes" to
continue. If you answer "no" then USB restore will be skipped.
[y|n]
```

- 3 Enter n to skip the USB restore.

The Restore process resumes, displaying text like this:

```
Step 1 of 1: Register VMs on shared storage -
INFO - Successfully registered VM <vm_name>.vmx on NAS
datastore <nas_name>
The task Restore previously backed up Forge failover VMs
completed successfully.
```

and then this:

```
Starting task Restore Forge failover VMs.
Step 1 of 3: Update contracts
Step 2 of 3: Importing Forge Server Contracts \-/
Step 3 of 3: Refreshing Forge ESX Server container
The task Restore Forge failover VMs completed successfully.

Restore Summary:
The task "Validate user input" completed successfully.
    Step Setting Default Values completed successfully.
    Step Getting Required Passwords completed successfully.
    Step Validating Parameters completed successfully.
    Step Confirming restore completed successfully.
    Step Confirming that failover VMs should be restored
completed successfully.
The task Restore previously backed up Forge failover VMs
completed successfully.
    Step Register VMs on shared storage completed
successfully.
The task Restore Forge failover VMs completed successfully.
    Step Update contracts completed successfully.
    Step Importing Forge Server Contracts completed
successfully.
    Step Refreshing Forge ESX Server container completed
successfully.
```

4 Check the imported VMs.

4a From the vSphere client, select each of the imported VMs:

4b Select the **Summary** tab.

4c (Conditional) If a VM is tagged with a message like this:

```
msg.uuid.altered: This virtual machine might have been
moved or copied
```

Select **I Moved it** to preserve the UUID for the VM.

For more information, see the VMware Knowledge Base article:
[Changing or keeping a UUID for a moved virtual machine.](#)

3.7 Known Issues

This section includes some known anomalies and issues discovered in the upgrade process. They are listed here for your convenience:

- ♦ **The `esx_username` parameter:** The `forgeuser` account (or equivalent) is needed to enable SSH for `root` user. If `root` is specified instead of `forgeuser` (or equivalent), the utility does not prompt for the `forgeuser` account's password separately. At this point, the utility runs successfully only if the `root` user already has SSH enabled
- ♦ **Some VMs not registered after Restore:** If some VMs are not registered back after running the Restore process and the container is refreshed, the contract becomes unusable and must be re-created. You can rerun restore to fix the issue.
- ♦ **NFS datastores:** NFS datastores have not been tested and might not work.
- ♦ **GetForgeVMInfo files:** If you see the output (not on domain) in the log file, the `.xml` file shows the same output as blank: `<Domain></Domain>`.
- ♦ **Inserting a USB drive during upgrade:** Inserting a USB drive into the administrative computer during upgrade corrupts the console display until the display refreshes at interval. The corruption consists of text superimposed over console prompts. If the USB device has a problem, any errors being displayed might be unreadable.

A Upgrading Forge 3.x Appliance 2

If you are upgrading Forge 3.x (Appliance 2) to Forge 4 (Appliance 2), the installation/upgrade utility, `PlateSpinForgeSetup-4.0.0.xxxx.exe` automatically exports and imports data from your previous installation.

This section includes the following information:

- ♦ [Section A.1, “Upgrade Procedure,” on page 47](#)
- ♦ [Section A.2, “Post-Upgrade Tasks,” on page 47](#)

A.1 Upgrade Procedure

Use this procedure to upgrade your PlateSpin Forge 3.x (Appliance 2) product.

- 1 From the *Forge 11 Upgrade Kit*, run `PlateSpinForgeSetup-4.0.0.xxxx.exe` and follow the on-screen instructions.

Make sure that you select the *Save data* option when prompted during the server installation.

TIP: In some situations the installation program might fail to automatically re-import data that it exports during the upgrade process. If this happens, use the `PlateSpin.ImportExport.bat` utility to recover this data from the following directory on your server host:

- ♦ **Windows Server 2003 Systems:** `\Documents and Settings\All Users\Application Data\PlateSpin`
-

A.2 Post-Upgrade Tasks

Use these steps after you have performed the upgrade.

- 1 Check the Workloads page for any paused replication schedules. In particular, look for *Tasks* (special workload protection events with optional commands) generated for automatically upgrading protection contracts that were using a legacy block-based component from earlier versions of the product. This requires a reboot of the protected workload.
- 2 Reapply the required `.config` parameters in the new `.config` files.

Glossary

administrative computer. A Windows machine used externally from the Appliance host to perform the upgrade. We recommend that you use a laptop for this process because the Forge Hardware Appliance build and the configuration procedure requires a direct connection to the Dell Hardware that is used as the Forge Appliance Host.

appliance management software. Software that uses either a terminal console (getty) or a proprietary, browser-based interface (Forge Appliance Configuration Console or *Forge ACC*) to connect directly to an appliance for installation and configuration purposes (for example, setting the Host/VM IP addresses, Hostnames, and user password configuration).

appliance version. The version of [appliance management software](#) used to manage network settings on the Forge ESX Host and the Forge Appliance VM. Appliance (version) 1 uses a getty interface, appliance (version) 2 uses the Django Web framework and the ACC interface. Appliance version updates are motivated primarily by changes to the underlying VMware ESX version.

You can determine the appliance version of your Forge unit by using one of the following methods:

- **Forge Web Client:** Look up the appliance version number in the *Help > About* page of the ACC. You can only do this if you are reconfiguring Forge.
- **Local Configuration Interface Type:** Connect a monitor to the appliance and power it on. If the system displays the blue screen of the Forge Console, your appliance version is 1. If the system displays the ESX configuration screen, your appliance version is 2.
- **Remote Configuration Interface:** Using a Web browser and the IP address of your Forge unit (`http://<forge_esx_server>:1000`), attempt to launch the Forge Appliance Configuration Console (ACC). If you are able to connect, your appliance version is 2.

backup. The process of exporting existing database data, which includes existing workloads and contracts. This process also backs up the VMs that reside on the datastore local to the Forge Appliance Host.

contract data. Exported data for the protection contracts. The upgrade utility stores this in a .zip file.

See also [protection contracts](#).

Forge Appliance. A Forge Appliance Host containing a virtual machine running a Microsoft Windows OS with Forge software installed.

Forge Appliance Hardware. Dell hardware (PowerEdge 1950, 2950, R610, R710, R620 or R720) shipped by PlateSpin partner [Avnet, Inc.](#) The version of PlateSpin Forge you purchase is installed on a particular Dell model. For more information, see [Section 1.1, "Possible Forge Configurations," on page 9](#).

Forge Appliance Host. The VMware ESX software running on supported hardware.

Forge installation/upgrade executable. The executable file that upgrades the Forge Appliance software. The executable (also referred to as an "upgrade utility,") is included in the *Forge 11 Upgrade Kit*.

Forge software. PlateSpin software engineered by NetIQ to protect a specific virtual workload (that is, an ESX VM's operating system, middleware, and data) by using virtualization technology. If there is a production server outage or disaster, a virtualized replica of a workload can be rapidly powered on within the target container (a VM host), and continue to run as normal until the production environment is restored.

outputdirectory. (Also **output folder**). The network location where important backup data is stored on the [administrative computer](#). For example, D:\forge_backup\out.

protection contract. A collection of currently-active settings pertaining to the complete lifecycle of a workload's protection (*Add-inventory*, initial and ongoing *Replications*, *Failover*, *Failback*, and *Reprotect*).

rebuild. The process of configuring the Forge Dell hardware, the Forge ESX Host, and the Forge Appliance that is running on Windows 2003 Server.

restore. The process of importing existing database data (including workloads and contracts) as it existed prior to [backup](#). The process also restores all local VMs that formerly resided on the Forge Appliance Host.

working directory. The network location where the Forge upgrade kit is copied. For example, D:\forge_backup\11.0_kit.